

Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| Document group: | 08-7211-9 | Version number: | 9.02 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2022/09/22 | Supercedes Date: | 2021/02/23 |

SECTION 1: Identification

1.1. Product identifier

QS2013-3T-3C Transition Splice Kit (Resin 4N)

Product Identification Numbers

78-8120-1194-4 80-6109-8293-8

1.2. Recommended use and restrictions on use

Recommended use

Electrical, SPLICING MEDIUM VOLTAGE LEAD SHEATHED POWER CABLE

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577

E Mail:

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

24-9848-3, 05-4288-6, 35-7972-9, 40-0153-3, 06-4861-8, 34-7684-3

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

QS2013-3T-3C Transition Splice Kit (Resin 4N)

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 2 of 2



Safety Data Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 35-7972-9
 Version number:
 5.00

 Issue Date:
 2023/03/08
 Supercedes Date:
 2022/08/23

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M[™] Scotchcast[™] Electrical Insulating Resin 4N, Part B

Product Identification Numbers

LH-A100-1885-2 LH-A100-1949-3 LH-A100-1949-4 LH-A100-1949-5 LH-A100-1949-6

LH-A100-1949-7

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Specific Use

Part B of Resin 4N

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4. Acute Toxicity (dermal): Category 4. Serious Eye Damage/Irritation: Category 1. Skin Corrosion/Irritation: Category 1B.

3MTM ScotchcastTM Electrical Insulating Resin 4N, Part B

Skin Sensitizer: Category 1A. Reproductive Toxicity: Category 2. Carcinogenicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion Exclamation mark | Health Hazard |

Pictograms







Hazard statements

Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause cancer.

Causes damage to organs through prolonged or repeated exposure: respiratory system

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves, protective clothing, and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Storage:

Store locked up.

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

May cause chemical gastrointestinal burns.

18% of the mixture consists of ingredients of unknown acute oral toxicity.

36% of the mixture consists of ingredients of unknown acute dermal toxicity.

100% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|--|--------------|------------------------|---|
| Styrenated Phenol | 61788-44-1 | 30 - 60 Trade Secret * | Phenol, styrenated |
| N-Aminoethylpiperazine | 140-31-8 | 5 - 22 | 1-Piperazineethanamine |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | 64742-11-6 | 5 - 20 | Extracts, petroleum, heavy naphthenic distillate solvent solvent extraction process. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C20 through C50. This stream is likely to contain 5 wt. % or more o |
| Alkyl Acids, Reaction Products With Triethylenetetramine | Trade Secret | 5 - 17 | Not Applicable |
| Alykl Acids, Reaction Products With TETA And DGEBA | Trade Secret | 4 - 10 | Not Applicable |
| Reaction product of cycloaliphatic amine with aromatic epoxy resin | Trade Secret | 1 - 8 | Not Applicable |
| PETROLEUM DISTILLATES | Trade Secret | 1 - 7 Trade Secret * | Not Applicable |
| Thermal cracked residuum (petroleum) | 64741-80-6 | 1 - 7 Trade Secret * | Residues, petroleum, thermal crackedion from distillation of the product from a thermal cracking process. It consists predominantly of unsaturated hydrocarbons having carbon numbers predominantly greater than C20 and boiling above approximately 350.degree |
| Tris(2,4,6-dimethylaminomonomethyl)phe nol | 90-72-2 | 1 - 5 Trade Secret * | Phenol, 2,4,6-tris[(dimethylamino)methyl]- |
| Triethylenetetramine | 112-24-3 | <= 2 | 1,2-Ethanediamine, N,N'-bis(2-aminoethyl)- |
| Bis[(Dimethylamino)Methyl]Ph enol | 71074-89-0 | <= 1 | Phenol, bis[(dimethylamino)methyl]- |
| Carbon Black | 1333-86-4 | <1 | Carbon black |

Alykl Acids, Reaction Products With TETA And DGEBA is a non-hazardous Trade Secret material according to WHMIS criteria.

Reaction product of cycloaliphatic amine with aromatic epoxy resin is a non-hazardous Trade Secret material according to WHMIS criteria.

Bis[(Dimethylamino)Methyl]Phenol is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

Triethylenetetramine is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

Heavy Naphthenic Distillate Solvent Petroleum Extracts is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

N-Aminoethylpiperazine is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

Alkyl Acids, Reaction Products With Triethylenetetramine is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

Thermal cracked residuum (petroleum) is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

Petroleum Distillates is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eve Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| Substance | <u>Condition</u> |
|--------------------|-------------------|
| Amine Compounds | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Oxides of Nitrogen | During Combustion |

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralize spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralizing agent until reaction stops. Let cool before collecting. Or use a commercially available caustic (alkaline or basic) spill clean-up kit. Follow kit directions exactly. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|----------------------|------------|--------|---------------------------|----------------------------|
| Triethylenetetramine | 112-24-3 | AIHA | TWA:6 mg/m3(1 ppm) | SKIN |
| Carbon Black | 1333-86-4 | ACGIH | TWA(inhalable fraction):3 | |
| | | | mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| information on basic physical and chemical propertie | | |
|--|-------------------------------------|--|
| Physical state | Liquid | |
| Specific Physical Form: | Resin | |
| | | |
| Colour | Black | |
| Odour | Amine | |
| Odour threshold | No Data Available | |
| рН | 10 - 12 | |
| Melting point/Freezing point | No Data Available | |
| Boiling point | 319.4 °C | |
| Flash Point | No flash point | |
| Evaporation rate | No Data Available | |
| Flammability (solid, gas) | Not Applicable | |
| Flammable Limits(LEL) | No Data Available | |
| Flammable Limits(UEL) | No Data Available | |
| Vapour Pressure | 533.3 Pa | |
| Vapour Density and/or Relative Vapour Density | No Data Available | |
| Density | 1.03 g/ml | |
| Relative density | 1.03 [Ref Std:WATER=1] | |
| Water solubility | 660 ppm [@ 77 °F] | |
| Solubility- non-water | No Data Available | |
| Partition coefficient: n-octanol/ water | No Data Available | |
| Autoignition temperature | No Data Available | |
| Decomposition temperature | No Data Available | |
| Viscosity/Kinematic Viscosity | 3,000 mPa-s - 4,500 mPa-s [@ 25 °C] | |
| Volatile Organic Compounds | No Data Available | |
| Percent volatile | le 3 - 5 % | |
| VOC Less H2O & Exempt Solvents | No Data Available | |
| verage particle size No Data Available | | |
| | ı | |

| Bulk density | No Data Available |
|------------------|-------------------|
| Molecular weight | Not Applicable |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids

No Data Available

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Harmful in contact with skin. Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|--|--------------|--------------------------------|---|
| Fuel oils, residual (heavy) | 64741-80-6 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| PETROLEUM DISTILLATES | Trade Secret | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Soot (as found in occupational exposure of chimney sweeps) | 1333-86-4 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Soots | 1333-86-4 | Known To Be Human Carcinogen. | National Toxicology Program Carcinogens |
| Carbon black | 1333-86-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >1,000 - =2,000 |
| • | | | mg/kg |
| Overall product | Inhalation- | | No data available; calculated ATE >5 - =12.5 mg/l |
| • | Dust/Mist(4 | | |
| | hr) | | |
| Overall product | Ingestion | | No data available; calculated ATE >300 - =2,000 |
| • | | | mg/kg |
| Styrenated Phenol | Dermal | Rat | LD50 > 2,000 mg/kg |
| Styrenated Phenol | Ingestion | Rat | LD50 > 2,000 mg/kg |
| N-Aminoethylpiperazine | Dermal | Rabbit | LD50 865 mg/kg |
| N-Aminoethylpiperazine | Ingestion | Rat | LD50 1,470 mg/kg |
| Alkyl Acids, Reaction Products With Triethylenetetramine | Ingestion | Rat | LD50 > 2,000 mg/kg |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT | Dermal | similar | LD50 > 3,000 mg/kg |
| PETROLEUM EXTRACTS | | compoun | |
| | | ds | |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT | Inhalation- | similar | LC50 > 5 mg/l |
| PETROLEUM EXTRACTS | Dust/Mist | compoun | |
| | (4 hours) | ds | |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT | Ingestion | similar | LD50 > 5,000 mg/kg |
| PETROLEUM EXTRACTS | | compoun | |
| | | ds | |
| Alkyl Acids, Reaction Products With Triethylenetetramine | Dermal | similar | LD50 estimated to be > 5,000 mg/kg |
| | | health | |
| | | hazards | |
| PETROLEUM DISTILLATES | Dermal | similar | LD50 > 2,000 mg/kg |
| | | compoun | |
| | | ds | |

 p_{acc} q of 12

| PETROLEUM DISTILLATES | Inhalation- Dust/Mist (4 hours) | similar compoun ds | LC50 4.1 mg/l |
|---|---------------------------------------|--------------------------|--|
| PETROLEUM DISTILLATES | Ingestion | similar compoun ds | LD50 4,320 mg/kg |
| Thermal cracked residuum (petroleum) | Dermal | similar compoun ds | LD50 > 2,000 mg/kg |
| Thermal cracked residuum (petroleum) | Inhalation- Dust/Mist (4 hours) | similar compoun ds | LC50 4.1 mg/l |
| Thermal cracked residuum (petroleum) | Ingestion | similar compoun ds | LD50 4,320 mg/kg |
| Tris(2,4,6-dimethylaminomonomethyl)phenol | Dermal | Rat | LD50 1,280 mg/kg |
| Tris(2,4,6-dimethylaminomonomethyl)phenol | Ingestion | Rat | LD50 1,000 mg/kg |
| Triethylenetetramine | Dermal | Rabbit | LD50 550 mg/kg |
| Triethylenetetramine | Ingestion | Rat | LD50 2,500 mg/kg |
| Bis[(Dimethylamino)Methyl]Phenol | Ingestion | | LD50 estimated to be 300 - 2,000 mg/kg |
| Carbon Black | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Carbon Black | Ingestion | Rat | LD50 > 8,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|--------------------------|---------------------------|
| Styrenated Phenol | Rabbit | No significant irritation |
| N-Aminoethylpiperazine | Rabbit | Corrosive |
| Alkyl Acids, Reaction Products With Triethylenetetramine | In vitro data | No significant irritation |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | similar compoun ds | Mild irritant |
| PETROLEUM DISTILLATES | similar compoun ds | No significant irritation |
| Thermal cracked residuum (petroleum) | similar compoun ds | No significant irritation |
| Tris(2,4,6-dimethylaminomonomethyl)phenol | Rabbit | Corrosive |
| Triethylenetetramine | Rabbit | Corrosive |
| Bis[(Dimethylamino)Methyl]Phenol | similar compoun ds | Corrosive |
| Carbon Black | Rabbit | No significant irritation |

Serious Eve Damage/Irritation

| Name | Species | Value |
|--|--------------------------|---------------------------|
| Styrenated Phenol | Rabbit | Mild irritant |
| N-Aminoethylpiperazine | Rabbit | Corrosive |
| Alkyl Acids, Reaction Products With Triethylenetetramine | In vitro data | Severe irritant |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | similar compoun ds | No significant irritation |
| PETROLEUM DISTILLATES | similar compoun ds | Mild irritant |
| Thermal cracked residuum (petroleum) | similar compoun ds | Mild irritant |
| Tris(2,4,6-dimethylaminomonomethyl)phenol | Rabbit | Corrosive |
| Triethylenetetramine | Rabbit | Corrosive |

Page: 9 of 13

3MTM ScotchcastTM Electrical Insulating Resin 4N, Part B

| Bis[(Dimethylamino)Methyl]Phenol | similar | Corrosive |
|----------------------------------|---------|---------------------------|
| | compoun | |
| | ds | |
| Carbon Black | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|--|---------|----------------|
| Styrenated Phenol | Mouse | Sensitizing |
| N-Aminoethylpiperazine | Guinea | Sensitizing |
| | pig | - |
| Alkyl Acids, Reaction Products With Triethylenetetramine | Guinea | Sensitizing |
| | pig | |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | similar | Not classified |
| | compoun | |
| | ds | |
| PETROLEUM DISTILLATES | Guinea | Not classified |
| | pig | |
| Thermal cracked residuum (petroleum) | similar | Not classified |
| | compoun | |
| | ds | |
| Tris(2,4,6-dimethylaminomonomethyl)phenol | Guinea | Not classified |
| | pig | |
| Triethylenetetramine | Guinea | Sensitizing |
| | pig | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| N-Aminoethylpiperazine | In vivo | Not mutagenic |
| N-Aminoethylpiperazine | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Alkyl Acids, Reaction Products With Triethylenetetramine | In Vitro | Not mutagenic |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | In vivo | Some positive data exist, but the data are not sufficient for classification |
| PETROLEUM DISTILLATES | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Thermal cracked residuum (petroleum) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Tris(2,4,6-dimethylaminomonomethyl)phenol | In Vitro | Not mutagenic |
| Carbon Black | In Vitro | Not mutagenic |
| Carbon Black | In vivo | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|--------------------------------|------------------|
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | Dermal | similar compoun | Carcinogenic |
| PETROLEUM DISTILLATES | Dermal | ds similar compoun ds | Carcinogenic |
| Thermal cracked residuum (petroleum) | Dermal | similar compoun ds | Carcinogenic |
| Carbon Black | Dermal | Mouse | Not carcinogenic |
| Carbon Black | Ingestion | Mouse | Not carcinogenic |
| Carbon Black | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|--|-----------|--|--------------------------|-------------------------|------------------------------|
| N-Aminoethylpiperazine | Ingestion | Not classified for female reproduction | Rat | NOAEL 598 mg/kg/day | premating & during gestation |
| N-Aminoethylpiperazine | Ingestion | Not classified for male reproduction | Rat | NOAEL 409 mg/kg/day | 32 days |
| N-Aminoethylpiperazine | Ingestion | Toxic to development | Rabbit | NOAEL 75 mg/kg/day | during gestation |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | Ingestion | Not classified for male reproduction | similar compoun ds | NOAEL 125 mg/kg/day | 13 weeks |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | Dermal | Toxic to development | similar compoun ds | NOAEL 5 mg/kg/day | during gestation |
| PETROLEUM DISTILLATES | Dermal | Toxic to development | similar compoun ds | NOAEL 0.05 mg/kg/day | during gestation |
| Thermal cracked residuum (petroleum) | Dermal | Toxic to development | similar compoun ds | NOAEL 0.05 mg/kg/day | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|------------|------------------------|--|------------------------------|------------------------|----------------------|
| N-Aminoethylpiperazine | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| Alkyl Acids, Reaction Products With Triethylenetetramine | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| HEAVY NAPHTHENIC DISTILLATE SOLVENT PETROLEUM EXTRACTS | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL not available | |
| Tris(2,4,6- dimethylaminomonomethyl)phenol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|------------------------|------------|--|--|---------|-----------------------------|----------------------|
| N-Aminoethylpiperazine | Dermal | skin | Not classified | Rat | NOAEL 100 mg/kg/day | 29 days |
| N-Aminoethylpiperazine | Dermal | hematopoietic system nervous system kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 29 days |
| N-Aminoethylpiperazine | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | NOAEL 0.2 mg/m3 | 13 weeks |
| N-Aminoethylpiperazine | Inhalation | hematopoietic system eyes kidney and/or bladder | Not classified | Rat | NOAEL 53.8 mg/m3 | 13 weeks |
| N-Aminoethylpiperazine | Ingestion | heart endocrine system hematopoietic system liver nervous system kidney and/or bladder | Not classified | Rat | NOAEL 598 mg/kg/day | 28 days |
| HEAVY NAPHTHENIC | Dermal | endocrine system | May cause damage to organs | similar | LOAEL 30 | 90 days |

| DISTILLATE SOLVENT PETROLEUM EXTRACTS | | gastrointestinal tract hematopoietic system liver immune system kidney and/or bladder | though prolonged or repeated exposure | compoun ds | mg/kg/day | |
|---|------------|--|--|--------------------------|-------------------------|-----------------------|
| PETROLEUM | Dermal | liver immune | May cause damage to organs | similar | NOAEL 10.6 | 13 weeks |
| DISTILLATES | | system | though prolonged or repeated exposure | ds compoun | mg/kg/day | |
| PETROLEUM DISTILLATES | Dermal | hematopoietic system | May cause damage to organs though prolonged or repeated exposure | similar compoun ds | NOAEL 1.06 mg/kg/day | 13 weeks |
| Thermal cracked residuum (petroleum) | Dermal | liver immune system | May cause damage to organs though prolonged or repeated exposure | similar compoun ds | NOAEL 10.6 mg/kg/day | 13 weeks |
| Thermal cracked residuum (petroleum) | Dermal | hematopoietic system | May cause damage to organs though prolonged or repeated exposure | similar compoun ds | NOAEL 1.06 mg/kg/day | 13 weeks |
| Tris(2,4,6-dimethylaminomonomethyl)phenol | Dermal | skin liver nervous system auditory system hematopoietic system eyes | Not classified | Rat | NOAEL 125 mg/kg/day | 28 days |
| Carbon Black | Inhalation | pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

| Name | Value |
|--------------------------------------|-------------------|
| PETROLEUM DISTILLATES | Aspiration hazard |
| Thermal cracked residuum (petroleum) | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Trade Secret Information:

HMIRA Registry Number: Filing date: Claim status: Date of decision:

11690 13/07/2017 Claim for exemption has been

filed.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| Document group: | 35-7972-9 | Version number: | 5.00 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2023/03/08 | Supercedes Date: | 2022/08/23 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

n.... 12 .c. 1



Article Information Sheet

Copyright, 2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Article Information Sheet is provided as a courtesy in response to a customer request. A Safety Data Sheet (SDS) has not been prepared for these product(s) because they are articles. Articles are not subject to the Hazardous Products Act or Regulations. As defined in the act: "Article" means any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product.

Document group: 05-4288-6 **Version number:** 1.02

Issue Date: 2020/10/09 **Supercedes Date:** 2019/08/14

SECTION 1: Identification

1.1. Product identifier

Scotch-Seal[™] Tapes, Pads, and Strips 2229

Product Identification Numbers

 2229
 11-0023-7476-4
 80-0000-0789-0
 80-6105-9441-0
 80-6107-3291-1

 80-6107-3292-9
 80-6109-2897-2
 80-6109-2916-0
 80-6114-3998-7
 80-6114-5741-9

1.2. Recommended use and restrictions on use

Intended Use

Electrical insulating and moisture seal

Specific Use

Moisture and Corrosion Protection

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

This product is exempt from hazard classification according to the Hazardous Products Act because it meets the manufactured article exemption.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|--------------------------|------------|---------|----------------|
| Nonregulated Fillers | Mixture | 50 - 60 | Not Applicable |
| Synthetic Rubber Mixture | Mixture | 30 - 40 | Not Applicable |
| Asphalt | 8052-42-4 | 5 - 12 | Asphalt |
| Carbon Black | 1333-86-4 | 1 - 5 | Carbon black |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

No need for first aid is anticipated.

If Swallowed:

No need for first aid is anticipated.

SECTION 5: Fire-fighting measures

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions. No engineering controls or personal protective equipment (PPE) are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| information on basic physical and chemical properties | |
|---|---|
| Physical state | Solid |
| Specific Physical Form: | Rubber tape strip or pad with paper liner |
| Colour | Black |
| Odour | Rubber |
| Odour threshold | Not Applicable |
| pH | Not Applicable |
| Melting point/Freezing point | No Data Available |
| Boiling point | Not Applicable |
| Flash Point | No Data Available |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapour Pressure | Not Applicable |
| Viscosity/Kinematic Viscosity Viscosity/Kinematic | Not Applicable |
| Viscosity | |
| Relative density | Approximately 1.2 [Test Method: Tested per ASTM protocol] |
| | [Ref Std:WATER=1] |
| Water solubility | Nil |
| Solubility- non-water | Not Applicable |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | Not Applicable |
| Viscosity/Kinematic Viscosity | Not Applicable |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | |
| VOC Less H2O & Exempt Solvents | Not Applicable |
| Molecular weight | No Data Available |
| | |

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

This material is considered to be non reactive under normal use conditions.

SECTION 11: Toxicological information

Inhalation:

No health effects are expected

Skin Contact:

No health effects are expected

Scotch-Seal[™] Tapes, Pads, and Strips 2229

Eye Contact:

No health effects are expected

Ingestion:

No health effects are expected

Additional Information:

This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Dispose of contents/container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

This product is an article as defined by CEPA and is exempt from DSL inventory listing.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document group: | 05-4288-6 | Version number: | 1.02 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2020/10/09 | Supercedes Date: | 2019/08/14 |

Reason for Reissue

Conversion to GHS format SDS.

The information in this Article Information Sheet (AIS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining

whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 24-9848-3
 Version number:
 3.06

 Issue Date:
 2020/10/19
 Supercedes Date:
 2020/03/05

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotchcast™ Electrical Insulating Resin 4N, Part A and 3M™ Scotchcast™ Electrical Insulating Resin 4, Part A

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Specific Use

Part A of Resin 4 & Resin 4N

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2B. Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark

Pictograms



Hazard statements

Causes eye irritation. May cause an allergic skin reaction.

Precautionary statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name | | |
|-----------------------------|------------|-------------------------|---|--|--|
| 2,2-Bis(p- | 25085-99-8 | 80 - 100 Trade Secret * | Oxirane, 2,2'-[(1-methylethylidene)bis(4,1- | | |
| hydroxyphenyl)propane | | | phenyleneoxymethylene)]bis-, | | |
| diglycidyl ether polymer | | | homopolymer | | |
| Oxirane, Mono[(C12-14- | 68609-97-2 | 5 - 10 Trade Secret * | Oxirane, mono[(C12-14-alkyloxy)methyl] | | |
| Alkyloxy)Methyl]Derivatives | | | derivs. | | |

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionToxic Vapor, Gas, ParticulateDuring Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Liquid |
|-------------------------|--------|
| Specific Physical Form: | Resin |
| | |
| Colour | Amber |
| Odour | Epoxy |

| Odour threshold | No Data Available |
|---|-------------------------------------|
| pH | No Data Available |
| Melting point/Freezing point | No Data Available |
| Boiling point | >= 93.9 °C |
| Flash Point | >= 93.9 °C [Test Method:Closed Cup] |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapour Pressure | <= 186,158.4 Pa [@ 55 °C] |
| Viscosity/Kinematic Viscosity Viscosity/Kinematic | No Data Available |
| Viscosity | |
| Density | 1.16 g/ml |
| Relative density | 1.16 [Ref Std:WATER=1] |
| Water solubility | Negligible |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | 3,000 mPa-s - 5,000 mPa-s |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | |
| VOC Less H2O & Exempt Solvents | No Data Available |
| Average particle size | No Data Available |
| Bulk density | No Data Available |
| Molecular weight | No Data Available |
| Softening point | No Data Available |

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Moderate Eve Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|-----------|---------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Dermal | Rat | LD50 > 1,600 mg/kg |
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Ingestion | Rat | LD50 > 1,000 mg/kg |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | Dermal | Rabbit | LD50 > 4,000 mg/kg |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | Ingestion | Rat | LD50 17,100 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|---------|---------------|
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Rabbit | Mild irritant |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | Rabbit | Mild irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|-------------------|
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Rabbit | Moderate irritant |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | Rabbit | Mild irritant |

Skin Sensitization

| Name | Species | Value |
|------|---------|-------|
| | | |

3MTM ScotchcastTM Electrical Insulating Resin 4N, Part A and 3MTM ScotchcastTM Electrical Insulating Resin 4, Part A

| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Human | Sensitizing |
|--|--------|-------------|
| | and | |
| | animal | |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | Guinea | Sensitizing |
| | pig | |

Respiratory Sensitization

| Name | Species | Value |
|--|---------|----------------|
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Human | Not classified |

Germ Cell Mutagenicity

| Name Rout | | Value |
|--|----------|--|
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | In vivo | Not mutagenic |
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | | Some positive data exist, but the data are not sufficient for classification |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | In vivo | Not mutagenic |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | | Species | Value |
|--|--|---------|--|
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | | Mouse | Some positive data exist, but the data are not |
| | | | sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|--|-----------|--|---------|------------------------|-----------------------------|
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Ingestion | Not classified for male reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Dermal | Not classified for development | Rabbit | NOAEL 300 mg/kg/day | during organogenesi s |
| 2,2-Bis(p-hydroxyphenyl)propane diglycidyl ether polymer | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | 2 generation |
| Oxirane, Mono[(C12-14-Alkyloxy)Methyl]Derivatives | Dermal | Not classified for development | Rat | NOAEL 200 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Specific Turget Organ Toxicity Single exposure | | | | | | |
|--|--------|-----------------------|----------------|---------|-------------|----------|
| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure |
| | | | | | | Duration |
| Oxirane, Mono[(C12-14- | Dermal | heart blood liver | Not classified | Rabbit | NOAEL | 24 hours |
| Alkyloxy)Methyl]Derivativ | | nervous system | | | 4,000 mg/kg | |
| es | | kidney and/or | | | | |
| | | bladder | | | | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|--------|-----------------|----------------|---------|-----------------------------|----------------------|
| 2,2-Bis(p- hydroxyphenyl)propane diglycidyl ether polymer | Dermal | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| 2,2-Bis(p- hydroxyphenyl)propane diglycidyl ether polymer | Dermal | nervous system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |

Page: 7 of 9

| 2,2-Bis(p- hydroxyphenyl)propane diglycidyl ether polymer | Ingestion | auditory system heart endocrine system hematopoietic system liver eyes kidney and/or | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
|---|-----------|---|----------------|-----|-----------------------------|----------|
| Oxirane, Mono[(C12-14- Alkyloxy)Methyl]Derivati ves | Dermal | nervous system respiratory system | Not classified | Rat | NOAEL 100 mg/kg/day | 14 weeks |
| Oxirane, Mono[(C12-14- Alkyloxy)Methyl]Derivati ves | Dermal | blood liver eyes kidney and/or bladder | Not classified | Rat | NOAEL 100 mg/kg/day | 13 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components

of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| Document group: | 24-9848-3 | Version number: | 3.06 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2020/10/19 | Supercedes Date: | 2020/03/05 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

D 0 C



Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 40-0153-3
 Version number:
 1.02

 Issue Date:
 2022/09/21
 Supercedes Date:
 2021/02/10

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M Sheath Wrap Roll

Product Identification Numbers

CE-1006-9128-2 CE-1006-9129-0 UU-0102-5729-1 UU-0102-5730-9 UU-0102-5913-1 UU-0102-5914-9 UU-0102-5915-6 UU-0102-5936-2 UU-0102-5937-0 UU-0102-5938-8

UU-0102-6051-9 UU-0102-6052-7 UU-0112-2563-6

1.2. Recommended use and restrictions on use

Intended Use

Industrial use

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Electronics & Energy Business Spons

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Respiratory Sensitizer: Category 1. Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |







Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure: respiratory system

Precautionary statements

Prevention:

Do not breathe dust/fume/gas/mist/vapours/spray. In case of inadequate ventilation wear respiratory protection. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|--------------------------|--------------|--------------------------|--|
| Oxide glass chemicals | 65997-17-3 | 40 - 70 | Glass, oxide, chemicals |
| Polymer | Trade Secret | 30 - 60 | Not Applicable |
| Iron Oxide (FE3O4) | 1317-61-9 | 1 - 5 | Iron oxide (Fe3O4) |
| P,P'-Methylenebis(phenyl | 101-68-8 | 1 - 5 Trade Secret * | Benzene, 1,1'-methylenebis[4-isocyanato- |
| isocyanate) | | | 5 |
| Diphenylmethane-2,4'- | 5873-54-1 | 0.5 - 1.5 Trade Secret * | Benzene, 1-isocyanato-2-[(4- |
| diisocyanate | | | isocyanatophenyl)methyl]- |
| CHROMIUM (CR+6) | 18540-29-9 | 0.001 - 0.02 | No Data Available |

Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

Page: 2 of 11

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

No need for first aid is anticipated.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|--------------------|--------------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Hydrogen Cyanide | During Combustion |
| Oxides of Nitrogen | During Combustion |

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon

Page: 3 of 11

as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|------------|-------------------------|--|----------------------------------|
| P,P'-Methylenebis(phenyl isocyanate) | 101-68-8 | ACGIH | TWA:0.005 ppm | |
| CHROMIUM (HEXAVALENT COMPOUNDS) | 18540-29-9 | ACGIH | TWA(as Cr(IV), inhalable fraction):0.0002 mg/m3;STEL(as Cr(IV), inhalable fraction):0.0005 mg/m3 | |
| CHROMIUM (VI), WATER SOLUBLE COMPOUNDS | 18540-29-9 | ACGIH | TWA(as Cr(IV), inhalable fraction):0.0002 mg/m3;TWA(as Cr):0.05 mg/m3;STEL(as Cr(IV), inhalable fraction):0.0005 mg/m3 | Dermal/Respiratory Sensitizer |
| Chromium(6+), insoluble compounds | 18540-29-9 | ACGIH | TWA(as Cr):0.01 mg/m3 | |
| Water-soluble inorganic Cr(6+) compounds | 18540-29-9 | ACGIH | TWA(as Cr):0.05 mg/m3 | |
| Oxide glass chemicals | 65997-17-3 | Manufacturer determined | TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection

Page: 4 of 11

equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Solid |
|---|-----------------------------------|
| Specific Physical Form: | Resin Sat.Glass Tape |
| | |
| Colour | Black |
| Odour | Slight Odour |
| Odour threshold | Not Applicable |
| pH | No Data Available |
| Melting point/Freezing point | Not Applicable |
| Boiling point | Not Applicable |
| Flash Point | 174.4 °C [Test Method:Closed Cup] |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | No Data Available |
| Flammable Limits(UEL) | No Data Available |
| Vapour Pressure | No Data Available |
| Vapour Density and/or Relative Vapour Density | No Data Available |
| Density | No Data Available |
| Relative density | Not Applicable |
| Water solubility | Nil |
| Solubility- non-water | Nil [Details: water sulubility] |
| Partition coefficient: n-octanol/ water | No Data Available |

Page: 5 of 11

| Autoignition temperature | No Data Available |
|--------------------------------|-------------------|
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | Not Applicable |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | No Data Available |
| VOC Less H2O & Exempt Solvents | No Data Available |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Alcohols Amines

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Page: 6 of 11

Eve Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

| <u>Ingredient</u> | CAS No. | Class Description | Regulation |
|--|------------|--------------------------------|---|
| Chromium Hexavalent Compounds | 18540-29-9 | Known To Be Human Carcinogen. | National Toxicology Program Carcinogens |
| Chromium[VI] compounds | 18540-29-9 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Hexavalent chromium compounds | 18540-29-9 | Cancer hazard | OSHA Carcinogens |
| Glass Wool Fibers (Inhalable), Certain | 65997-17-3 | Anticipated human carcinogen | National Toxicology Program Carcinogens |

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--------------------------------------|---------------------------------------|------------------|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| Oxide glass chemicals | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Oxide glass chemicals | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Polymer | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Polymer | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| P,P'-Methylenebis(phenyl isocyanate) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation- Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| P,P'-Methylenebis(phenyl isocyanate) | Ingestion | Rat | LD50 31,600 mg/kg |
| Iron Oxide (FE3O4) | Dermal | Not available | LD50 3,100 mg/kg |
| Iron Oxide (FE3O4) | Ingestion | Not available | LD50 3,700 mg/kg |
| Diphenylmethane-2,4'-diisocyanate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Diphenylmethane-2,4'-diisocyanate | Inhalation- Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| Diphenylmethane-2,4'-diisocyanate | Ingestion | Rat | LD50 31,600 mg/kg |
| CHROMIUM (CR+6) | Dermal | | LD50 estimated to be 200 - 1,000 mg/kg |
| CHROMIUM (CR+6) | Inhalation- Dust/Mist | | LC50 estimated to be 0 - 0.05 mg/l |
| CHROMIUM (CR+6) | Ingestion | | LD50 estimated to be 5 - 50 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Page: 7 of 11

| Name | Species | Value |
|--------------------------------------|------------|---------------------------|
| | | |
| Oxide glass chemicals | Professio | No significant irritation |
| | nal | |
| | judgeme | |
| | nt | |
| P,P'-Methylenebis(phenyl isocyanate) | official | Irritant |
| | classifica | |
| | tion | |
| Iron Oxide (FE3O4) | Rabbit | No significant irritation |
| Diphenylmethane-2,4'-diisocyanate | official | Irritant |
| | classifica | |
| | tion | |
| CHROMIUM (CR+6) | Human | Corrosive |

Serious Eve Damage/Irritation

| Name | Species | Value |
|--------------------------------------|------------|---------------------------|
| | | |
| Oxide glass chemicals | Professio | No significant irritation |
| | nal | |
| | judgeme | |
| | nt | |
| P,P'-Methylenebis(phenyl isocyanate) | official | Severe irritant |
| | classifica | |
| | tion | |
| Iron Oxide (FE3O4) | Rabbit | No significant irritation |
| Diphenylmethane-2,4'-diisocyanate | official | Severe irritant |
| | classifica | |
| | tion | |
| CHROMIUM (CR+6) | similar | Corrosive |
| | health | |
| | hazards | |

Skin Sensitization

| Skiii Schsitization | | |
|--------------------------------------|------------|----------------|
| Name | Species | Value |
| P,P'-Methylenebis(phenyl isocyanate) | official | Sensitizing |
| | classifica | |
| | tion | |
| Iron Oxide (FE3O4) | Human | Not classified |
| Diphenylmethane-2,4'-diisocyanate | official | Sensitizing |
| | classifica | |
| | tion | |
| CHROMIUM (CR+6) | Human | Sensitizing |
| | and | |
| | animal | |

Respiratory Sensitization

| Name | Species | Value |
|--------------------------------------|---------|----------------|
| P,P'-Methylenebis(phenyl isocyanate) | Human | Sensitizing |
| Diphenylmethane-2,4'-diisocyanate | Human | Sensitizing |
| CHROMIUM (CR+6) | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|--------------------------------------|----------|--|
| Oxide glass chemicals | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| P,P'-Methylenebis(phenyl isocyanate) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Iron Oxide (FE3O4) | In Vitro | Not mutagenic |
| Diphenylmethane-2,4'-diisocyanate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| CHROMIUM (CR+6) | In Vitro | Some positive data exist, but the data are not |

Page: 8 of 11

| | | sufficient for classification |
|-----------------|---------|-------------------------------|
| CHROMIUM (CR+6) | In vivo | Mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--------------------------------------|------------------|-------------------------------|--|
| Oxide glass chemicals | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| Iron Oxide (FE3O4) | Inhalation | Human | Some positive data exist, but the data are not sufficient for classification |
| Diphenylmethane-2,4'-diisocyanate | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| CHROMIUM (CR+6) | Not Specified | Human | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|--------------------------------------|------------|--|---------|-----------------------|-----------------------------|
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesi s |
| Diphenylmethane-2,4'-diisocyanate | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesi s |
| CHROMIUM (CR+6) | Inhalation | Not classified for female reproduction | Rat | NOAEL 0.0002 mg/l | 3 generation |
| CHROMIUM (CR+6) | Inhalation | Not classified for male reproduction | Rat | NOAEL 0.0002 mg/l | 3 generation |
| CHROMIUM (CR+6) | Inhalation | Not classified for development | Rat | NOAEL 0.0002 mg/l | 3 generation |
| CHROMIUM (CR+6) | Ingestion | Toxic to female reproduction | Mouse | LOAEL 6 mg/kg/day | 12 weeks |
| CHROMIUM (CR+6) | Ingestion | Toxic to male reproduction | Mouse | LOAEL 6 mg/kg/day | 12 weeks |
| CHROMIUM (CR+6) | Ingestion | Toxic to development | Mouse | LOAEL 57 mg/kg/day | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|--------------------------------------|------------|---------------------------------|----------------------------------|--------------------------------|------------------------|---------------------------|
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory irritation | May cause respiratory irritation | official classifica tion | NOAEL Not available | |
| Diphenylmethane-2,4'-diisocyanate | Inhalation | respiratory irritation | May cause respiratory irritation | official classifica tion | NOAEL Not available | |
| CHROMIUM (CR+6) | Dermal | kidney and/or bladder | Not classified | Human | NOAEL Not available | |
| CHROMIUM (CR+6) | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | occupational exposure |
| CHROMIUM (CR+6) | Ingestion | kidney and/or bladder | Causes damage to organs | Human | NOAEL Not available | |
| CHROMIUM (CR+6) | Ingestion | hematoppoitic system liver | Not classified | Human | NOAEL Not available | |
| CHROMIUM (CR+6) | Ingestion | nervous system | Not classified | Human | NOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

Page: 9 of 11

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------------------------------|------------|--|--|-------------------------------|------------------------|-----------------------|
| Oxide glass chemicals | Inhalation | respiratory system | Not classified | Human | NOAEL not available | occupational exposure |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| Iron Oxide (FE3O4) | Inhalation | pulmonary fibrosis pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Diphenylmethane-2,4'- diisocyanate | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| CHROMIUM (CR+6) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| CHROMIUM (CR+6) | Inhalation | immune system | Not classified | Rat | NOAEL Not available | 90 days |
| CHROMIUM (CR+6) | Inhalation | heart endocrine system hematopoietic system liver nervous system kidney and/or bladder | Not classified | Rat | NOAEL 0.02 mg/l | 2 years |
| CHROMIUM (CR+6) | Ingestion | kidney and/or bladder | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 100 mg/kg/day | 28 days |
| CHROMIUM (CR+6) | Ingestion | nervous system | Not classified | Rat | LOAEL 98 mg/kg/day | 28 days |
| CHROMIUM (CR+6) | Ingestion | liver | Not classified | Multiple animal species | NOAEL Not available | |
| CHROMIUM (CR+6) | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL Not available | 1 generation |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document group: | 40-0153-3 | Version number: | 1.02 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2022/09/21 | Supercedes Date: | 2021/02/10 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 11 of 11



Article Information Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Article Information Sheet is provided as a courtesy in response to a customer request. A Safety Data Sheet (SDS) has not been prepared for these product(s) because they are articles. Articles are not subject to the Hazardous Products Act or Regulations. As defined in the act: "Article" means any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product.

Document group: 34-7684-3 **Version number:** 1.03

Issue Date: 2023/01/12 **Supercedes Date:** 2020/10/16

SECTION 1: Identification

1.1. Product identifier

Black EPDM Tubing (on plastic core)

Product Identification Numbers

78-8125-9775-1

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

This product is exempt from hazard classification according to the Hazardous Products Act because it meets the manufactured article exemption.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|-----------------------------|------------|---------|-------------------|
| Black EPDM Tubing Composite | None | 100 | No Data Available |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

No need for first aid is anticipated.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

No need for first aid is anticipated.

If Swallowed:

No need for first aid is anticipated.

SECTION 5: Fire-fighting measures

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Not applicable.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Not applicable.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions. No engineering controls or personal protective equipment (PPE) are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| DI I I I | 0.11 |
|---|-------------------|
| Physical state | Solid |
| Colour | Black |
| Odour | Rubber |
| Odour threshold | Not Applicable |
| pH | Not Applicable |
| Melting point/Freezing point | No Data Available |
| Boiling point | Not Applicable |
| Flash Point | No flash point |
| Evaporation rate | Not Applicable |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapour Density and/or Relative Vapour Density | Not Applicable |
| Density | No Data Available |
| Relative density | No Data Available |
| Water solubility | Not Applicable |
| Solubility- non-water | Not Applicable |
| Partition coefficient: n-octanol/ water | Not Applicable |
| Autoignition temperature | Not Applicable |
| Decomposition temperature | No Data Available |
| Viscosity/Kinematic Viscosity | Not Applicable |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | No Data Available |
| VOC Less H2O & Exempt Solvents | No Data Available |
| Molecular weight | Not Applicable |
| L | • |

SECTION 10: Stability and reactivity

This material is considered to be non reactive under normal use conditions.

SECTION 11: Toxicological information

Inhalation:

No health effects are expected

Skin Contact:

No health effects are expected

Eye Contact:

No health effects are expected

Ingestion:

No health effects are expected

Additional Information:

This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Dispose of contents/container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

This product is an article as defined by CEPA and is exempt from DSL inventory listing.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| Document group: | 34-7684-3 | Version number: | 1.03 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2023/01/12 | Supercedes Date: | 2020/10/16 |

The information in this Article Information Sheet (AIS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



Safety Data Sheet

Copyright, 2021, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 06-4861-8
 Version number:
 11.05

 Issue Date:
 2021/06/08
 Supercedes Date:
 2021/03/25

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM P55/R Lubricant, Red

Product Identification Numbers

78-8096-4318-8 78-8126-9891-4 78-9237-1424-6 80-0002-2677-1 80-6116-0479-6 CE-1006-8786-8 CE-1006-9277-7 CE-1006-9374-2 GE-7000-2862-6 GE-7000-2863-4

JE-4100-0831-0 UU-0082-9519-6

1.2. Recommended use and restrictions on use

Intended Use

Electrical

Specific Use

ELECTRICAL LUBRICATING GREASE

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

2.2. Label elements

3MTM P55/R Lubricant, Red

Signal word

Not applicable.

Symbols

Not applicable.

Pictograms

Not applicable.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|-----------------------------|-------------|---------|--|
| 1,1,2,3,3,3-HEXAFLUORO-1- | 69991-67-9 | 95 - 98 | 1-Propene, 1,1,2,3,3,3-hexafluoro-, |
| PROPENE, OXIDIZED, | | | oxidized, polymd. |
| POLYMD. | | | |
| Synthetic Amorphous Silica, | 112945-52-5 | <= 5 | Fumed amorphous silica, crystalline-free |
| Fumed, Crystalline Free | | | |
| C.I. PIGMENT RED 170 | 2786-76-7 | <= 0.05 | No Data Available |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

Skin Contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

No need for first aid is anticipated.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

 n_{ana} γ_{af}

Substance

Carbonyl Fluoride Carbon monoxide Carbon dioxide Hydrogen Fluoride Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Avoid release to the environment. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Liquid |
|---|---|
| Specific Physical Form: | Paste |
| | |
| Colour | Red |
| Odour | Odourless |
| Odour threshold | Not Applicable |
| рН | Not Applicable |
| Melting point/Freezing point | Not Applicable |
| Boiling point | 270 °C [Details: MITS data (per supplier info)] |
| Flash Point | Flash point > 93 °C (200 °F) |
| Evaporation rate | No Data Available |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | Not Applicable |
| Flammable Limits(UEL) | Not Applicable |
| Vapour Pressure | <=1.3 Pa |
| Vapour Density and/or Relative Vapour Density | No Data Available |
| Density | No Data Available |
| Relative density | Approximately 1.99 [Ref Std:WATER=1] |
| Water solubility | Nil |
| Solubility- non-water | Not Applicable |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | Not Applicable |
| Decomposition temperature | Not Applicable |
| Viscosity/Kinematic Viscosity | No Data Available |
| Volatile Organic Compounds | No Data Available |
| Percent volatile | 0 % |
| VOC Less H2O & Exempt Solvents | No Data Available |
| Average particle size | No Data Available |
| Bulk density | No Data Available |
| Molecular weight | No Data Available |
| Softening point | No Data Available |

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

Page: 4 of 8

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Not determined

10.5. Incompatible materials

Strong acids

Strong bases

Reactive metals

No Data Available

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No known health effects.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

No known health effects.

Toxicological Data

3MTM P55/R Lubricant, Red

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|-------------|---------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Inhalation- | Rat | LC50 > 0.691 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Rat | LD50 > 5,110 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Rabbit | No significant irritation |

Serious Eve Damage/Irritation

| Name | Species | Value |
|---|---------|---------------------------|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---|---------|----------------|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Human | Not classified |
| | and | |
| | animal | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|---------------|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | In Vitro | Not mutagenic |

Carcinogenicity

| - · · · · · · · · · · · · · · · · · · · | | | |
|---|-----------|---------|--|
| Name | Route | Species | Value |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Not | Mouse | Some positive data exist, but the data are not |
| | Specified | | sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|--|-----------|--|---------|--------------------------|-----------------------------|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesi s |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure |
|---|------------|-----------------------------------|----------------|---------|---------------------|-----------------------|
| | | | | | | Duration |
| Synthetic Amorphous Silica, Fumed, Crystalline | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Free | | | | | | |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty and clean product containers may be disposed as nonhazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS. Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Page: 7 of 8

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 0 Flammability: 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| Document group: | 06-4861-8 | Version number: | 11.05 |
|-----------------|------------|------------------|------------|
| Issue Date: | 2021/06/08 | Supercedes Date: | 2021/03/25 |

Reason for Reissue

Conversion to GHS format SDS.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 8 of 8