

# **Safety Data Sheet**

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 08-6846-3
 Version number:
 15.03

 Issue Date:
 2024/06/12
 Supercedes Date:
 2021/10/13

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>TM</sup> Sprayable Hot Melt Adhesive 6111HT

#### **Product Identification Numbers**

62-6113-7222-8 62-6113-8530-3 62-6113-9331-5 62-6113-9332-3 62-6113-9335-6 62-6113-9337-2 62-6113-9339-8 62-6113-9395-0 62-6113-9399-2 JS-3000-5030-4

### 1.2. Recommended use and restrictions on use

#### **Intended Use**

Industrial use

### Restrictions on use

Not applicable

### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

# **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

Not classified according to the Canadian Hazardous Products Regulation.

### 2.2. Label elements

### Signal word

Not applicable.

**Symbols** 

\_\_\_\_

### 3M™ Sprayable Hot Melt Adhesive 6111HT

Not applicable.

#### **Pictograms**

Not applicable.

#### 2.3. Other hazards

May cause thermal burns.

50% of the mixture consists of ingredients of unknown acute oral toxicity.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
1-Butene, Polymer with	Unknown	30 - 60	Not Applicable
Ethylene and Propene			
Hydrocarbon Resin	Trade Secret	30 - 60	Not Applicable
1-Propene, Polymer with Ethene	9010-79-1	1 - 20	1-Propene, polymer with ethene
Styrene-Butadiene Polymer	Trade Secret	1 - 20	Not Applicable

Hydrocarbon Resin is a non-hazardous Trade Secret material according to WHMIS criteria.

Styrene-Butadiene Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

#### **Skin Contact:**

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

### **Eye Contact:**

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

### If Swallowed:

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Ketones	During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin contact with hot material. For industrial or professional use only. Not for consumer sale or use.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### **Eve/face protection**

None required.

# Skin/hand protection

\_\_\_\_\_

### 3MTM Sprayable Hot Melt Adhesive 6111HT

No chemical protective gloves are required.

### **Respiratory protection**

None required.

### Thermal hazards

Wear heat insulating gloves - Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties					
Physical state	Solid				
Specific Physical Form:	Waxy Solid				
Colour	Light Tan				
Odour	Mild Resinous				
Odour threshold	No Data Available				
рН	Not Applicable				
Melting point/Freezing point	No Data Available				
Boiling point	Not Applicable				
Flash Point	No flash point				
Evaporation rate	Not Applicable				
Flammability	Not Applicable				
Flammable Limits(LEL)	Not Applicable				
Flammable Limits(UEL)	Not Applicable				
Vapour Density and/or Relative Vapour Density	Nil				
Density	0.92 g/ml				
Relative density	0.92 [Ref Std:WATER=1]				
Water solubility	Nil				
Solubility- non-water	No Data Available				
Partition coefficient: n-octanol/ water	No Data Available				
Autoignition temperature	Not Applicable				
Decomposition temperature	No Data Available				
Kinematic Viscosity	Not Applicable				
Volatile Organic Compounds	0 % [Test Method:calculated SCAQMD rule 443.1]				
Percent volatile	0 % weight				
VOC Less H2O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]				
Molecular weight	No Data Available				
Solids Content	100 %				

Particle Characteristics	Not Applicable
r at ticle Characteristics	Noi Applicable

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

\_\_\_\_\_

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

No health effects are expected.

### **Skin Contact:**

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

#### **Eve Contact:**

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

### **Ingestion:**

No known health effects.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbon Resin	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Hydrocarbon Resin	Ingestion	Professio nal judgeme nt	LD50 7,000 mg/kg
1-Propene, Polymer with Ethene	Dermal	Rabbit	LD50 > 2,000 mg/kg

### 3M™ Sprayable Hot Melt Adhesive 6111HT

1-Propene, Polymer with Ethene	Ingestion	Rat	LD50 > 5,000 mg/kg
Styrene-Butadiene Polymer	ner Dermal LD50 estimated to be > 5,000 mg/kg		LD50 estimated to be > 5,000 mg/kg
Styrene-Butadiene Polymer Ingest			LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbon Resin	Professio nal judgeme nt	No significant irritation
1-Propene, Polymer with Ethene	Rabbit	No significant irritation

#### Serious Eve Damage/Irritation

Name	Species	Value
1-Propene, Polymer with Ethene	Rabbit	No significant irritation

#### **Skin Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbon Resin	In Vitro	Not mutagenic

#### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Reproductive Toxicity

### Reproductive and/or Developmental Effects

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Target Organ(s)

### **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Specific Target Organ Toxicity - repeated exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

Page: 6 of 8

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	08-6846-3	Version number:	15.03
Issue Date:	2024/06/12	Supercedes Date:	2021/10/13

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR

PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca