



Safety Data Sheet

Copyright, 2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	08-1690-0	Version number:	15.02
Issue Date:	2020/10/19	Supersedes Date:	2020/04/21

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

1.2. Recommended use and restrictions on use

Intended Use

Marine

Specific Use

Compounding of marine paint.

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Marine & Specialty Vehicle
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 3.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard statements

Flammable liquid and vapour.

May cause drowsiness or dizziness. May cause cancer.

Causes damage to organs through prolonged or repeated exposure: respiratory system |

Precautionary statements

General:

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF exposed or concerned: Get medical advice/attention. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Tripoli (Crystalline Silica)	1317-95-9	30 - 60 Trade Secret *	Tripoli
Water	7732-18-5	10 - 30	Water
KEROSENE	8008-20-6	0 - 19	Kerosine, petroleum
Oleic Acid	112-80-1	1 - 5	9-Octadecenoic acid (Z)-
Hydrotreated light paraffinic distillates (petroleum)	64742-55-8	0 - 1.5	Distillates (petroleum), hydrotreated light paraffinic
Diethanolamine	111-42-2	0.1 - 1	Ethanol, 2,2'-iminobis-

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Diethanolamine	111-42-2	ACGIH	TWA(inhalable fraction and vapour):1 mg/m ³	Danger of cutaneous absorption
Tripoli (Crystalline Silica)	1317-95-9	ACGIH	TWA(respirable fraction):0.025 mg/m ³	
Mineral oils (untreated and mildly treated)	64742-55-8	ACGIH	Limit value not established:	Cntrl all exposr-low as possib
KEROSENE	8008-20-6	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m ³	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Fluoroelastomer

Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Viscous
Colour	Tan
Odour	Slight Pine
Odour threshold	No Data Available
pH	9.4 - 9.6
Melting point/Freezing point	No Data Available
Boiling point	100 °C
Flash Point	56.1 °C [Test Method:Pensky-Martens Closed Cup]
Evaporation rate	>=1 [Ref.Std:ETHER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	1.6 %
Flammable Limits(UEL)	6 %
Vapour Pressure	No Data Available
Viscosity/Kinematic Viscosity Viscosity/Kinematic Viscosity	No Data Available
Density	1.28 - 1.38 g/ml
Relative density	1.28 - 1.38 [Ref.Std:WATER=1]

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

Water solubility	Slight (less than 10%)
Solubility- non-water	Slight (less than 10%)
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	7,000 - 12,000 mPa-s
Volatile Organic Compounds	379 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile Organic Compounds	19.5 % weight [Test Method:calculated per CARB title 2]
Percent volatile	48.7 % weight
VOC Less H2O & Exempt Solvents	508 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No Data Available

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

and throat pain. May cause additional health effects (see below).

Skin Contact:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin. May cause additional health effects (see below).

Eye Contact:

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Silicosis: Signs/symptoms may include breathlessness, weakness, chest pain, persistent cough, increased amounts of sputum, and heart disease.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYST AIRRESP	1317-95-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYST AIRRESP	1317-95-9	Known human carcinogen	National Toxicology Program Carcinogens
Diethanolamine	111-42-2	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Naphthalene	91-20-3	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Naphthalene	91-20-3	Anticipated human carcinogen	National Toxicology Program Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Tripoli (Crystalline Silica)	Dermal		LD50 estimated to be > 5,000 mg/kg
Tripoli (Crystalline Silica)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
KEROSENE	Dermal	Rabbit	LD50 > 2,000 mg/kg
KEROSENE	Inhalation-Vapor (4 hours)	Rat	LC50 > 5 mg/l
KEROSENE	Ingestion	Rat	LD50 > 5,000 mg/kg
Oleic Acid	Dermal	Guinea pig	LD50 > 3,000 mg/kg
Oleic Acid	Ingestion	Rat	LD50 57,000 mg/kg
Diethanolamine	Dermal	Rabbit	LD50 8,180 mg/kg
Diethanolamine	Ingestion	Rat	LD50 1,410 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

Tripoli (Crystalline Silica)	Professional judgement	No significant irritation
KEROSENE	Rabbit	Minimal irritation
Oleic Acid	Rabbit	Minimal irritation
Diethanolamine	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
KEROSENE	Rabbit	No significant irritation
Oleic Acid	Rabbit	Mild irritant
Diethanolamine	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
KEROSENE	Guinea pig	Not classified
Diethanolamine	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Tripoli (Crystalline Silica)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Tripoli (Crystalline Silica)	In vivo	Some positive data exist, but the data are not sufficient for classification
KEROSENE	In Vitro	Some positive data exist, but the data are not sufficient for classification
KEROSENE	In vivo	Some positive data exist, but the data are not sufficient for classification
Oleic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diethanolamine	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Tripoli (Crystalline Silica)	Inhalation	Human and animal	Carcinogenic
KEROSENE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Oleic Acid	Dermal	Mouse	Not carcinogenic
Oleic Acid	Ingestion	Rat	Not carcinogenic
Oleic Acid	Not Specified	Multiple animal species	Not carcinogenic
Diethanolamine	Dermal	Mouse	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
KEROSENE	Dermal	Not classified for female reproduction	Rat	NOAEL 494 mg/kg/day	prematuring & during

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

KEROSENE	Dermal	Not classified for male reproduction	Rat	NOAEL 494 mg/kg/day	gestation pre-mating & during gestation
KEROSENE	Dermal	Not classified for development	Rat	NOAEL 494 mg/kg/day	pre-mating & during gestation
KEROSENE	Inhalation	Not classified for development	Rat	NOAEL 400 ppm	during organogenesis
Diethanolamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 97 mg/kg/day	13 weeks
Diethanolamine	Dermal	Not classified for development	Rabbit	NOAEL 100 mg/kg/day	during organogenesis
Diethanolamine	Ingestion	Not classified for development	Rat	NOAEL 50 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
KEROSENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	occupational exposure
KEROSENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL not available	not available
KEROSENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL not available	poisoning and/or abuse
KEROSENE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL not available	not applicable
KEROSENE	Ingestion	liver	Not classified	Rat	LOAEL 18,912 mg/kg	not applicable
KEROSENE	Ingestion	heart hematopoietic system	Not classified	Human	NOAEL not available	poisoning and/or abuse
Diethanolamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL not available	
Diethanolamine	Ingestion	kidney and/or bladder	May cause damage to organs	Rat	NOAEL 200 mg/kg	not applicable
Diethanolamine	Ingestion	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 200 mg/kg	not applicable
Diethanolamine	Ingestion	liver	Not classified	Rat	NOAEL 1,600 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tripoli (Crystalline Silica)	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
KEROSENE	Dermal	hematopoietic system	Not classified	Mouse	NOAEL 500 mg/kg/day	13 weeks
KEROSENE	Dermal	liver immune system kidney and/or bladder	Not classified	Mouse	NOAEL 500 mg/kg/day	2 years
KEROSENE	Dermal	nervous system	Not classified	Mouse	NOAEL 2,700 mg/kg/day	1 weeks
KEROSENE	Dermal	heart gastrointestinal tract muscles respiratory system	Not classified	Mouse	NOAEL 500 mg/kg/day	2 years

3M™ Marine Super Duty Rubbing Compound / 3M™ Marine Rubbing Compound, 09004

KEROSENE	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL not available	1 years
KEROSENE	Inhalation	liver	Not classified	Rat	NOAEL 0.231 mg/l	14 weeks
KEROSENE	Inhalation	heart	Not classified	Guinea pig	LOAEL 20.4 mg/l	not available
KEROSENE	Inhalation	gastrointestinal tract hematopoietic system muscles respiratory system	Not classified	Multiple animal species	NOAEL 0.1 mg/l	13 weeks
Oleic Acid	Ingestion	liver immune system	Not classified	Rat	NOAEL 2,250 mg/kg/day	108 weeks
Oleic Acid	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,550 mg/kg/day	108 weeks
Diethanolamine	Dermal	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 32 mg/kg/day	13 weeks
Diethanolamine	Dermal	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8 mg/kg/day	2 years
Diethanolamine	Dermal	liver	Not classified	Rat	NOAEL 500 mg/kg/day	13 weeks
Diethanolamine	Inhalation	liver kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	13 weeks
Diethanolamine	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 14 mg/kg/day	13 weeks
Diethanolamine	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 57 mg/kg/day	13 weeks
Diethanolamine	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL not available	13 weeks
Diethanolamine	Ingestion	liver	Not classified	Rat	NOAEL 436 mg/kg/day	13 weeks

Aspiration Hazard

Name	Value
KEROSENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 1 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	08-1690-0	Version number:	15.02
Issue Date:	2020/10/19	Supercedes Date:	2020/04/21

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca