

Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 08-4391-2
 Version number:
 10.08

 Issue Date:
 2024/01/26
 Supercedes Date:
 2023/07/20

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Screen Printable Adhesive SP-7533

Product Identification Numbers

62-4533-7030-6 62-4533-7035-5 62-4533-7530-5 62-4533-7535-4 62-4533-8530-4 62-4533-9530-3 JS-3000-4678-1 JT-2700-6493-7 JT-2700-7301-1 UU-0111-2151-2 WS-2000-2617-7 WT-3000-2333-8 XF-6001-3998-4 XI-0039-0766-8

1.2. Recommended use and restrictions on use

Intended Use

Screen Printable Adhesive

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Health Hazard

Pictograms



Hazard statements

Suspected of causing cancer.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves.

Response:

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Vinylacetate and acrylic ester	Trade Secret	40 - 70	Not Applicable
copolymer			
Water	7732-18-5	15 - 40	Water
Isopropyl Alcohol	67-63-0	<= 0.5	2-Propanol
Vinyl Acetate	108-05-4	<= 0.3	Acetic acid ethenyl ester
Ammonium Hydroxide	1336-21-6	< 0.25	Ammonium hydroxide ((NH4)(OH))
NONYLPHENOXYPOLY(OX	9016-45-9	<= 0.099	Poly(oxy-1,2-ethanediyl), .alpha
YETHYLENE)ETHANOL			(nonylphenyl)omegahydroxy-

Vinylacetate and acrylic ester copolymer is a non-hazardous Trade Secret material according to WHMIS criteria.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If you are concerned, get medical advice.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been

read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Vinyl Acetate	108-05-4	ACGIH	TWA:10 ppm;STEL:15 ppm	
Ammonia	1336-21-6	ACGIH	TWA:25 ppm;STEL:35 ppm	
AMMONIA RELEASED FROM	1336-21-6	ACGIH	TWA:25 ppm;STEL:35 ppm	
AMMONIUM				
HYDROXIDE/AQUEOUS				
AMMONIA SOLUTIONS				
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Butyl Rubber

Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

Page: 4 of 10

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical propertie		
Physical state	Liquid	
Colour	White	
Odour	Slight Acrylic	
Odour threshold	No Data Available	
pH	7	
Melting point/Freezing point	Not Applicable	
Boiling point	Approximately 100 °C	
Flash Point	No flash point	
Evaporation rate	Not Applicable	
Flammability (solid, gas)	Not Applicable	
Flammable Limits(LEL)	Not Applicable	
Flammable Limits(UEL)	Not Applicable	
Vapour Pressure	Not Applicable	
Vapour Density and/or Relative Vapour Density	Not Applicable	
Density	1.02 g/ml	
Relative density	1 - 1.1 [<i>Ref Std</i> :WATER=1]	
Water solubility	Appreciable	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	Not Applicable	
Decomposition temperature	No Data Available	
Viscosity/Kinematic Viscosity	24,000 - 40,000 mPa-s [@ 20 °C]	
Volatile Organic Compounds	No Data Available	
Percent volatile	No Data Available	
VOC Less H2O & Exempt Solvents	<=8 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]	
Molecular weight	No Data Available	
	I	

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong acids Strong bases

Reactive metals

10.6. Hazardous decomposition products

Dagg. 5 of 10

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eve Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Vinyl acetate	108-05-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation- Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Vinyl Acetate	Dermal	Rabbit	LD50 2,320 mg/kg
Vinyl Acetate	Inhalation- Vapor (4 hours)	Rat	LC50 11.3 mg/l

Page: 6 of 10

Vinyl Acetate	Ingestion	Rat	LD50 2,920 mg/kg
Ammonium Hydroxide	Ingestion	Rat	LD50 350 mg/kg
NONYLPHENOXYPOLY(OXYETHYLENE)ETHANOL	Dermal	Rabbit	LD50 2,091 mg/kg
NONYLPHENOXYPOLY(OXYETHYLENE)ETHANOL	Ingestion	Rat	LD50 1,310 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isopropyl Alcohol	Multiple animal species	No significant irritation
Vinyl Acetate	Rabbit	Minimal irritation
Ammonium Hydroxide	Rabbit	Corrosive
NONYLPHENOXYPOLY(OXYETHYLENE)ETHANOL	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Isopropyl Alcohol	Rabbit	Severe irritant
Vinyl Acetate	Rabbit	Mild irritant
Ammonium Hydroxide	Rabbit	Corrosive
NONYLPHENOXYPOLY(OXYETHYLENE)ETHANOL	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
Isopropyl Alcohol	Guinea	Not classified
	pig	
Vinyl Acetate	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Oct in Cent Mudagementy			
Name	Route	Value	
Isopropyl Alcohol	In Vitro	Not mutagenic	
Isopropyl Alcohol	In vivo	Not mutagenic	
Vinyl Acetate	In Vitro	Some positive data exist, but the data are not sufficient for classification	
Vinyl Acetate	In vivo	Some positive data exist, but the data are not sufficient for classification	

Carcinogenicity

en en egenerej			
Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Vinyl Acetate	Ingestion	Multiple animal species	Carcinogenic
Vinyl Acetate	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Reproductive and/or Bevelopmental Effects							
Name	Route	Value	Species	Test result	Exposure		
					Duration		
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000	2 generation		
				mg/kg/day			
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500	2 generation		

				mg/kg/day	
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400	during
				mg/kg/day	organogenesi
					S
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9	during
				mg/l	gestation
Vinyl Acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 140	2 generation
				mg/kg/day	
Vinyl Acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 140	2 generation
				mg/kg/day	
Vinyl Acetate	Ingestion	Not classified for development	Rat	NOAEL 700	2 generation
		-		mg/kg/day	
Vinyl Acetate	Inhalation	Not classified for development	Rat	NOAEL 0.7	during
-		•		mg/l	organogenesi
					S

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Vinyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Vinyl Acetate	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Ammonium Hydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
Vinyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.2 mg/l	104 weeks
Vinyl Acetate	Inhalation	heart hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 2.1 mg/l	104 weeks
Vinyl Acetate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.07 mg/l	120 days
Vinyl Acetate	Inhalation	immune system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	3 months
Vinyl Acetate	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 2.1 mg/l	104 weeks
Vinyl Acetate	Inhalation	gastrointestinal tract	Not classified	Mouse	NOAEL 3.5 mg/l	3 months

Vinyl Acetate	Ingestion	liver	Not classified	Rat	LOAEL 684 mg/kg/day	3 months
Vinyl Acetate	Ingestion	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
Vinyl Acetate	Ingestion	immune system respiratory system	Not classified	Mouse	NOAEL 950 mg/kg/day	3 months
Vinyl Acetate	Ingestion	heart	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to

address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	08-4391-2	Version number:	10.08
Issue Date:	2024/01/26	Supercedes Date:	2023/07/20

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 10 of 10