



## Safety Data Sheet

Copyright,2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 08-8510-3 **Version number:** 25.01  
**Issue Date:** 2023/10/20 **Supersedes Date:** 2023/09/19

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Fire Barrier Water Tight Sealant 1000 NS

#### Product Identification Numbers

98-0400-5276-7 98-0400-5277-5 98-0400-5278-3 98-0400-5280-9 98-0400-5286-6  
98-0400-5287-4 98-0400-5555-4 JE-4100-2480-4 XE-1014-9424-5 XE-1014-9429-4

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Fire Protection

##### Specific Use

This product is a watertight sealant that will help control the spread of fire, smoke and noxious gases.

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

**Company:** 3M Canada Company  
**Division:** Industrial Adhesives and Tapes Division  
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1  
**Telephone:** (800) 364-3577  
**Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

The following product identification number(s) are sold in the consumer market place:  
XE-1014-9424-5

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.  
Carcinogenicity: Category 1B.  
Specific Target Organ Toxicity (repeated exposure): Category 2.

## 2.2. Label elements

### Signal word

Danger

### Symbols

Exclamation mark | Health Hazard |

### Pictograms



### Hazard statements

Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer.

May cause damage to organs through prolonged or repeated exposure: blood or blood-forming organs | respiratory system

### Precautionary statements

#### General:

Keep out of reach of children.

#### Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

#### Storage:

Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

None known.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

2% of the mixture consists of ingredients of unknown acute dermal toxicity.

2% of the mixture consists of ingredients of unknown acute inhalation toxicity.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Calcium Carbonate	1317-65-3	15 - 40	Limestone primarily of calcium carbonate.
Poly(Dimethylsiloxane)	63148-62-9	15 - 40	Siloxanes and Silicones, di-Me
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated	70131-67-8	15 - 40	Siloxanes and Silicones, di-Me, hydroxy-terminated
Ketoxime Silane	22984-54-9	3 - 7 Trade Secret *	2-Butanone, O,O',O''-(methylsilyldyne)trioxime
Amorphous Silica	7631-86-9	0.5 - 5	Silica
Pigments	Mixture	1 - 2	Not Applicable
(Trimethoxysilylpropyl)Ethylene diamine	1760-24-3	0.5 - 1.5 Trade Secret *	1,2-Ethanediamine, N-[3-(trimethoxysilyl)propyl]-
Methyl ethyl ketone oxime	96-29-7	0.01 - 1.2	No Data Available
Octamethylcyclotetrasiloxane	556-67-2	0 - 0.1	Octamethylcyclotetrasiloxane

\*The actual concentration of this ingredient has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Formaldehyde  
Carbon monoxide

#### Condition

During Combustion  
During Combustion

Carbon dioxide  
Oxides of Nitrogen

During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1317-65-3	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1317-65-3	ACGIH	TWA(respirable particles):3 mg/m3	
Octamethylcyclotetrasiloxane	556-67-2	AIHA	TWA:10 ppm	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	7631-86-9	ACGIH	TWA(inhalable particulates):10 mg/m3	
Particles (insoluble or poorly soluble) not otherwise specified,	7631-86-9	ACGIH	TWA(respirable particles):3 mg/m3	

respirable particles				
Methyl ethyl ketone oxime	96-29-7	AIHA	TWA:36 mg/m3(10 ppm)	Dermal Sensitizer

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Gray
<b>Odour</b>	Low Odour
<b>Odour threshold</b>	No Data Available
<b>pH</b>	No Data Available
<b>Melting point/Freezing point</b>	No Data Available

<b>Boiling point</b>	<i>Not Applicable</i>
<b>Flash Point</b>	> 100 °C [ <i>Test Method: Closed Cup</i> ]
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Flammability (solid, gas)</b>	Not Classified
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapour Pressure</b>	< 666.6 Pa [ <i>@ 25 °C</i> ]
<b>Vapour Density and/or Relative Vapour Density</b>	>=1 [ <i>Ref Std: AIR=1</i> ]
<b>Density</b>	1.32 g/cm <sup>3</sup>
<b>Relative density</b>	1.31 - 1.33 [ <i>Ref Std: WATER=1</i> ]
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity/Kinematic Viscosity</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	<=4 % weight [ <i>Test Method: tested per EPA method 24</i> ]
<b>Percent volatile</b>	<i>No Data Available</i>
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	<=53 g/l [ <i>Test Method: tested per EPA method 24</i> ]
<b>Molecular weight</b>	<i>No Data Available</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Not determined

### 10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

### 10.6. Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

## 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

#### Additional Health Effects:

#### Prolonged or repeated exposure may cause target organ effects:

Hematopoietic Effects: Signs/symptoms may include generalized weakness, fatigue and alterations in numbers of circulating blood cells. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Siloxanes and Silcones, Di-Me, Hydroxy-Terminated	Dermal	Rabbit	LD50 > 16,000 mg/kg
Siloxanes and Silcones, Di-Me, Hydroxy-Terminated	Ingestion	Rat	LD50 > 64,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist	Rat	LC50 > 0.691 mg/l

**3M™ Fire Barrier Water Tight Sealant 1000 NS**

	(4 hours)		
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Ketoxime Silane	Dermal	Rat	LD50 > 2,000 mg/kg
Ketoxime Silane	Ingestion	Rat	LD50 2,260 mg/kg
Methyl ethyl ketone oxime	Dermal	official classification	LD50 1,100 mg/kg
Methyl ethyl ketone oxime	Ingestion	official classification	LD50 100 mg/kg
Methyl ethyl ketone oxime	Inhalation-Vapor	Rat	LC50 estimated to be 20 - 50 mg/l
(Trimethoxysilylpropyl)Ethylenediamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
(Trimethoxysilylpropyl)Ethylenediamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 >1.49, <2.44 mg/l
(Trimethoxysilylpropyl)Ethylenediamine	Ingestion	Rat	LD50 1,897 mg/kg
Octamethylcyclotetrasiloxane	Dermal	Rat	LD50 > 2,400 mg/kg
Octamethylcyclotetrasiloxane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 36 mg/l
Octamethylcyclotetrasiloxane	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Amorphous Silica	Rabbit	No significant irritation
Ketoxime Silane	Rabbit	No significant irritation
Methyl ethyl ketone oxime	Rabbit	Irritant
(Trimethoxysilylpropyl)Ethylenediamine	Rabbit	Mild irritant
Octamethylcyclotetrasiloxane	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Amorphous Silica	Rabbit	No significant irritation
Ketoxime Silane	Rabbit	Moderate irritant
Methyl ethyl ketone oxime	Rabbit	Corrosive
(Trimethoxysilylpropyl)Ethylenediamine	Rabbit	Corrosive
Octamethylcyclotetrasiloxane	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Amorphous Silica	Human and animal	Not classified
Ketoxime Silane	Guinea pig	Sensitizing
Methyl ethyl ketone oxime	Guinea pig	Sensitizing
(Trimethoxysilylpropyl)Ethylenediamine	Multiple animal species	Sensitizing
Octamethylcyclotetrasiloxane	Human and animal	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.



**Germ Cell Mutagenicity**

Name	Route	Value
Siloxanes and Silcones, Di-Me, Hydroxy-Terminated	In Vitro	Not mutagenic
Amorphous Silica	In Vitro	Not mutagenic
Ketoxime Silane	In Vitro	Not mutagenic
Methyl ethyl ketone oxime	In Vitro	Not mutagenic
Methyl ethyl ketone oxime	In vivo	Not mutagenic
(Trimethoxysilylpropyl)Ethylenediamine	In Vitro	Not mutagenic
(Trimethoxysilylpropyl)Ethylenediamine	In vivo	Not mutagenic
Octamethylcyclotetrasiloxane	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl ethyl ketone oxime	Inhalation	Multiple animal species	Carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Ketoxime Silane	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	prematuring into lactation
Ketoxime Silane	Ingestion	Not classified for male reproduction	Rat	NOAEL 250 mg/kg/day	28 days
Ketoxime Silane	Ingestion	Not classified for development	Rat	NOAEL 250 mg/kg/day	prematuring into lactation
Methyl ethyl ketone oxime	Ingestion	Not classified for female reproduction	Rat	NOAEL 200 mg/kg/day	2 generation
Methyl ethyl ketone oxime	Ingestion	Not classified for male reproduction	Rat	NOAEL 200 mg/kg/day	2 generation
Methyl ethyl ketone oxime	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	during organogenesis
(Trimethoxysilylpropyl)Ethylenediamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	prematuring into lactation
(Trimethoxysilylpropyl)Ethylenediamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	28 days
(Trimethoxysilylpropyl)Ethylenediamine	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	during gestation
Octamethylcyclotetrasiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.5 mg/l	2 generation
Octamethylcyclotetrasiloxane	Ingestion	Toxic to female reproduction	Rabbit	NOAEL 50 mg/kg/day	during organogenesis
Octamethylcyclotetrasiloxane	Inhalation	Toxic to female reproduction	Rat	NOAEL 3.6 mg/l	2 generation

## Target Organ(s)

## Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Ketoxime Silane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Methyl ethyl ketone oxime	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Methyl ethyl ketone oxime	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL 100 mg/kg	
(Trimethoxysilylpropyl)Ethylenediamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

## Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Amorphous Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Ketoxime Silane	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 10 mg/kg/day	28 days
Ketoxime Silane	Ingestion	endocrine system   liver   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 250 mg/kg/day	28 days
Methyl ethyl ketone oxime	Inhalation	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.36 mg/l	28 days
Methyl ethyl ketone oxime	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Mouse	NOAEL 0.01 mg/l	90 days
Methyl ethyl ketone oxime	Inhalation	liver	Not classified	Rat	NOAEL 1.44 mg/l	28 days
Methyl ethyl ketone oxime	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 25 mg/kg/day	90 days
Methyl ethyl ketone oxime	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	90 days
Methyl ethyl ketone oxime	Ingestion	nervous system	Not classified	Rat	NOAEL 400 mg/kg/day	90 days
Methyl ethyl ketone oxime	Ingestion	liver   kidney and/or bladder   heart   endocrine system   bone, teeth, nails, and/or hair   immune system	Not classified	Rat	NOAEL 335 mg/kg/day	90 days
(Trimethoxysilylpropyl)Ethylenediamine	Dermal	skin   endocrine system   hematopoietic system   kidney and/or bladder	Not classified	Rat	NOAEL 1,545 mg/kg/day	11 days
(Trimethoxysilylpropyl)Ethylenediamine	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.015 mg/l	90 days
(Trimethoxysilylpropyl)Ethylenediamine	Inhalation	hematopoietic system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 0.044 mg/l	90 days

**3M™ Fire Barrier Water Tight Sealant 1000 NS**

(Trimethoxysilylpropyl)Et hylenediamine	Ingestion	hematopoietic system   nervous system	Not classified	Rat	NOAEL 500 mg/kg/day	28 days
Octamethylcyclotetrasiloxa ne	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 960 mg/kg/day	3 weeks
Octamethylcyclotetrasiloxa ne	Inhalation	liver	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
Octamethylcyclotetrasiloxa ne	Inhalation	endocrine system   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 8.5 mg/l	2 generation
Octamethylcyclotetrasiloxa ne	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
Octamethylcyclotetrasiloxa ne	Ingestion	liver	Not classified	Rat	NOAEL 1,600 mg/kg/day	2 weeks

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental

Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **HMIS Hazard Classification**

**Health: \*2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document group:</b>	08-8510-3	<b>Version number:</b>	25.01
<b>Issue Date:</b>	2023/10/20	<b>Supersedes Date:</b>	2023/09/19

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**