

# **Safety Data Sheet**

Copyright,2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	36-0138-2	Version number:	3.00
Issue Date:	2023/01/30	Supercedes Date:	2022/04/04

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

<b>SECTION 1:</b>	Identification
-------------------	----------------

#### 1.1. Product identifier

Scotchgard<sup>™</sup> Rug & Carpet Cleaner (Cat. No. 4107-14, 4107-16)

Product Identification	Numbers			
70-0052-8382-8	70-0052-8384-4	70-0068-4740-7	70-0070-4113-3	70-0070-4114-1
70-0070-7983-6	70-0070-7984-4			

#### 1.2. Recommended use and restrictions on use

# Intended Use

Fabric and carpet cleaner

# **Restrictions on use**

Not applicable

#### 1.3. Supplier's details

Company:	3M Canada Company	
Division:	Home Care Division	
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario	N6A 4T1
Telephone:	(800) 364-3577	
Website:	www.3M.ca	

#### **1.4. Emergency telephone number**

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

# **SECTION 2: Hazard identification**

The following product identification number(s) are sold in the consumer market place: 70006847407

# 2.1. Classification of the substance or mixture


Gas Under Pressure: Liquefied gas. Specific Target Organ Toxicity (single exposure): Category 1.

# 2.2. Label elements

Signal word

Danger

Symbols



# Pictograms



Hazard statements Contains gas under pressure; may explode if heated.

Causes damage to organs: cardiovascular system

**Precautionary statements General:** Keep out of reach of children.

#### **Prevention:**

Do not breathe dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

#### **Response:**

IF exposed or concerned: Call a POISON CENTRE or doctor/physician. Specific treatment (see Notes to Physician on this label).

#### Storage:

Protect from sunlight. Store in a well-ventilated place. Store locked up.

#### **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

# This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Water	7732-18-5	80 - 95	Water
ISOBUTANE	75-28-5	1 - 5 Trade Secret *	Propane, 2-methyl-
STYRENE-MALEIC	26022-09-3	1 - 5	No Data Available
ANHYDRIDE COPOLYMER			
Sodium Mono-C10-16-Alkyl	68585-47-7	1 - 1.5	Sulfuric acid, mono-C10-16-alkyl esters,
Sulfates			sodium saltslcohol sulfuric acid sodium
			salt and SDA Reporting Number: 15-062-
			04. Consult SDA Substance Identification

			Procedure.
LAURYLDIMETHYLAMINE OXIDE	1643-20-5	< 0.2	1-Dodecanamine, N,N-dimethyl-, N-oxide
Sodium Nitrite	7632-00-0	< 0.2	Nitrous acid, sodium salt

\*The actual concentration of this ingredient has been withheld as a trade secret.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. Get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Target organ effects. See Section 11 for additional details.

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### Hazardous Decomposition or By-Products

<u>Condition</u>
During Combustion
During Combustion
During Combustion

#### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

# **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or

bodies of water.

#### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Keep out of reach of children. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

# 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat.

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
ISOBUTANE	75-28-5	ACGIH	STEL:1000 ppm	
Natural gas	75-28-5	ACGIH	Limit value not established:	simple asphyxiant
	. 1 7 1 1 7	· · · ·		

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

# 8.2. Exposure controls

# 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

# **8.2.2.** Personal protective equipment (PPE)

# Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

# **Respiratory protection**

During heating: Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

information on basic physical and chemical properti			
Physical state	Liquid		
Specific Physical Form:	Aerosol		
Colour	Milky White		
Odour	Floral		
Odour threshold	No Data Available		
рН	9.3		
Melting point/Freezing point	Not Applicable		
Boiling point	98 °C - 100 °C [Details:(Liquid Product)]		
Flash Point	No flash point		
Evaporation rate	Not Applicable		
Flammability (solid, gas)	Not Applicable		
Flammable Limits(LEL)	No Data Available		
Flammable Limits(UEL)	No Data Available		
Vapour Pressure	1,999.8 Pa - 2,266.5 Pa [@ 20 °C ] [Test Method: Tested per		
	ASTM protocol] [Details:(Liquid Product)]		
Vapour Density and/or Relative Vapour Density			
Density	1 g/ml [Details:(Liquid Product)]		
Relative density	1 [ <i>Ref Std</i> :WATER=1] [ <i>Details</i> :(Liquid Product)]		
Water solubility	Complete		
Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ water	No Data Available		
Autoignition temperature	Not Applicable		
Decomposition temperature	No Data Available		
Viscosity/Kinematic Viscosity	1.29 mPa-s		
Volatile Organic Compounds	4.9 %		
Percent volatile	Approximately 95 %		
VOC Less H2O & Exempt Solvents	No Data Available		

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2.** Chemical stability Stable.

**10.3. Possibility of hazardous reactions** Hazardous polymerization will not occur.

**10.4. Conditions to avoid** Heat

**10.5. Incompatible materials** None known.

#### 10.6. Hazardous decomposition products

<u>Substance</u>

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

# Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### **Additional Health Effects:**

# Single exposure may cause target organ effects:

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

# **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

# Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
ISOBUTANE	Inhalation- Gas (4 hours)	Rat	LC50 276,000 ppm
Sodium Mono-C10-16-Alkyl Sulfates	Dermal	Rat	LD50 > 2,000 mg/kg
Sodium Mono-C10-16-Alkyl Sulfates	Ingestion	Rat	LD50 1,800 mg/kg
LAURYLDIMETHYLAMINE OXIDE	Dermal	similar compoun ds	LD50 > 2,000 mg/kg
LAURYLDIMETHYLAMINE OXIDE	Ingestion	similar compoun ds	LD50 1,064 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
ISOBUTANE	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Sodium Mono-C10-16-Alkyl Sulfates	Rabbit	Irritant
LAURYLDIMETHYLAMINE OXIDE	similar	Irritant
	compoun	
	ds	

# Serious Eye Damage/Irritation

Name	Species	Value
ISOBUTANE	Professio nal judgeme nt	No significant irritation
Sodium Mono-C10-16-Alkyl Sulfates	Rabbit	Corrosive
LAURYLDIMETHYLAMINE OXIDE	similar compoun	Corrosive
	ds	

#### **Skin Sensitization**

Name	Species	Value
Sodium Mono-C10-16-Alkyl Sulfates	Guinea	Not classified
	pig	
LAURYLDIMETHYLAMINE OXIDE	Guinea	Not classified
	pig	

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
ISOBUTANE	In Vitro	Not mutagenic
Sodium Mono-C10-16-Alkyl Sulfates	In Vitro	Not mutagenic
LAURYLDIMETHYLAMINE OXIDE	In Vitro	Not mutagenic

#### Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

# **Reproductive Toxicity**

#### **Reproductive and/or Developmental Effects**

Reproductive and/or Developmental Effects						
Name	Route	Value	Species	Test result	Exposure Duration	
Sodium Mono-C10-16-Alkyl Sulfates	Ingestion	Not classified for development	Rat	NOAEL 250 mg/kg/day	during organogenesi s	

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
ISOBUTANE	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
ISOBUTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
ISOBUTANE	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Sodium Mono-C10-16- Alkyl Sulfates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
LAURYLDIMETHYLAM INE OXIDE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not Available	

#### **Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
ISOBUTANE	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
LAURYLDIMETHYLAM INE OXIDE	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	similar compoun ds	NOAEL 88 mg/kg/day	90 days

# Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None Aerosol Storage Code: 1

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

# HMIS Hazard ClassificationHealth: 4Flammability: 1Physical Hazard: 0Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	36-0138-2	Version number:	3.00
Issue Date:	2023/01/30	Supercedes Date:	2022/04/04

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

# 3M Canada SDSs are available at www.3M.ca