

# Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 36-3452-4
 Version number:
 3.00

 Issue Date:
 2024/09/25
 Supercedes Date:
 2023/01/05

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> VHB<sup>TM</sup> Tape Universal Primer UV

#### **Product Identification Numbers**

70-0075-0487-4 70-0075-0502-0 70-0075-0505-3 70-0075-0506-1 70-0075-0507-9 70-0075-0508-7 HB-0045-5390-3 HB-0045-5391-1 IA-1201-0222-2 IA-1201-0276-8 JS-3000-4939-7 XF-6001-4059-4 XP-0038-5621-6 XP-0038-5624-0

#### 1.2. Recommended use and restrictions on use

#### **Intended Use**

Adhesion Promoter

#### Restrictions on use

Not applicable

#### 1.3. Supplier's details

**Company:** 3M Canada Company

**Division:** Industrial Adhesives and Tapes Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1800 364 3577

### **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2B.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1A. Aspiration Hazard: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

\_\_\_\_

#### 2.2. Label elements

#### Signal word

Danger

**Symbols** 

Flame | Exclamation mark | Health Hazard |

**Pictograms** 







#### **Hazard statements**

Highly flammable liquid and vapour.

Causes eye irritation. Causes skin irritation. May cause an allergic skin reaction. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness.

#### **Precautionary statements**

#### **Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Call a POISON centre or doctor/physician if you feel unwell. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

None known.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

1% of the mixture consists of ingredients of unknown acute dermal toxicity.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Heptane, branched, cyclic and	426260-76-6	30 - 60 Trade Secret *	No Data Available

linear			
Methyl Acetate	79-20-9	30 - 60 Trade Secret *	Acetic acid, methyl ester
2-Methylhexane	591-76-4	10 - 30 Trade Secret *	Hexane, 2-methyl-
3-Methylhexane	589-34-4	10 - 30 Trade Secret *	Hexane, 3-methyl-
Non-Volatile Polymeric	Trade Secret	1 - 6	Not Applicable
Components			
Citric Acid, Tributyl Ester,	77-90-7	< 2	1,2,3-Propanetricarboxylic acid, 2-
Acetate			(acetyloxy)-, tributyl ester
Dimethylcyclopentane	2532-58-3	< 2	Cyclopentane, 1,3-dimethyl-, cis- Brake
			Cleaner
Beta-(3,4-	3388-04-3	0.1 - 1	Silane, trimethoxy[2-(7-
Epoxycyclohexyl)Ethyltrimetho			oxabicyclo[4.1.0]hept-3-yl)ethyl]-
xy Silane			
Cyclohexane	110-82-7	< 1	Cyclohexane
Methylcyclohexane	108-87-2	< 1	Cyclohexane, methyl-
Maleic Anhydride	108-31-6	< 0.05	2,5-Furandione

Non-volatile polymeric components is a non-hazardous Trade Secret material according to WHMIS criteria.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Do not induce vomiting. Get immediate medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching). Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

# **4.3.** Indication of any immediate medical attention and special treatment required Not applicable.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### 5.2. Unsuitable extinguishing media

None Determined

\_\_\_\_\_

<sup>\*</sup>The actual concentration of this ingredient has been withheld as a trade secret.

#### 5.3. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### **Hazardous Decomposition or By-Products**

Substance
Carbon monoxide
Carbon dioxide

Condition
During Combustion
During Combustion

#### 5.4. Special protection actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

#### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from oxidizing agents.

### **SECTION 8: Exposure controls/personal protection**

\_\_\_\_\_

#### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Maleic Anhydride	108-31-6	ACGIH	TWA(inhalable fraction and	Dermal/Respiratory
-			vapor): 0.01 mg/m3	Sensitizer
Methylcyclohexane	108-87-2	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
3-Methylhexane	589-34-4	ACGIH	TWA:400 ppm;STEL:500 ppm	
2-Methylhexane	591-76-4	ACGIH	TWA:400 ppm;STEL:500 ppm	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

information on basic physical and chemical propertie			
Physical state	Liquid		
Specific Physical Form:	Liquid		
Colour	Colourless		
Odour	Mild Solvent		
Odour threshold	No Data Available		
pH	4.4		
Melting point/Freezing point	Not Applicable		
<b>Boiling point</b>	61.9 °C [@ 101,324.72 Pa ]		
Flash Point	-10 °C [Test Method:Closed Cup]		
Evaporation rate	No Data Available		
Flammability	Flammable Liquid: Category 2.		
Flammable Limits(LEL) 1.2 % [Details:Heptane]			
Flammable Limits(UEL)	16 % [Details: Methyl Acetate]		
Vapour Pressure	20,318.3 Pa [@ 20 °C ]		
Vapour Density and/or Relative Vapour Density	No Data Available		
Density	0.77 g/ml [@ 23 °C ]		
Relative density	0.77 [@ 23 °C ] [Ref Std:WATER=1]		
Water solubility	23 % [@ 23 °C]		
Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ water	No Data Available		
Autoignition temperature	No Data Available		
Decomposition temperature	No Data Available		
Kinematic Viscosity	30.5 mm2/sec		
Volatile Organic Compounds	429 g/l [Test Method:calculated SCAQMD rule 443.1]		
Percent volatile	<=96 % weight [Test Method: Estimated]		
VOC Less H2O & Exempt Solvents	700 g/l [Test Method:calculated SCAQMD rule 443.1]		
Molecular weight	Not Applicable		
	I		

Particle Characteristics Not Applicable
-----------------------------------------

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

Sparks and/or flames

#### 10.5. Incompatible materials

Strong oxidizing agents

# 10.6. Hazardous decomposition products

**Substance Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### **Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Ingestion:**

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

#### **Additional Health Effects:**

#### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Heptane, branched, cyclic and linear	Dermal	Rabbit	LD50 > 2,920 mg/kg
Heptane, branched, cyclic and linear	Inhalation- Vapor (4 hours)	Rat	LC50 > 23.3 mg/l
Heptane, branched, cyclic and linear	Ingestion	Rat	LD50 > 5,840 mg/kg

Page: 7 of 14

	- ·	_	
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-	Rat	LC50 > 49 mg/l
	Vapor (4		
	hours)		
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
3-Methylhexane	Dermal	similar	LD50 > 2,000 mg/kg
, and the second		compoun	
		ds	
3-Methylhexane	Inhalation-	similar	LC50 > 33.5 mg/l
	Vapor (4	compoun	
	hours)	ds	
3-Methylhexane	Ingestion	similar	LD50 > 5,000 mg/kg
5 Welly mexalle	mgestion	compoun	2550 × 3,000 mg/kg
		ds	
2-Methylhexane	Dermal	similar	LD50 > 2,000 mg/kg
2-Methyllicane	Delillai		LD30 > 2,000 mg/kg
		compoun	
2 M-4h-1h	T-1-1-4	ds	L C50 > 22.5 ··· -//
2-Methylhexane	Inhalation-	similar	LC50 > 33.5 mg/l
	Vapor (4	compoun	
***	hours)	ds	
2-Methylhexane	Ingestion	similar	LD50 > 5,000 mg/kg
		compoun	
		ds	
Citric Acid, Tributyl Ester, Acetate	Ingestion	Rat	LD50 > 31,500 mg/kg
Citric Acid, Tributyl Ester, Acetate	Dermal	similar	LD50 estimated to be > 5,000 mg/kg
		health	
		hazards	
Dimethylcyclopentane	Inhalation-	Rat	LC50 > 25.3 mg/l
	Vapor (4		
	hours)		
Dimethylcyclopentane	Ingestion	Rat	LD50 > 5,000 mg/kg
Dimethylcyclopentane	Dermal	similar	LD50 estimated to be > 5,000 mg/kg
y .yp		health	3 3
		hazards	
Methylcyclohexane	Inhalation-	Professio	LC50 estimated to be 20 - 50 mg/l
Mediyleyelollekalle	Vapor	nal	Eco commune to be 20 of mg i
	v upor	judgeme	
		nt	
Methylcyclohexane	Ingestion	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
Methylcyclonexane	ingestion	nal	ED30 estimated to be 2,000 - 3,000 mg/kg
		judgeme	
Medical and all annua	D1	nt	LD50 > 2,000/l
Methylcyclohexane	Dermal	similar	LD50 > 2,000 mg/kg
		compoun	
D . (2.4 E		ds	Y D 50 ( 500
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	Dermal	Rabbit	LD50 6,700 mg/kg
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	Inhalation-	Rat	LC50 > 7  mg/l
	Vapor (4		
	hours)		
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	Ingestion	Rat	LD50 13,100 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-	Rat	LC50 > 32.9 mg/l
	Vapor (4		
	hours)		
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Maleic Anhydride	Dermal	Rabbit	LD50 2,620 mg/kg
Maleic Anhydride	Ingestion	Rat	LD50 1,030 mg/kg
111u1cic / Hillyuriuc	mgestion	rui	1,000 mg/kg

 $\overline{ATE}$  = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
Heptane, branched, cyclic and linear	Rabbit	Irritant
Methyl Acetate	Rabbit	No significant irritation
3-Methylhexane	Professio	Mild irritant
	nal	

Page: 8 of 14

# 3M<sup>TM</sup> VHB<sup>TM</sup> Tape Universal Primer UV

	judgeme	
	nt	
2-Methylhexane	Professio	Mild irritant
	nal	
	judgeme	
	nt	
Citric Acid, Tributyl Ester, Acetate	Rabbit	No significant irritation
Dimethylcyclopentane	Rabbit	No significant irritation
Methylcyclohexane	Rabbit	No significant irritation
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	Rabbit	Minimal irritation
Cyclohexane	Rabbit	Mild irritant
Maleic Anhydride	Human	Corrosive
	and	
	animal	

**Serious Eye Damage/Irritation** 

Name	Species	Value
Heptane, branched, cyclic and linear	Rabbit	Mild irritant
Methyl Acetate	Rabbit	Moderate irritant
3-Methylhexane	similar	Mild irritant
	compoun	
	ds	
2-Methylhexane	similar	Mild irritant
	compoun	
	ds	
Citric Acid, Tributyl Ester, Acetate	Rabbit	Mild irritant
Dimethylcyclopentane	Rabbit	Mild irritant
Methylcyclohexane	Rabbit	No significant irritation
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	Rabbit	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Maleic Anhydride	Rabbit	Corrosive

# **Skin Sensitization**

Name	Species	Value
Heptane, branched, cyclic and linear	Guinea	Not classified
<u>F</u> ,, -)	pig	
Methyl Acetate	Human	Not classified
3-Methylhexane	similar	Not classified
	compoun	
	ds	
2-Methylhexane	similar	Not classified
·	compoun	
	ds	
Citric Acid, Tributyl Ester, Acetate	Guinea	Not classified
	pig	
Dimethylcyclopentane	similar	Not classified
	compoun	
	ds	
Methylcyclohexane	similar	Not classified
	compoun	
	ds	
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	similar	Sensitizing
	compoun	
	ds	
Maleic Anhydride	Multiple	Sensitizing
	animal	
	species	

**Respiratory Sensitization** 

Name	Species	Value
Maleic Anhydride	Human	Sensitizing

Page: 9 of 14

**Germ Cell Mutagenicity** 

Name	Route	Value
Heptane, branched, cyclic and linear	In Vitro	Not mutagenic
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
3-Methylhexane	In Vitro	Not mutagenic
2-Methylhexane	In Vitro	Not mutagenic
Citric Acid, Tributyl Ester, Acetate	In Vitro	Not mutagenic
Citric Acid, Tributyl Ester, Acetate	In vivo	Not mutagenic
Dimethylcyclopentane	In vivo	Not mutagenic
Dimethylcyclopentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methylcyclohexane	In Vitro	Not mutagenic
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Maleic Anhydride	In vivo	Not mutagenic
Maleic Anhydride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Citric Acid, Tributyl Ester, Acetate	Ingestion	Rat	Not carcinogenic
Methylcyclohexane	Inhalation	Multiple	Not carcinogenic
		animal	
		species	
Beta-(3,4-Epoxycyclohexyl)Ethyltrimethoxy Silane	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Heptane, branched, cyclic and linear	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Heptane, branched, cyclic and linear	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Heptane, branched, cyclic and linear	Not Specified	Not classified for development	Rat	NOAEL Not available	2 generation
Citric Acid, Tributyl Ester, Acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Citric Acid, Tributyl Ester, Acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Citric Acid, Tributyl Ester, Acetate	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
Methylcyclohexane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Methylcyclohexane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Beta-(3,4- Epoxycyclohexyl)Ethyltrimethoxy Silane	Ingestion	Not classified for development	Rabbit	NOAEL 0.27 mg/kg/day	during organogenesi s
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Maleic Anhydride	Ingestion	Not classified for female reproduction	Rat	NOAEL 55	2 generation

# 3M<sup>TM</sup> VHB<sup>TM</sup> Tape Universal Primer UV

				mg/kg/day	
Maleic Anhydride	Ingestion	Not classified for male reproduction	Rat	NOAEL 55	2 generation
-		_		mg/kg/day	
Maleic Anhydride	Ingestion	Not classified for development	Rat	NOAEL 140	during
		•		mg/kg/day	organogenesi
					S

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

specific ranger Organ	TOXICITY - S	migic exposure				
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Heptane, branched, cyclic and linear	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
3-Methylhexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
3-Methylhexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
3-Methylhexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Methylhexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Methylhexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-Methylhexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Dimethylcyclopentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Dimethylcyclopentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Methylcyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Methylcyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Maleic Anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration

Page: 11 of 14

Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
3-Methylhexane	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
3-Methylhexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks
3-Methylhexane	Inhalation	hematopoietic system   kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
2-Methylhexane	Inhalation	nervous system	Not classified	Rat	NOAEL 6.15 mg/l	30 weeks
2-Methylhexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 12.5 mg/l	16 weeks
2-Methylhexane	Inhalation	hematopoietic system   kidney and/or bladder	Not classified	Rat	NOAEL 12.2 mg/l	26 weeks
Citric Acid, Tributyl Ester, Acetate	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Citric Acid, Tributyl Ester, Acetate	Ingestion	immune system   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Citric Acid, Tributyl Ester, Acetate	Ingestion	heart   endocrine system   hematopoietic system   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Dimethylcyclopentane	Inhalation	liver   kidney and/or bladder   heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles   nervous system   eyes   respiratory system   vascular system	Not classified	Rat	NOAEL 20.2 mg/l	13 weeks
Dimethylcyclopentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL 800 mg/kg/day	8 weeks
Dimethylcyclopentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	4 weeks
Methylcyclohexane	Inhalation	kidney and/or bladder   heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   liver   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder   heart   gastrointestinal tract	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

D 12 C 14

Cyclohexane	Inhalation	bone, teeth, nails, and/or hair   immune system   muscles   nervous system   eyes   respiratory system	Not classified	Rat	NOAEL 24	90 days
Cyclonicxane	Illiaiation	nvei	Tvot classified	Kat	mg/l	70 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Maleic Anhydride	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
Maleic Anhydride	Inhalation	endocrine system   hematopoietic system   nervous system   kidney and/or bladder   heart   liver   eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
Maleic Anhydride	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
Maleic Anhydride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
Maleic Anhydride	Ingestion	heart   nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
Maleic Anhydride	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
Maleic Anhydride	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
Maleic Anhydride	Ingestion	skin   endocrine system   immune system   eyes   respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

**Aspiration Hazard** 

ispii attoii 11azai u					
Name	Value				
Heptane, branched, cyclic and linear	Aspiration hazard				
3-Methylhexane	Aspiration hazard				
2-Methylhexane	Aspiration hazard				
Dimethylcyclopentane	Aspiration hazard				
Methylcyclohexane	Aspiration hazard				
Cyclohexane	Aspiration hazard				

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

# 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

#### 3M<sup>TM</sup> VHB<sup>TM</sup> Tape Universal Primer UV

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

# **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	36-3452-4	Version number:	3.00
Issue Date:	2024/09/25	Supercedes Date:	2023/01/05

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES. EXPRESS OR IMPLIED. STATUTORY OR OTHERWISE. INCLUDING. BUT NOT LIMITED TO. ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE. COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

#### 3M Canada SDSs are available at www.3M.ca