

## Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	37-6003-0	Version number:	1.03
Issue Date:	2022/03/11	Supercedes Date:	2020/10/29

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotchcast<sup>TM</sup> Potting Kit 2136 (Part A, Part B and CC-3)

#### **Product Identification Numbers**

80-6114-6849-9

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Electrical

#### 1.3. Supplier's details

**Company:** 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577

E Mail:

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

30-1314-1, 11-4628-1, 29-4839-6

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 2 of 2



## Safety Data Sheet

Copyright, 2022, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 29-4839-6
 Version number:
 4.04

 Issue Date:
 2022/03/11
 Supercedes Date:
 2020/10/09

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Scotchcast<sup>TM</sup> Wet-Niche Potting Compound 2136 (Part A)

#### **Product Identification Numbers**

LH-A100-0949-9 LH-A100-1638-9

## 1.2. Recommended use and restrictions on use

#### **Intended Use**

Electrical

### **Specific Use**

Part A of two-part electrical resin.

#### Restrictions on use

Not applicable

#### 1.3. Supplier's details

**Company:** 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

## **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2. Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

## 3M™ Scotchcast™ Wet-Niche Potting Compound 2136 (Part A)

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

## Signal word

Danger

#### **Symbols**

Exclamation mark | Health Hazard |

#### **Pictograms**





#### Hazard statements

Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure: respiratory system

### **Precautionary statements**

#### **Prevention:**

Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

## **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

### Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
POLYETHER-	154517-54-1	35 - 45	Poly[oxy(methyl-1,2-ethanediyl)], .alpha
HYDROCARBON-			hydroomegahydroxy-, polymers with
URETHANE POLYMER			hydroxy-terminated polybutadiene and

Page: 2 of 11

			1,1'-methylenebis[isocyanatobenzene]
P,P'-	101-68-8	15 - 40 Trade Secret *	Benzene, 1,1'-methylenebis[4-isocyanato-
METHYLENEBIS(PHENYL			
ISOCYANATE)			
DIUNDECYL PHTHALATE	3648-20-2	< 15	1,2-Benzenedicarboxylic acid, diundecyl
			ester
DIUNDECYL PHTHALATE,	85507-79-5	< 15	1,2-Benzenedicarboxylic acid, diundecyl
BRANCHED AND LINEAR			ester, branched and linear
BENZENE, 1,1'-	39310-05-9	5 - 13 Trade Secret *	Benzene, 1,1'-methylenebis[isocyanato-,
METHYLENEBIS[ISOCYANA			homopolymer
TO-, HOMOPOLYMER			
1,1'-	26447-40-5	1 - 5 Trade Secret *	Benzene, 1,1'-methylenebis[isocyanato-
METHYLENEBIS(ISOCYANA			
TOBENZENE)			
1,1,3-TRIS(3-TERT-BUTYL-4-	1843-03-4	0.1 - 1 Trade Secret *	No Data Available
HYDROXY-6-			
METHYLPHENYL)BUTANE			

<sup>\*</sup>The actual concentration of this ingredient has been withheld as a trade secret.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

## **Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

## **Hazardous Decomposition or By-Products**

Substance

Carbon monoxide During Combustion

Condition

## 3M™ Scotchcast™ Wet-Niche Potting Compound 2136 (Part A)

Carbon dioxide Hydrogen Cyanide Oxides of Nitrogen

**During Combustion During Combustion During Combustion** 

### 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Protect from sunlight. Store away from heat. Store away from strong bases. Store away from areas where product may come into contact with food or pharmaceuticals. Store in a dry place.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-	101-68-8	ACGIH	TWA:0.005 ppm	
METHYLENEBIS(PHENYL				

## 3M<sup>TM</sup> Scotchcast<sup>TM</sup> Wet-Niche Potting Compound 2136 (Part A)

## ISOCYANATE)

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

**Indirect Vented Goggles** 

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Light Straw
Odour	Pungent Odour
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	>=148.9 °C
Flash Point	>=148.9 °C [Test Method:Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable

Flammable Limits(LEL)	No Data Available		
Flammable Limits(UEL)	No Data Available		
Vapour Pressure	No Data Available		
Vapour Density and/or Relative Vapour Density	No Data Available		
Density	No Data Available		
Relative density	1.08 [Ref Std:WATER=1]		
Water solubility	Nil		
Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ water	No Data Available		
Autoignition temperature	No Data Available		
Decomposition temperature	No Data Available		
Viscosity/Kinematic Viscosity	700 - 900 mPa-s		
Volatile Organic Compounds	No Data Available		
Percent volatile	No Data Available		
VOC Less H2O & Exempt Solvents	10.5 g/l		
Average particle size	No Data Available		
Bulk density	No Data Available		
Molecular weight	No Data Available		
Softening point	No Data Available		

#### **Nanoparticles**

This material does not contain nanoparticles.

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

#### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

#### 10.4. Conditions to avoid

None known.

## 10.5. Incompatible materials

Strong bases

Alcohols

Water

#### 10.6. Hazardous decomposition products

## Substance

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be

present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

#### **Skin Contact:**

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### **Eve Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

### Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

#### **Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
POLYETHER-HYDROCARBON-URETHANE POLYMER	Dermal		LD50 estimated to be > 5,000 mg/kg
POLYETHER-HYDROCARBON-URETHANE POLYMER	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Ingestion	Rat	LD50 31,600 mg/kg
DIUNDECYL PHTHALATE	Dermal	Rabbit	LD50 > 7,900 mg/kg
DIUNDECYL PHTHALATE	Ingestion	Rat	LD50 > 15,000 mg/kg
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	Dermal	Rat	LD50 > 2,000 mg/kg
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	Ingestion	Rat	LD50 > 15,800 mg/kg
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-,	Dermal	Rabbit	LD50 > 5,000 mg/kg
HOMOPOLYMER			
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-,	Inhalation-	Rat	LC50 0.368 mg/l
HOMOPOLYMER	Dust/Mist		
	(4 hours)		
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-,	Ingestion	Rat	LD50 31,600 mg/kg
HOMOPOLYMER			

1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Ingestion	Rat	LD50 31,600 mg/kg
1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-	Dermal	Rat	LD50 > 2,000 mg/kg
METHYLPHENYL)BUTANE			
1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-	Ingestion	Rat	LD50 > 5,000 mg/kg
METHYLPHENYL)BUTANE	_		

ATE = acute toxicity estimate

## **Skin Corrosion/Irritation**

Name	Species	Value
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	official classifica tion	Irritant
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	Rabbit	No significant irritation
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER	official classifica tion	Irritant
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official classifica tion	Irritant
1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE	In vitro data	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	official	Severe irritant
	classifica	
	tion	
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	Rabbit	Mild irritant
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER	official	Severe irritant
	classifica	
	tion	
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official	Severe irritant
	classifica	
	tion	
1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE	In vitro	No significant irritation
	data	

## **Skin Sensitization**

Name	Species	Value
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	official	Sensitizing
	classifica	
	tion	
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	Human	Not classified
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER	official	Sensitizing
	classifica	
	tion	
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official	Sensitizing
	classifica	
	tion	
1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE	Mouse	Sensitizing

**Respiratory Sensitization** 

Name	Species	Value
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Human	Sensitizing
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER	Human	Sensitizing
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Human	Sensitizing

Page: 8 of 11

**Germ Cell Mutagenicity** 

Name	Route	Value
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	In Vitro	Some positive data exist, but the data are not sufficient for classification
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	In Vitro	Not mutagenic
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1,3-TRIS(3-TERT-BUTYL-4-HYDROXY-6-METHYLPHENYL)BUTANE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
BENZENE, 1,1'-METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
P,P'-METHYLENEBIS(PHENYL ISOCYANATE)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,100 mg/kg/day	21 days
DIUNDECYL PHTHALATE, BRANCHED AND LINEAR	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
BENZENE, 1,1'- METHYLENEBIS[ISOCYANATO-, HOMOPOLYMER	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s
1,1'- METHYLENEBIS(ISOCYANATOBENZE NE)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesi s

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
P,P'- METHYLENEBIS(PHEN YL ISOCYANATE)	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
BENZENE, 1,1'- METHYLENEBIS[ISOCY ANATO-, HOMOPOLYMER	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
1,1'- METHYLENEBIS(ISOCY ANATOBENZENE)	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
P,P'- METHYLENEBIS(PHEN YL ISOCYANATE)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
DIUNDECYL PHTHALATE,	Ingestion	liver	Not classified	Rat	NOAEL 2,100	21 days

Page: 9 of 11

BRANCHED AND LINEAR					mg/kg/day	
BENZENE, 1,1'- METHYLENEBIS[ISOCY ANATO-, HOMOPOLYMER	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
1,1'- METHYLENEBIS(ISOCY ANATOBENZENE)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
1,1,3-TRIS(3-TERT- BUTYL-4-HYDROXY-6- METHYLPHENYL)BUT ANE	Ingestion	endocrine system   hematopoietic system   liver   eyes	Not classified	Rat	NOAEL 392 mg/kg/day	13 weeks

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

No data available.

## **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to

p. 10 c 1

address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### **HMIS Hazard Classification**

Health: \*3 Flammability: 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	29-4839-6	Version number:	4.04
Issue Date:	2022/03/11	Supercedes Date:	2020/10/09

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

#### 3M Canada SDSs are available at www.3M.ca



## **Safety Data Sheet**

Copyright, 2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 30-1314-1
 Version number:
 4.04

 Issue Date:
 2020/10/22
 Supercedes Date:
 2018/10/03

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>™</sup> Scotchcast<sup>™</sup> Wet-Niche Potting Compound 2136 (Part B)

#### 1.2. Recommended use and restrictions on use

#### **Intended Use**

Electrical

#### Specific Use

Part B of two-part electrical resin.

#### Restrictions on use

Not applicable

### 1.3. Supplier's details

**Company:** 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577 **Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

## **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1. Carcinogenicity: Category 2.

#### 2.2. Label elements

Signal word

Danger

**Symbols** 

Corrosion | Health Hazard |

**Pictograms** 



#### **Hazard statements**

Causes serious eye damage. Suspected of causing cancer.

## **Precautionary statements**

#### **Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves and eye/face protection.

## **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician. IF exposed or concerned: Get medical advice/attention.

#### Storage:

Store locked up.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

None known.

3% of the mixture consists of ingredients of unknown acute oral toxicity.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
1,3-BUTADIENE,	69102-90-5	35 - 45	1,3-Butadiene, homopolymer, hydroxy-
HOMOPOLYMER,			terminated
HYDROXY-TERMINATED			
DIUNDECYL PHTHALATE	3648-20-2	15 - 25	1,2-Benzenedicarboxylic acid, diundecyl
			ester
Polypropylene glycol	25322-69-4	10 - 20	Poly[oxy(methyl-1,2-ethanediyl)], .alpha
			hydroomegahydroxy-
N,N-DI(2-	3077-13-2	7 - 13 Trade Secret *	2-Propanol, 1,1'-(phenylimino)bis-
HYDROXYPROPYL)			
ANILINE			
DIPROPYLENE GLYCOL	25265-71-8	5 - 10	Propanol, oxybis-
4,4'-METHYLENEBIS(2,6-	13680-35-8	1 - 6	Benzenamine, 4,4'-methylenebis[2,6-
DIETHYLANILINE)			diethyl-
ALUMINUM POTASSIUM	12736-96-8	1 - 5	Silicic acid, aluminum potassium sodium
SODIUM SILICATE			salt

Page: 2 of 10

## **3M<sup>TM</sup> Scotchcast<sup>TM</sup> Wet-Niche Potting Compound 2136 (Part B)**

Carbon Black	1333-86-4	1 - 5 Trade Secret *	Carbon black
Castor oil	8001-79-4	1 - 5	Castor oil

<sup>\*</sup>The actual concentration of this ingredient has been withheld as a trade secret.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## 5.3. Special protective actions for fire-fighters

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air.

#### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

D 2 C 10

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3	
			mg/m3	
Polypropylene glycol	25322-69-4	AIHA	TWA(as aerosol):10 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

#### Skin/hand protection

No chemical protective gloves are required.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

information on basic physical and chemical properties	
Physical state	Liquid
Colour	Black
Odour	Characteristic Odour
Odour threshold	No Data Available
рН	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	> 148.9 °C
Flash Point	> 300 °C
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapour Pressure	< 186,158.4 Pa [@ 55 °C]
Viscosity/Kinematic Viscosity Viscosity/Kinematic	No Data Available
Viscosity	
Density	No Data Available
Relative density	0.98 [Details:Ref Std: Water = 1]
Water solubility	Not Applicable
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	1,600 mPa-s - 2,000 mPa-s
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available
Average particle size	Not Applicable
Bulk density	No Data Available
Molecular weight	No Data Available
Softening point	No Data Available

## Nanoparticles

This material contains nanoparticles.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

## 10.4. Conditions to avoid

Sparks and/or flames

\_\_\_\_\_

#### 10.5. Incompatible materials

Not determined

No Data Available

### 10.6. Hazardous decomposition products

**Substance** Condition Carbon monoxide Not Specified Not Specified Carbon dioxide

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Vapours released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### **Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation.

### **Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### **Ingestion:**

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY- TERMINATED	Dermal		LD50 estimated to be > 5,000 mg/kg

1,3-BUTADIENE, HOMOPOLYMER, HYDROXY- TERMINATED	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
DIUNDECYL PHTHALATE	Dermal	Rabbit	LD50 > 7,900 mg/kg
DIUNDECYL PHTHALATE	Ingestion	Rat	LD50 > 15,000 mg/kg
Polypropylene glycol	Dermal	Rabbit	LD50 > 10,000 mg/kg
Polypropylene glycol	Ingestion	Rat	LD50 > 2,000 mg/kg
N,N-DI(2-HYDROXYPROPYL) ANILINE	Dermal	Rabbit	LD50 > 2,000 mg/kg
N,N-DI(2-HYDROXYPROPYL) ANILINE	Ingestion	Rat	LD50 3,800 mg/kg
DIPROPYLENE GLYCOL	Dermal	Rabbit	LD50 > 5,010 mg/kg
DIPROPYLENE GLYCOL	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.34 mg/l
DIPROPYLENE GLYCOL	Ingestion	Rat	LD50 > 5,010 mg/kg
4,4'-METHYLENEBIS(2,6-DIETHYLANILINE)	Ingestion	Rat	LD50 1,901 mg/kg
Castor oil	Dermal		LD50 estimated to be > 5,000
Castor oil	Ingestion		LD50 estimated to be > 5,000
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Polypropylene glycol	Rabbit	No significant irritation
N,N-DI(2-HYDROXYPROPYL) ANILINE	Professio	Minimal irritation
	nal	
	judgeme	
	nt	
DIPROPYLENE GLYCOL	Rabbit	No significant irritation
4,4'-METHYLENEBIS(2,6-DIETHYLANILINE)	Rabbit	Minimal irritation
Castor oil	Human	Minimal irritation
Carbon Black	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
Polypropylene glycol	Rabbit	No significant irritation
N,N-DI(2-HYDROXYPROPYL) ANILINE	Professio	Corrosive
	nal	
	judgeme	
	nt	
DIPROPYLENE GLYCOL	Rabbit	No significant irritation
4,4'-METHYLENEBIS(2,6-DIETHYLANILINE)	Rabbit	No significant irritation
Castor oil	Rabbit	Mild irritant
Carbon Black	Rabbit	No significant irritation

## **Skin Sensitization**

Name	Species	Value
DIPROPYLENE GLYCOL	Guinea	Not classified
	pig	
Castor oil	Human	Not classified

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
DIPROPYLENE GLYCOL	In Vitro	Not mutagenic
DIPROPYLENE GLYCOL	In vivo	Not mutagenic
4,4'-METHYLENEBIS(2,6-DIETHYLANILINE)	In Vitro	Not mutagenic
Castor oil	In Vitro	Not mutagenic

Page: 7 of 10

## 3M<sup>TM</sup> Scotchcast<sup>TM</sup> Wet-Niche Potting Compound 2136 (Part B)

Castor oil	In vivo	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not
		sufficient for classification

#### Carcinogenicity

Name	Route	Species	Value
DIPROPYLENE GLYCOL	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

## Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
DIPROPYLENE GLYCOL	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesi
					S

## Target Organ(s)

## Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
DIPROPYLENE GLYCOL	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 470 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	heart	Not classified	Rat	NOAEL 470 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	endocrine system   liver	Not classified	Rat	NOAEL 3,040 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 115 mg/kg/day	105 weeks
DIPROPYLENE GLYCOL	Ingestion	skin   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   vascular system	Not classified	Rat	NOAEL 3,040 mg/kg/day	105 weeks
Castor oil	Ingestion	heart   hematopoietic system   liver	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
Castor oil	Ingestion	kidney and/or bladder	Not classified	Mouse	NOAEL 13,000 mg/kg/day	13 weeks
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

\_\_\_\_\_

## **SECTION 12: Ecological information**

No data available.

## **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	30-1314-1	Version number:	4.04
Issue Date:	2020/10/22	Supercedes Date:	2018/10/03

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca



# **Safety Data Sheet**

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 11-4628-1
 Version number:
 19.07

 Issue Date:
 2023/05/08
 Supercedes Date:
 2022/06/24

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> Cable Preparation Kit CC-3 (Bag)

#### **Product Identification Numbers**

UK-REAC-0005- GBCDMS00140 GBCDMS00272 GBCDMS00275 GBC	CDMS00278
1 GBCDMS00299 GBCDMS00304 GBCDMS00307 GBCDMS00316 GBC	CDMS00319
	8141-5782-8
80-6105-9300-8 80-6114-2770-1 80-6116-0612-2 CE-1006-9099-5 CE-	1006-9182-9
CE-1006-9199-3 CE-1006-9288-4 CE-1006-9289-2 CE-1006-9329-6 CE-	1006-9424-5
CE-1006-9468-2 CE-1006-9576-2 CE-1006-9585-3 CE-1006-9587-9 CE-	1006-9588-7
CE-1006-9589-5 CE-1006-9590-3 CE-1006-9591-1 CE-1006-9592-9 CE-	1006-9614-1
CE-1006-9969-9 FQ-1000-7576-8 J6-4900-1202-4 JE-4100-4639-3 JE-4	4100-4640-1
JE-4100-4641-9 JE-4100-4642-7 JE-4100-4643-5 JE-4100-4644-3 JE-4	4100-4645-0
JE-4100-4646-8 JE-4100-4647-6 JE-4100-4652-6 JE-4100-4735-9 JE-4	4100-4736-7
JE-4100-4737-5 JE-4100-4738-3 JE-4100-4739-1 JE-4100-4740-9 JE-4	4100-4741-7
JE-4100-4742-5 JE-4100-4743-3 JE-4100-4744-1 JE-4100-4745-8 JE-4	4100-4746-6
JE-4100-4747-4 JE-4100-4748-2 JE-4100-4749-0 JE-4100-4750-8 JE-4	4100-4751-6
JE-4100-4752-4 RE-0002-3970-7 RE-0005-5660-5 UU-0103-3488-4 UU-	-0117-9990-3
UU-0117-9991-1 UU-0117-9992-9 UU-0117-9993-7 WE-0001-7202-6 XE-	-1014-7228-2

#### 1.2. Recommended use and restrictions on use

#### **Intended Use**

Electrical

## **Specific Use**

Solvent soaked pads for cleaning cable.

### Restrictions on use

Not applicable

## 1.3. Supplier's details

**Company:** 3M Canada Company **Division:** Electrical Markets Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577

## 3M<sup>TM</sup> Cable Preparation Kit CC-3 (Bag)

Website: www.3M.ca

## 1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

## **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 4. Skin Sensitizer: Category 1B.

#### 2.2. Label elements

#### Signal word

Warning

#### **Symbols**

Exclamation mark

## **Pictograms**



#### Hazard statements

Combustible liquid.

May cause an allergic skin reaction.

## **Precautionary statements**

#### **Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Contaminated work clothing must not be allowed out of the workplace.

### **Response:**

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### Storage:

Store in a well-ventilated place.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Other hazards

None known.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
HYDROTREATED HEAVY	64742-48-9	50 - 70	Naphtha, petroleum, hydrotreated heavy
NAPHTHA (PETROLEUM)			
Cotton Pads	None	25 - 40	Not Applicable
D-LIMONENE	5989-27-5	5 - 20	Cyclohexene, 1-methyl-4-(1-
			methylethenyl)-, (R)-

Cotton Pads is a non-hazardous Trade Secret material according to WHMIS criteria.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eve Contact:**

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## 5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

\_\_\_\_\_

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces.

- No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
D-LIMONENE	5989-27-5	AIHA	TWA:165.5 mg/m3(30 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### **Eye/face protection**

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Nitrile Rubber

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile Apron – polymer laminate

## **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical properties			
Physical state	Solid (Lint-free cloths soaked with liquid)		
Specific Physical Form:	Cloth pads soaked in liquid in can or bag		
Colour	White		
Odour	Citrus		
Odour threshold	No Data Available		
рН	7		
Melting point/Freezing point	No Data Available		
Boiling point	193.3 °C - 248.9 °C		
Flash Point	62.2 °C [Test Method:Closed Cup]		
Evaporation rate	No Data Available		
Flammability (solid, gas)	Not Classified		
Flammable Limits(LEL)	No Data Available		
Flammable Limits(UEL)	No Data Available		
Vapour Pressure	< 133.3 Pa [@ 25 °C]		
Vapour Density and/or Relative Vapour Density	> 1 [ <i>Ref Std</i> :AIR=1]		
Density	0.76 g/ml		
Relative density	0.76 [Ref Std:WATER=1]		
Water solubility Nil			
Solubility- non-water	No Data Available		
Partition coefficient: n-octanol/ water	No Data Available		
Autoignition temperature	No Data Available		
Decomposition temperature	No Data Available		
Viscosity/Kinematic Viscosity	1.5 mPa-s		
Volatile Organic Compounds Approximately 740 %			
Percent volatile	No Data Available		
VOC Less H2O & Exempt Solvents 760 g/l			
Molecular weight	No Data Available		

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

#### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Sparks and/or flames

#### 10.5. Incompatible materials

Strong oxidizing agents

## 10.6. Hazardous decomposition products

Condition **Substance** Carbon monoxide Not Specified Carbon dioxide Not Specified

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

#### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eve Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

## **Ingestion:**

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Inhalation- Vapor		LC50 estimated to be 20 - 50 mg/l
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
D-LIMONENE	Inhalation-	Mouse	LC50 > 3.14  mg/l

## 3M<sup>TM</sup> Cable Preparation Kit CC-3 (Bag)

	Vapor (4 hours)		
D-LIMONENE	Dermal	Rabbit	LD50 > 5,000 mg/kg
D-LIMONENE	Ingestion	Rat	LD50 4,400 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

5mm C0110500m/11100000			
Name	Species	Value	
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Rabbit	Minimal irritation	
D-LIMONENE	Rabbit	Mild irritant	

## **Serious Eye Damage/Irritation**

Name		Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Rabbit	Mild irritant
D-LIMONENE	Rabbit	Mild irritant

## **Skin Sensitization**

Name	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Guinea	Not classified
	pig	
D-LIMONENE	Mouse	Sensitizing

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Ser in Centification				
Name	Route	Value		
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In Vitro	Not mutagenic		
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	In vivo	Not mutagenic		
D-LIMONENE	In Vitro	Not mutagenic		
D-LIMONENE	In vivo	Not mutagenic		

Carcinogenicity

Name	Route	Species	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not available	Not carcinogenic
D-LIMONENE	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for female reproduction	Not available	NOAEL NA	1 generation
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for male reproduction	Not available	NOAEL NA	28 days
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Not Specified	Not classified for development	Not applicabl e	NOAEL NA	during gestation
D-LIMONENE	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	premating & during gestation
D-LIMONENE	Ingestion	Not classified for development	Multiple animal species	NOAEL 591 mg/kg/day	during organogenesi s

Page: 7 of 9

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
D-LIMONENE	Ingestion	nervous system	Not classified		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
D-LIMONENE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 75 mg/kg/day	103 weeks
D-LIMONENE	Ingestion	liver	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
D-LIMONENE	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 600 mg/kg/day	103 weeks

**Aspiration Hazard** 

Name	Value
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)	Aspiration hazard
D-LIMONENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## **SECTION 12: Ecological information**

No data available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **HMIS Hazard Classification**

**Health:** 2 Flammability: 2 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	11-4628-1	Version number:	19.07
Issue Date:	2023/05/08	Supercedes Date:	2022/06/24

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

#### 3M Canada SDSs are available at www.3M.ca