



Safety Data Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	32-6787-9	Version number:	4.00
Issue Date:	2023/01/06	Supersedes Date:	2020/10/22

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Threadlocker TL43, Blue

Product Identification Numbers

62-3428-1060-3	62-3428-1065-2	62-3428-3960-2	62-3428-5060-9	62-3428-8360-0
UU-0015-0356-2	UU-0015-0358-8	UU-0015-0360-4	UU-0015-0366-1	UU-0015-0379-4
UU-0015-0380-2	UU-0015-1095-5	UU-0015-1096-3	UU-0015-1125-0	UU-0015-5279-1
UU-0015-5311-2	UU-0015-6016-6			

1.2. Recommended use and restrictions on use

Intended Use

Adhesive

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Industrial Adhesives and Tapes Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2A.
 Skin Corrosion/Irritation: Category 2.
 Skin Sensitizer: Category 1.
 Carcinogenicity: Category 1B.
 Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements**Signal word**

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard statements**

Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction. May cause cancer.

Causes damage to organs through prolonged or repeated exposure: nervous system | respiratory system |

Precautionary statements**Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Triethylene Glycol Dimethacrylate	109-16-0	30 - 60 Trade Secret *	2-Propenoic acid, 2-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester
Diisopropylnaphthalene	38640-62-9	15 - 40 Trade Secret *	Naphthalene, bis(1-methylethyl)-
Amorphous Silica	68909-20-6	1 - 10	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica

Hydroxypropyl Methacrylate	27813-02-1	5 - 10 Trade Secret *	2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol
Polyester Resin	Trade Secret	1 - 10	Not Applicable
Cumene Hydroperoxide	80-15-9	1 - 5 Trade Secret *	Hydroperoxide, 1-methyl-1-phenylethyl
Silica	67762-90-7	1 - 5	Siloxanes and Silicones, di-Me, reaction products with silica
Saccharin	81-07-2	<= 2	1,2-Benzisothiazol-3(2H)-one, 1,1-dioxide
1-Acetyl-2-Phenylhydrazine	114-83-0	0.1 - 1 Trade Secret *	Acetic acid, 2-phenylhydrazide
2,2'-(P-Tolylimino)diethanol	3077-12-1	< 1	Ethanol, 2,2'-[(4-methylphenyl)imino]bis-
Acrylic Acid	79-10-7	< 1	2-Propenoic acid
Ethylene Glycol	107-21-1	< 1	1,2-Ethanediol
N,N-Dimethyl-p-toluidine	99-97-8	0.1 - 1 Trade Secret *	Benzenamine, N,N,4-trimethyl-
Naphthalene, (1-methylethyl)-	29253-36-9	< 1	No Data Available
2,6-di-tert-Butyl-p-cresol	128-37-0	<= 0.5	Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-
Titanium Dioxide	13463-67-7	<= 0.1	Titanium oxide (TiO2)

Polyester Resin is a non-hazardous Trade Secret material according to WHMIS criteria.

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Condition

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen
Oxides of Sulfur

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylene Glycol	107-21-1	ACGIH	TWA(Vapor fraction):25 ppm;STEL(Vapor fraction):50 ppm;STEL(Inhalable aerosol):10 mg/m3	
2,6-di-tert-Butyl-p-cresol	128-37-0	ACGIH	TWA(inhalable fraction and	

			vapor):2 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	
Acrylic Acid	79-10-7	ACGIH	TWA:2 ppm	Danger of cutaneous absorption
Cumene Hydroperoxide	80-15-9	AIHA	TWA:6 mg/m3(1 ppm)	SKIN
N,N-Dimethyl-p-toluidine	99-97-8	AIHA	TWA:0.5 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety Glasses with side shields
- Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

- Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
----------------	--------

Specific Physical Form:	Thixotropic Liquid
Colour	Blue
Odour	Mild Odour
Odour threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point	≥ 148.9 °C [<i>@ 101,324.72 Pa</i>]
Flash Point	≥ 100 °C [<i>Test Method: Tagliabue Closed Cup</i>]
Evaporation rate	Negligible
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapour Pressure	≤ 666.6 Pa
Vapour Density and/or Relative Vapour Density	1.01 [<i>Ref Std: AIR=1</i>]
Density	1.1 - 1.15 g/ml [<i>@ 20 °C</i>]
Relative density	1.1 - 1.15 [<i>@ 20 °C</i>] [<i>Ref Std: WATER=1</i>]
Water solubility	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity/Kinematic Viscosity	2,500 - 4,000 mPa-s [<i>@ 20 °C</i>]
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	< 5 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Light

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Dimethyl-p-toluidine	99-97-8	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Triethylene Glycol Dimethacrylate	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg

3M™ Scotch-Weld™ Threadlocker TL43, Blue

Triethylene Glycol Dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg
Diisopropyl naphthalene	Dermal	Rat	LD50 > 4,500 mg/kg
Diisopropyl naphthalene	Inhalation-Dust/Mist	Rat	LC50 > 5.64 mg/l
Diisopropyl naphthalene	Ingestion	Rat	LD50 4,130 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 11,200 mg/kg
Saccharin	Dermal		LD50 estimated to be > 5,000 mg/kg
Saccharin	Ingestion	Mouse	LD50 17,000 mg/kg
Cumene Hydroperoxide	Dermal	Rat	LD50 500 mg/kg
Cumene Hydroperoxide	Inhalation-Vapor (4 hours)	Rat	LC50 1.4 mg/l
Cumene Hydroperoxide	Ingestion	Rat	LD50 382 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Acrylic Acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Acrylic Acid	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3.8 mg/l
Acrylic Acid	Ingestion	Rat	LD50 1,250 mg/kg
Ethylene Glycol	Ingestion	Human	LD50 1,600 mg/kg
Ethylene Glycol	Inhalation-Dust/Mist (4 hours)	Other	LC50 estimated to be 5 - 12.5 mg/l
Ethylene Glycol	Dermal	Rabbit	9,530 mg/kg
1-Acetyl-2-Phenylhydrazine	Dermal		LD50 estimated to be 200 - 1,000 mg/kg
1-Acetyl-2-Phenylhydrazine	Ingestion	Mouse	LD50 270 mg/kg
2,6-di-tert-Butyl-p-cresol	Dermal	Rat	LD50 > 2,000 mg/kg
2,6-di-tert-Butyl-p-cresol	Ingestion	Rat	LD50 > 2,930 mg/kg
N,N-Dimethyl-p-toluidine	Ingestion	Mouse	LD50 140 mg/kg
N,N-Dimethyl-p-toluidine	Dermal	Rabbit	LD50 > 2,000 mg/kg
N,N-Dimethyl-p-toluidine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.4 mg/l
2,2'-(P-Tolylimino)diethanol	Dermal	Rabbit	LD50 > 2,000 mg/kg
2,2'-(P-Tolylimino)diethanol	Ingestion	Rat	LD50 959 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Triethylene Glycol Dimethacrylate	Guinea pig	Mild irritant
Diisopropyl naphthalene	Rabbit	Minimal irritation
Amorphous Silica	Rabbit	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Minimal irritation
Cumene Hydroperoxide	Rabbit	Corrosive
Silica	Rabbit	No significant irritation
Acrylic Acid	Rabbit	Corrosive
Ethylene Glycol	Rabbit	Minimal irritation
2,6-di-tert-Butyl-p-cresol	Human	Minimal irritation

	and animal	
N,N-Dimethyl-p-toluidine	Rabbit	No significant irritation
2,2'-(P-Tolylimino)diethanol	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Triethylene Glycol Dimethacrylate	Professional judgement	Moderate irritant
Diisopropyl naphthalene	Rabbit	Severe irritant
Amorphous Silica	Rabbit	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
Cumene Hydroperoxide	Rabbit	Corrosive
Silica	Rabbit	No significant irritation
Acrylic Acid	Rabbit	Corrosive
Ethylene Glycol	Rabbit	Mild irritant
2,6-di-tert-Butyl-p-cresol	Rabbit	Mild irritant
N,N-Dimethyl-p-toluidine	Rabbit	No significant irritation
2,2'-(P-Tolylimino)diethanol	Rabbit	Corrosive
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Triethylene Glycol Dimethacrylate	Human and animal	Sensitizing
Diisopropyl naphthalene	Guinea pig	Not classified
Amorphous Silica	Human and animal	Not classified
Hydroxypropyl Methacrylate	Human and animal	Sensitizing
Silica	Human and animal	Not classified
Acrylic Acid	Guinea pig	Not classified
Ethylene Glycol	Human	Not classified
1-Acetyl-2-Phenylhydrazine	Professional judgement	Sensitizing
2,6-di-tert-Butyl-p-cresol	Human	Not classified
N,N-Dimethyl-p-toluidine	Guinea pig	Sensitizing
2,2'-(P-Tolylimino)diethanol	Mouse	Sensitizing
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Triethylene Glycol Dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Diisopropylnaphthalene	In Vitro	Not mutagenic
Diisopropylnaphthalene	In vivo	Not mutagenic
Amorphous Silica	In Vitro	Not mutagenic
Hydroxypropyl Methacrylate	In vivo	Not mutagenic
Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cumene Hydroperoxide	In vivo	Not mutagenic
Cumene Hydroperoxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica	In Vitro	Not mutagenic
Acrylic Acid	In vivo	Not mutagenic
Acrylic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethylene Glycol	In Vitro	Not mutagenic
Ethylene Glycol	In vivo	Not mutagenic
1-Acetyl-2-Phenylhydrazine	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,6-di-tert-Butyl-p-cresol	In Vitro	Not mutagenic
2,6-di-tert-Butyl-p-cresol	In vivo	Not mutagenic
N,N-Dimethyl-p-toluidine	In vivo	Not mutagenic
N,N-Dimethyl-p-toluidine	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,2'-(P-Tolylimino)diethanol	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Triethylene Glycol Dimethacrylate	Dermal	Mouse	Not carcinogenic
Diisopropylnaphthalene	Ingestion	Rat	Not carcinogenic
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Acrylic Acid	Ingestion	Rat	Not carcinogenic
Acrylic Acid	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylene Glycol	Ingestion	Multiple animal species	Not carcinogenic
2,6-di-tert-Butyl-p-cresol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
N,N-Dimethyl-p-toluidine	Ingestion	Multiple animal species	Carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Triethylene Glycol Dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene Glycol Dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene Glycol Dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
Diisopropylnaphthalene	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	during organogenesis

3M™ Scotch-Weld™ Threadlocker TL43, Blue

Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Acrylic Acid	Ingestion	Not classified for female reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic Acid	Ingestion	Not classified for male reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic Acid	Inhalation	Not classified for development	Rat	NOAEL 1.1 mg/l	during organogenesis
Acrylic Acid	Ingestion	Not classified for development	Rat	NOAEL 53 mg/kg/day	2 generation
Ethylene Glycol	Dermal	Not classified for development	Mouse	NOAEL 3,549 mg/kg/day	during organogenesis
Ethylene Glycol	Ingestion	Not classified for development	Mouse	LOAEL 750 mg/kg/day	during organogenesis
Ethylene Glycol	Inhalation	Not classified for development	Mouse	NOAEL 1,000 mg/kg/day	during organogenesis
2,6-di-tert-Butyl-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-di-tert-Butyl-p-cresol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
2,6-di-tert-Butyl-p-cresol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
N,N-Dimethyl-p-toluidine	Ingestion	Not classified for female reproduction	Rat	NOAEL 60 mg/kg/day	90 days

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Diisopropyl-naphthalene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Hydroxypropyl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Cumene Hydroperoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Cumene Hydroperoxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Cumene Hydroperoxide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

3M™ Scotch-Weld™ Threadlocker TL43, Blue

Acrylic Acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Ethylene Glycol	Ingestion	heart nervous system kidney and/or bladder respiratory system	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylene Glycol	Ingestion	liver	Not classified	Human	NOAEL Not available	poisoning and/or abuse
2,2'-(P-Tolylimino)diethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Triethylene Glycol Dimethacrylate	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
Diisopropyl naphthalene	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 170 mg/kg/day	6 months
Diisopropyl naphthalene	Ingestion	liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 170 mg/kg/day	6 months
Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydroxypropyl Methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxypropyl Methacrylate	Ingestion	hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Cumene Hydroperoxide	Inhalation	nervous system respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	7 days
Cumene Hydroperoxide	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	90 days
Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Ethylene Glycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	vascular system	Not classified	Rat	NOAEL 200 mg/kg/day	2 years
Ethylene Glycol	Ingestion	heart hematopoietic system liver immune system muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	respiratory system	Not classified	Mouse	NOAEL 12,000 mg/kg/day	2 years
Ethylene Glycol	Ingestion	skin endocrine system bone, teeth, nails, and/or hair nervous system eyes	Not classified	Multiple animal species	NOAEL 1,000 mg/kg/day	2 years
1-Acetyl-2-Phenylhydrazine	Ingestion	hematopoietic system	Causes damage to organs through prolonged or repeated exposure	Dog	LOAEL 4 mg/kg/day	7 days
2,6-di-tert-Butyl-p-cresol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	28 days
2,6-di-tert-Butyl-p-cresol	Ingestion	kidney and/or	Not classified	Rat	NOAEL 500	2 generation

		bladder			mg/kg/day	
2,6-di-tert-Butyl-p-cresol	Ingestion	blood	Not classified	Rat	LOAEL 420 mg/kg/day	40 days
2,6-di-tert-Butyl-p-cresol	Ingestion	endocrine system	Not classified	Rat	NOAEL 25 mg/kg/day	2 generation
2,6-di-tert-Butyl-p-cresol	Ingestion	heart	Not classified	Mouse	NOAEL 3,480 mg/kg/day	10 weeks
N,N-Dimethyl-p-toluidine	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 20 mg/kg/day	3 months
N,N-Dimethyl-p-toluidine	Ingestion	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 20 mg/kg/day	2 years
N,N-Dimethyl-p-toluidine	Ingestion	liver immune system kidney and/or bladder heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair muscles nervous system eyes vascular system	Not classified	Rat	NOAEL 60 mg/kg/day	2 years
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Diisopropyl-naphthalene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	32-6787-9	Version number:	4.00
Issue Date:	2023/01/06	Supersedes Date:	2020/10/22

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca