

Safety Data Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 31-7612-0
 Version number:
 6.00

 Issue Date:
 2023/04/17
 Supercedes Date:
 2020/10/22

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Super Silicone Sealant (Black), 08662, 08664

Product Identification Numbers

60-4550-7161-7 60-4550-7163-3 62-5248-1609-7

1.2. Recommended use and restrictions on use

Intended Use

Automotive

Specific Use

General purpose bonding and sealing, as well as formed-in-place gasket applications.

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company **Division:** Automotive Aftermarket

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion Exclamation mark | Health Hazard |





Hazard statements

Causes serious eye damage. Causes skin irritation. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. Suspected of causing cancer.

Precautionary statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves and eve/face protection. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. Immediately call a POISON CENTRE or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

May cause chemical gastrointestinal burns.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

11% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
SILOXANES AND	70131-67-8	60 - 100	Siloxanes and Silicones, di-Me, hydroxy-
SILICONES, DI-ME,			terminated
HYDROXY-TERMINATED			

Page: 2 of 12

Silica	7631-86-9	5 - 10	Silica
Siloxanes and Silicones, di-Me	63148-62-9	5 - 10	Siloxanes and Silicones, di-Me
Solvent Refined Hydrotreated	64742-46-7	5 - 10	Distillates, petroleum, hydrotreated middle
Middle Distillate			
ETHYLTRIACETOXYSILANE	17689-77-9	1 - 5 Trade Secret *	Silanetriol, ethyl-, triacetate
METHYLTRIACETOXYSILA	4253-34-3	1 - 5 Trade Secret *	Silanetriol, methyl-, triacetate
NE			
Carbon Black	1333-86-4	0.1 - 1 Trade Secret *	Carbon black
DECAMETHYLCYCLOPENT	541-02-6	<= 1	Cyclopentasiloxane, decamethyl-
ASILOXANE			
OCTAMETHYLCYCLOTETR	556-67-2	0 - 1	Octamethylcyclotetrasiloxane
ASILOXANE			
POLYDIMETHYLCYCLOSIL	69430-24-6	<= 1	Cyclosiloxanes, di-Me
OXANE			
Stannane, dimethylbis[(1-	68928-76-7	0 - 0.1	No Data Available
oxoneodecyl)oxy]-			

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Carbon monoxide Carbon dioxide

Condition

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3	
			mg/m3	
DECAMETHYLCYCLOPENTA	541-02-6	AIHA	TWA:10 ppm	
SILOXANE				
OCTAMETHYLCYCLOTETRA	556-67-2	AIHA	TWA:10 ppm	
SILOXANE				
TIN, ORGANIC COMPOUNDS	68928-76-7	ACGIH	TWA(as Sn):0.1	SKIN
			mg/m3;STEL(as Sn):0.2	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Colour	Black
Odour	Acetic Acid
Odour threshold	No Data Available
pH	No Data Available
Melting point/Freezing point	No Data Available

Page: 5 of 12

Boiling point	No Data Available	
Flash Point	>=212 °C [Test Method:Closed Cup]	
Evaporation rate	No Data Available	
Flammability (solid, gas)	Not Applicable	
Flammable Limits(LEL)	No Data Available	
Flammable Limits(UEL)	No Data Available	
Vapour Pressure	No Data Available	
Vapour Density and/or Relative Vapour Density	No Data Available	
Density	1 g/ml	
Relative density	1 [Ref Std:WATER=1]	
Water solubility	No Data Available	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Viscosity/Kinematic Viscosity	No Data Available	
Volatile Organic Compounds	<=3 % weight [Test Method:calculated per CARB title 2]	
Volatile Organic Compounds	<=0.3 g/l [Test Method:calculated SCAQMD rule 443.1]	
Percent volatile	No Data Available	
VOC Less H2O & Exempt Solvents	<=30 g/l [Test Method:calculated SCAQMD rule 443.1]	

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

SubstanceConditionFormaldehydeHeat

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	CAS No.	Class Description	Regulation
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
SILOXANES AND SILICONES, DI-ME, HYDROXY- TERMINATED	Dermal	Rabbit	LD50 > 16,000 mg/kg
SILOXANES AND SILICONES, DI-ME, HYDROXY- TERMINATED	Ingestion	Rat	LD50 > 64,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me	Dermal	Rabbit	LD50 > 19,400 mg/kg
Solvent Refined Hydrotreated Middle Distillate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Siloxanes and Silicones, di-Me	Ingestion	Rat	LD50 > 17,000 mg/kg
Solvent Refined Hydrotreated Middle Distillate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 4.6 mg/l
Solvent Refined Hydrotreated Middle Distillate	Ingestion	Rat	LD50 > 5,000 mg/kg
ETHYLTRIACETOXYSILANE	Ingestion	Rat	LD50 1,462 mg/kg
METHYLTRIACETOXYSILANE	Ingestion	Rat	LD50 1,602 mg/kg
DECAMETHYLCYCLOPENTASILOXANE	Dermal	Rabbit	LD50 > 15,000 mg/kg
DECAMETHYLCYCLOPENTASILOXANE	Inhalation-	Rat	LC50 8.7 mg/l

	Dust/Mist		
	(4 hours)		
DECAMETHYLCYCLOPENTASILOXANE	Ingestion	Rat	LD50 > 24,134 mg/kg
OCTAMETHYLCYCLOTETRASILOXANE	Dermal	Rat	LD50 > 2,400 mg/kg
OCTAMETHYLCYCLOTETRASILOXANE	Inhalation-	Rat	LC50 36 mg/l
	Dust/Mist		
	(4 hours)		
OCTAMETHYLCYCLOTETRASILOXANE	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Stannane, dimethylbis[(1-oxoneodecyl)oxy]-	Ingestion	Rat	LD50 892 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Silica	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
Solvent Refined Hydrotreated Middle Distillate	Rabbit	Minimal irritation
ETHYLTRIACETOXYSILANE	Rabbit	Corrosive
METHYLTRIACETOXYSILANE	Rabbit	Corrosive
DECAMETHYLCYCLOPENTASILOXANE	Rabbit	No significant irritation
OCTAMETHYLCYCLOTETRASILOXANE	Rabbit	Minimal irritation
Carbon Black	Rabbit	No significant irritation
Stannane, dimethylbis[(1-oxoneodecyl)oxy]-	In vitro	Irritant
	data	

Serious Eye Damage/Irritation

Name	Species	Value
Silica	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me	Rabbit	No significant irritation
Solvent Refined Hydrotreated Middle Distillate	Not	Mild irritant
	available	
ETHYLTRIACETOXYSILANE	similar	Corrosive
	health	
	hazards	
METHYLTRIACETOXYSILANE	Rabbit	Corrosive
DECAMETHYLCYCLOPENTASILOXANE	Rabbit	No significant irritation
OCTAMETHYLCYCLOTETRASILOXANE	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation
Stannane, dimethylbis[(1-oxoneodecyl)oxy]-	In vitro	No significant irritation
	data	

Skin Sensitization

Name	Species	Value
Silica	Human	Not classified
	and	
	animal	
ETHYLTRIACETOXYSILANE	Guinea	Not classified
	pig	
METHYLTRIACETOXYSILANE	Guinea	Not classified
	pig	
DECAMETHYLCYCLOPENTASILOXANE	Mouse	Not classified
OCTAMETHYLCYCLOTETRASILOXANE	Human	Not classified
	and	
	animal	
Stannane, dimethylbis[(1-oxoneodecyl)oxy]-	similar	Sensitizing
	compoun	
	ds	

Respiratory SensitizationFor the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SILOXANES AND SILICONES, DI-ME, HYDROXY-TERMINATED	In Vitro	Not mutagenic
Silica	In Vitro	Not mutagenic
Solvent Refined Hydrotreated Middle Distillate	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHYLTRIACETOXYSILANE	In Vitro	Not mutagenic
METHYLTRIACETOXYSILANE	In Vitro	Not mutagenic
DECAMETHYLCYCLOPENTASILOXANE	In Vitro	Not mutagenic
DECAMETHYLCYCLOPENTASILOXANE	In vivo	Not mutagenic
OCTAMETHYLCYCLOTETRASILOXANE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Stannane, dimethylbis[(1-oxoneodecyl)oxy]-	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Solvent Refined Hydrotreated Middle Distillate	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
DECAMETHYLCYCLOPENTASILOXANE	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
DECAMETHYLCYCLOPENTASILOXA NE	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.43 mg/l	2 generation
DECAMETHYLCYCLOPENTASILOXA NE	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.43 mg/l	2 generation
DECAMETHYLCYCLOPENTASILOXA NE	Inhalation	Not classified for development	Rat	NOAEL 2.43 mg/l	2 generation
OCTAMETHYLCYCLOTETRASILOXA NE	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.5 mg/l	2 generation
OCTAMETHYLCYCLOTETRASILOXA NE	Ingestion	Toxic to female reproduction	Rabbit	NOAEL 50 mg/kg/day	during organogenesi s
OCTAMETHYLCYCLOTETRASILOXA NE	Inhalation	Toxic to female reproduction	Rat	NOAEL 3.6 mg/l	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

opecinc Target Organ Toxicity - single exposure						
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Solvent Refined Hydrotreated Middle	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for	Not available	NOAEL NA	

Page: 9 of 12

Distillate		respiratory irritation	classification			
Solvent Refined Hydrotreated Middle	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Not available	NOAEL NA	
Distillate						
ETHYLTRIACETOXYSI LANE	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
METHYLTRIACETOXYS ILANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
DECAMETHYLCYCLOP ENTASILOXANE	Dermal	hematopoietic system eyes	Not classified	Rat	NOAEL 1,600 mg/kg/day	28 days
DECAMETHYLCYCLOP ENTASILOXANE	Inhalation	hematopoietic system respiratory system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 2.42 mg/l	2 years
DECAMETHYLCYCLOP ENTASILOXANE	Ingestion	liver immune system respiratory system heart hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
OCTAMETHYLCYCLOT ETRASILOXANE	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 960 mg/kg/day	3 weeks
OCTAMETHYLCYCLOT ETRASILOXANE	Inhalation	liver	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
OCTAMETHYLCYCLOT ETRASILOXANE	Inhalation	endocrine system immune system kidney and/or bladder	Not classified	Rat	NOAEL 8.5 mg/l	2 generation
OCTAMETHYLCYCLOT ETRASILOXANE	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
OCTAMETHYLCYCLOT ETRASILOXANE	Ingestion	liver	Not classified	Rat	NOAEL 1,600 mg/kg/day	2 weeks
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

_	110 011 1110 1111 1111 1111 1111 1111 1111 1111 1111					
Ī	Name	Value				
	Solvent Refined Hydrotreated Middle Distillate	Aspiration hazard				

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative. incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered. stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 Flammability: 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	31-7612-0	Version number:	6.00
Issue Date:	2023/04/17	Supercedes Date:	2020/10/22

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES

Page: 11 of 12

NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca