



Safety Data Sheet

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 31-0315-7 | Version number: | 3.05 |
| Issue Date: | 2020/10/22 | Supersedes Date: | 2019/02/04 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61

Product Identification Numbers

62-5269-2830-4 62-5269-2835-3

1.2. Recommended use and restrictions on use

Intended Use

Accelerator

Restrictions on use

Not applicable

1.3. Supplier's details

| | |
|-------------------|------------------------------------------------------------------------|
| Company: | 3M Canada Company |
| Division: | Industrial Adhesives and Tapes Division |
| Address: | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| Telephone: | (800) 364-3577 |
| Website: | www.3M.ca |

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 4.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard statements

Combustible liquid.

May cause drowsiness or dizziness. May damage fertility or the unborn child.

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---------------------------------------------------------|------------|------------------------|------------------------------------------------------------------------|
| Calcium Carbonate | 471-34-1 | 40 - 60 | Carbonic acid calcium salt (1:1) |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | 64742-47-8 | 10 - 30 Trade Secret * | Distillates, petroleum, hydrotreated light |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | 68515-49-1 | 10 - 30 Trade Secret * | 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich |
| DMDEE | 6425-39-4 | 1 - 5 | Morpholine, 4,4'-(oxydi-2,1-ethanediyl)bis- |
| NON HAZARDOUS INGREDIENTS | Mixture | 1 - 5 | Not Applicable |
| Titanium Dioxide | 13463-67-7 | 1 - 5 | Titanium oxide (TiO2) |

NON HAZARDOUS INGREDIENTS is a non-hazardous Trade Secret material according to WHMIS criteria.

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|---------------------------|-------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Irritant Vapours or Gases | During Combustion |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|----------------------|------------|--------|--------------------------------------------------------|---------------------|
| Titanium Dioxide | 13463-67-7 | ACGIH | TWA:10 mg/m3 | |
| Kerosine (petroleum) | 64742-47-8 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3 | SKIN |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-------------------------------------------------------------------------|----------------------------------------------------|
| Physical state | Liquid |
| Specific Physical Form: | Paste |
| Colour | White |
| Odour | Light Odour |
| Odour threshold | <i>No Data Available</i> |
| pH | <i>No Data Available</i> |
| Melting point/Freezing point | <i>No Data Available</i> |
| Boiling point | 190 °C |
| Flash Point | 70 °C [Test Method:Closed Cup] |
| Evaporation rate | <i>No Data Available</i> |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | 0.6 % volume |
| Flammable Limits(UEL) | 7 % volume |
| Vapour Pressure | <i>No Data Available</i> |
| Viscosity/Kinematic Viscosity Viscosity/Kinematic Viscosity | <i>No Data Available</i> |
| Density | 1.4 g/ml |
| Relative density | 1.4 [Ref Std:WATER=1] |
| Water solubility | Moderate |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | >=200 °C |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity/Kinematic Viscosity | 200,000 mPa-s |
| Volatile Organic Compounds | <=24 % |
| Percent volatile | |
| VOC Less H2O & Exempt Solvents | 359 g/l [Test Method:calculated SCAQMD rule 443.1] |
| Molecular weight | <i>No Data Available</i> |

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

| Ingredient | CAS No. | Class Description | Regulation |
|------------------|------------|-------------------------------|---------------------------------------------|
| Titanium Dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---------------------------------------------------------|--------------------------------|---------|------------------------------------------------|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Calcium Carbonate | Dermal | Rat | LD50 > 2,000 mg/kg |
| Calcium Carbonate | Inhalation-Dust/Mist (4 hours) | Rat | LC50 3 mg/l |
| Calcium Carbonate | Ingestion | Rat | LD50 6,450 mg/kg |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Dermal | Rabbit | LD50 > 3,160 mg/kg |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 3 mg/l |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Ingestion | Rat | LD50 > 5,000 mg/kg |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Dermal | Rabbit | LD50 > 3,160 mg/kg |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 12.5 mg/l |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Ingestion | Rat | LD50 > 9,700 mg/kg |
| DMDEE | Dermal | Rabbit | LD50 3,030 mg/kg |
| DMDEE | Ingestion | Rat | LD50 2,020 mg/kg |
| Titanium Dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium Dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---------------------------------------------------------|---------|---------------------------|
| Calcium Carbonate | Rabbit | No significant irritation |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Rabbit | Mild irritant |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Rabbit | Minimal irritation |
| DMDEE | Rabbit | Mild irritant |
| Titanium Dioxide | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---------------------------------------------------------|---------|---------------------------|
| Calcium Carbonate | Rabbit | No significant irritation |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Rabbit | Mild irritant |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Rabbit | Mild irritant |
| DMDEE | Rabbit | Severe irritant |
| Titanium Dioxide | Rabbit | No significant irritation |

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61**Skin Sensitization**

| Name | Species | Value |
|---------------------------------------------------------|------------------|----------------|
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Guinea pig | Not classified |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Guinea pig | Not classified |
| DMDEE | Guinea pig | Not classified |
| Titanium Dioxide | Human and animal | Not classified |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---------------------------------------------------------|----------|---------------|
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | In Vitro | Not mutagenic |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | In Vitro | Not mutagenic |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | In vivo | Not mutagenic |
| DMDEE | In Vitro | Not mutagenic |
| DMDEE | In vivo | Not mutagenic |
| Titanium Dioxide | In Vitro | Not mutagenic |
| Titanium Dioxide | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|------------------------------------------|------------|-------------------------|------------------------------------------------------------------------------|
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium Dioxide | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|---------------------------------------------------------|-----------|----------------------------------------|---------|---------------------|-------------------------------|
| Calcium Carbonate | Ingestion | Not classified for development | Rat | NOAEL 625 mg/kg/day | pre mating & during gestation |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Ingestion | Not classified for female reproduction | Rat | NOAEL 927 mg/kg/day | 2 generation |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Ingestion | Not classified for male reproduction | Rat | NOAEL 929 mg/kg/day | 2 generation |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Ingestion | Toxic to development | Rat | NOAEL 38 mg/kg/day | 2 generation |
| DMDEE | Ingestion | Not classified for female reproduction | Rat | NOAEL 300 mg/kg/day | pre mating into lactation |
| DMDEE | Ingestion | Not classified for male reproduction | Rat | NOAEL 300 mg/kg/day | 28 days |
| DMDEE | Ingestion | Not classified for development | Rat | NOAEL 300 mg/kg/day | pre mating into lactation |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|-------------------|------------|--------------------|----------------|---------|------------------|-------------------|
| Calcium Carbonate | Inhalation | respiratory system | Not classified | Rat | NOAEL 0.812 mg/l | 90 minutes |

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61

| | | | | | | |
|------------------------------------------|------------|-----------------------------------|------------------------------------------------------------------------------|------------------------|---------------------|--|
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| DMDEE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---------------------------------------------------------|------------|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|---------|---------------------|-----------------------|
| Calcium Carbonate | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Inhalation | respiratory system hematopoietic system liver | Not classified | Rat | NOAEL 0.5 mg/l | 2 weeks |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 0.5 mg/l | 2 generation |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Ingestion | endocrine system | Not classified | Rat | NOAEL 686 mg/kg/day | 90 days |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Ingestion | liver kidney and/or bladder heart | Not classified | Rat | NOAEL 500 mg/kg/day | 90 days |
| PHTHALIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10 RICH | Ingestion | hematopoietic system | Not classified | Dog | NOAEL 320 mg/kg/day | 90 days |
| DMDEE | Ingestion | heart endocrine system hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 300 mg/kg/day | 28 days |
| Titanium Dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium Dioxide | Inhalation | pulmonary fibrosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

| Name | Value |
|------------------------------------------|-------------------|
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

3M(TM) Polyurethane Adhesive Sealant Accelerator AC61

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 1 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|------------|-------------------------|------------|
| Document group: | 31-0315-7 | Version number: | 3.05 |
| Issue Date: | 2020/10/22 | Supersedes Date: | 2019/02/04 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE,

COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca