



## Safety Data Sheet

Copyright, 2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	33-2559-4	<b>Version number:</b>	4.02
<b>Issue Date:</b>	2020/10/22	<b>Supersedes Date:</b>	2018/10/10

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ All Purpose Sealant Primer P591, BLACK

#### Product Identification Numbers

62-5570-0031-2      62-5570-0036-1      62-5570-0251-6      62-5570-0256-5      70-0075-1716-5

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Primer

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

<b>Company:</b>	3M Canada Company
<b>Division:</b>	Industrial Adhesives and Tapes Division
<b>Address:</b>	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
<b>Telephone:</b>	(800) 364-3577
<b>Website:</b>	www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 2.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

## **2.2. Label elements**

### **Signal word**

Danger

### **Symbols**

Flame | Exclamation mark | Health Hazard |

### **Pictograms**



### **Hazard statements**

Highly flammable liquid and vapour.

Causes serious eye irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of causing cancer.

May cause damage to organs: respiratory system |

Causes damage to organs through prolonged or repeated exposure: respiratory system |

### **Precautionary statements**

#### **Prevention:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### **Storage:**

Store in a well-ventilated place. Keep cool. Store locked up.

#### **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## **2.3. Other hazards**

None known.

3% of the mixture consists of ingredients of unknown acute oral toxicity.

3% of the mixture consists of ingredients of unknown acute dermal toxicity.

14% of the mixture consists of ingredients of unknown acute inhalation toxicity.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Methyl Ethyl Ketone	78-93-3	30 - 60 Trade Secret *	2-Butanone
N-Butyl Acetate	123-86-4	10 - 30 Trade Secret *	Acetic acid, butyl ester
1,6-Hexamethylene diisocyanate-TDI copolymer	63368-95-6	5 - 10 Trade Secret *	Benzene, 1,3-diisocyanatomethyl-, polymer with 1,6-diisocyanatohexane
Polymethylene Polyphenylene Isocyanate	9016-87-9	5 - 10 Trade Secret *	Isocyanic acid, polymethylenepolyphenylene ester
1-methoxy-2-propyl acetate	108-65-6	1 - 5	2-Propanol, 1-methoxy-, acetate
3-(trimethoxysilyl)propyl glycidyl ether	2530-83-8	1 - 5 Trade Secret *	Silane, trimethoxy[3-(oxiranylmethoxy)propyl]-
Alkyl Isocyanate Silane	Trade Secret	1 - 5	Not Applicable
Carbon Black	1333-86-4	1 - 5 Trade Secret *	Carbon black
Diphenylmethane-2,4'-diisocyanate	5873-54-1	1 - 5 Trade Secret *	Benzene, 1-isocyanato-2-[(4-isocyanatophenyl)methyl]-
Hexamethylene diisocyanate polymer	28182-81-2	1 - 5 Trade Secret *	Hexane, 1,6-diisocyanato-, homopolymer
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	1 - 5 Trade Secret *	Benzene, 1,1'-methylenebis[4-isocyanato-
Polyurethane Resin	Trade Secret	1 - 5	Not Applicable
P-Toluenesulfonamide	70-55-3	< 1.5	Benzenesulfonamide, 4-methyl-
Dibutyltin dichloride	683-18-1	< 0.1	Stannane, dibutyldichloro-
Hexamethylene diisocyanate	822-06-0	< 0.06	Hexane, 1,6-diisocyanato-
Toluene 2,4-diisocyanate	584-84-9	< 0.06	Benzene, 2,4-diisocyanato-1-methyl-

Alkyl Isocyanate Silane is a non-hazardous Trade Secret material according to WHMIS criteria.

Polyurethane Resin is a non-hazardous Trade Secret material according to WHMIS criteria.

\*The actual concentration of this ingredient has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Cyanide	During Combustion
Oxides of Nitrogen	During Combustion
Oxides of Sulfur	During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in

## 3M™ All Purpose Sealant Primer P591, BLACK

eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
1-methoxy-2-propyl acetate	108-65-6	AIHA	TWA:50 ppm	
N-Butyl Acetate	123-86-4	ACGIH	TWA:50 ppm;STEL:150 ppm	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	
Toluene 2,4-diisocyanate	584-84-9	ACGIH	TWA(inhalable fraction and vapour):0.001 ppm;STEL(inhalable fraction and vapour):0.005 ppm	Dermal/Respiratory Sensitizer
TIN, ORGANIC COMPOUNDS	683-18-1	ACGIH	TWA(as Sn):0.1 mg/m3;STEL(as Sn):0.2 mg/m3	Danger of cutaneous absorption
Methyl Ethyl Ketone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	
Hexamethylene diisocyanate	822-06-0	ACGIH	TWA:0.005 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Butyl Rubber

Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Colour</b>	Black
<b>Odour</b>	Ketones
<b>Odour threshold</b>	No Data Available
<b>pH</b>	Not Applicable
<b>Melting point/Freezing point</b>	Not Applicable
<b>Boiling point</b>	79 °C
<b>Flash Point</b>	-8 °C [Test Method: Closed Cup]
<b>Evaporation rate</b>	No Data Available
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	1.8 % volume
<b>Flammable Limits(UEL)</b>	11.5 % volume
<b>Vapour Pressure</b>	No Data Available
<b>Viscosity/Kinematic Viscosity</b>	2.8 [Ref Std: AIR=1]
<b>Viscosity</b>	
<b>Density</b>	0.9 g/ml
<b>Relative density</b>	0.9 [Ref Std: WATER=1]
<b>Water solubility</b>	Moderate
<b>Solubility- non-water</b>	No Data Available
<b>Partition coefficient: n-octanol/ water</b>	No Data Available
<b>Autoignition temperature</b>	> 200 °C
<b>Decomposition temperature</b>	No Data Available
<b>Viscosity/Kinematic Viscosity</b>	10 mPa-s
<b>Volatile Organic Compounds</b>	
<b>Percent volatile</b>	
<b>VOC Less H2O &amp; Exempt Solvents</b>	602 g/l [Test Method: calculated SCAQMD rule 443.1]

#### Nanoparticles

This material contains nanoparticles.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames

Heat

### 10.5. Incompatible materials

Alcohols

Amines

Strong acids

Strong bases

Strong oxidizing agents

Water

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

#### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**3M™ All Purpose Sealant Primer P591, BLACK****Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Prolonged or repeated exposure may cause target organ effects:**

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

<b>Ingredient</b>	<b>CAS No.</b>	<b>Class Description</b>	<b>Regulation</b>
Generic: Benzene, 1,3-diisocyanatomethyl-	584-84-9	Anticipated human carcinogen	National Toxicology Program Carcinogens
Carbon Black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Toluene 2,4-diisocyanate	584-84-9	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b>Name</b>	<b>Route</b>	<b>Species</b>	<b>Value</b>
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Ethyl Ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Methyl Ethyl Ketone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Methyl Ethyl Ketone	Ingestion	Rat	LD50 2,737 mg/kg
N-Butyl Acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
N-Butyl Acetate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.4 mg/l
N-Butyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 20 mg/l
N-Butyl Acetate	Ingestion	Rat	LD50 > 8,800 mg/kg
Polymethylene Polyphenylene Isocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polymethylene Polyphenylene Isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
Polymethylene Polyphenylene Isocyanate	Ingestion	Rat	LD50 31,600 mg/kg



**3M™ All Purpose Sealant Primer P591, BLACK**

1,6-Hexamethylene diisocyanate-TDI copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
1,6-Hexamethylene diisocyanate-TDI copolymer	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
1,6-Hexamethylene diisocyanate-TDI copolymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
Diphenylmethane-2,4'-diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Diphenylmethane-2,4'-diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
Diphenylmethane-2,4'-diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Polyurethane Resin	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyurethane Resin	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
3-(trimethoxysilyl)propyl glycidyl ether	Dermal	Rabbit	LD50 4,000 mg/kg
3-(trimethoxysilyl)propyl glycidyl ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Rat	LD50 7,010 mg/kg
Hexamethylene diisocyanate polymer	Inhalation-Dust/Mist (4 hours)	Professional judgement	LC50 estimated to be 1 - 5 mg/l
Hexamethylene diisocyanate polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hexamethylene diisocyanate polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
P-Toluenesulfonamide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
P-Toluenesulfonamide	Ingestion	Rat	LD50 > 2,000 mg/kg
1-methoxy-2-propyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
1-methoxy-2-propyl acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 28.8 mg/l
1-methoxy-2-propyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
Toluene 2,4-diisocyanate	Inhalation-Vapor (4 hours)	Mouse	LC50 0.12 mg/l
Toluene 2,4-diisocyanate	Dermal	Rabbit	LD50 > 9,400 mg/kg
Toluene 2,4-diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.35 mg/l
Toluene 2,4-diisocyanate	Ingestion	Rat	LD50 > 5,000 mg/kg
Hexamethylene diisocyanate	Dermal	Rat	LD50 > 7,000 mg/kg
Hexamethylene diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.124 mg/l
Hexamethylene diisocyanate	Inhalation-Vapor (4 hours)	Rat	LC50 0.124 mg/l
Hexamethylene diisocyanate	Ingestion	Rat	LD50 710 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Methyl Ethyl Ketone	Rabbit	Minimal irritation
N-Butyl Acetate	Rabbit	Minimal irritation
Polymethylene Polyphenylene Isocyanate	official classification	Irritant
1,6-Hexamethylene diisocyanate-TDI copolymer	Rabbit	Minimal irritation
Carbon Black	Rabbit	No significant irritation

**3M™ All Purpose Sealant Primer P591, BLACK**

Diphenylmethane-2,4'-diisocyanate	official classification	Irritant
P,P'-Methylenebis(phenyl isocyanate)	official classification	Irritant
3-(trimethoxysilyl)propyl glycidyl ether	Rabbit	Mild irritant
Hexamethylene diisocyanate polymer	Rabbit	Minimal irritation
P-Toluenesulfonamide	Rabbit	No significant irritation
1-methoxy-2-propyl acetate	Rabbit	No significant irritation
Toluene 2,4-diisocyanate	Rabbit	Irritant
Hexamethylene diisocyanate	Rabbit	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Methyl Ethyl Ketone	Rabbit	Severe irritant
N-Butyl Acetate	Rabbit	Moderate irritant
Polymethylene Polyphenylene Isocyanate	official classification	Severe irritant
1,6-Hexamethylene diisocyanate-TDI copolymer	Rabbit	Moderate irritant
Carbon Black	Rabbit	No significant irritation
Diphenylmethane-2,4'-diisocyanate	official classification	Severe irritant
P,P'-Methylenebis(phenyl isocyanate)	official classification	Severe irritant
3-(trimethoxysilyl)propyl glycidyl ether	Rabbit	Corrosive
Hexamethylene diisocyanate polymer	Rabbit	Mild irritant
P-Toluenesulfonamide	Rabbit	No significant irritation
1-methoxy-2-propyl acetate	Rabbit	Mild irritant
Toluene 2,4-diisocyanate	Rabbit	Corrosive
Hexamethylene diisocyanate	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
N-Butyl Acetate	Multiple animal species	Not classified
Polymethylene Polyphenylene Isocyanate	official classification	Sensitizing
1,6-Hexamethylene diisocyanate-TDI copolymer	Guinea pig	Sensitizing
Diphenylmethane-2,4'-diisocyanate	official classification	Sensitizing
P,P'-Methylenebis(phenyl isocyanate)	official classification	Sensitizing
3-(trimethoxysilyl)propyl glycidyl ether	Guinea pig	Not classified
Hexamethylene diisocyanate polymer	Guinea pig	Sensitizing
1-methoxy-2-propyl acetate	Guinea pig	Not classified
Toluene 2,4-diisocyanate	Human and animal	Sensitizing
Hexamethylene diisocyanate	Multiple animal species	Sensitizing

**3M™ All Purpose Sealant Primer P591, BLACK****Respiratory Sensitization**

Name	Species	Value
Polymethylene Polyphenylene Isocyanate	Human	Sensitizing
1,6-Hexamethylene diisocyanate-TDI copolymer		Sensitizing
Diphenylmethane-2,4'-diisocyanate	Human	Sensitizing
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitizing
Hexamethylene diisocyanate polymer	similar compounds	Not classified
Toluene 2,4-diisocyanate	Human	Sensitizing
Hexamethylene diisocyanate	Human and animal	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Methyl Ethyl Ketone	In Vitro	Not mutagenic
N-Butyl Acetate	In Vitro	Not mutagenic
Polymethylene Polyphenylene Isocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification
Diphenylmethane-2,4'-diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-(trimethoxysilyl)propyl glycidyl ether	In vivo	Not mutagenic
3-(trimethoxysilyl)propyl glycidyl ether	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hexamethylene diisocyanate polymer	In Vitro	Not mutagenic
Hexamethylene diisocyanate polymer	In vivo	Not mutagenic
1-methoxy-2-propyl acetate	In Vitro	Not mutagenic
Toluene 2,4-diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hexamethylene diisocyanate	In Vitro	Not mutagenic
Hexamethylene diisocyanate	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Methyl Ethyl Ketone	Inhalation	Human	Not carcinogenic
Polymethylene Polyphenylene Isocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic
Diphenylmethane-2,4'-diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
3-(trimethoxysilyl)propyl glycidyl ether	Dermal	Mouse	Not carcinogenic
Toluene 2,4-diisocyanate	Inhalation	Human and animal	Not carcinogenic
Toluene 2,4-diisocyanate	Ingestion	Multiple animal species	Carcinogenic
Hexamethylene diisocyanate	Inhalation	Rat	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

**3M™ All Purpose Sealant Primer P591, BLACK**

Name	Route	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
N-Butyl Acetate	Inhalation	Not classified for female reproduction	Rat	NOAEL 7.1 mg/l	premating & during gestation
N-Butyl Acetate	Inhalation	Not classified for development	Rat	NOAEL 7.1 mg/l	premating & during gestation
Polymethylene Polyphenylene Isocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Diphenylmethane-2,4'-diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
P-Toluenesulfonamide	Ingestion	Not classified for reproduction and/or development	Rat	NOAEL 300 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
1-methoxy-2-propyl acetate	Inhalation	Not classified for development	Rat	NOAEL 21.6 mg/l	during organogenesis
Toluene 2,4-diisocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	2 generation
Toluene 2,4-diisocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.002 mg/l	2 generation
Toluene 2,4-diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Hexamethylene diisocyanate	Inhalation	Not classified for female reproduction	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene diisocyanate	Inhalation	Not classified for male reproduction	Rat	NOAEL 0.014 mg/l	4 weeks

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

**3M™ All Purpose Sealant Primer P591, BLACK**

Methyl Ethyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
Methyl Ethyl Ketone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
N-Butyl Acetate	Inhalation	respiratory system	May cause damage to organs	Rat	LOAEL 2.6 mg/l	4 hours
N-Butyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
N-Butyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	not available
N-Butyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Polymethylene Polyphenylene Isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
1,6-Hexamethylene diisocyanate-TDI copolymer	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
Diphenylmethane-2,4'-diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Hexamethylene diisocyanate polymer	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
1-methoxy-2-propyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Toluene 2,4-diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Hexamethylene diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Hexamethylene diisocyanate	Inhalation	blood	Not classified	Human	NOAEL Not available	occupational exposure

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Methyl Ethyl Ketone	Inhalation	liver   kidney and/or bladder   heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   immune system   muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
Methyl Ethyl Ketone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
N-Butyl Acetate	Inhalation	olfactory system	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
N-Butyl Acetate	Inhalation	liver   kidney and/or bladder	Not classified	Rabbit	NOAEL 7.26 mg/l	13 days
Polymethylene Polyphenylene Isocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

**3M™ All Purpose Sealant Primer P591, BLACK**

Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Diphenylmethane-2,4'-diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
3-(trimethoxysilyl)propyl glycidyl ether	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Hexamethylene diisocyanate polymer	Inhalation	immune system   blood	Not classified	Rat	NOAEL 0.084 mg/l	2 weeks
1-methoxy-2-propyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 16.2 mg/l	9 days
1-methoxy-2-propyl acetate	Inhalation	olfactory system	Not classified	Mouse	LOAEL 1.62 mg/l	9 days
1-methoxy-2-propyl acetate	Inhalation	blood	Not classified	Multiple animal species	NOAEL 16.2 mg/l	9 days
1-methoxy-2-propyl acetate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	44 days
Toluene 2,4-diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL 0 mg/l	occupational exposure
Hexamethylene diisocyanate	Inhalation	liver   kidney and/or bladder	Not classified	Rat	NOAEL 0.002 mg/l	3 weeks
Hexamethylene diisocyanate	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.0014 mg/l	4 weeks
Hexamethylene diisocyanate	Inhalation	blood	Not classified	Rat	NOAEL 0.0012 mg/l	2 years
Hexamethylene diisocyanate	Inhalation	nervous system	Not classified	Rat	NOAEL 0.002 mg/l	7 weeks
Hexamethylene diisocyanate	Inhalation	heart	Not classified	Rat	NOAEL 0.001 mg/l	90 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**SECTION 16: Other information**

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 2 Flammability: 3 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	33-2559-4	<b>Version number:</b>	4.02
<b>Issue Date:</b>	2020/10/22	<b>Supersedes Date:</b>	2018/10/10

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**