



Safety Data Sheet

Copyright, 2024, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-7532-2	Version number:	2.02
Issue Date:	2024/07/09	Supersedes Date:	2024/05/08

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M™ Interam™ Endothermic Mat E-5A-4, E-54A, E-54C

Product Identification Numbers

98-0042-9365-4	98-0400-5620-6	98-0400-5621-4	98-0400-5622-2	98-0400-5623-0
98-0400-5649-5	98-0441-1012-4	98-0441-1079-3	AT-0194-4269-1	

1.2. Recommended use and restrictions on use

Intended Use

Fire Barrier Mat

Restrictions on use

Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Industrial Specialties Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Health Hazard |

Pictograms



Hazard statements

Suspected of causing cancer by inhalation.

Precautionary statements

Prevention:

Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear protective gloves. Use personal protective equipment as required: see Section 8 of the Safety Data Sheet.

Response:

IF exposed or concerned: Get medical advice/attention.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Alumina Trihydrate	21645-51-2	60 - 90	Aluminum hydroxide (Al(OH) ₃)
Polymer	Trade Secret	1 - 10	Not Applicable
Refractory Ceramic Fibers (RCF)	142844-00-6	3 - 10 Trade Secret *	Refractories, fibers, aluminosilicate
Water	7732-18-5	1 - 6	Water

Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

*The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide

Carbon dioxide

Condition

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect spilled material using a vacuum cleaner with a High Efficiency Particulate Air (HEPA) filter. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Glass wool fibers	142844-00-6	ACGIH	TWA(as fiber):1 fiber/cc	
Rock wool fibers	142844-00-6	ACGIH	TWA(as fiber):1 fiber/cc	
Slag wool fibers	142844-00-6	ACGIH	TWA(as fiber):1 fiber/cc	
Special purpose glass fibers	142844-00-6	ACGIH	TWA(as fiber):1 fiber/cc	
Aluminum, insoluble compounds	21645-51-2	ACGIH	TWA(respirable fraction):1 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

Respiratory protection

3M has conducted air sampling during simulated use of this product. For more information, see www.3m.com/firestop.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Roll of material
Colour	White
Odour	Odourless
Odour threshold	<i>Not Applicable</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapour Pressure	<i>Not Applicable</i>
Vapour Density and/or Relative Vapour Density	<i>Not Applicable</i>
Density	0.866 g/cm3
Relative density	<i>No Data Available</i>
Water solubility	Nil
Solubility- non-water	<i>Not Applicable</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>Not Applicable</i>
Kinematic Viscosity	<i>Not Applicable</i>
Volatile Organic Compounds	<i>Not Applicable</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	<i>Not Applicable</i>
Molecular weight	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye Contact:

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
Refractory ceramic fibres	142844-00-6	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

<u>Name</u>	<u>Route</u>	<u>Species</u>	<u>Value</u>
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Alumina Trihydrate	Dermal		LD50 estimated to be > 5,000 mg/kg
Alumina Trihydrate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Alumina Trihydrate	Ingestion	Rat	LD50 > 5,000 mg/kg
Refractory Ceramic Fibers (RCF)	Dermal		LD50 estimated to be > 5,000 mg/kg
Refractory Ceramic Fibers (RCF)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Polymer	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Alumina Trihydrate	Rabbit	No significant irritation
Polymer	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Alumina Trihydrate	Rabbit	No significant irritation
Polymer	Professional judgement	Mild irritant

Skin Sensitization

Name	Species	Value
Alumina Trihydrate	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Carcinogenicity

Name	Route	Species	Value
Alumina Trihydrate	Not Specified	Multiple animal species	Not carcinogenic
Refractory Ceramic Fibers (RCF)	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Alumina Trihydrate	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Refractory Ceramic Fibers (RCF)	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL 36 fibers/cc	12 months
Refractory Ceramic Fibers (RCF)	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 187 fibers/cc	18 months

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 1 **Flammability:** 0 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *0 **Flammability:** 0 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	30-7532-2	Version number:	2.02
------------------------	-----------	------------------------	------

Issue Date:	2024/07/09	Supersedes Date:	2024/05/08
--------------------	------------	-------------------------	------------

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca