

Safety Data Sheet

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 30-0260-7
 Version number:
 4.03

 Issue Date:
 2020/10/22
 Supercedes Date:
 2020/08/27

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Fluorosurfactant FC-4430

Product Identification Numbers

98-0212-3628-0 98-0212-3629-8 98-0212-3630-6 98-0212-3670-2 AF-0194-2085-6 HB-0042-5443-7 HB-0042-5447-8 HB-0042-5448-6 HB-0046-5408-1 JF-1000-4260-1

UU-0100-7696-4 UU-0100-7697-2 UU-0107-9154-7

1.2. Recommended use and restrictions on use

Intended Use

Industrial use

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company
Division: Advanced Materials Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 2. Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard

Pictograms



Hazard statements

May damage fertility or the unborn child.

May cause damage to organs: nervous system

May cause damage to organs through prolonged or repeated exposure: liver

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

Response:

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
2-Propenoic Acid, 2-	1017237-78-3	85 - 95	No Data Available
[Methyl[(Nonafluorobutyl)Sulfo			
nyl]Amino]Ethyl Ester, Telomer			
With Methyloxirane Polymer			
With Oxirane Di-2-Propenoate			
and Methyloxirane Polymer			
With Oxirane Mono-Propenoate			
Polyether Polymer	Trade Secret	5 - 10	Not Applicable
2-	34590-94-8	0 - 5	Propanol, 1(or 2)-(2-
METHOXYMETHYLETHOXY			methoxymethylethoxy)-
PROPANOL			

1-Butanesulfonamide,	34454-97-2	0 - 1	1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-
1,1,2,2,3,3,4,4,4-Nonafluoro-N-			nonafluoro-N-(2-hydroxyethyl)-N-m ethyl-
(2-Hydroxyethyl)-N-Methyl-			
2-PROPENOIC ACID, 2-	67584-55-8	< 1	2-Propenoic acid, 2-
[METHYL[(NONAFLUOROB			[methyl[(nonafluorobutyl)sulfonyl]amino]e
UTYL)SULFONYL]AMINO]E			thyl ester
THYL ESTER			
Toluene	108-88-3	0 - 0.9	No Data Available
1-BUTANESULFONAMIDE,	68298-12-4	0 - 0.5	1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-
1,1,2,2,3,3,4,4,4-			nonafluoro-N-methyl-
NONAFLUORO-N-METHYL-			

Polyether Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If you feel unwell, get medical attention.

Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

Hazardous Decomposition or By-Products

Substance	Condition
Carbonyl Fluoride	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Fluoride	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Avoid skin contact with hot material. For industrial use only. Not intended for use as a medical device or drug. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	
1-Butanesulfonamide,	34454-97-2	Manufacturer	TWA:1 mg/m3(0.07 ppm)	
1,1,2,2,3,3,4,4,4-Nonafluoro-N-		determined		
(2-Hydroxyethyl)-N-Methyl-				
2-	34590-94-8	ACGIH	TWA:100 ppm;STEL:150 ppm	Danger of cutaneous
METHOXYMETHYLETHOXY				absorption
PROPANOL				
1-BUTANESULFONAMIDE,	68298-12-4	Manufacturer	TWA:3 mg/m3(0.24 ppm)	
1,1,2,2,3,3,4,4,4-		determined		
NONAFLUORO-N-METHYL-				

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

D. . . A . C . 12

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release. exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Viscous liquid
Colour	Amber
Odour	Mercaptan

Page: 5 of 13

No Data Available
Not Applicable
Not Applicable
>=200 °C
Flash point > 93 °C (200 °F)
No Data Available
Not Applicable
No Data Available
No Data Available
<=38.7 Pa [@ 20 °C]
5.7 [@ 20 °C] [<i>Ref Std</i> :AIR=1]
1.15 g/ml
1.15 [<i>Ref Std</i> :WATER=1]
Complete
No Data Available
No Data Available
Not Applicable
No Data Available
2,000 mPa-s - 10,000 mPa-s
34.5 g/l [Test Method:calculated SCAQMD rule 443.1]
<=3 %
No Data Available
No Data Available

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance
None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Eve Contact:

No known health effects.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Prolonged or repeated exposure may cause target organ effects:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
2-Propenoic Acid, 2- [Methyl[(Nonafluorobutyl)Sulfonyl]Amino]Ethyl Ester, Telomer With Methyloxirane Polymer With Oxirane Di-2-Propenoate and Methyloxirane Polymer With Oxirane Mono-Propenoate	Dermal	Rat	LD50 > 2,000 mg/kg
2-Propenoic Acid, 2- [Methyl](Nonafluorobutyl)Sulfonyl]Amino]Ethyl Ester, Telomer With Methyloxirane Polymer With Oxirane Di-2-Propenoate and Methyloxirane Polymer With Oxirane Mono-Propenoate	Ingestion	Rat	LD50 > 2,000 mg/kg

_

Polyether Polymer	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	
		judgeme	
		nt	
Polyether Polymer	Ingestion	Rat	LD50 5,700 mg/kg
2-METHOXYMETHYLETHOXYPROPANOL	Dermal	Rabbit	LD50 > 19,000 mg/kg
2-METHOXYMETHYLETHOXYPROPANOL	Inhalation-	Rat	LC50 > 50 mg/l
	Dust/Mist		
	(4 hours)		
2-METHOXYMETHYLETHOXYPROPANOL	Ingestion	Rat	LD50 5,180 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
	hours)		
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-	Dermal	Rat	LD50 > 2,000 mg/kg
Hydroxyethyl)-N-Methyl-			
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-	Ingestion	Rat	LD50 > 2,000 mg/kg
Hydroxyethyl)-N-Methyl-			, , ,
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-	Ingestion	Rat	LD50 200-2000 mg/kg
NONAFLUORO-N-METHYL-	3-2		, , , , , , , , , , , , , , , , , , ,
2-PROPENOIC ACID, 2-	Dermal	Rat	LD50 > 2,000 mg/kg
[METHYL](NONAFLUOROBUTYL)SULFONYL]AMINO]ET			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
HYL ESTER			
2-PROPENOIC ACID, 2-	Ingestion	Rat	LD50 > 2,000 mg/kg
[METHYL[(NONAFLUOROBUTYL)SULFONYL]AMINO]ET		1	
HYL ESTER			

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-METHOXYMETHYLETHOXYPROPANOL	Human	No significant irritation
	and	
	animal	
Toluene	Rabbit	Irritant
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-Hydroxyethyl)-N-	Rabbit	No significant irritation
Methyl-		
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-NONAFLUORO-N-METHYL-	Rabbit	No significant irritation
2-PROPENOIC ACID, 2-	Rabbit	No significant irritation
[METHYL[(NONAFLUOROBUTYL)SULFONYL]AMINO]ETHYL ESTER		

Serious Eye Damage/Irritation

Name	Species	Value
2-METHOXYMETHYLETHOXYPROPANOL	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-Hydroxyethyl)-N-	Rabbit	Mild irritant
Methyl-		
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-NONAFLUORO-N-METHYL-	Rabbit	Severe irritant
2-PROPENOIC ACID, 2-	Rabbit	Mild irritant
[METHYL[(NONAFLUOROBUTYL)SULFONYL]AMINO]ETHYL ESTER		

Skin Sensitization

Name	Species	Value
2-Propenoic Acid, 2-[Methyl[(Nonafluorobutyl)Sulfonyl]Amino]Ethyl Ester,	Guinea	Not classified
Telomer With Methyloxirane Polymer With Oxirane Di-2-Propenoate and	pig	
Methyloxirane Polymer With Oxirane Mono-Propenoate		
2-METHOXYMETHYLETHOXYPROPANOL	Human	Not classified
Toluene	Guinea	Not classified
	pig	
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-Hydroxyethyl)-N-	Guinea	Not classified
Methyl-	pig	
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-NONAFLUORO-N-METHYL-	Guinea	Not classified
	pig	

2-PROPENOIC ACID, 2-	Guinea	Sensitizing
[METHYL[(NONAFLUOROBUTYL)SULFONYL]AMINO]ETHYL ESTER	pig	_

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-Propenoic Acid, 2-[Methyl[(Nonafluorobutyl)Sulfonyl]Amino]Ethyl Ester, Telomer With Methyloxirane Polymer With Oxirane Di-2-Propenoate and Methyloxirane Polymer With Oxirane Mono-Propenoate	In Vitro	Not mutagenic
2-METHOXYMETHYLETHOXYPROPANOL	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4-Nonafluoro-N-(2-Hydroxyethyl)-N-Methyl-	In Vitro	Not mutagenic
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-NONAFLUORO-N-METHYL-	In Vitro	Not mutagenic
2-PROPENOIC ACID, 2- [METHYL[(NONAFLUOROBUTYL)SULFONYL]AMINO]ETHYL ESTER	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Toluene	Dermal Mouse Some positive data exist, but		Some positive data exist, but the data are not
			sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not
	_		sufficient for classification
Toluene	Inhalation Mouse Some positive data exist, but the		Some positive data exist, but the data are not
			sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2- METHOXYMETHYLETHOXYPROPAN OL	Inhalation	Not classified for development	Multiple animal species	NOAEL 1.82 mg/l	during organogenesi s
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4- Nonafluoro-N-(2-Hydroxyethyl)-N-Methyl-	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	premating & during gestation
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4- Nonafluoro-N-(2-Hydroxyethyl)-N-Methyl-	Ingestion	Not classified for male reproduction	Rat	NOAEL 250 mg/kg/day	premating & during gestation
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4- Nonafluoro-N-(2-Hydroxyethyl)-N-Methyl-	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	premating & during gestation
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-NONAFLUORO-N- METHYL-	Ingestion	Toxic to female reproduction	Rat	NOAEL 150 mg/kg/day	premating & during gestation
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-NONAFLUORO-N- METHYL-	Ingestion	Toxic to male reproduction	Rat	NOAEL 150 mg/kg/day	28 days
1-BUTANESULFONAMIDE, 1,1,2,2,3,3,4,4,4-NONAFLUORO-N- METHYL-	Ingestion	Toxic to development	Rat	NOAEL 150 mg/kg/day	premating & during gestation

2-PROPENOIC ACID, 2-	Ingestion	Not classified for development	Rat	NOAEL 100	during
[METHYL](NONAFLUOROBUTYL)SUL		_		mg/kg/day	gestation
FONYL]AMINO]ETHYL ESTER					_

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2- METHOXYMETHYLETH OXYPROPANOL	Dermal	central nervous system depression	Not classified	Rabbit	NOAEL 2,850 mg/kg	
2- METHOXYMETHYLETH OXYPROPANOL	Inhalation	central nervous system depression	Not classified	Rat	LOAEL 3.07 mg/l	7 hours
2- METHOXYMETHYLETH OXYPROPANOL	Ingestion	central nervous system depression	Not classified	Rat	LOAEL 5,000 mg/kg	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4- Nonafluoro-N-(2- Hydroxyethyl)-N-Methyl-	Ingestion	nervous system	May cause damage to organs	Rat	LOAEL 2,000 mg/kg	not applicable
I- BUTANESULFONAMID E, 1,1,2,2,3,3,4,4- NONAFLUORO-N- METHYL-	Ingestion	nervous system	Not classified	Rat	NOAEL 200 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-Propenoic Acid, 2- [Methyl[(Nonafluorobutyl) Sulfonyl]Amino]Ethyl Ester, Telomer With Methyloxirane Polymer With Oxirane Di-2- Propenoate and Methyloxirane Polymer With Oxirane Mono- Propenoate	Ingestion	heart endocrine system hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
2- METHOXYMETHYLET HOXYPROPANOL	Dermal	kidney and/or bladder heart endocrine system hematopoietic system liver respiratory system	Not classified	Rabbit	NOAEL 9,500 mg/kg/day	90 days
2- METHOXYMETHYLET HOXYPROPANOL	Inhalation	heart hematopoietic system liver immune system nervous system eyes kidney and/or bladder	Not classified	Rat	NOAEL 1.21 mg/l	90 days
2- METHOXYMETHYLET HOXYPROPANOL	Ingestion	liver heart endocrine system bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

		hematopoietic system immune system nervous system kidney and/or bladder				
Toluene	Inhalation	respiratory system auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4- Nonafluoro-N-(2- Hydroxyethyl)-N-Methyl-	Ingestion	liver	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 50 mg/kg/day	28 days
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4- Nonafluoro-N-(2- Hydroxyethyl)-N-Methyl-	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 50 mg/kg/day	28 days
1-Butanesulfonamide, 1,1,2,2,3,3,4,4,4- Nonafluoro-N-(2- Hydroxyethyl)-N-Methyl-	Ingestion	kidney and/or bladder heart endocrine system hematopoietic system nervous system respiratory system	Not classified	Rat	NOAEL 250 mg/kg/day	28 days
1- BUTANESULFONAMID E, 1,1,2,2,3,3,4,4,4- NONAFLUORO-N- METHYL-	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	premating & during gestation
I- BUTANESULFONAMID E, 1,1,2,2,3,3,4,4,4- NONAFLUORO-N-	Ingestion	hematopoietic system liver immune system heart endocrine	Not classified	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

METHYL-		system kidney and/or bladder respiratory system				
2-PROPENOIC ACID, 2- [METHYL](NONAFLUO ROBUTYL)SULFONYL] AMINO]ETHYL ESTER	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 100 mg/kg/day	
2-PROPENOIC ACID, 2- [METHYL](NONAFLUO ROBUTYL)SULFONYL] AMINO]ETHYL ESTER	Ingestion	endocrine system gastrointestinal tract hematopoietic system immune system heart bone, teeth, nails, and/or hair nervous system eyes respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in

compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	30-0260-7	Version number:	4.03
Issue Date:	2020/10/22	Supercedes Date:	2020/08/27

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 13 of 13