

# Safety Data Sheet

### Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-5619-8	Version Number:	4.00
Issue Date:	05/11/2021	Supercedes Date:	14/12/2020

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

#### 1.1. Product identifier

3M<sup>™</sup> Foam Fast 74 Spray Adhesive Orange

**Product Identification Numbers** 

62-4935-4920-8	62-4935-4921-6	62-4935-4950-5	62-4935-4955-4	62-4935-4970-3
62-4935-4975-2				

### 1.2. Recommended use and restrictions on use

### Recommended use

Adhesive, Aerosol foam adhesive

For Industrial or Professional use only

#### 1.3. Supplier's details

ADDRESS:3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301<br/>Petaling, Jaya, SelangorTelephone:03-7884 2888E Mail:3mmyehsr@mmm.comWebsite:www.3M.com.my

#### 1.4. Emergency telephone number

+60 03-7884 2888

# **SECTION 2: Hazard identification**

## 2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1. Gas Under Pressure: Liquefied gas. Serious Eye Damage/Irritation: Category 1. Reproductive Toxicity: Category 1B. Specific Target Organ Toxicity (single exposure): Category 1. Chronic Aquatic Toxicity: Category 3.

2.2. Label elements Signal word

# Danger

# Symbols

Flame |Gas cylinder |Corrosion |Health Hazard |

# Pictograms



Hazard Statements:			
H222	Extremely flammable aerosol.		
H280	Contains gas under pressure; may explode if heated.		
H318	Causes serious eye damage.		
H360	May damage fertility or the unborn child.		
H370	Causes damage to organs: cardiovascular system.		
H412	Harmful to aquatic life with long lasting effects.		
Precautionary statements			
General:			
P101	If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.		
Prevention:			
P201	Obtain special instructions before use.		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.		
	No smoking.		
P211	Do not spray on an open flame or other ignition source.		
P251	Do not pierce or burn, even after use.		
P260	Do not breathe dust/fume/gas/mist/vapors/spray.		
P280A	Wear eye/face protection.		
P281	Use personal protective equipment as required.		
Response:			
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact		
	lenses, if present and easy to do. Continue rinsing.		
P310	Immediately call a POISON CENTER or doctor/physician.		
Storage:			
P405	Store locked up.		
P410 + P403	Protect from sunlight. Store in a well-ventilated place.		
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.		
Disposal:			
P501	Dispose of contents/container in accordance with applicable		
	local/regional/national/international regulations.		

# 2.3. Other hazards

A similar mixture has been tested for eye damage/irritation and the test results are reflected in the assigned classification., A similar mixture has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification., A spiration classification does not apply as this product is sold in sealed, self-pressurized containers with nozzles designed to

prevent formation of a stream during usage., Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal., May cause drowsiness or dizziness., May displace oxygen and cause rapid suffocation.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Acetone	67-64-1	15 - 25
Dimethyl Ether	115-10-6	15 - 25
Isobutane	75-28-5	10 - 20
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6- TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2- METHYLENEBICYCLO[3.1.1]HEPTANE	31393-98-3	5 - 15
Non-hazardous components	Trade Secret	5 - 15
Pentane	109-66-0	7 - 13
Methyl acetate	79-20-9	3 - 7
Cyclohexane	110-82-7	1 - 5
Petroleum naphtha	64742-48-9	1 - 3
Toluene	108-88-3	<1

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. Get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

#### 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

# 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50 ppm)	SKIN
Pentane	109-66-0	ACGIH	TWA:1000 ppm	
Pentane, all isomers	109-66-0	Malaysia OELs	TWA(8 hours):1770 mg/m3(600 ppm)	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	Malaysia OELs	TWA(8 hours):1030 mg/m3(300 ppm)	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin
Acetone	67-64-1	Malaysia OELs	TWA(8 hours):1187 mg/m3(500 ppm)	
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
Natural gas	75-28-5	ACGIH	Limit value not established:	simple asphyxiant
Methyl acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl acetate	79-20-9	Malaysia OELs	TWA(8 hours):606 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### **8.2. Exposure controls**

#### 8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield

Indirect Vented Goggles

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended:

## **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Specific Physical Form:	Aerosol	
Color	Orange	
Odor	Sweet Odor, Fruity Odor	
Odor threshold	No Data Available	
рН	No Data Available	
Melting point/Freezing point	No Data Available	
Boiling point/Initial boiling point/Boiling range	[Details:Compressed gas]Not Applicable	
Flash Point	-45.6 °C [Test Method: Tagliabue Closed Cup]	
Evaporation rate	1.9 [ <i>Ref Std</i> :ETHER=1]	
Flammability (solid, gas)	Not Applicable	
Flammable Limits(LEL)	No Data Available	
Flammable Limits(UEL)	No Data Available	
Vapor Pressure	[Details:Compressed gas]Not Applicable	
Vapor Density and/or Relative Vapor Density		
Density	0.718 g/ml	
Relative Density	0.718 [ <i>Ref Std</i> :WATER=1]	
Water solubility	Nil	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Viscosity/Kinematic Viscosity	Not Applicable	
Volatile Organic Compounds <a></a>		
	[Details:Material VOC]	
Volatile Organic Compounds	<=55 % [Test Method:calculated per CARB title 2]	
Percent volatile	No Data Available	
VOC Less H2O & Exempt Solvents	Solvents No Data Available	
Molecular weight	No Data Available	

## Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

Stable.

# 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

**10.4. Conditions to avoid** Heat

### **10.5. Incompatible materials** Strong oxidizing agents

## 10.6. Hazardous decomposition products

<u>Substance</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

Condition

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

#### Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

## Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

## Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

## Additional Health Effects:

## Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

#### **Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isobutane	Inhalation- Gas (4 hours)	Rat	LC50 276,000 ppm
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation- Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Dimethyl Ether	Inhalation- Gas (4 hours)	Rat	LC50 164,000 ppm
Pentane	Dermal	Rabbit	LD50 3,000 mg/kg
Pentane	Inhalation- Vapor (4 hours)	Rat	LC50 > 18 mg/l
Pentane	Ingestion	Rat	LD50 > 2,000 mg/kg
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6-DIMETHYL-2- METHYLENEBICYCLO[3.1.1]HEPTANE	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6-DIMETHYL-2- METHYLENEBICYCLO[3.1.1]HEPTANE	Ingestion	Rat	LD50 > 2,000 mg/kg
Non-hazardous components	Dermal	Rabbit	LD50 > 2,000 mg/kg
Non-hazardous components	Ingestion	Rat	LD50 > 5,000 mg/kg
Methyl acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl acetate	Inhalation- Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation- Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Petroleum naphtha	Inhalation- Vapor		LC50 estimated to be 20 - 50 mg/l
Petroleum naphtha	Dermal	Rabbit	LD50 > 3,000 mg/kg
Petroleum naphtha	Ingestion	Rat	LD50 > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation- Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

# ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Isobutane	Professio	No significant irritation
	nal	
	judgemen t	
Acetone	Mouse	Minimal irritation
Pentane	Rabbit	Minimal irritation
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	In vitro data	No significant irritation
Non-hazardous components	Professio nal	No significant irritation
	judgemen t	
Methyl acetate	Rabbit	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Petroleum naphtha	Rabbit	Irritant
Toluene	Rabbit	Irritant

# Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Corrosive
Isobutane	Professio	No significant irritation
	nal	
	judgemen	
	t	
Acetone	Rabbit	Severe irritant
Pentane	Rabbit	Mild irritant
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6-	In vitro	No significant irritation
DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	data	
Methyl acetate	Rabbit	Moderate irritant
Cyclohexane	Rabbit	Mild irritant
Petroleum naphtha	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant

### Sensitization:

### **Skin Sensitization**

Name	Species	Value
Pentane	Guinea pig	Not classified
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	Multiple animal species	Not classified
Methyl acetate	Human	Not classified
Petroleum naphtha	Guinea pig	Not classified
Toluene	Guinea pig	Not classified

# **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

# Germ Cell Mutagenicity

Name	Route	Value
Isobutane	In Vitro	Not mutagenic

Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Pentane	In vivo	Not mutagenic
Pentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
BICYCLO[3.1.1]HEPT-2-ENE,2,6,6-TRIMETHYL-,POLYMER WITH 6,6- DIMETHYL-2-METHYLENEBICYCLO[3.1.1]HEPTANE	In Vitro	Not mutagenic
Methyl acetate	In Vitro	Not mutagenic
Methyl acetate	In vivo	Not mutagenic
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Petroleum naphtha	In vivo	Not mutagenic
Petroleum naphtha	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

# Carcinogenicity

Name	Route	Species	Value
Acetone	Not	Multiple	Not carcinogenic
	Specified	animal	
		species	
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
Petroleum naphtha	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Petroleum naphtha	Inhalation	Human	Some positive data exist, but the data are not
		and	sufficient for classification
		animal	
Toluene	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not
			sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not
			sufficient for classification

# **Reproductive Toxicity**

# **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Dimethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
Pentane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
Pentane	Inhalation	Not classified for development	Rat	NOAEL 30 mg/l	during organogenesis
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Petroleum naphtha	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not	occupational

				available	exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3	1 generation
				mg/l	
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520	during
	_	-		mg/kg/day	gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not	poisoning
		-		available	and/or abuse

# Target Organ(s)

# Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Pentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
Pentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
Pentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	not available
Pentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	not available
Methyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal	NOAEL Not available	

				judgeme nt		
Petroleum naphtha	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Petroleum naphtha	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Petroleum naphtha	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Petroleum naphtha	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

# Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Dimethyl Ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Pentane	Inhalation	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Pentane	Inhalation	heart   skin	Not classified	Rat	NOAEL 20	13 weeks

	1	1	1			1
		endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system			mg/l	
Pentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
BICYCLO[3.1.1]HEPT-2- ENE,2,6,6- TRIMETHYL-,POLYME R WITH 6,6-DIMETHYL- 2- METHYLENEBICYCLO[ 3.1.1]HEPTANE	Ingestion	heart   gastrointestinal tract   hematopoietic system   liver   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 331 mg/kg/day	90 days
Methyl acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Petroleum naphtha	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Petroleum naphtha	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Petroleum naphtha	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Petroleum naphtha	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Petroleum naphtha	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not	20 days

					available	
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

## **Aspiration Hazard**

Name	Value
Pentane	Aspiration hazard
Cyclohexane	Aspiration hazard
Petroleum naphtha	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

# 12.1. Toxicity

Acute aquatic hazard: GHS Acute 2: Toxic to aquatic life.

### **Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Туре	Exposure	Test Endpoint	Test Result
Acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Crustecea other	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Rainbow Trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100

Dimethyl Ether	115 10 6	Bacteria	Experimental		EC10	>1,600 mg/l
			Experimental	96 hours	LC50	>4,100 mg/l
Dimethyl Ether		Guppy Water flea		48 hours	EC50	2 0
Dimethyl Ether Isobutane	75-28-5	water nea	Experimental Data not available or	48 nours	EC30	>4,400 mg/l N/A
			insufficient for classification			
BICYCLO[3.1. 1]HEPT-2- ENE,2,6,6-	31393-98-3	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
TRIMETHYL-, POLYMER						
WITH 6,6- DIMETHYL- 2-						
METHYLENE BICYCLO[3.1. 1]HEPTANE						
	31393-98-3	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
POLYMER WITH 6,6- DIMETHYL-						
2- METHYLENE BICYCLO[3.1.						
1]HEPTANE BICYCLO[3.1.	31393-98-3	Water flea	Endpoint not	21 days	EL10	>100 mg/l
1]HEPT-2- ENE,2,6,6- TRIMETHYL-,			reached			
POLYMER WITH 6,6- DIMETHYL-						
2- METHYLENE						
BICYCLO[3.1. 1]HEPTANE						
Non-hazardous components	Trade Secret		Data not available or insufficient for classification			N/A
Pentane	109-66-0	Green Algae	Experimental	72 hours	EC50	10.7 mg/l
Pentane	109-66-0	Rainbow Trout	Experimental	96 hours	LC50	4.26 mg/l
Pentane	109-66-0	Water flea	Experimental	48 hours	EC50	2.7 mg/l
Pentane	109-66-0	Green Algae	Experimental	72 hours	NOEC	2.04 mg/l
Methyl acetate	79-20-9	Bacteria	Experimental	16 hours	EC50	6,000 mg/l
Methyl acetate	79-20-9	Green algae	Experimental	72 hours	EC50	>120 mg/l
Methyl acetate	79-20-9	Water flea	Experimental	48 hours	EC50	1,026.7 mg/l
Methyl acetate	79-20-9	Green algae	Experimental	72 hours	NOEC	120 mg/l
Cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
Cyclohexane	110-82-7	Fathead Minnow	Experimental	96 hours	LC50	4.53 mg/l

Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Petroleum naphtha	64742-48-9	Fathead Minnow	Estimated	96 hours	LL50	8.2 mg/l
Petroleum naphtha	64742-48-9	Green Algae	Estimated	72 hours	EL50	3.1 mg/l
Petroleum naphtha	64742-48-9	Water flea	Estimated	48 hours	EL50	4.5 mg/l
Petroleum naphtha	64742-48-9	Green Algae	Estimated	72 hours	NOEL	0.5 mg/l
Petroleum naphtha	64742-48-9	Water flea	Estimated	21 days	NOEL	2.6 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

# 12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Acetone	67-64-1	Experimental		Photolytic half-	147 days (t 1/2)	
		Photolysis		life (in air)		
Acetone	67-64-1	Experimental	28 days	Biological	78 %	OECD 301D - Closed
		Biodegradation		Oxygen	BOD/ThBOD	Bottle Test
				Demand		
Dimethyl Ether	115-10-6	Experimental		Photolytic half-	12.4 days (t	Non-standard method
		Photolysis		life (in air)	1/2)	
Dimethyl Ether	115-10-6	Experimental	28 days	Biological	5 % weight	OECD 301D - Closed
		Biodegradation		Oxygen		Bottle Test
				Demand		
Isobutane	75-28-5	Experimental		Photolytic half-	13.4 days (t	Non-standard method
		Photolysis		life (in air)	1/2)	
L .	31393-98-3	Experimental	28 days	Biological	4 %	OECD 301D - Closed
1]HEPT-2-		Biodegradation		Oxygen	BOD/ThBOD	Bottle Test
ENE,2,6,6-				Demand		
TRIMETHYL-,						
POLYMER						
WITH 6,6-						
DIMETHYL-						
2-						
METHYLENE						
BICYCLO[3.1.						

1]HEPTANE						
Non-hazardous components	Trade Secret	Data not availbl- insufficient			N/A	
Pentane	109-66-0	Experimental Photolysis		Photolytic half- life (in air)	8.07 days (t 1/2)	Non-standard method
Pentane	109-66-0	Experimental Biodegradation	28 days	Biological Oxygen Demand	87 % BOD/ThBOD	OECD 301F - Manometric Respiro
Methyl acetate	79-20-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	70 % weight	OECD 301D - Closed Bottle Test
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half- life (in air)	4.14 days (t 1/2)	Non-standard method
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	Biological Oxygen Demand	77 % BOD/ThBOD	OECD 301F - Manometric Respiro
Petroleum naphtha	64742-48-9	Estimated Biodegradation	28 days	Biological Oxygen Demand	10 % BOD/ThBOD	OECD 301D - Closed Bottle Test
Toluene	108-88-3	Experimental Photolysis		Photolytic half- life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater

# 12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Acetone	67-64-1	Experimental		Bioaccumulatio	0.65	
		BCF - Other		n Factor		
Acetone	67-64-1	Experimental		Log of	-0.24	
		Bioconcentrati		Octanol/H2O		
		on		part. coeff		
Dimethyl Ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Isobutane	75-28-5	Experimental Bioconcentrati on		Log of Octanol/H2O part. coeff	2.76	Non-standard method
BICYCLO[3.1.	31393-98-3	Experimental		Log of	7.41	Non-standard method
1]HEPT-2-		Bioconcentrati		Octanol/H2O		
ENE,2,6,6-		on		part. coeff		
TRIMETHYL-,						
POLYMER						
WITH 6,6-						
DIMETHYL-						
2-						
METHYLENE						
BICYCLO[3.1.						
1]HEPTANE						
Non-hazardous	Trade Secret	Data not	N/A	N/A	N/A	N/A
components		available or				
		insufficient for				

		classification				
Pentane	109-66-0	Estimated Bioconcentrati on		Bioaccumulatio n Factor	26	Est: Bioconcentration factor
Methyl acetate	79-20-9	Experimental Bioconcentrati on		Log of Octanol/H2O part. coeff	0.18	Non-standard method
Cyclohexane	110-82-7	Experimental BCF-Carp	56 days	Bioaccumulatio n Factor	129	OECD 305E-Bioaccum Fl-thru fis
Petroleum naphtha	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulatio n Factor	90	
Toluene	108-88-3	Experimental Bioconcentrati on		Log of Octanol/H2O part. coeff	2.73	

# 12.4. Mobility in soil

Please contact manufacturer for more details

## 12.5 Other adverse effects

No information available

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

# **SECTION 14: Transport Information**

## Marine Transport (IMDG)

UN Number:UN1950 Proper Shipping Name:AEROSOLS, FLAMMABLE Technical Name:None assigned. Hazard Class/Division:2.1 Subsidiary Risk:None assigned. Packing Group:None assigned. Limited Quantity:Yes Marine Pollutant: None assigned. Marine Pollutant Technical Name: None assigned. Other Dangerous Goods Descriptions: None assigned.

Air Transport (IATA)

UN Number:UN1950 Proper Shipping Name:AEROSOLS, FLAMMABLE Technical Name:None assigned. Hazard Class/Division:2.1 Subsidiary Risk:None assigned. Packing Group:None assigned. Limited Quantity:None assigned. Marine Pollutant: None assigned. Marine Pollutant Technical Name: None assigned. Other Dangerous Goods Descriptions: None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

# **SECTION 16: Other information**

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

## 3M Malaysia SDSs are available at www.3M.com.my