



Safety Data Sheet

Copyright, 2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-0641-7	Version Number:	5.00
Issue Date:	30/04/2020	Supersedes Date:	10/05/2015

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M(TM) Fire Barrier Moldable Putty Stix MP+

Product Identification Numbers

42-0016-4776-9	44-0042-9356-7	44-0042-9357-5	44-0042-9358-3	44-0042-9360-9
70-0067-7248-0	98-0400-5417-7	XF-0038-6975-7		

1.2. Recommended use and restrictions on use

Recommended use

Passive fire protection in industrial applications

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS:	3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone:	03-7884 2888
E Mail:	3mmyehsr@mmm.com
Website:	www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Acute Aquatic Toxicity: Category 1.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Warning

3M(TM) Fire Barrier Moldable Putty Stix MP+

Symbols

Exclamation mark | Health Hazard | Environment |

Pictograms



Hazard Statements

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.

H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

General:

P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.

Prevention:

P280B Wear protective gloves and eye/face protection.
P280E Wear protective gloves.
P273 Avoid release to the environment.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Zinc Borate 2335	138265-88-0	10 - 30
Petrolatum	8009-03-8	10 - 15
Sodium Silicate	1344-09-8	10 - 15
Polymer NJTS Reg. No. 04499600-7315	Trade Secret	10 - 15
Melamine Phosphate	41583-09-9	7 - 13
Polybutylene	9003-29-6	7 - 13

3M(TM) Fire Barrier Moldable Putty Stix MP+

Butadiene-Styrene-Meta-Divinylbenzene Polymer	26471-45-4	3 - 7
OXIDE GLASS CHEMICALS	65997-17-3	3 - 7
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	1 - 5
Non-hazardous ingredients	Mixture	1 - 5
Rayon Fiber	None	< 5
Alpha-Methylstyrene-Isoamylene-Piperylene Polymer	62258-49-5	< 2
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER (MW unknown or <=700)	25068-38-6	< 2
Rosin	8050-09-7	< 1

Any remaining components do not contribute to the hazards of this material.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Aldehydes
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

3M(TM) Fire Barrier Moldable Putty Stix MP+

Hydrogen Chloride

During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from areas where product may come into contact with food or pharmaceuticals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
GLASS FILAMENTS	65997-17-3	Malaysia OELs	TWA(as fiber)(8 hours):1 fibers/ml;TWA(inhalable fraction)(8 hours):5 mg/m3	
OXIDE GLASS CHEMICALS	65997-17-3	Manufacturer determined	TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3;TWA(as non-fibrous, respirable)(8 hours):3 mg/m3	
MINERAL OILS, HIGHLY-REFINED OILS	8009-03-8	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
OIL MIST, MINERAL	8009-03-8	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m3	
Rosin	8050-09-7	ACGIH	Limit value not established:	Dermal/Respiratory Sensitizer, Cntrl all

3M(TM) Fire Barrier Moldable Putty Stix MP+

				exposr-low as possib
Rosin	8050-09-7	Malaysia OELs	Limit value not established:	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Putty
Color	Red
Odor	Odorless
Odor threshold	No Data Available
pH	No Data Available
Melting point/Freezing point	Not Applicable
Boiling point/Initial boiling point/Boiling range	Not Applicable
Flash Point	Flash point > 93 °C (200 °F)
Evaporation rate	Not Applicable

3M(TM) Fire Barrier Moldable Putty Stix MP+

Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Density	1.25 g/cm ³
Relative Density	1.25 [Ref Std: WATER=1]
Water solubility	<i>No Data Available</i>
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	< 1 % weight
VOC Less H ₂ O & Exempt Solvents	< 1 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

3M(TM) Fire Barrier Moldable Putty Stix MP+**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Zinc Borate 2335	Dermal	Rabbit	LD50 > 5,000 mg/kg
Zinc Borate 2335	Inhalation-Dust/Mist	Rat	LC50 > 4.95 mg/l
Zinc Borate 2335	Ingestion	Rat	LD50 > 5,000 mg/kg
Sodium Silicate	Dermal	Rabbit	LD50 > 4,640 mg/kg
Sodium Silicate	Ingestion	Rat	LD50 500 mg/kg
Petrolatum	Dermal		LD50 estimated to be > 5,000 mg/kg
Petrolatum	Ingestion	Rat	LD50 > 5,000 mg/kg
Polymer NJTS Reg. No. 04499600-7315	Dermal	Rabbit	LD50 > 2,000 mg/kg
Polymer NJTS Reg. No. 04499600-7315	Ingestion	Rat	LD50 > 5,000 mg/kg
Polybutylene	Dermal	Rat	LD50 > 10,250 mg/kg
Polybutylene	Ingestion	Rat	LD50 > 34,600 mg/kg
Melamine Phosphate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Melamine Phosphate	Ingestion	Rat	LD50 > 4,000 mg/kg
OXIDE GLASS CHEMICALS	Dermal		LD50 estimated to be > 5,000 mg/kg
OXIDE GLASS CHEMICALS	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Butadiene-Styrene-Meta-Divinylbenzene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Butadiene-Styrene-Meta-Divinylbenzene Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER (MW unknown or <=700)	Dermal	Rat	LD50 > 1,600 mg/kg
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-	Ingestion	Rat	LD50 > 1,000 mg/kg

3M(TM) Fire Barrier Moldable Putty Stix MP+

EPICHLOROHYDRIN POLYMER (MW unknown or <=700)			
Alpha-Methylstyrene-Isoamylene-Piperylene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Alpha-Methylstyrene-Isoamylene-Piperylene Polymer	Ingestion	Rat	LD50 > 40,000 mg/kg
Rosin	Dermal	Rabbit	LD50 > 2,500 mg/kg
Rosin	Ingestion	Rat	LD50 7,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Zinc Borate 2335	Rabbit	No significant irritation
Sodium Silicate	Rabbit	Corrosive
Polymer NJTS Reg. No. 04499600-7315	Professional judgement	No significant irritation
Polybutylene	Rabbit	Minimal irritation
OXIDE GLASS CHEMICALS	Professional judgement	No significant irritation
Butadiene-Styrene-Meta-Divinylbenzene Polymer	Professional judgement	Minimal irritation
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER (MW unknown or <=700)	Rabbit	Mild irritant
Rosin	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Zinc Borate 2335	Rabbit	Severe irritant
Sodium Silicate	Rabbit	Corrosive
Polybutylene	Rabbit	Mild irritant
OXIDE GLASS CHEMICALS	Professional judgement	No significant irritation
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER (MW unknown or <=700)	Rabbit	Moderate irritant
Rosin	Rabbit	Mild irritant

Sensitization:**Skin Sensitization**

Name	Species	Value
Zinc Borate 2335	Guinea pig	Not classified
Sodium Silicate	Mouse	Not classified
Synthetic amorphous silica, fumed, crystalline-free	Human and animal	Not classified
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER (MW unknown or <=700)	Human and animal	Sensitizing
Rosin	Guinea pig	Sensitizing

Respiratory Sensitization

3M(TM) Fire Barrier Moldable Putty Stix MP+

Name	Species	Value
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	Human	Not classified
Rosin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Zinc Borate 2335	In Vitro	Some positive data exist, but the data are not sufficient for classification
Sodium Silicate	In Vitro	Not mutagenic
Sodium Silicate	In vivo	Not mutagenic
OXIDE GLASS CHEMICALS	In Vitro	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	In Vitro	Not mutagenic
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	In vivo	Not mutagenic
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
OXIDE GLASS CHEMICALS	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Zinc Borate 2335	Ingestion	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	92 days
Zinc Borate 2335	Ingestion	Toxic to development	Rat	LOAEL 100 mg/kg/day	during gestation
Sodium Silicate	Ingestion	Not classified for development	Mouse	NOAEL 200 mg/kg/day	during gestation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
NUC - 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER (MW unknown or <=700)	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

3M(TM) Fire Barrier Moldable Putty Stix MP+**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Zinc Borate 2335	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Sodium Silicate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Zinc Borate 2335	Inhalation	immune system respiratory system heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	2 weeks
Zinc Borate 2335	Ingestion	endocrine system liver kidney and/or bladder heart skin bone, teeth, nails, and/or hair hematopoietic system immune system nervous system eyes respiratory system vascular system	Not classified	Rat	NOAEL 375 mg/kg/day	92 days
Sodium Silicate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 2,400 mg/kg/day	4 weeks
Sodium Silicate	Ingestion	endocrine system blood	Not classified	Rat	NOAEL 804 mg/kg/day	3 months
Sodium Silicate	Ingestion	heart liver	Not classified	Rat	NOAEL 1,259 mg/kg/day	8 weeks
Polybutylene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.07 mg/l	2 weeks
Polybutylene	Inhalation	liver	Not classified	Rat	NOAEL 0.7 mg/l	2 weeks
OXIDE GLASS CHEMICALS	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Synthetic amorphous silica, fumed, crystalline-free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
NUC - 4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER (MW unknown or <=700)	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
NUC - 4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER (MW unknown or <=700)	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
NUC - 4,4'-	Ingestion	auditory system	Not classified	Rat	NOAEL	28 days

3M(TM) Fire Barrier Moldable Putty Stix MP+

ISOPROPYLLIDENEDIPH ENOL- EPICHLOROHYDRIN POLYMER (MW unknown or <=700)		heart endocrine system hematopoietic system liver eyes kidney and/or bladder			1,000 mg/kg/day	
---	--	---	--	--	--------------------	--

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Zinc Borate 2335	138265-88-0	Chinook Salmon	Estimated	96 hours	Lethal Concentration 50%	0.43 mg/l
Zinc Borate 2335	138265-88-0	Green Algae	Estimated	72 hours	Effect Concentration 50%	0.085 mg/l
Zinc Borate 2335	138265-88-0	Water flea	Estimated	48 hours	Effect Concentration 50%	5.9 mg/l
Zinc Borate 2335	138265-88-0	Green Algae	Estimated	72 hours	No obs Effect Conc	0.039 mg/l
Petrolatum	8009-03-8	Fathead Minnow	Estimated	96 hours	Lethal Level 50%	>100 mg/l
Petrolatum	8009-03-8	Water flea	Estimated	48 hours	Effect Level 50%	>10,000 mg/l
Petrolatum	8009-03-8	Green Algae	Estimated	72 hours	No obs Effect Level	100 mg/l
Petrolatum	8009-03-8	Water flea	Estimated	21 days	No obs Effect Level	10 mg/l
Polymer NJTS Reg. No. 04499600-7315	Trade Secret		Data not available or insufficient for classification			
Sodium Silicate	1344-09-8	Green algae	Experimental	72 hours	Effect	>345.4 mg/l

3M(TM) Fire Barrier Moldable Putty Stix MP+

					Concentration 50%	
Sodium Silicate	1344-09-8	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	281 mg/l
Sodium Silicate	1344-09-8	Water flea	Experimental	48 hours	Effect Concentration 50%	1,700 mg/l
Sodium Silicate	1344-09-8	Green algae	Experimental	72 hours	No obs Effect Conc	35 mg/l
Melamine Phosphate	41583-09-9	Green Algae	Estimated	96 hours	Effect Concentration 50%	1,700 mg/l
Melamine Phosphate	41583-09-9	Guppy	Estimated	96 hours	Lethal Concentration 50%	>5,300 mg/l
Melamine Phosphate	41583-09-9	Water flea	Estimated	48 hours	Effect Concentration 50%	85 mg/l
Melamine Phosphate	41583-09-9	Green Algae	Estimated	96 hours	No obs Effect Conc	>570 mg/l
Melamine Phosphate	41583-09-9	Water flea	Estimated	21 days	No obs Effect Conc	32 mg/l
Polybutylene	9003-29-6		Data not available or insufficient for classification			
Butadiene- Styrene-Meta- Divinylbenzene Polymer	26471-45-4		Data not available or insufficient for classification			
OXIDE GLASS CHEMICALS	65997-17-3	Green algae	Experimental	72 hours	Effect Concentration 50%	>1,000 mg/l
OXIDE GLASS CHEMICALS	65997-17-3	Water flea	Experimental	72 hours	Effect Concentration 50%	>1,000 mg/l
OXIDE GLASS CHEMICALS	65997-17-3	Zebra Fish	Experimental	96 hours	Lethal Concentration 50%	>1,000 mg/l
OXIDE GLASS CHEMICALS	65997-17-3	Green algae	Experimental	72 hours	No obs Effect Conc	>=1,000 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Green Algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Water flea	Experimental	24 hours	Effect Concentration 50%	>100 mg/l
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Zebra Fish	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l

3M(TM) Fire Barrier Moldable Putty Stix MP+

Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Green Algae	Experimental	72 hours	No obs Effect Conc	60 mg/l
Alpha-Methylstyrene-Isoamylene-Piperylene Polymer	62258-49-5		Data not available or insufficient for classification			
NUC - 4,4'-ISOPROPYLI DENEDIPHENOL-EPICHLOROH YDRIN POLYMER (MW unknown or <=700)	25068-38-6	Rainbow Trout	Estimated	96 hours	Lethal Concentration 50%	2 mg/l
NUC - 4,4'-ISOPROPYLI DENEDIPHENOL-EPICHLOROH YDRIN POLYMER (MW unknown or <=700)	25068-38-6	Water flea	Estimated	48 hours	Lethal Concentration 50%	1.8 mg/l
NUC - 4,4'-ISOPROPYLI DENEDIPHENOL-EPICHLOROH YDRIN POLYMER (MW unknown or <=700)	25068-38-6	Green Algae	Experimental	72 hours	Effect Concentration 50%	>11 mg/l
NUC - 4,4'-ISOPROPYLI DENEDIPHENOL-EPICHLOROH YDRIN POLYMER (MW unknown or <=700)	25068-38-6	Green Algae	Experimental	72 hours	No obs Effect Conc	4.2 mg/l
NUC - 4,4'-ISOPROPYLI DENEDIPHENOL-EPICHLOROH YDRIN POLYMER (MW unknown or <=700)	25068-38-6	Water flea	Experimental	21 days	No obs Effect Conc	0.3 mg/l
Rosin	8050-09-7	Green Algae	Experimental	72 hours	Effect Level	>100 mg/l

3M(TM) Fire Barrier Moldable Putty Stix MP+

					50%	
Rosin	8050-09-7	Water flea	Experimental	48 hours	Effect Level 50%	911 mg/l
Rosin	8050-09-7	Zebra Fish	Experimental	96 hours	Lethal Level 50%	>1 mg/l
Rosin	8050-09-7	Green Algae	Experimental	72 hours	No obs Effect Level	>100 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Zinc Borate 2335	138265-88-0	Data not availbl- insufficient			N/A	
Petrolatum	8009-03-8	Estimated Biodegradation	28 days	Biological Oxygen Demand	31 %BOD/CO D	OECD 301F - Manometric Respiro
Polymer NJTS Reg. No. 04499600-7315	Trade Secret	Data not availbl- insufficient			N/A	
Sodium Silicate	1344-09-8	Data not availbl- insufficient			N/A	
Melamine Phosphate	41583-09-9	Estimated Biodegradation	14 days	Biological Oxygen Demand	0 % BOD/ThBOD	OECD 301C - MITI (I)
Polybutylene	9003-29-6	Data not availbl- insufficient			N/A	
Butadiene- Styrene-Meta- Divinylbenzene Polymer	26471-45-4	Data not availbl- insufficient			N/A	
OXIDE GLASS CHEMICALS	65997-17-3	Data not availbl- insufficient			N/A	
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Data not availbl- insufficient			N/A	
Alpha- Methylstyrene- Isoamylene- Piperylene Polymer	62258-49-5	Estimated Biodegradation	28 days	Carbon dioxide evolution	18.7 % weight	OECD 301B - Mod. Sturm or CO2
NUC - 4,4'- ISOPROPYLI DENEDIPHEN OL- EPICHLOROH YDRIN POLYMER (MW unknown or <=700)	25068-38-6	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	Other methods
NUC - 4,4'-	25068-38-6	Experimental	28 days	Biological	5 %BOD/COD	OECD 301F -

3M(TM) Fire Barrier Moldable Putty Stix MP+

ISOPROPYLI DENEDIPHEN OL- EPICHLOROH YDRIN POLYMER (MW unknown or <=700)		Biodegradation		Oxygen Demand		Manometric Respiro
Rosin	8050-09-7	Experimental Biodegradation	28 days	Carbon dioxide evolution	64 % weight	OECD 301B - Mod. Sturm or CO2

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Zinc Borate 2335	138265-88-0	Estimated Bioconcentrati on		Bioaccumulatio n Factor	=217	OECD 305E-Bioaccum FI-thru fis
Petrolatum	8009-03-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polymer NJTS Reg. No. 04499600-7315	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sodium Silicate	1344-09-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Melamine Phosphate	41583-09-9	Estimated BCF-Carp	42 days	Bioaccumulatio n Factor	<3.8	OECD 305E-Bioaccum FI-thru fis
Polybutylene	9003-29-6	Estimated Bioconcentrati on		Bioaccumulatio n Factor	<=78	Est: Bioconcentration factor
Butadiene- Styrene-Meta- Divinylbenzene Polymer	26471-45-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
OXIDE GLASS CHEMICALS	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic amorphous silica, fumed, crystalline-free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Alpha- Methylstyrene- Isoamylene- Piperylene Polymer	62258-49-5	Estimated Bioconcentrati on		Bioaccumulatio n Factor	7.7	Est: Bioconcentration factor
NUC - 4,4'- ISOPROPYLI DENEDIPHEN OL-	25068-38-6	Experimental Bioconcentrati on		Log of Octanol/H2O part. coeff	3.242	Other methods

3M(TM) Fire Barrier Moldable Putty Stix MP+

EPICHLOROH YDRIN POLYMER (MW unknown or <=700)						
Rosin	8050-09-7	Estimated BCF - Rainbow Tr	20 days	Bioaccumulation Factor	129	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

Air Transport (IATA)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

3M(TM) Fire Barrier Moldable Putty Stix MP+

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my