



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	10-2794-5	Version Number:	5.00
Issue Date:	01/02/2024	Supersedes Date:	17/02/2022

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

Product Identification Numbers

62-1300-2631-3 62-1300-2632-1 62-1300-6530-3 62-1300-7530-2 62-1300-8530-1

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Industrial use

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 2.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (repeated exposure): Category 1.
Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard | Environment |

Pictograms



Hazard Statements:

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H360 May damage fertility or the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure: nervous system.
- H373 May cause damage to organs through prolonged or repeated exposure: nervous system | sensory organs.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P273 Avoid release to the environment.
- P281 Use personal protective equipment as required.

Response:

- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Disposal:

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Aspiration classification does not apply due to the viscosity of the product., May cause drowsiness or dizziness.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Petroleum Distillates	64741-84-0	20 - 35
Methyl Ethyl Ketone	78-93-3	20 - 30
Magnesium Resinate	68037-42-3	< 25

Hexane	110-54-3	5 - 20*
Polychloroprene	9010-98-4	10 - 20
P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	25085-50-1	7 - 15
Toluene	108-88-3	< 10
Heptane	142-82-5	< 10*
Magnesium Oxide	1309-48-4	3 - 7
2-Methylpentane	107-83-5	< 5*
3-Methylpentane	96-14-0	< 5*
Cyclohexane	110-82-7	< 5*
Ethylbenzene	100-41-4	< 1
Acetone	67-64-1	< 1
Zinc Oxide	1314-13-2	< 1
Rosin	8050-09-7	< 1
Styrenated Phenol	61788-44-1	< 1
p-Tert-Butylphenol	98-54-4	< 0.2

*These components are contained as a part of Petroleum Distillates(64741-84-0)

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes

Hydrocarbons

Condition

During Combustion

During Combustion

Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Irritant Vapors or Gases

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin., Ototoxicant
Ethylbenzene	100-41-4	Malaysia OELs	TWA(8 hours):434 mg/m ³ (100 ppm)	
2-Methylpentane	107-83-5	ACGIH	TWA:500 ppm;STEL:1000 ppm	
HEXANE (ISOMERS OTHER THAN N-HEXANE)	107-83-5	Malaysia OELs	TWA(8 hours):1760 mg/m ³ (500 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m ³ (50 ppm)	SKIN
Hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous absorption
Hexane	110-54-3	Malaysia OELs	TWA(8 hours):176 mg/m ³ (50 ppm)	SKIN
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	Malaysia OELs	TWA(8 hours):1030 mg/m ³ (300 ppm)	
DUST, INERT OR NUISANCE	1309-48-4	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m ³ ;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m ³	
Magnesium Oxide	1309-48-4	ACGIH	TWA(inhalable fraction):10 mg/m ³	A4: Not class. as human carcin
Magnesium Oxide	1309-48-4	Malaysia OELs	TWA(as fume)(8 hours):10 mg/m ³	
DUST, INERT OR NUISANCE	1314-13-2	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m ³ ;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m ³	
Zinc Oxide	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m ³ ;STEL(respirable fraction):10 mg/m ³	
Zinc Oxide	1314-13-2	Malaysia OELs	TWA(as fume)(8 hours):5 mg/m ³ ;TWA(as dust)(8 hours):10 mg/m ³	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Heptane	142-82-5	Malaysia OELs	TWA(8 hours):1640 mg/m ³ (400 ppm)	
Naphtha	64741-84-0	Malaysia OELs	TWA(8 hours):1590 mg/m ³ (400 ppm)	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin
Acetone	67-64-1	Malaysia OELs	TWA(8 hours):1187 mg/m ³ (500 ppm)	

Methyl Ethyl Ketone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	
Methyl Ethyl Ketone	78-93-3	Malaysia OELs	TWA(8 hours):590 mg/m3(200 ppm)	
Rosin	8050-09-7	ACGIH	TWA(as Resin, inhalable fraction):0.001 mg/m3	Dermal/Respiratory Sensitizer
Rosin	8050-09-7	Malaysia OELs	Limit value not established:	
3-Methylpentane	96-14-0	ACGIH	TWA:500 ppm;STEL:1000 ppm	
HEXANE (ISOMERS OTHER THAN N-HEXANE)	96-14-0	Malaysia OELs	TWA(8 hours):1760 mg/m3(500 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Yellow
Odor	Solvent
Odor threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	>=80 °C
Flash Point	-20 °C [Test Method:Closed Cup] [Details:Petroleum Distillates]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	1 % volume
Flammable Limits(UEL)	10 % volume
Vapor Pressure	<=12,132.3 Pa [@ 25 °C]
Vapor Density and/or Relative Vapor Density	>=2.41 [Ref Std:AIR=1]
Density	0.88 g/ml
Relative Density	0.88 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	1,500 - 4,000 mPa-s [@ 27 °C]
Volatile Organic Compounds	<=615 g/l [Details:EU VOC content]
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	<=610 g/l [Test Method:calculated SCAQMD rule 443.1]
Molecular weight	No Data Available
Solids Content	30 - 50 %

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Petroleum Distillates	Dermal	Rat	LD50 > 2,800 mg/kg
Petroleum Distillates	Inhalation-Vapor (4 hours)	Rat	LC50 > 25.2 mg/l
Petroleum Distillates	Ingestion	Rat	LD50 > 5,840 mg/kg
Methyl Ethyl Ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Methyl Ethyl Ketone	Inhalation-Vapor (4 hours)	Rat	LC50 34.5 mg/l
Methyl Ethyl Ketone	Ingestion	Rat	LD50 2,737 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
Magnesium Resinate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium Resinate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Polychloroprene	Dermal		LD50 estimated to be > 5,000 mg/kg
Polychloroprene	Ingestion	Rat	LD50 > 20,000 mg/kg
P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	Dermal		LD50 estimated to be > 5,000 mg/kg
P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	Ingestion	Rat	LD50 5,660 mg/kg
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg
Heptane	Inhalation-Vapor (4 hours)	Rat	LC50 103 mg/l
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
2-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Inhalation-Vapor		LC50 estimated to be > 50 mg/l
2-Methylpentane	Ingestion		LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
3-Methylpentane	Inhalation-Vapor		LC50 estimated to be > 50 mg/l
3-Methylpentane	Ingestion		LD50 estimated to be > 5,000 mg/kg
Magnesium Oxide	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium Oxide	Ingestion	Rat	LD50 3,870 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Zinc Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Zinc Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
Zinc Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Rosin	Dermal	Rabbit	LD50 > 2,500 mg/kg
Rosin	Ingestion	Rat	LD50 7,600 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Styrenated Phenol	Dermal	Rat	LD50 > 2,000 mg/kg
Styrenated Phenol	Ingestion	Rat	LD50 > 2,000 mg/kg
p-Tert-Butylphenol	Dermal	Rabbit	LD50 2,318 mg/kg
p-Tert-Butylphenol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.6 mg/l
p-Tert-Butylphenol	Ingestion	Rat	LD50 4,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Petroleum Distillates	Rabbit	Irritant
Methyl Ethyl Ketone	Rabbit	Minimal irritation
Hexane	Human and animal	Mild irritant
Polychloroprene	Human	No significant irritation
Heptane	Human	Mild irritant
Toluene	Rabbit	Irritant
2-Methylpentane	Professional judgement	Mild irritant
3-Methylpentane	Professional judgement	Mild irritant
Magnesium Oxide	Professional judgement	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Acetone	Mouse	Minimal irritation
Zinc Oxide	Human and animal	No significant irritation
Rosin	Rabbit	No significant irritation
Ethylbenzene	Rabbit	Mild irritant
Styrenated Phenol	Rabbit	No significant irritation
p-Tert-Butylphenol	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Petroleum Distillates	Rabbit	Mild irritant
Methyl Ethyl Ketone	Rabbit	Severe irritant
Hexane	Rabbit	Mild irritant

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

Polychloroprene	Professional judgement	No significant irritation
Heptane	Professional judgement	Moderate irritant
Toluene	Rabbit	Moderate irritant
2-Methylpentane	Professional judgement	Moderate irritant
3-Methylpentane	Professional judgement	Moderate irritant
Cyclohexane	Rabbit	Mild irritant
Acetone	Rabbit	Severe irritant
Zinc Oxide	Rabbit	Mild irritant
Rosin	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant
Styrenated Phenol	Rabbit	Mild irritant
p-Tert-Butylphenol	Rabbit	Corrosive

Sensitization:
Skin Sensitization

Name	Species	Value
Petroleum Distillates	Guinea pig	Not classified
Hexane	Human	Not classified
P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	Human	Some positive data exist, but the data are not sufficient for classification
Toluene	Guinea pig	Not classified
Zinc Oxide	Guinea pig	Not classified
Rosin	Guinea pig	Sensitizing
Ethylbenzene	Human	Not classified
Styrenated Phenol	Mouse	Sensitizing
p-Tert-Butylphenol	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
Rosin	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Methyl Ethyl Ketone	In Vitro	Not mutagenic
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
Heptane	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Magnesium Oxide	In Vitro	Not mutagenic
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not

		sufficient for classification
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Zinc Oxide	In vivo	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
p-Tert-Butylphenol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Methyl Ethyl Ketone	Inhalation	Human	Not carcinogenic
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Magnesium Oxide	Not Specified	Human and animal	Some positive data exist, but the data are not sufficient for classification
Acetone	Not Specified	Multiple animal species	Not carcinogenic
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic
p-Tert-Butylphenol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Petroleum Distallates	Ingestion	Toxic to male reproduction	similar compounds	NOAEL not available	not available
Petroleum Distallates	Inhalation	Toxic to male reproduction	similar compounds	NOAEL not available	not available
Methyl Ethyl Ketone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520	during

				mg/kg/day	gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Zinc Oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
p-Tert-Butylphenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	2 generation
p-Tert-Butylphenol	Ingestion	Not classified for development	Rat	NOAEL 70 mg/kg/day	2 generation
p-Tert-Butylphenol	Ingestion	Toxic to female reproduction	Rat	NOAEL 200 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	not available
Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	not available
Methyl Ethyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classification	NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
Methyl Ethyl Ketone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
2-Methylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	
2-Methylpentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
3-Methylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
3-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
3-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	
3-Methylpentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Magnesium Oxide	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
p-Tert-Butylphenol	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	LOAEL 5.6	4 hours

					mg/l	
--	--	--	--	--	------	--

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Distillates	Inhalation	peripheral nervous system	May cause damage to organs though prolonged or repeated exposure	similar compounds	NOAEL not available	not available
Methyl Ethyl Ketone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Methyl Ethyl Ketone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
Methyl Ethyl Ketone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
Hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
Hexane	Inhalation	auditory system immune system eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart skin endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
Heptane	Inhalation	liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks
Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic	Not classified	Human	NOAEL Not available	occupational

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

		system vascular system			available	exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
2-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
2-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
2-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg	28 days
3-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
3-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
3-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg	28 days
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500	13 weeks

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

					mg/kg/day	
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Zinc Oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
Zinc Oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
p-Tert-Butylphenol	Ingestion	endocrine system liver kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	2 generation
p-Tert-Butylphenol	Ingestion	blood	Not classified	Rat	NOAEL 200 mg/kg	6 weeks

Aspiration Hazard

Name	Value
Petroleum Distillates	Aspiration hazard
Hexane	Aspiration hazard
Heptane	Aspiration hazard
Toluene	Aspiration hazard
2-Methylpentane	Aspiration hazard
3-Methylpentane	Aspiration hazard
Cyclohexane	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300
Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Petroleum Distallates	64741-84-0	Green algae	Estimated	72 hours	EC50	30 mg/l
Petroleum Distallates	64741-84-0	Rainbow Trout	Estimated	96 hours	LL50	11.4 mg/l
Petroleum Distallates	64741-84-0	Water flea	Estimated	48 hours	EL50	3 mg/l
Petroleum Distallates	64741-84-0	Green algae	Estimated	72 hours	NOEL	3 mg/l
Petroleum Distallates	64741-84-0	Water flea	Estimated	21 days	NOEL	1 mg/l
Methyl Ethyl Ketone	78-93-3	Fathead Minnow	Experimental	96 hours	LC50	2,993 mg/l
Methyl Ethyl Ketone	78-93-3	Green algae	Experimental	96 hours	ErC50	2,029 mg/l
Methyl Ethyl Ketone	78-93-3	Water flea	Experimental	48 hours	EC50	308 mg/l
Methyl Ethyl Ketone	78-93-3	Green algae	Experimental	96 hours	ErC10	1,289 mg/l
Methyl Ethyl Ketone	78-93-3	Water flea	Experimental	21 days	NOEC	100 mg/l
Methyl Ethyl Ketone	78-93-3	Bacteria	Experimental	16 hours	LOEC	1,150 mg/l
Magnesium Resinate	68037-42-3	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
Hexane	110-54-3	Fathead Minnow	Experimental	96 hours	LC50	2.5 mg/l
Hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l
Polychloroprene	9010-98-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
P-TERT-BUTYLPHENOL-FORMALDEHYD E RESIN	25085-50-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Heptane	142-82-5	Water flea	Experimental	48 hours	EC50	1.5 mg/l
Heptane	142-82-5	Water flea	Estimated	21 days	NOEC	0.17 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Magnesium Oxide	1309-48-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

2-Methylpentane	107-83-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
3-Methylpentane	96-14-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
Cyclohexane	110-82-7	Fathead Minnow	Experimental	96 hours	LC50	4.53 mg/l
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Acetone	67-64-1	Algae or other aquatic plants	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Rainbow Trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
Ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l
Ethylbenzene	100-41-4	Atlantic Silverside	Experimental	96 hours	LC50	5.1 mg/l
Ethylbenzene	100-41-4	Green algae	Experimental	96 hours	EC50	3.6 mg/l
Ethylbenzene	100-41-4	Mysid Shrimp	Experimental	96 hours	LC50	2.6 mg/l
Ethylbenzene	100-41-4	Rainbow Trout	Experimental	96 hours	LC50	4.2 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	48 hours	EC50	1.8 mg/l
Ethylbenzene	100-41-4	Water flea	Experimental	7 days	NOEC	0.96 mg/l
Rosin	8050-09-7	Bacteria	Experimental	N/A	EC50	76.1 mg/l
Rosin	8050-09-7	Green algae	Experimental	72 hours	EL50	>100 mg/l
Rosin	8050-09-7	Water flea	Experimental	48 hours	EL50	911 mg/l
Rosin	8050-09-7	Zebra Fish	Experimental	96 hours	LL50	>1 mg/l
Rosin	8050-09-7	Green algae	Experimental	72 hours	NOEL	100 mg/l
Styrenated Phenol	61788-44-1	Activated sludge	Experimental	3 hours	EC50	362 mg/l
Styrenated Phenol	61788-44-1	Green algae	Experimental	72 hours	EC50	1.35 mg/l
Styrenated Phenol	61788-44-1	Medaka	Experimental	96 hours	LC50	5.6 mg/l
Styrenated Phenol	61788-44-1	Water flea	Experimental	48 hours	EC50	4.6 mg/l
Styrenated Phenol	61788-44-1	Green algae	Experimental	72 hours	NOEC	0.42 mg/l
Styrenated Phenol	61788-44-1	Water flea	Experimental	21 days	NOEC	0.2 mg/l
Zinc Oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
Zinc Oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
Zinc Oxide	1314-13-2	Rainbow Trout	Estimated	96 hours	LC50	0.21 mg/l
Zinc Oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
Zinc Oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
Zinc Oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l
p-Tert-Butylphenol	98-54-4	Ciliated protozoa	Experimental	60 hours	IC50	18.4 mg/l
p-Tert-Butylphenol	98-54-4	Green algae	Experimental	72 hours	ErC50	14 mg/l
p-Tert-Butylphenol	98-54-4	Invertebrate	Experimental	96 hours	LC50	1.9 mg/l
p-Tert-Butylphenol	98-54-4	Medaka	Experimental	96 hours	LC50	5.1 mg/l
p-Tert-Butylphenol	98-54-4	Water flea	Experimental	48 hours	EC50	3.9 mg/l
p-Tert-Butylphenol	98-54-4	Fathead Minnow	Experimental	128 days	NOEC	0.01 mg/l
p-Tert-Butylphenol	98-54-4	Green algae	Experimental	72 hours	NOEC	0.32 mg/l
p-Tert-Butylphenol	98-54-4	Water flea	Experimental	21 days	NOEC	0.73 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Petroleum Distallates	64741-84-0	Estimated Biodegradation	28 days	Biological Oxygen Demand	98 %BOD/ThOD	OECD 301F - Manometric Respiro
Methyl Ethyl Ketone	78-93-3	Experimental Biodegradation	28 days	Biological Oxygen Demand	98 %BOD/ThOD	OECD 301D - Closed Bottle Test
Magnesium Resinate	68037-42-3	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hexane	110-54-3	Experimental Bioconcentration	28 days	Biological Oxygen Demand	100 %BOD/ThOD	OECD 301C - MITI (I)
Hexane	110-54-3	Experimental		Photolytic half-life	5.4 days (t 1/2)	

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

		Photolysis		(in air)		
Polychloroprene	9010-98-4	Data not available/insufficient	N/A	N/A	N/A	N/A
P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	25085-50-1	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 %CO2 evolution/THCO2 evolution	
Heptane	142-82-5	Experimental Biodegradation	28 days	Biological Oxygen Demand	101 %BOD/ThOD	OECD 301C - MITI (I)
Heptane	142-82-5	Experimental Photolysis		Photolytic half-life (in air)	4.24 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Magnesium Oxide	1309-48-4	Data not available/insufficient	N/A	N/A	N/A	N/A
2-Methylpentane	107-83-5	Experimental Biodegradation	28 days	Biological Oxygen Demand	93 %BOD/ThOD	OECD 301C - MITI (I)
2-Methylpentane	107-83-5	Experimental Photolysis		Photolytic half-life (in air)	6.1 days (t 1/2)	
3-Methylpentane	96-14-0	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	93 %BOD/ThOD	OECD 301C - MITI (I)
3-Methylpentane	96-14-0	Experimental Photolysis		Photolytic half-life (in air)	6.1 days (t 1/2)	
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	Biological Oxygen Demand	77 %BOD/ThOD	OECD 301F - Manometric Respiro
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.1 days (t 1/2)	
Acetone	67-64-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	78 %BOD/ThOD	OECD 301D - Closed Bottle Test
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Ethylbenzene	100-41-4	Experimental Biodegradation	28 days	Carbon dioxide evolution	70-80 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
Ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	
Rosin	8050-09-7	Experimental Biodegradation	28 days	Carbon dioxide evolution	64 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Styrenated Phenol	61788-44-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	7 %BOD/ThOD	OECD 301F - Manometric Respiro
Zinc Oxide	1314-13-2	Data not available/insufficient	N/A	N/A	N/A	N/A
p-Tert-Butylphenol	98-54-4	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	EC C.4.A. DOC Die-Away Test

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Petroleum Distillates	64741-84-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Methyl Ethyl Ketone	78-93-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.3	OECD 117 log Kow HPLC method
Magnesium Resinate	68037-42-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hexane	110-54-3	Modeled Bioconcentration		Bioaccumulation Factor	50	Catalogic™
Polychloroprene	9010-98-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

3M™ Neoprene High Performance Rubber and Gasket Adhesive 1300

P-TERT-BUTYLPHENOL-FORMALDEHYDE RESIN	25085-50-1	Estimated Bioconcentration		Bioaccumulation Factor	7.4	
Heptane	142-82-5	Estimated Bioconcentration		Bioaccumulation Factor	105	
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation Factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.73	
Magnesium Oxide	1309-48-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Methylpentane	107-83-5	Modeled Bioconcentration		Bioaccumulation Factor	47	Catalogic™
2-Methylpentane	107-83-5	Modeled Bioconcentration		Log of Octanol/H2O part. coeff	3.21	Episuite™
3-Methylpentane	96-14-0	Modeled Bioconcentration		Bioaccumulation Factor	81	Catalogic™
3-Methylpentane	96-14-0	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3.6	
Cyclohexane	110-82-7	Experimental BCF - Fish	56 days	Bioaccumulation Factor	129	OECD305-Bioconcentration
Cyclohexane	110-82-7	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3.44	
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulation Factor	0.65	
Acetone	67-64-1	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-0.24	
Ethylbenzene	100-41-4	Experimental BCF - Fish	42 days	Bioaccumulation Factor	1	
Rosin	8050-09-7	Analogous Compound BCF - Fish	20 days	Bioaccumulation Factor	129	
Styrenated Phenol	61788-44-1	Experimental BCF - Fish	10 days	Bioaccumulation Factor	10395	
Zinc Oxide	1314-13-2	Experimental BCF - Fish	56 days	Bioaccumulation Factor	≤217	OECD305-Bioconcentration
p-Tert-Butylphenol	98-54-4	Experimental BCF - Fish	56 days	Bioaccumulation Factor	88	OECD305-Bioconcentration
p-Tert-Butylphenol	98-54-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3	OECD 117 log Kow HPLC method

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations
13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN1133
Proper Shipping Name:ADHESIVES
Technical Name:None assigned.
Hazard Class/Division:3
Subsidiary Risk:None assigned.
Packing Group:II
Limited Quantity:Yes
Marine Pollutant: No
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Air Transport (IATA)

UN Number:UN1133
Proper Shipping Name:ADHESIVES
Technical Name:None assigned.
Hazard Class/Division:3
Subsidiary Risk:None assigned.
Packing Group:II
Limited Quantity:None assigned.
Marine Pollutant: No
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my