



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	10-3174-9	Version Number:	10.00
Issue Date:	27/02/2023	Supersedes Date:	09/10/2021

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Gray Part A

Product Identification Numbers

62-2217-8530-6 62-2217-8535-5 62-2217-9531-3

1.2. Recommended use and restrictions on use

Recommended use

Structural adhesive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Acute Aquatic Toxicity: Category 1.

Chronic Aquatic Toxicity: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark |Health Hazard |Environment |

Pictograms



Hazard Statements:

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.

- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

- P201 Obtain special instructions before use.
- P273 Avoid release to the environment.
- P280E Wear protective gloves.
- P281 Use personal protective equipment as required.

Response:

- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Although titanium dioxide is classified as a carcinogen, exposures associated with this health effect are not expected during normal, intended use of this product., May cause drowsiness or dizziness., Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines., The principle of dilution was used to bridge test results for eye damage/irritation. The test results are reflected in the assigned classification.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
ALIPHATIC POLYMER DIAMINE	68911-25-1	30 - 70
KAOLIN	1332-58-7	30 - 60
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	< 5
Titanium Dioxide	13463-67-7	< 1
TOLUENE	108-88-3	< 0.75

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Amine Compounds	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TOLUENE	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
TOLUENE	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50 ppm)	SKIN
KAOLIN	1332-58-7	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
KAOLIN	1332-58-7	Malaysia OELs	TWA (proposed)(respirable fraction)(8 hours):2 mg/m3	
DUST, INERT OR NUISANCE	13463-67-7	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m3;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m3	
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	Malaysia OELs	TWA(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Viscous
Color	Gray
Odor	Pungent Odor
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	<i>No Data Available</i>
Flash Point	≥ 93.9 °C [<i>Test Method: Closed Cup</i>]
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	≤ 13.3 Pa [<i>@ 25 °C</i>]
Vapor Density and/or Relative Vapor Density	<i>Not Applicable</i>
Density	1.26 g/ml [<i>@ 20 °C</i>]
Relative Density	1.26 [<i>@ 20 °C</i>] [<i>Ref Std: WATER=1</i>]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>

Decomposition temperature	<i>No Data Available</i>
Viscosity/Kinematic Viscosity	40,000 - 80,000 mPa-s [@ 20 °C] [<i>Test Method: Brookfield</i>]
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	3.7 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>] [<i>Details: when used as intended with Part B</i>]
VOC Less H2O & Exempt Solvents	< 0.5 % [<i>Test Method: calculated SCAQMD rule 443.1</i>] [<i>Details: when used as intended with Part B</i>]
VOC Less H2O & Exempt Solvents	6.12 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>] [<i>Details: as supplied</i>]
Molecular weight	<i>No Data Available</i>

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
 Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
ALIPHATIC POLYMER DIAMINE	Dermal	Rat	LD50 > 2,000 mg/kg
ALIPHATIC POLYMER DIAMINE	Ingestion	Rat	LD50 > 2,000 mg/kg
KAOLIN	Dermal		LD50 estimated to be > 5,000 mg/kg
KAOLIN	Ingestion	Human	LD50 > 15,000 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Dermal	Rabbit	LD50 2,525 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	Rat	LD50 2,850 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
TOLUENE	Dermal	Rat	LD50 12,000 mg/kg
TOLUENE	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
TOLUENE	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ALIPHATIC POLYMER DIAMINE	Rat	Irritant

KAOLIN	Professional judgement	No significant irritation
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Rabbit	Corrosive
Titanium Dioxide	Rabbit	No significant irritation
TOLUENE	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
ALIPHATIC POLYMER DIAMINE	In vitro data	Severe irritant
KAOLIN	Professional judgement	No significant irritation
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Rabbit	Corrosive
Titanium Dioxide	Rabbit	No significant irritation
TOLUENE	Rabbit	Moderate irritant

Sensitization:

Skin Sensitization

Name	Species	Value
ALIPHATIC POLYMER DIAMINE	Guinea pig	Sensitizing
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Professional judgement	Sensitizing
Titanium Dioxide	Human and animal	Not classified
TOLUENE	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
ALIPHATIC POLYMER DIAMINE	In Vitro	Not mutagenic
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic
TOLUENE	In Vitro	Not mutagenic
TOLUENE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
KAOLIN	Inhalation	Multiple animal species	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
TOLUENE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Ingestion	Rat	Some positive data exist, but the data are not

			sufficient for classification
TOLUENE	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ALIPHATIC POLYMER DIAMINE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
ALIPHATIC POLYMER DIAMINE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
ALIPHATIC POLYMER DIAMINE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
TOLUENE	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
TOLUENE	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
TOLUENE	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ALIPHATIC POLYMER DIAMINE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
ALIPHATIC POLYMER DIAMINE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
TOLUENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
TOLUENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
TOLUENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ALIPHATIC POLYMER DIAMINE	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Gray Part A

		system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system				
KAOLIN	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
KAOLIN	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
TOLUENE	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
TOLUENE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
TOLUENE	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
TOLUENE	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
TOLUENE	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
TOLUENE	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
TOLUENE	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
TOLUENE	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
TOLUENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
ALIPHATIC POLYMER DIAMINE	68911-25-1	Fathead Minnow	Experimental	96 hours	LL50	2.16 mg/l
ALIPHATIC POLYMER DIAMINE	68911-25-1	Green algae	Experimental	72 hours	EL50	0.43 mg/l
ALIPHATIC POLYMER DIAMINE	68911-25-1	Water flea	Experimental	48 hours	EL50	0.57 mg/l
ALIPHATIC POLYMER DIAMINE	68911-25-1	Green algae	Experimental	72 hours	NOEL	0.28 mg/l
ALIPHATIC POLYMER DIAMINE	68911-25-1	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
KAOLIN	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Green algae	Experimental	72 hours	ErC50	>500 mg/l
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE	4246-51-9	Green algae	Experimental	72 hours	ErC10	5.4 mg/l

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Gray Part A

GLYCOL						
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
Titanium Dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium Dioxide	13463-67-7	Fathead Minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium Dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
TOLUENE	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
TOLUENE	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
TOLUENE	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
TOLUENE	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
TOLUENE	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
TOLUENE	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
TOLUENE	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
TOLUENE	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
TOLUENE	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
TOLUENE	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
TOLUENE	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
TOLUENE	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
TOLUENE	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
TOLUENE	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
ALIPHATIC POLYMER DIAMINE	68911-25-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	0 %BOD/ThOD	OECD 301F - Manometric Respiro
KAOLIN	1332-58-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Experimental Biodegradation	25 days	Carbon dioxide evolution	-8 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Titanium Dioxide	13463-67-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
TOLUENE	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
TOLUENE	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
ALIPHATIC POLYMER DIAMINE	68911-25-1	Modeled Bioconcentration		Bioaccumulation Factor	42	Catalogic™
ALIPHATIC POLYMER DIAMINE	68911-25-1	Modeled Bioconcentration		Log of Octanol/H2O part. coeff	11.7	Episuite™
KAOLIN	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
BIS(3-AMINOPROPYL)	4246-51-9	Experimental Bioconcentration		Log of Octanol/H2O part.	-1.25	

ETHER OF DIETHYLENE GLYCOL				coeff		
Titanium Dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation Factor	9.6	
TOLUENE	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation Factor	90	
TOLUENE	108-88-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.73	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN3082

Proper Shipping Name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name:None assigned.

Hazard Class/Division:9

Subsidiary Risk:None assigned.

Packing Group:III

Limited Quantity:None assigned.

Marine Pollutant: Yes

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN3082

Proper Shipping Name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name:None assigned.

Hazard Class/Division:9

Subsidiary Risk:None assigned.

Packing Group:III

Limited Quantity:None assigned.

Marine Pollutant: Yes

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation

classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my