



Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	10-3173-1	Version Number:	4.00
Issue Date:	30/08/2018	Supersedes Date:	24/11/2014

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

Product Identification Numbers

62-3608-8535-4 62-3608-9530-4

1.2. Recommended use and restrictions on use

Recommended use

Part a of two part epoxy adhesive, Structural adhesive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

Pictograms



Hazard Statements

H318	Causes serious eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.

Precautionary statements

General:

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.

Prevention:

P201	Obtain special instructions before use.
P280B	Wear protective gloves and eye/face protection.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
ALIPHATIC POLYMER DIAMINE	68911-25-1	85 - 99
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	1 - 15
TOLUENE	108-88-3	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Amine Compounds	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TOLUENE	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
TOLUENE	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Viscous
Appearance/Odor	amber, pungent odor.
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	<i>Not Applicable</i>
Flash Point	>=94 °C [<i>Test Method:Estimated</i>]
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<=1.3 Pa [<i>@ 20 °C</i>]
Vapor Density	<i>Not Applicable</i>
Density	0.97 g/ml
Relative Density	0.97 [<i>Ref Std: WATER=1</i>]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	Approximately 7,000 mPa-s [<i>@ 20 °C</i>]
Molecular weight	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	3.9 g/l [<i>Test Method:calculated SCAQMD rule 443.1</i>] [<i>Details:when used as intended with Part B</i>]
VOC Less H2O & Exempt Solvents	< 10 g/l [<i>Test Method:calculated SCAQMD rule 443.1</i>] [<i>Details:as supplied</i>]
VOC Less H2O & Exempt Solvents	0.4 % [<i>Test Method:calculated SCAQMD rule 443.1</i>] [<i>Details:when used as intended with Part B</i>]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A**Additional Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Dermal	Rabbit	LD50 2,500 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	Rat	LD50 3,160 mg/kg
TOLUENE	Dermal	Rat	LD50 12,000 mg/kg
TOLUENE	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
TOLUENE	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product		Irritant
ALIPHATIC POLYMER DIAMINE	Rabbit	Irritant
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Rabbit	Corrosive
TOLUENE	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
ALIPHATIC POLYMER DIAMINE	similar health hazards	Corrosive
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	similar health hazards	Corrosive
TOLUENE	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
Overall product		Sensitizing
ALIPHATIC POLYMER DIAMINE	Guinea pig	Sensitizing
TOLUENE	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
TOLUENE	In Vitro	Not mutagenic
TOLUENE	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
------	-------	---------	-------

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

TOLUENE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
TOLUENE	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
TOLUENE	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
TOLUENE	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
TOLUENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
TOLUENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
TOLUENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
TOLUENE	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
TOLUENE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
TOLUENE	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
TOLUENE	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
TOLUENE	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for	Rat	NOAEL 625 mg/kg/day	13 weeks

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

			classification			
TOLUENE	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
TOLUENE	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
TOLUENE	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
TOLUENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
ALIPHATIC POLYMER DIAMINE	68911-25-1		Data not available or insufficient for classification			
BIS(3- AMINOPROP YL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Golden Orfe	Experimental	96 hours	Lethal Concentration 50%	>1,000 mg/l
BIS(3- AMINOPROP YL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Green algae	Experimental	72 hours	Effect Concentration 50%	>500 mg/l
BIS(3-	4246-51-9	Water flea	Experimental	48 hours	Effect	220 mg/l

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL					Concentration 50%	
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Green algae	Experimental	72 hours	Effect Concentration 10%	5.4 mg/l
TOLUENE	108-88-3	Coho Salmon	Experimental	96 hours	Lethal Concentration 50%	5.5 mg/l
TOLUENE	108-88-3	Fish other	Experimental	96 hours	Lethal Concentration 50%	6.41 mg/l
TOLUENE	108-88-3	Green Algae	Experimental	72 hours	Effect Concentration 50%	12.5 mg/l
TOLUENE	108-88-3	Water flea	Experimental	48 hours	Effect Concentration 50%	3.78 mg/l
TOLUENE	108-88-3	Coho salmon	Experimental	40 days	No obs Effect Conc	1.39 mg/l
TOLUENE	108-88-3	Water flea	Experimental	7 days	No obs Effect Conc	0.74 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
ALIPHATIC POLYMER DIAMINE	68911-25-1	Data not available - insufficient			N/A	
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	4246-51-9	Experimental Biodegradation	25 days	Carbon dioxide evolution	-8 % weight	OECD 301B - Mod. Sturm or CO2
TOLUENE	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	Other methods
TOLUENE	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 % weight	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
ALIPHATIC POLYMER DIAMINE	68911-25-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
BIS(3-AMINOPROP	4246-51-9	Estimated Bioconcentration		Log of Octanol/H2O	-1.46	Est: Octanol-water part. coeff

3M™ Scotch-Weld™ Epoxy Adhesive 2216 Translucent Part A

YL) ETHER OF DIETHYLENE GLYCOL		on		part. coeff		
TOLUENE	108-88-3	Experimental Bioconcentrati on		Log of Octanol/H2O part. coeff	2.73	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my