



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	28-8279-3	Version Number:	3.00
Issue Date:	26/02/2019	Supersedes Date:	14/07/2014

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M(TM) Marine Adhesive Sealant Fast Cure 4000 UV, White, PN05280

Product Identification Numbers

62-5563-1632-1 62-5563-5232-6

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Reproductive Toxicity: Category 1B.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard | Environment |

3M(TM) Marine Adhesive Sealant Fast Cure 4000 UV, White, PN05280

Pictograms



Hazard Statements

- H360 May damage fertility or the unborn child.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

General:

- P102 Keep out of reach of children.
- P101 If medical advice is needed, have product container or label at hand.

Prevention:

- P201 Obtain special instructions before use.
- P280E Wear protective gloves.
- P281 Use personal protective equipment as required.
- P273 Avoid release to the environment.

Response:

- P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

- P405 Store locked up.

Disposal:

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Calcium Carbonate	471-34-1	30 - 60
Polyether (NJTS Reg. No. 04499600-6434)	Trade Secret	15 - 40
Diisodecyl Phthalate	68515-49-1	10 - 20
Titanium Dioxide	13463-67-7	5 - 10

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

3M(TM) Marine Adhesive Sealant Fast Cure 4000 UV, White, PN05280

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

DO NOT USE WATER Use a fire fighting agent suitable for the surrounding fire. In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human carcin
Titanium Dioxide	13463-67-7	Malaysia OELs	TWA(8 hours):10 mg/m3	
Limestone	471-34-1	Malaysia OELs	TWA (proposed)(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Appearance/Odor	White viscous liquid with slight odor.
Odor threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	<i>Not Applicable</i>
Flash Point	No flash point
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<i>Not Applicable</i>
Vapor Density	<i>Not Applicable</i>
Density	1.3 - 1.5 g/ml
Relative Density	1.3 - 1.5 [Ref Std: WATER=1]
Water solubility	<i>No Data Available</i>
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	16 g/l [Test Method: tested per EPA method 24]
Percent volatile	0.93 % weight
VOC Less H2O & Exempt Solvents	16 g/l [Test Method: tested per EPA method 24]
VOC Less H2O & Exempt Solvents	0.93 % [Test Method: tested per EPA method 24]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Alcohols

Amines

Water

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

3M(TM) Marine Adhesive Sealant Fast Cure 4000 UV, White, PN05280**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Polyether (NJTS Reg. No. 04499600-6434)	Dermal		LD50 estimated to be > 5,000 mg/kg
Polyether (NJTS Reg. No. 04499600-6434)	Ingestion	Rat	LD50 5,000 mg/kg
Diisodecyl Phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisodecyl Phthalate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 12.5 mg/l
Diisodecyl Phthalate	Ingestion	Rat	LD50 > 9,700 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Minimal irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Calcium Carbonate	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Diisodecyl Phthalate	Guinea pig	Not classified
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Diisodecyl Phthalate	In Vitro	Not mutagenic
Diisodecyl Phthalate	In vivo	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

3M(TM) Marine Adhesive Sealant Fast Cure 4000 UV, White, PN05280

Name	Route	Species	Value
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Diisodecyl Phthalate	Ingestion	Not classified for female reproduction	Rat	NOAEL 927 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Not classified for male reproduction	Rat	NOAEL 929 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Toxic to development	Rat	NOAEL 38 mg/kg/day	2 generation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Diisodecyl Phthalate	Inhalation	respiratory system hematopoietic system liver	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Diisodecyl Phthalate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.5 mg/l	2 generation
Diisodecyl Phthalate	Ingestion	endocrine system	Not classified	Rat	NOAEL 686 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	liver kidney and/or bladder heart	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 320 mg/kg/day	90 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be

reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Calcium Carbonate	471-34-1	Green algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
Calcium Carbonate	471-34-1	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Calcium Carbonate	471-34-1	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
Calcium Carbonate	471-34-1	Green algae	Experimental	72 hours	Effect Concentration 10%	>100 mg/l
Polyether (NJTS Reg. No. 04499600-6434)	Trade Secret		Data not available or insufficient for classification			
Diisodecyl Phthalate	68515-49-1	Green algae	Experimental	96 hours	Effect Concentration 50%	>100 mg/l
Diisodecyl Phthalate	68515-49-1	Rainbow Trout	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Diisodecyl Phthalate	68515-49-1	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
Diisodecyl Phthalate	68515-49-1	Green algae	Experimental	96 hours	No obs Effect Conc	>100 mg/l
Diisodecyl Phthalate	68515-49-1	Water flea	Experimental	21 days	No obs Effect Conc	>100 mg/l
Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	Effect Concentration 50%	>10,000 mg/l
Titanium Dioxide	13463-67-7	Fathead Minnow	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Titanium Dioxide	13463-67-7	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
Titanium Dioxide	13463-67-7	Diatom	Experimental	72 hours	No obs Effect Conc	5,600 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Calcium Carbonate	471-34-1	Data not availbl-insufficient			N/A	
Polyether (NJTS Reg. No. 04499600-6434)	Trade Secret	Data not availbl-insufficient			N/A	
Diisodecyl Phthalate	68515-49-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	74 % BOD/ThBOD	OECD 301F - Manometric Respiro
Titanium Dioxide	13463-67-7	Data not availbl-insufficient			N/A	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Calcium Carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyether (NJTS Reg. No. 04499600-6434)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diisodecyl Phthalate	68515-49-1	Estimated BCF-Carp	56 days	Bioaccumulation Factor	<14.4	OECD 305E-Bioaccum Fl-thru fis
Titanium Dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulation Factor	9.6	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:None assigned.

Proper Shipping Name:None assigned.

3M(TM) Marine Adhesive Sealant Fast Cure 4000 UV, White, PN05280

Technical Name:None assigned.
Hazard Class/Division:None assigned.
Subsidiary Risk:None assigned.
Packing Group:None assigned.
Limited Quantity:None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

Air Transport (IATA)

UN Number:None assigned.
Proper Shipping Name:None assigned.
Technical Name:None assigned.
Hazard Class/Division:None assigned.
Subsidiary Risk:None assigned.
Packing Group:None assigned.
Limited Quantity:None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my