



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-1382-5	Version Number:	7.00
Issue Date:	03/11/2021	Supersedes Date:	03/05/2021

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Hi-Strength Post Forming 94 CA Cylinder Spray Adhesive, Clear or Red

Product Identification Numbers

62-4960-8010-2	62-4960-8030-0	62-4960-8150-6	62-4960-8300-7	62-4970-8010-1
62-4970-8030-9	62-4970-8150-5	62-4970-8300-6		

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Industrial use

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.
Serious Eye Damage/Irritation: Category 2.
Skin Sensitizer: Category 1.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame |Exclamation mark |Health Hazard |

Pictograms



Hazard Statements:

- H225 Highly flammable liquid and vapor.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H360 May damage fertility or the unborn child.
- H335 May cause respiratory irritation.

Precautionary statements

Prevention:

- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
- P280E Wear protective gloves.
- P281 Use personal protective equipment as required.

Response:

- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

2.3. Other hazards

May cause drowsiness or dizziness., Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Methyl Acetate	79-20-9	65 - 75
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	68515-02-6	10 - 20
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Trade Secret	10 - 20
Acetone	67-64-1	< 2
8anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-	71566-55-7	< 1

methylethoxy)propyl]benzenesulfonamidato (2-)]cobaltate(1-)		
Dimethyl Ether	115-10-6	< 1
Hexane	110-54-3	< 1
Toluene	108-88-3	< 1
Isobutane	75-28-5	< 0.5
Propane	74-98-6	< 0.5
Tris(Nonylphenyl) Phosphite	26523-78-4	< 0.25

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes
 Hydrocarbons
 Formaldehyde
 Methane
 Carbon monoxide
 Carbon dioxide
 Ketones
 Toxic Vapor, Gas, Particulate

Condition

During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure

demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant

Toluene	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50 ppm)	SKIN
Hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous absorption
Hexane	110-54-3	Malaysia OELs	TWA(8 hours):176 mg/m3(50 ppm)	SKIN
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin
Acetone	67-64-1	Malaysia OELs	TWA(8 hours):1187 mg/m3(500 ppm)	
Cobalt, inorganic compounds	71566-55-7	ACGIH	TWA(as Co, inhalable fraction):0.02 mg/m3;TWA(as Co):0.02 mg/m3	A3: Confirmed animal carcin., Dermal/Respiratory Sensitizer
Cobalt, inorganic compounds	71566-55-7	Malaysia OELs	TWA(as Co)(8 hours):0.02 mg/m3	
Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
Propane	74-98-6	Malaysia OELs	TWA(8 hours):2500 ppm	
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	Malaysia OELs	TWA(8 hours):606 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid
Color	Multicolor
Odor	Solvent
Odor threshold	<i>No Data Available</i>
pH	<i>No Data Available</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	60 °C
Flash Point	-13.3 °C [<i>Test Method: Closed Cup</i>]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	3.1 % volume
Flammable Limits(UEL)	16 % volume
Vapor Pressure	21,731.5 Pa [<i>@ 20 °C</i>]
Vapor Density and/or Relative Vapor Density	2.8 [<i>Ref Std: AIR=1</i>]
Density	0.93 - 0.95 g/ml
Relative Density	0.93 - 0.95 [<i>Ref Std: WATER=1</i>]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>Not Applicable</i>
Viscosity/Kinematic Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H2O & Exempt Solvents	<=40 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Molecular weight	<i>No Data Available</i>
Solids Content	25 - 35 % weight

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Dermal	Not available	LD50 > 2,000 mg/kg
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Ingestion	Not available	LD50 > 2,000 mg/kg
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	Ingestion	Rat	LD50 > 5,000 mg/kg
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Dimethyl Ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
8anthylum, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
8anthylum, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	Ingestion	Rat	LD50 > 2,000 mg/kg
Tris(Nonylphenyl) Phosphite	Dermal	Rabbit	LD50 > 2,000 mg/kg
Tris(Nonylphenyl) Phosphite	Ingestion	Rat	LD50 19,500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	No significant irritation
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Professional judgement	No significant irritation
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	Rabbit	No significant irritation
Acetone	Mouse	Minimal irritation
Hexane	Human and animal	Mild irritant
Toluene	Rabbit	Irritant
Isobutane	Professional judgement	No significant irritation
Propane	Rabbit	Minimal irritation
8anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	Rabbit	No significant irritation
Tris(Nonylphenyl) Phosphite	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	Moderate irritant
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Professional judgement	No significant irritation
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	Rabbit	Moderate irritant
Acetone	Rabbit	Severe irritant
Hexane	Rabbit	Mild irritant
Toluene	Rabbit	Moderate irritant
Isobutane	Professional judgement	No significant irritation
Propane	Rabbit	Mild irritant
8anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	Rabbit	No significant irritation
Tris(Nonylphenyl) Phosphite	Rabbit	No significant irritation

Sensitization:

Skin Sensitization

Name	Species	Value
Methyl Acetate	Human	Not classified
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)		Not classified
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	Mouse	Sensitizing
Hexane	Human	Not classified
Toluene	Guinea pig	Not classified
8anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	Guinea pig	Not classified
Tris(Nonylphenyl) Phosphite	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Isobutane	In Vitro	Not mutagenic
Propane	In Vitro	Not mutagenic
8anthylum, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	In Vitro	Not mutagenic
Tris(Nonylphenyl) Phosphite	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Acetone	Not Specified	Multiple animal species	Not carcinogenic
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
8anthylum, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	Not Specified	similar compounds	Carcinogenic
Tris(Nonylphenyl) Phosphite	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	Not Specified	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	Not Specified	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200	during organogenesis

				mg/kg/day	
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Dimethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
Tris(Nonylphenyl) Phosphite	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	1 generation
Tris(Nonylphenyl) Phosphite	Ingestion	Not classified for female reproduction	Rat	NOAEL 200 mg/kg/day	1 generation
Tris(Nonylphenyl) Phosphite	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL	3 hours

3M™ Hi-Strength Post Forming 94 CA Cylinder Spray Adhesive, Clear or Red

					0.004 mg/l	
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Hexane	Inhalation	peripheral nervous	Causes damage to organs through	Human	NOAEL Not	occupational

3M™ Hi-Strength Post Forming 94 CA Cylinder Spray Adhesive, Clear or Red

		system	prolonged or repeated exposure		available	exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
Hexane	Inhalation	auditory system immune system eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart skin endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Dimethyl Ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks

3M™ Hi-Strength Post Forming 94 CA Cylinder Spray Adhesive, Clear or Red

Tris(Nonylphenyl) Phosphite	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	2 years
Tris(Nonylphenyl) Phosphite	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 200 mg/kg/day	1 generation
Tris(Nonylphenyl) Phosphite	Ingestion	respiratory system	Not classified	Rat	NOAEL 500 mg/kg/day	2 years

Aspiration Hazard

Name	Value
Hexane	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Methyl Acetate	79-20-9	Bacteria	Experimental	16 hours	EC50	6,000 mg/l
Methyl Acetate	79-20-9	Green algae	Experimental	72 hours	EC50	>120 mg/l
Methyl Acetate	79-20-9	Water flea	Experimental	48 hours	EC50	1,026.7 mg/l
Methyl Acetate	79-20-9	Green algae	Experimental	72 hours	NOEC	120 mg/l
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Trade Secret		Data not available or insufficient for classification			N/A
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	68515-02-6		Data not available or insufficient for classification			N/A
Acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Crustacea other	Experimental	24 hours	LC50	2,100 mg/l
Acetone	67-64-1	Rainbow Trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
Santhylum, 9-(2-	71566-55-7	Activated sludge	Experimental	3 hours	IC50	>100 mg/l

carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)						
8-anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	71566-55-7	Duckweed	Experimental	7 days	EL50	28.7 mg/l
8-anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	71566-55-7	Water flea	Experimental	48 hours	EL50	76.8 mg/l
8-anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	71566-55-7	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l

methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)						
8anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	71566-55-7	Duckweed	Experimental	7 days	EL10	3.48 mg/l
Dimethyl Ether	115-10-6	Bacteria	Experimental		EC10	>1,600 mg/l
Dimethyl Ether	115-10-6	Guppy	Experimental	96 hours	LC50	>4,100 mg/l
Dimethyl Ether	115-10-6	Water flea	Experimental	48 hours	EC50	>4,400 mg/l
Hexane	110-54-3	Fathead Minnow	Experimental	96 hours	LC50	2.5 mg/l
Hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Isobutane	75-28-5		Data not available or insufficient for classification			N/A

Propane	74-98-6		Data not available or insufficient for classification			N/A
Tris(Nonylphenyl) Phosphite	26523-78-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Tris(Nonylphenyl) Phosphite	26523-78-4	Rainbow Trout	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Tris(Nonylphenyl) Phosphite	26523-78-4	Water flea	Experimental	48 hours	EC50	0.3 mg/l
Tris(Nonylphenyl) Phosphite	26523-78-4	Blackworm	Experimental	28 days	EC10	44 mg/kg (Wet Weight)
Tris(Nonylphenyl) Phosphite	26523-78-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Methyl Acetate	79-20-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	70 % weight	OECD 301D - Closed Bottle Test
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Trade Secret	Data not availbl-insufficient			N/A	
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	68515-02-6	Data not availbl-insufficient			N/A	
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Acetone	67-64-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	78 % BOD/ThBOD	OECD 301D - Closed Bottle Test
8anthylum, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-)	71566-55-7	Experimental Biodegradation	28 days	Carbon dioxide evolution	<10 %CO2 evolution/THC O2 evolution	OECD 301B - Mod. Sturm or CO2
Dimethyl Ether	115-10-6	Experimental Photolysis		Photolytic half-life (in air)	12.4 days (t 1/2)	Non-standard method

Dimethyl Ether	115-10-6	Experimental Biodegradation	28 days	Biological Oxygen Demand	5 % weight	OECD 301D - Closed Bottle Test
Hexane	110-54-3	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	Non-standard method
Hexane	110-54-3	Experimental Bioconcentration	28 days	Biological Oxygen Demand	100 % weight	OECD 301C - MITI (I)
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater
Isobutane	75-28-5	Experimental Photolysis		Photolytic half-life (in air)	13.4 days (t 1/2)	Non-standard method
Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Non-standard method
Tris(Nonylphenyl) Phosphite	26523-78-4	Experimental Biodegradation	28 days	Biological Oxygen Demand	<4 % BOD/ThBOD	OECD 301D - Closed Bottle Test

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Methyl Acetate	79-20-9	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	0.18	Non-standard method
Non-Hazardous Components (NJTS Reg. No. 04499600-7322)	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Rosin, Polymer with Isophthalic Acid and Pentaerythritol	68515-02-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulation Factor	0.65	
Acetone	67-64-1	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	-0.24	
8anthylium, 9-(2-carboxyphenyl)-3,6-bis(diethylamino)-, bis[3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-4-hydroxy-N-[3-(1-	71566-55-7	Estimated Bioconcentration		Log of Octanol/H ₂ O part. coeff	1.63	Non-standard method

methylethoxy)propyl]benzenesulfonamidato(2-)]cobaltate(1-						
Dimethyl Ether	115-10-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hexane	110-54-3	Estimated Bioconcentration		Bioaccumulation Factor	50	Est: Bioconcentration factor
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation Factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.73	
Isobutane	75-28-5	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.76	Non-standard method
Propane	74-98-6	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.36	Non-standard method
Tris(Nonylphenyl) Phosphite	26523-78-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	14	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN3501

Proper Shipping Name:CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.

Technical Name:(Dimethyl Ether and Methyl Acetate)

Hazard Class/Division:2.1

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN3501

Proper Shipping Name:CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S.

Technical Name:(Dimethyl Ether and Methyl Acetate)

Hazard Class/Division:2.1

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my