



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-2290-9	Version Number:	3.00
Issue Date:	26/02/2019	Supersedes Date:	31/12/2014

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

IDENTIFICATION

1.1. Product identifier

3M™ Super Fast Plastic Repair Adhesive PN 04247

Product Identification Numbers

41-0003-6681-9 41-0003-8011-7 41-3701-2156-2 62-2644-3830-0

1.2. Recommended use and restrictions on use

Recommended use

Industrial use

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

22-1873-3, 22-1818-8

TRANSPORT INFORMATION

Not hazardous for transportation.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to

transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-1818-8	Version Number:	3.00
Issue Date:	26/02/2019	Supersedes Date:	31/12/2014

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

1.2. Recommended use and restrictions on use

Recommended use

Two-part urethane system., Industrial use

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

- H319 Causes serious eye irritation.
- H315 Causes skin irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.

- H372 Causes damage to organs through prolonged or repeated exposure: respiratory system |

Precautionary statements

General:

- P102 Keep out of reach of children.
- P101 If medical advice is needed, have product container or label at hand.

Prevention:

- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P285 In case of inadequate ventilation wear respiratory protection.
- P280E Wear protective gloves.

Response:

- P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

- P405 Store locked up.

Disposal:

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	25 - 60

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

Castor oil, polymer with 1,1'-methylenebis[4-isocyanatobenzene]	68424-09-9	15 - 40
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	7 - 30
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	2530-83-8	1 - 2
ISOCYANIC ACID, 3-(TRIETHOXYSILYL)PROPYL ESTER	24801-88-5	0.5 - 1

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide
Hydrogen Cyanide
Oxides of Nitrogen
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Malaysia OELs	TWA(8 hours):0.051 mg/m ³ (0.005 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Viscous
Appearance/Odor	Low or no detectable odor, clear.
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	>=204.4 °C
Flash Point	>=143.3 °C [<i>Test Method: Tagliabue Closed Cup</i>]
Evaporation rate	<=1 [<i>Details: Gels with exposure to humidity.</i>]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Vapor Pressure	<=0 Pa [<i>@ 20 °C</i>]
Vapor Density	>=1 [<i>Ref Std: AIR=1</i>]
Density	1.1 g/ml
Relative Density	1.1 [<i>Ref Std: WATER=1</i>]
Water solubility	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

Decomposition temperature	No Data Available
Viscosity	1,000 - 2,000 mPa-s
Molecular weight	No Data Available
Volatile Organic Compounds	22 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile Organic Compounds	2 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	2 % weight [<i>Test Method</i> :Estimated]
VOC Less H2O & Exempt Solvents	22 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Water

Strong acids

Strong bases

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE ₂₀ - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
P,P'-Methylenebis(Phenyl Isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(Phenyl Isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-Diisocyanatodiphenylmethane Polymer	Ingestion	Rat	LD50 31,600 mg/kg
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	Dermal	Rabbit	LD50 4,000 mg/kg
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Rat	LD50 7,010 mg/kg
ISOCYANIC ACID, 3-(TRIETHOXSILYL)PROPYL ESTER	Dermal	Rabbit	LD50 1,259 mg/kg
ISOCYANIC ACID, 3-(TRIETHOXSILYL)PROPYL ESTER	Inhalation-Vapor (4 hours)	Rat	LC50 0.36 mg/l
ISOCYANIC ACID, 3-(TRIETHOXSILYL)PROPYL ESTER	Ingestion	Rat	LD50 706 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classificat	Irritant

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

	ion	
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Irritant
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	Rabbit	Mild irritant
ISOCYANIC ACID, 3-(TRIETHOXSILYL)PROPYL ESTER	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Severe irritant
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Severe irritant
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	Rabbit	Corrosive
ISOCYANIC ACID, 3-(TRIETHOXSILYL)PROPYL ESTER	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	official classification	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Sensitizing
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	Guinea pig	Not classified
ISOCYANIC ACID, 3-(TRIETHOXSILYL)PROPYL ESTER	similar compounds	Sensitizing

Respiratory Sensitization

Name	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	Human	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	Human	Sensitizing
ISOCYANIC ACID, 3-(TRIETHOXSILYL)PROPYL ESTER	similar compounds	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
P,P'-Methylenebis(Phenyl Isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	In vivo	Not mutagenic
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
3-(TRIMETHOXSILYL)PROPYL GLYCIDYL ETHER	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(Phenyl Isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
3-(TRIMETHOXYSILYL)PROPYL GLYCIDYL ETHER	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Green algae	Estimated	72 hours	Effect Concentration 50%	>1,640 mg/l
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Water flea	Estimated	24 hours	Effect Concentration 50%	>1,000 mg/l
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Zebra Fish	Estimated	96 hours	Lethal Concentration 50%	>1,000 mg/l
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Green algae	Estimated	72 hours	No obs Effect Conc	1,640 mg/l
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Water flea	Estimated	21 days	No obs Effect Conc	10 mg/l
Castor oil, polymer with 1,1'-methylenebis[4-isocyanatobenzene]	68424-09-9		Data not available or insufficient for classification			
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	Green algae	Estimated	72 hours	Effect Concentration 50%	>1,640 mg/l
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	Ricefish	Estimated	96 hours	Lethal Concentration 50%	>3,000 mg/l
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	Water flea	Estimated	24 hours	Effect Concentration 50%	>1,000 mg/l
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	Green algae	Estimated	72 hours	No obs Effect Conc	1,640 mg/l

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

4,4'-Diisocyanatodi phenylmethane Polymer	25686-28-6	Water flea	Estimated	21 days	No obs Effect Conc	>=10 mg/l
3-(TRIMETHOXY Silyl)propyl Glycidyl Ether	2530-83-8	Common Carp	Experimental	96 hours	Lethal Concentration 50%	55 mg/l
3-(TRIMETHOXY Silyl)propyl Glycidyl Ether	2530-83-8	Crustacea other	Experimental	48 hours	Lethal Concentration 50%	324 mg/l
3-(TRIMETHOXY Silyl)propyl Glycidyl Ether	2530-83-8	Green algae	Experimental	96 hours	Effect Concentration 50%	350 mg/l
3-(TRIMETHOXY Silyl)propyl Glycidyl Ether	2530-83-8	Green Algae	Experimental	96 hours	No obs Effect Conc	130 mg/l
3-(TRIMETHOXY Silyl)propyl Glycidyl Ether	2530-83-8	Water flea	Experimental	21 days	No obs Effect Conc	>=100 mg/l
ISOCYANIC ACID, 3-(TRIETHOXY Silyl)propyl Ester	24801-88-5	Green algae	Estimated	72 hours	Effect Concentration 50%	>1,000 mg/l
ISOCYANIC ACID, 3-(TRIETHOXY Silyl)propyl Ester	24801-88-5	Water flea	Estimated	48 hours	Effect Concentration 50%	331 mg/l
ISOCYANIC ACID, 3-(TRIETHOXY Silyl)propyl Ester	24801-88-5	Zebra Fish	Estimated	96 hours	Lethal Concentration 50%	>934 mg/l
ISOCYANIC ACID, 3-(TRIETHOXY Silyl)propyl Ester	24801-88-5	Green algae	Estimated	72 hours	No obs Effect Conc	1.3 mg/l
ISOCYANIC	24801-88-5	Water flea	Estimated	21 days	No obs Effect	>=100 mg/l

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

ACID, 3-(TRIETHOXY SILYL)PROPYL ESTER					Conc	
---------------------------------------	--	--	--	--	------	--

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	Other methods
Castor oil, polymer with 1,1'-methylenebis[4-isocyanatobenzene]	68424-09-9	Data not available - insufficient			NA	
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	Other methods
3-(TRIMETHOXY SILYL)PROPYL GLYCIDYL ETHER	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life	6.5 hours (t 1/2)	Other methods
3-(TRIMETHOXY SILYL)PROPYL GLYCIDYL ETHER	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 % weight	Other methods
ISOCYANIC ACID, 3-(TRIETHOXY SILYL)PROPYL ESTER	24801-88-5	Estimated Hydrolysis		Hydrolytic half-life	8.5 hours (t 1/2)	Other methods

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
P,P'-Methylenebis(Phenyl Isocyanate)	101-68-8	Experimental BCF-Carp	28 days	Bioaccumulation Factor	200	OECD 305E-Bioaccumulation thru fish
Castor oil, polymer with 1,1'-methylenebis[4-isocyanatobenzene]	68424-09-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	Estimated BCF-Carp	28 days	Bioaccumulation Factor	200	OECD 305E-Bioaccumulation FI-thru fish
3-(TRIMETHOXY-SILYL)PROPYL GLYCIDYL ETHER	2530-83-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ISOCYANIC ACID, 3-(TRIETHOXY-SILYL)PROPYL ESTER	24801-88-5	Estimated BCF-Carp	56 days	Bioaccumulation Factor	<3.4	OECD 305E-Bioaccumulation FI-thru fish

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

04247 DURAMIX™ Super Fast Plastic Repair Adhesive (Part A)

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-1873-3	Version Number:	3.00
Issue Date:	26/02/2019	Supersedes Date:	31/12/2014

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

1.2. Recommended use and restrictions on use

Recommended use

Two-part urethane system., Industrial use

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

General:

P102 Keep out of reach of children.
P101 If medical advice is needed, have product container or label at hand.

Prevention:

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Polyether Polyol	9082-00-2	40 - 70
Propoxylated trimethylolpropane	25723-16-4	10 - 30
Tetrakis(2-hydroxypropyl)ethylenediamine	102-60-3	10 - 30
M-xylene-alpha,alpha'-diamine	1477-55-0	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. Keep out of reach of children. Avoid

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
M-xylene-alpha,alpha'-diamine	1477-55-0	ACGIH	CEIL:0.1 mg/m ³	SKIN
M-xylene-alpha,alpha'-diamine	1477-55-0	Malaysia OELs	CEIL:0.1 mg/m ³	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber
Fluoroelastomer

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Respiratory protection

In case of inadequate ventilation wear respiratory protection. An exposure assessment may be needed to decide if a

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Gel
Appearance/Odor	Slight ammonia like odor, clear.
Odor threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	>=204.4 °C
Flash Point	>=143.3 °C [Test Method:Tagliabue Closed Cup]
Evaporation rate	<=1 [Ref Std:WATER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	Not Applicable
Flammable Limits(UEL)	Not Applicable
Vapor Pressure	Not Applicable
Vapor Density	>=1 [Ref Std:AIR=1]
Density	1.02 g/ml
Relative Density	1.02 [Ref Std:WATER=1]
Water solubility	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	Not Applicable
Decomposition temperature	No Data Available
Viscosity	1,300 - 2,000 mPa-s
Molecular weight	No Data Available
Volatile Organic Compounds	0 % weight [Test Method:calculated per CARB title 2]
Volatile Organic Compounds	0 g/l [Test Method:calculated SCAQMD rule 443.1]
Percent volatile	<=1 % weight [Test Method:Estimated]
VOC Less H2O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

No known health effects.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyether Polyol	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polyether Polyol	Ingestion	Rat	LD50 > 10,000 mg/kg
Propoxylated trimethylolpropane	Dermal	Rat	LD50 > 2,000 mg/kg
Propoxylated trimethylolpropane	Ingestion	Rat	LD50 > 2,500 mg/kg
Tetrakis(2-hydroxypropyl)ethylenediamine	Dermal	Rat	LD50 > 2,000 mg/kg

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	Rat	LD50 2,890 mg/kg
M-xylene-alpha,alpha'-diamine	Dermal	Rabbit	LD50 > 2,000 mg/kg
M-xylene-alpha,alpha'-diamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.2 mg/l
M-xylene-alpha,alpha'-diamine	Ingestion	Rat	LD50 980 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Propoxylated trimethylolpropane	Rabbit	No significant irritation
Tetrakis(2-hydroxypropyl)ethylenediamine	Rabbit	No significant irritation
M-xylene-alpha,alpha'-diamine	Rat	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Propoxylated trimethylolpropane	Rabbit	Mild irritant
Tetrakis(2-hydroxypropyl)ethylenediamine	Rabbit	Severe irritant
M-xylene-alpha,alpha'-diamine	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Tetrakis(2-hydroxypropyl)ethylenediamine	Guinea pig	Not classified
M-xylene-alpha,alpha'-diamine	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Tetrakis(2-hydroxypropyl)ethylenediamine	In Vitro	Not mutagenic
M-xylene-alpha,alpha'-diamine	In Vitro	Not mutagenic
M-xylene-alpha,alpha'-diamine	In vivo	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	30 days
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
M-xylene-alpha,alpha'-diamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
M-xylene-alpha,alpha'-diamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 450 mg/kg	1 generation
M-xylene-alpha,alpha'-diamine	Ingestion	Not classified for development	Rat	NOAEL 450	1 generation

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

				mg/kg/day	
--	--	--	--	-----------	--

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Tetrakis(2-hydroxypropyl)ethylenediamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Positive	
M-xylene-alpha,alpha'-diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	30 days
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	30 days
M-xylene-alpha,alpha'-diamine	Ingestion	endocrine system blood bone marrow	Not classified	Rat	NOAEL 600 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Polyether Polyol	9082-00-2	Inland Silverside	Estimated	96 hours	Lethal Concentration 50%	650 mg/l
Propoxylated trimethylolpropane	25723-16-4	Green algae	Experimental	72 hours	Effect Concentration 50%	>100 mg/l
Propoxylated trimethylolpropane	25723-16-4	Water flea	Experimental	48 hours	Effect Concentration 50%	>100 mg/l
Propoxylated trimethylolpropane	25723-16-4	Zebra Fish	Experimental	96 hours	Lethal Concentration 50%	>100 mg/l
Propoxylated trimethylolpropane	25723-16-4	Green algae	Experimental	72 hours	No obs Effect Conc	100 mg/l
Propoxylated trimethylolpropane	25723-16-4	Water flea	Experimental	21 days	No obs Effect Conc	8.5 mg/l
Tetrakis(2-hydroxypropyl) ethylenediamine	102-60-3	Green algae	Estimated	72 hours	Effect Concentration 50%	>100 mg/l
Tetrakis(2-hydroxypropyl) ethylenediamine	102-60-3	Water flea	Estimated	48 hours	Effect Concentration 50%	>500 mg/l
Tetrakis(2-hydroxypropyl) ethylenediamine	102-60-3	Fathead Minnow	Experimental	96 hours	Lethal Concentration 50%	>1,000 mg/l
Tetrakis(2-hydroxypropyl) ethylenediamine	102-60-3	Green algae	Estimated	72 hours	Effect Concentration 10%	16.1 mg/l
M-xylene-alpha,alpha'-diamine	1477-55-0	Green Algae	Experimental	72 hours	Effect Concentration 50%	28 mg/l
M-xylene-alpha,alpha'-diamine	1477-55-0	Ricefish	Experimental	96 hours	Lethal Concentration 50%	87.6 mg/l
M-xylene-alpha,alpha'-diamine	1477-55-0	Water flea	Experimental	48 hours	Effect Concentration 50%	15.2 mg/l
M-xylene-alpha,alpha'-diamine	1477-55-0	Green Algae	Experimental	72 hours	No obs Effect Conc	9.8 mg/l
M-xylene-alpha,alpha'-diamine	1477-55-0	Water flea	Experimental	21 days	No obs Effect Conc	4.7 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Polyether	9082-00-2	Data not			N/A	

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

Polyol		availbl-insufficient				
Propoxylated trimethylolpropane	25723-16-4	Experimental Biodegradation	28 days	Biological Oxygen Demand	84 % BOD/ThBOD	Other methods
Tetrakis(2-hydroxypropyl) ethylenediamine	102-60-3	Experimental Biodegradation	28 days	Biological Oxygen Demand	1 % weight	OECD 301C - MITI (I)
M-xylene-alpha,alpha'-diamine	1477-55-0	Experimental Biodegradation	28 days	Carbon dioxide evolution	49 % weight	OECD 301B - Mod. Sturm or CO2

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Polyether Polyol	9082-00-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propoxylated trimethylolpropane	25723-16-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	1.8	Other methods
Tetrakis(2-hydroxypropyl) ethylenediamine	102-60-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.27	Other methods
M-xylene-alpha,alpha'-diamine	1477-55-0	Experimental BCF-Carp	42 days	Bioaccumulation Factor	<2.7	OECD 305E-Bioaccum F1-thru fis

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

3M™ DURAMIX™ Super Fast Plastic Repair Adhesive PN 04247 Accelerator (Part B)

Hazard Class/Division:None assigned.
Subsidiary Risk:None assigned.
Packing Group:None assigned.
Limited Quantity:None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Air Transport (IATA)

UN Number:None assigned.
Proper Shipping Name:None assigned.
Technical Name:None assigned.
Hazard Class/Division:None assigned.
Subsidiary Risk:None assigned.
Packing Group:None assigned.
Limited Quantity:None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my