

Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 42-1620-6 **Version Number:** 2.00

Issue Date: 01/11/2023 **Supercedes Date:** 10/03/2021

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

SCOTCH-BRITE MULTI - HARD SURFACE DISINFECTANT WIPES

Product Identification Numbers

XA-0065-1641-4 XA-0065-1642-2 XA-0065-1643-0 XA-0065-1644-8

1.2. Recommended use and restrictions on use

Recommended use

clean and disinfect the floor

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Not applicable

Symbols

Not applicable

Pictograms

Not applicable

Hazard Statements:

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	60 - 90
Non-woven	None	10 - 30
Isopropyl Alcohol	67-63-0	< 1
1,6-HEXANEDIAMINE, POLYMER	27083-27-8	< 0.5
WITH N,N"'-1,6-HEXANEDIYLBIS[N'-		
CYANOGUANIDINE],		
HYDROCHLORIDE		
Benzalkonium chloride	68424-85-1	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide Condition
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human
				carcin
Isopropyl Alcohol	67-63-0	Malaysia OELs	TWA(8 hours):983	
			mg/m3(400 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer's Recommended Guidelines

Malaysia OELs: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Liquid for wipe
Color	Colorless
Odor	Citrus
Odor threshold	No Data Available
рН	5 - 7.5
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	< 100 °C
Flash Point	No Data Available
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Vapor Density and/or Relative Vapor Density	No Data Available
Density	0.99 - 1.03 g/cm3
Relative Density	0.99 - 1.03 [<i>Ref Std:</i> WATER=1]
Water solubility	Soluble
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available

Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	No Data Available
Volatile Organic Compounds No Data Available	
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

Temperatures above the boiling point

10.5. Incompatible materials

Strong acids
Strong oxidizing agents
Strong bases
Combustibles

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No known health effects.

Skin Contact:

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

No known health effects.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation- Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'-1,6- HEXANEDIYLBIS[N'-CYANOGUANIDINE], HYDROCHLORIDE	Dermal	Rat	LD50 > 5,000 mg/kg
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'-1,6- HEXANEDIYLBIS[N'-CYANOGUANIDINE], HYDROCHLORIDE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.29 mg/l
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'-1,6- HEXANEDIYLBIS[N'-CYANOGUANIDINE], HYDROCHLORIDE	Ingestion	Rat	LD50 501 mg/kg
Benzalkonium chloride	Dermal	Rabbit	LD50 3,413 mg/kg
Benzalkonium chloride	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.25 mg/l
Benzalkonium chloride	Ingestion	Rat	LD50 398 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isopropyl Alcohol	Multiple animal species	No significant irritation
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'-1,6-HEXANEDIYLBIS[N'-CYANOGUANIDINE], HYDROCHLORIDE	Rabbit	Mild irritant
Benzalkonium chloride	Rabbit	Corrosive

Serious Eye Damage/Irritation

serious Lyc Dumage, it reaction				
Name	Species	Value		
Isopropyl Alcohol	Rabbit	Severe irritant		
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'-1,6-HEXANEDIYLBIS[N'-CYANOGUANIDINE], HYDROCHLORIDE	Rabbit	Corrosive		
Benzalkonium chloride	Rabbit	Corrosive		

Sensitization:

Skin Sensitization

Skin Sensitization					
Name	Species	Value			
	~ p				
Isopropyl Alcohol	Guinea	Not classified			
	pig				
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'-1,6-HEXANEDIYLBIS[N'-	Guinea	Sensitizing			

CYANOGUANIDINE], HYDROCHLORIDE	pig	
Benzalkonium chloride	Guinea	Not classified
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
Benzalkonium chloride	In Vitro	Not mutagenic
Benzalkonium chloride	In vivo	Not mutagenic

Carcinogenicity

8 V			
Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'-1,6- HEXANEDIYLBIS[N'-CYANOGUANIDINE], HYDROCHLORIDE	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Benzalkonium chloride	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
Benzalkonium chloride	Ingestion	Not classified for female reproduction	Rat	NOAEL 48 mg/kg/day	2 generation
Benzalkonium chloride	Ingestion	Not classified for male reproduction	Rat	NOAEL 30.5 mg/kg/day	2 generation
Benzalkonium chloride	Ingestion	Not classified for development	Rat	NOAEL 48 mg/kg/day	2 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation central nervous system depression		May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation respiratory irritation		Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol Inhala		auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Benzalkonium chloride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not Available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
1,6-HEXANEDIAMINE, POLYMER WITH N,N"'- 1,6- HEXANEDIYLBIS[N'- CYANOGUANIDINE], HYDROCHLORIDE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL .000 02 mg/l	28 days
Benzalkonium chloride	Ingestion	heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 50 mg/kg/day	95 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Туре	Exposure	Test Endpoint	Test Result
Isopropyl Alcohol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
Isopropyl Alcohol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l

1.6	27002 27 0	C	E	72 hours	EC50	0.015/1
1,6-	27083-27-8	Green algae	Experimental	/2 nours	EC50	0.015 mg/l
HEXANEDIAMIN						
E, POLYMER						
WITH N,N"'-1,6-						
HEXANEDIYLBI						
S[N'-						
CYANOGUANIDI						
NE],						
HYDROCHLORI						
DE						
1,6-	27083-27-8	Rainbow Trout	Experimental	96 hours	LC50	0.026 mg/l
HEXANEDIAMIN						
E, POLYMER						
WITH N,N"'-1,6-						
HEXANEDIYLBI						
S[N'-						
CYANOGUANIDI						
NE],						
HYDROCHLORI						
DE						
1,6-	27083-27-8	Green algae	Experimental	72 hours	ErC10	0.008 mg/l
HEXANEDIAMIN		angue		110,010		
E, POLYMER			1			
WITH N,N"'-1,6-			1			
HEXANEDIYLBI						
			1			
S[N'- CYANOGUANIDI			1			
NE],						
HYDROCHLORI						
DE	25002 25 0	D 1		20.1	NODE	0.01
1,6-	27083-27-8	Rainbow Trout	Experimental	28 days	NOEC	0.01 mg/l
HEXANEDIAMIN						
E, POLYMER						
WITH N,N"'-1,6-						
HEXANEDIYLBI						
S[N'-						
CYANOGUANIDI						
NE],						
HYDROCHLORI						
DE						
1,6-	27083-27-8	Water flea	Experimental	21 days	NOEC	0.0084 mg/l
HEXANEDIAMIN						
E, POLYMER						
WITH N,N"'-1,6-						
HEXANEDIYLBI						
S[N'-						
CYANOGUANIDI			1			
NE],			1			
HYDROCHLORI			1			
DE			1			
1,6-	27083-27-8	Activated sludge	Experimental	4 hours	EC50	38 mg/l
HEXANEDIAMIN			"			
E, POLYMER						
WITH N,N"'-1,6-						
HEXANEDIYLBI						
S[N'-						
CYANOGUANIDI			1			
NE],			1			
HYDROCHLORI			1			
DE						
Benzalkonium	68424-85-1	Diatom	Experimental	96 hours	ErC50	0.089 mg/l
chloride	00424-03-1	Diatolli	Experimental	70 HOUIS	EICSU	0.009 IIIg/I
	(0424.05.1	C	E	72 1	E-C50	0.040 //
Benzalkonium	68424-85-1	Green algae	Experimental	72 hours	ErC50	0.049 mg/l
chloride	60424.05 1	N . 1 01 .	 	061	1.050	0.002
Benzalkonium	68424-85-1	Mysid Shrimp	Experimental	96 hours	LC50	0.092 mg/l
chloride			<u></u>			
Benzalkonium	68424-85-1	Rainbow Trout	Experimental	96 hours	LC50	0.064 mg/l
chloride						
Benzalkonium	68424-85-1	Sheepshead	Experimental	96 hours	LC50	0.86 mg/l

chloride		Minnow				
Benzalkonium chloride	68424-85-1	Water flea	Experimental	48 hours	EC50	0.0058 mg/l
Benzalkonium chloride	68424-85-1	Diatom	Experimental	96 hours	NOEC	0.035 mg/l
Benzalkonium chloride	68424-85-1	Fathead Minnow	Experimental	28 days	NOEC	0.0322 mg/l
Benzalkonium chloride	68424-85-1	Green algae	Experimental	72 hours	ErC10	0.009 mg/l
Benzalkonium chloride	68424-85-1	Water flea	Experimental	21 days	NOEC	0.00415 mg/l
Benzalkonium chloride	68424-85-1	Activated sludge	Experimental	3 hours	EC50	7.75 mg/l
Benzalkonium chloride	68424-85-1	Mustard	Experimental	16 days	EC50	277 mg/kg (Dry Weight)
Benzalkonium chloride	68424-85-1	Redworm	Experimental	14 days	LC50	7,070 mg/kg (Dry Weight)
Benzalkonium chloride	68424-85-1	Redworm	Experimental	56 days	NOEC	125 mg/kg (Dry Weight)
Benzalkonium chloride	68424-85-1	Soil microbes	Experimental	28 days	EC50	130 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Biodegradation	14 days	Biological Oxygen Demand	86 %BOD/ThOD	OECD 301C - MITI (I)
1,6- HEXANEDIAMIN E, POLYMER WITH N,N"-1,6- HEXANEDIYLBI S[N'- CYANOGUANIDI NE], HYDROCHLORI DE	27083-27-8	Experimental Biodegradation	28 days	Carbon dioxide evolution	<3.8 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Mod. Sturm or CO2
1,6- HEXANEDIAMIN E, POLYMER WITH N,N"-1,6- HEXANEDIYLBI S[N'- CYANOGUANIDI NE], HYDROCHLORI DE		Experimental Biodegradation	144 days	Carbon dioxide evolution	<1 %CO2 evolution/THCO2 evolution	OECD 303A - Simulated Aerobic
Benzalkonium chloride	68424-85-1	Experimental Biodegradation	28 days	Carbon dioxide evolution	95.5 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Benzalkonium chloride	68424-85-1	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	EC C.7 Hydrolysis at pH

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.05	
1,6- HEXANEDIAMIN E, POLYMER	27083-27-8	Estimated Bioconcentration		Log of Octanol/H2O part. coeff	-2.3	

WITH N,N"'-1,6- HEXANEDIYLBI S[N'-						
CYANOGUANIDI NE], HYDROCHLORI						
DE						
Benzalkonium chloride	68424-85-1	Experimental BCF - Fish	35 days	Bioaccumulation Factor	79	
Benzalkonium chloride	68424-85-1	Estimated Bioconcentration		Log of Octanol/H2O part. coeff	2.75	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number: None assigned.

Proper Shipping Name: None assigned.

Technical Name: None assigned.

Hazard Class/Division: None assigned.

Subsidiary Risk: None assigned.

Packing Group: None assigned.

Limited Quantity: None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number: None assigned.

Proper Shipping Name: None assigned.

Technical Name: None assigned.

Hazard Class/Division: None assigned.

Subsidiary Risk: None assigned.

Packing Group: None assigned.

Limited Quantity: None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my