

Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 06-6936-6
 Version Number:
 5.00

 Issue Date:
 17/02/2022
 Supercedes Date:
 23/03/2021

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M[™] Industrial Adhesive 4550, Translucent

Product Identification Numbers

62-4564-5530-2 62-4564-8530-9 62-4564-9530-8 62-4564-9535-7

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Industrial use

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2. Reproductive Toxicity: Category 1B. Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P281 Use personal protective equipment as required.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.

P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry

chemical or carbon dioxide to extinguish.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

Aspiration classification does not apply due to the viscosity of the product., May cause drowsiness or dizziness.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt |
|---|--------------|---------|
| 2-Methylpentane | 107-83-5 | 30 - 50 |
| Non-volatile Components | Trade Secret | 20 - 40 |
| Bicyclo[3.1.1]Hept-2-Ene,2,6,6- | 31393-98-3 | < 25 |
| Trimethyl-,Polymer With 6,6-Dimethyl-2- | | |
| Methylenebicyclo[3.1.1]Heptane | | |
| Cyclohexane | 110-82-7 | 15 - 24 |
| Limestone | 1317-65-3 | < 2 |
| n-Hexane | 110-54-3 | 1 - 2 |
| toluene | 108-88-3 | < 1 |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|------------------|--------------------------|
| Aldehydes | During Combustion |
| Hydrocarbons | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| | |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|-----------------------|------------|---------------|----------------------------|----------------------------|
| 2-Methylpentane | 107-83-5 | ACGIH | TWA:500 ppm;STEL:1000 | |
| | | | ppm | |
| HEXANE (ISOMERS OTHER | 107-83-5 | Malaysia OELs | TWA(8 hours):1760 | |
| THAN N-HEXANE) | | | mg/m3(500 ppm) | |
| toluene | 108-88-3 | ACGIH | TWA:20 ppm | A4: Not class. as human |
| | | | | carcin, Ototoxicant |
| toluene | 108-88-3 | Malaysia OELs | TWA(8 hours):188 mg/m3(50 | SKIN |
| | | | ppm) | |
| n-Hexane | 110-54-3 | ACGIH | TWA:50 ppm | Danger of cutaneous |
| | | | | absorption |
| n-Hexane | 110-54-3 | Malaysia OELs | TWA(8 hours):176 mg/m3(50 | SKIN |
| | | | ppm) | |
| Cyclohexane | 110-82-7 | ACGIH | TWA:100 ppm | |
| Cyclohexane | 110-82-7 | Malaysia OELs | TWA(8 hours):1030 | |
| | | | mg/m3(300 ppm) | |
| Limestone | 1317-65-3 | Malaysia OELs | TWA (proposed)(8 hours):10 | |
| | | | mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Liquid | | |
|---|------------------------------|--|--|
| | 1 | | |
| Color | Amber | | |
| Odor | Solvent | | |
| Odor threshold | No Data Available | | |
| pH | Not Applicable | | |
| Melting point/Freezing point | Not Applicable | | |
| Boiling point/Initial boiling point/Boiling range 60 °C | | | |
| ssh Point <=-28.9 °C [Test Method: Closed Cup] | | | |
| Evaporation rate | No Data Available | | |
| Flammability (solid, gas) | Not Applicable | | |
| Flammable Limits(LEL) | 1.1 % volume | | |
| Flammable Limits(UEL) | 8 % volume | | |
| Vapor Pressure | 46,662.7 Pa [@ 37.8 °C] | | |
| Vapor Density and/or Relative Vapor Density | >=1 [<i>Ref Std</i> :AIR=1] | | |
| Density | 0.77 g/ml | | |

| Relative Density | 0.77 [Ref Std:WATER=1] | |
|---|--|--|
| Water solubility | Nil | |
| Solubility- non-water | No Data Available | |
| Partition coefficient: n-octanol/ water | No Data Available | |
| Autoignition temperature | No Data Available | |
| Decomposition temperature | No Data Available | |
| Viscosity/Kinematic Viscosity | 200 - 1,500 mPa-s [@ 23 °C] | |
| Volatile Organic Compounds | No Data Available | |
| Percent volatile | No Data Available | |
| VOC Less H2O & Exempt Solvents | <=550 g/l [Test Method:calculated SCAQMD rule 443.1] | |
| Molecular weight | No Data Available | |
| Solids Content | 20 - 40 % | |

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance None known. Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|---------------------------------------|-----------------------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation- Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| 2-Methylpentane | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| 2-Methylpentane | Inhalation- Vapor | | LC50 estimated to be > 50 mg/l |
| 2-Methylpentane | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Cyclohexane | Dermal | Rat | LD50 > 2,000 mg/kg |
| Cyclohexane | Inhalation- Vapor (4 hours) | Rat | LC50 > 32.9 mg/l |
| Cyclohexane | Ingestion | Rat | LD50 6,200 mg/kg |
| Non-volatile Components | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Non-volatile Components | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Bicyclo[3.1.1]Hept-2-Ene,2,6,6-Trimethyl-,Polymer With 6,6- Dimethyl-2-Methylenebicyclo[3.1.1]Heptane | Dermal | Professio nal judgeme nt | LD50 estimated to be > 5,000 mg/kg |
| Bicyclo[3.1.1]Hept-2-Ene,2,6,6-Trimethyl-,Polymer With 6,6- Dimethyl-2-Methylenebicyclo[3.1.1]Heptane | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Limestone | Dermal | Rat | LD50 > 2,000 mg/kg |
| Limestone | Inhalation- Dust/Mist (4 hours) | Rat | LC50 3 mg/l |
| Limestone | Ingestion | Rat | LD50 6,450 mg/kg |
| n-Hexane | Dermal | Rabbit | LD50 > 2,000 mg/kg |

3MTM Industrial Adhesive 4550, Translucent

| n-Hexane | Inhalation- | Rat | LC50 170 mg/l |
|----------|-------------|-----|---------------------|
| | Vapor (4 | | |
| | hours) | | |
| n-Hexane | Ingestion | Rat | LD50 > 28,700 mg/kg |
| toluene | Dermal | Rat | LD50 12,000 mg/kg |
| toluene | Inhalation- | Rat | LC50 30 mg/l |
| | Vapor (4 | | |
| | hours) | | |
| toluene | Ingestion | Rat | LD50 5,550 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-----------------------------------|---------------------------|
| 2-Methylpentane | Professio nal judgemen t | Mild irritant |
| Cyclohexane | Rabbit | Mild irritant |
| Non-volatile Components | Professio nal judgemen t | Minimal irritation |
| Bicyclo[3.1.1]Hept-2-Ene,2,6,6-Trimethyl-,Polymer With 6,6-Dimethyl-2-Methylenebicyclo[3.1.1]Heptane | In vitro data | No significant irritation |
| Limestone | Rabbit | No significant irritation |
| n-Hexane | Human and animal | Mild irritant |
| toluene | Rabbit | Irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-----------------------------------|---------------------------|
| 2-Methylpentane | Professio nal judgemen t | Moderate irritant |
| Cyclohexane | Rabbit | Mild irritant |
| Bicyclo[3.1.1]Hept-2-Ene,2,6,6-Trimethyl-,Polymer With 6,6-Dimethyl-2- | In vitro | No significant irritation |
| Methylenebicyclo[3.1.1]Heptane | data | |
| Limestone | Rabbit | No significant irritation |
| n-Hexane | Rabbit | Mild irritant |
| toluene | Rabbit | Moderate irritant |

Sensitization:

Skin Sensitization

| OMI CONSTITUTION | | | |
|--|-------------------------------|----------------|--|
| Name | Species | Value | |
| Bicyclo[3.1.1]Hept-2-Ene,2,6,6-Trimethyl-,Polymer With 6,6-Dimethyl-2-Methylenebicyclo[3.1.1]Heptane | Multiple animal species | Not classified | |
| n-Hexane | Human | Not classified | |
| toluene | Guinea | Not classified | |
| | pig | | |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|------|-------|-------|
| | | |

D. . . . 0 . C . 1.

3MTM Industrial Adhesive 4550, Translucent

| Cyclohexane | In Vitro | Not mutagenic |
|--|----------|--|
| Cyclohexane | In vivo | Some positive data exist, but the data are not |
| | | sufficient for classification |
| Bicyclo[3.1.1]Hept-2-Ene,2,6,6-Trimethyl-,Polymer With 6,6-Dimethyl-2- | In Vitro | Not mutagenic |
| Methylenebicyclo[3.1.1]Heptane | | - |
| n-Hexane | In Vitro | Not mutagenic |
| n-Hexane | In vivo | Not mutagenic |
| toluene | In Vitro | Not mutagenic |
| toluene | In vivo | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|----------|------------|---------|--|
| n-Hexane | Dermal | Mouse | Not carcinogenic |
| n-Hexane | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |
| toluene | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| toluene | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |
| toluene | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|-------------|------------|--|---------|-----------------------------|------------------------------|
| Cyclohexane | Inhalation | Not classified for female reproduction | Rat | NOAEL 24 mg/l | 2 generation |
| Cyclohexane | Inhalation | Not classified for male reproduction | Rat | NOAEL 24 mg/l | 2 generation |
| Cyclohexane | Inhalation | Not classified for development | Rat | NOAEL 6.9 mg/l | 2 generation |
| Limestone | Ingestion | Not classified for development | Rat | NOAEL 625 mg/kg/day | premating & during gestation |
| n-Hexane | Ingestion | Not classified for development | Mouse | NOAEL 2,200 mg/kg/day | during organogenesis |
| n-Hexane | Inhalation | Not classified for development | Rat | NOAEL 0.7 mg/l | during gestation |
| n-Hexane | Ingestion | Toxic to male reproduction | Rat | NOAEL 1,140 mg/kg/day | 90 days |
| n-Hexane | Inhalation | Toxic to male reproduction | Rat | LOAEL 3.52 mg/l | 28 days |
| toluene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| toluene | Inhalation | Not classified for male reproduction | Rat | NOAEL 2.3 mg/l | 1 generation |
| toluene | Ingestion | Toxic to development | Rat | LOAEL 520 mg/kg/day | during gestation |
| toluene | Inhalation | Toxic to development | Human | NOAEL Not available | poisoning and/or abuse |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|-----------------|------------|--------------------------------------|-----------------------------------|-----------------------------------|------------------------|----------------------|
| 2-Methylpentane | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Professio nal judgeme nt | NOAEL Not available | |
| 2-Methylpentane | Inhalation | respiratory irritation | Some positive data exist, but the | | NOAEL Not | |

| | | | data are not sufficient for classification | | available | |
|-----------------|------------|--------------------------------------|--|-----------------------------------|------------------------|---------------------------|
| 2-Methylpentane | Inhalation | cardiac sensitization | Not classified | Dog | NOAEL Not available | |
| 2-Methylpentane | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professio nal judgeme nt | NOAEL Not available | |
| Cyclohexane | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Cyclohexane | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human and animal | NOAEL Not available | |
| Cyclohexane | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professio nal judgeme nt | NOAEL Not available | |
| Limestone | Inhalation | respiratory system | Not classified | Rat | NOAEL 0.812 mg/l | 90 minutes |
| n-Hexane | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | not available |
| n-Hexane | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Rabbit | NOAEL Not available | 8 hours |
| n-Hexane | Inhalation | respiratory system | Not classified | Rat | NOAEL 24.6 mg/l | 8 hours |
| toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| toluene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| toluene | Inhalation | immune system | Not classified | Mouse | NOAEL 0.004 mg/l | 3 hours |
| toluene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|---|--|---------|------------------------|-------------------------|
| 2-Methylpentane | Inhalation | peripheral nervous system | Not classified | Rat | NOAEL 5.3 mg/l | 14 weeks |
| 2-Methylpentane | Ingestion | peripheral nervous system | Not classified | Rat | NOAEL Not available | 8 weeks |
| 2-Methylpentane | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 2,000 mg/kg | 28 days |
| Cyclohexane | Inhalation | liver | Not classified | Rat | NOAEL 24 mg/l | 90 days |
| Cyclohexane | Inhalation | auditory system | Not classified | Rat | NOAEL 1.7 mg/l | 90 days |
| Cyclohexane | Inhalation | kidney and/or bladder | Not classified | Rabbit | NOAEL 2.7 mg/l | 10 weeks |
| Cyclohexane | Inhalation | hematopoietic system | Not classified | Mouse | NOAEL 24 mg/l | 14 weeks |
| Cyclohexane | Inhalation | peripheral nervous system | Not classified | Rat | NOAEL 8.6 mg/l | 30 weeks |
| Bicyclo[3.1.1]Hept-2- Ene,2,6,6- Trimethyl-,Polymer With 6,6-Dimethyl-2- Methylenebicyclo[3.1.1]H eptane | Ingestion | heart gastrointestinal tract hematopoietic system liver nervous system eyes kidney and/or bladder | Not classified | Rat | NOAEL 331 mg/kg/day | 90 days |
| Limestone | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupationa exposure |
| n-Hexane | Inhalation | peripheral nervous system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupationa exposure |

Page: 10 of 16

| n-Hexane | Inhalation respiratory system Some positive data exist, but the data are not sufficient for classification | | data are not sufficient for | Mouse | LOAEL 1.76 mg/l | 13 weeks |
|----------|--|--|--|-------------------------------|-----------------------------|---------------------------|
| n-Hexane | Inhalation | liver | Not classified | Rat | NOAEL Not available | 6 months |
| n-Hexane | Inhalation | kidney and/or bladder | Not classified | Rat | LOAEL 1.76 mg/l | 6 months |
| n-Hexane | Inhalation | hematopoietic system | Not classified | Mouse | NOAEL 35.2 mg/l | 13 weeks |
| n-Hexane | Inhalation | auditory system immune system eyes | Not classified | Human | NOAEL Not available | occupational exposure |
| n-Hexane | Inhalation | heart skin endocrine system | Not classified | Rat | NOAEL 1.76 mg/l | 6 months |
| n-Hexane | Ingestion | peripheral nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,140 mg/kg/day | 90 days |
| n-Hexane | Ingestion | endocrine system hematopoietic system liver immune system kidney and/or bladder | Not classified | Rat | NOAEL Not available | 13 weeks |
| toluene | Inhalation | auditory system eyes olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| toluene | Inhalation | nervous system | May cause damage to organs though prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| toluene | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2.3 mg/l | 15 months |
| toluene | Inhalation | heart liver kidney and/or bladder | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| toluene | Inhalation | endocrine system | Not classified | Rat | NOAEL 1.1 mg/l | 4 weeks |
| toluene | Inhalation | immune system | Not classified | Mouse | NOAEL Not available | 20 days |
| toluene | Inhalation | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1.1 mg/l | 8 weeks |
| toluene | Inhalation | hematopoietic system vascular system | Not classified | Human | NOAEL Not available | occupational exposure |
| toluene | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 11.3 mg/l | 15 weeks |
| toluene | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 625 mg/kg/day | 13 weeks |
| toluene | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| toluene | Ingestion | liver kidney and/or bladder | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| toluene | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 600 mg/kg/day | 14 days |
| toluene | Ingestion | endocrine system | Not classified | Mouse | NOAEL 105 mg/kg/day | 28 days |
| toluene | Ingestion | immune system | Not classified | Mouse | NOAEL 105 mg/kg/day | 4 weeks |

Aspiration Hazard

| · · · · · · · · · · · · · · · · · · · | | | | | | |
|---------------------------------------|-------------------|--|--|--|--|--|
| Name | Value | | | | | |
| 2-Methylpentane | Aspiration hazard | | | | | |
| Cyclohexane | Aspiration hazard | | | | | |
| n-Hexane | Aspiration hazard | | | | | |

D. . . . 11 - C - 10

toluene Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

| Material | Cas # | Organism | Type | Exposure | Test Endpoint | Test Result |
|--|--------------|------------------|--|----------|-----------------------------------|-------------|
| 2- Methylpentane | 107-83-5 | | Data not available or insufficient for classification | | | N/A |
| Non-volatile Components | Trade Secret | | Data not available or insufficient for classification | | | N/A |
| Bicyclo[3.1.1] Hept-2- Ene,2,6,6- Trimethyl-,Pol ymer With 6,6- Dimethyl-2- Methylenebicy clo[3.1.1]Hepta ne | 31393-98-3 | Activated sludge | Experimental | 3 hours | NOEC | 1,000 mg/l |
| Bicyclo[3.1.1] Hept-2- Ene,2,6,6- Trimethyl-,Pol ymer With 6,6- Dimethyl-2- Methylenebicy clo[3.1.1]Hepta ne | 31393-98-3 | Water flea | Experimental | 48 hours | No tox obs at lmt of water sol | >100 mg/l |
| Bicyclo[3.1.1] Hept-2- Ene,2,6,6- Trimethyl-,Pol ymer With 6,6- | 31393-98-3 | Water flea | Endpoint not reached | 21 days | EL10 | >100 mg/l |

| Dimethyl-2- | | | | | | |
|-----------------|-----------|-------------------|--------------|----------|------|------------------------------|
| Methylenebicy | | | | | | |
| clo[3.1.1]Hepta | | | | | | |
| ne | | | | | | |
| Cyclohexane | 110-82-7 | Bacteria | Experimental | 24 hours | IC50 | 97 mg/l |
| Cyclohexane | 110-82-7 | Fathead Minnow | Experimental | 96 hours | LC50 | 4.53 mg/l |
| Cyclohexane | 110-82-7 | Water flea | Experimental | 48 hours | EC50 | 0.9 mg/l |
| Limestone | 1317-65-3 | Green algae | Estimated | 72 hours | EC50 | >100 mg/l |
| Limestone | 1317-65-3 | Rainbow Trout | Estimated | 96 hours | LC50 | >100 mg/l |
| Limestone | 1317-65-3 | Water flea | Estimated | 48 hours | EC50 | >100 mg/l |
| Limestone | 1317-65-3 | Green algae | Estimated | 72 hours | EC10 | >100 mg/l |
| n-Hexane | 110-54-3 | Fathead Minnow | Experimental | 96 hours | LC50 | 2.5 mg/l |
| n-Hexane | 110-54-3 | Water flea | Experimental | 48 hours | LC50 | 3.9 mg/l |
| toluene | 108-88-3 | Coho Salmon | Experimental | 96 hours | LC50 | 5.5 mg/l |
| toluene | 108-88-3 | Grass Shrimp | Experimental | 96 hours | LC50 | 9.5 mg/l |
| toluene | 108-88-3 | Green Algae | Experimental | 72 hours | EC50 | 12.5 mg/l |
| toluene | 108-88-3 | Leopard frog | Experimental | 9 days | LC50 | 0.39 mg/l |
| toluene | 108-88-3 | Pink Salmon | Experimental | 96 hours | LC50 | 6.41 mg/l |
| toluene | 108-88-3 | Water flea | Experimental | 48 hours | EC50 | 3.78 mg/l |
| toluene | 108-88-3 | Coho Salmon | Experimental | 40 days | NOEC | 1.39 mg/l |
| toluene | 108-88-3 | Diatom | Experimental | 72 hours | NOEC | 10 mg/l |
| toluene | 108-88-3 | Water flea | Experimental | 7 days | NOEC | 0.74 mg/l |
| toluene | 108-88-3 | Activated sludge | Experimental | 12 hours | IC50 | 292 mg/l |
| toluene | 108-88-3 | Bacteria | Experimental | 16 hours | NOEC | 29 mg/l |
| toluene | 108-88-3 | Bacteria | Experimental | 24 hours | EC50 | 84 mg/l |
| toluene | 108-88-3 | Redworm | Experimental | 28 days | LC50 | >150 mg per kg of bodyweight |
| toluene | 108-88-3 | Soil microbes | Experimental | 28 days | NOEC | <26 mg/kg (Dry Weight) |

12.2. Persistence and degradability

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|--|--------------|--------------------------------|----------|-----------------------------------|----------------------|-----------------------------------|
| 2- Mathylpantana | 107-83-5 | Data not availbl- | | | N/A | |
| Methylpentane | | insufficient | | | | |
| Non-volatile Components | Trade Secret | Data not availbl-insufficient | | | N/A | |
| Bicyclo[3.1.1] Hept-2- Ene,2,6,6- Trimethyl-,Pol ymer With 6,6- Dimethyl-2- Methylenebicy clo[3.1.1]Hepta ne | 31393-98-3 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 4 % BOD/ThBOD | OECD 301D - Closed Bottle Test |
| Cyclohexane | 110-82-7 | Experimental Photolysis | | Photolytic half- life (in air) | 4.14 days (t 1/2) | Non-standard method |
| Cyclohexane | 110-82-7 | Experimental | 28 days | Biological | 77 % | OECD 301F - |

| | | Biodegradation | | Oxygen Demand | BOD/ThBOD | Manometric Respiro |
|-----------|-----------|--------------------------------------|---------|-----------------------------------|-------------------|-----------------------------------|
| Limestone | 1317-65-3 | Data not availbl- insufficient | | Demand | N/A | |
| n-Hexane | 110-54-3 | Experimental Photolysis | | Photolytic half- life (in air) | 5.4 days (t 1/2) | Non-standard method |
| n-Hexane | 110-54-3 | Experimental Bioconcentrati on | 28 days | Biological Oxygen Demand | 100 % weight | OECD 301C - MITI (I) |
| toluene | 108-88-3 | Experimental Photolysis | | Photolytic half- life (in air) | 5.2 days (t 1/2) | |
| toluene | 108-88-3 | Experimental Biodegradation | 20 days | Biological Oxygen Demand | 80 % BOD/ThBOD | APHA Std Meth Water/Wastewater |

12.3. Bioaccumulative potential

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|--|--------------|--|----------|--------------------------------------|-------------|-----------------------------------|
| 2- Methylpentane | 107-83-5 | Estimated Bioconcentrati on | | Bioaccumulatio n Factor | 150 | Est: Bioconcentration factor |
| Non-volatile Components | Trade Secret | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Bicyclo[3.1.1] Hept-2- Ene,2,6,6- Trimethyl-,Pol ymer With 6,6- Dimethyl-2- Methylenebicy clo[3.1.1]Hepta ne | 31393-98-3 | Experimental Bioconcentrati on | | Log of Octanol/H2O part. coeff | 7.41 | Non-standard method |
| Cyclohexane | 110-82-7 | Experimental BCF-Carp | 56 days | Bioaccumulatio n Factor | 129 | OECD 305E-Bioaccum Fl-thru fis |
| Limestone | 1317-65-3 | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| n-Hexane | 110-54-3 | Estimated Bioconcentrati on | | Bioaccumulatio n Factor | 50 | Est: Bioconcentration factor |
| toluene | 108-88-3 | Experimental BCF - Other | 72 hours | Bioaccumulatio n Factor | 90 | |
| toluene | 108-88-3 | Experimental Bioconcentrati on | | Log of Octanol/H2O part. coeff | 2.73 | |

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number: UN1133

Proper Shipping Name:ADHESIVES Technical Name: None assigned. Hazard Class/Division:3

Subsidiary Risk: None assigned.

Packing Group:II

Limited Quantity: None assigned. Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number: UN1133

Proper Shipping Name:ADHESIVES Technical Name: None assigned. Hazard Class/Division:3 Subsidiary Risk: None assigned.

Packing Group:II

Limited Quantity: None assigned. Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan

Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my