



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 07-1664-7
Issue Date: 03/04/2022

Version Number: 4.00
Supersedes Date: 26/02/2019

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

IDENTIFICATION

1.1. Product identifier

3M™ Panel Bonding Adhesive PN 08115

Product Identification Numbers

60-9800-2447-9 60-9800-3093-0 60-9800-4425-3

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Adhesive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

32-4327-6, 09-3599-9

TRANSPORT INFORMATION

This product is a kit that consists of two or more different regulated materials packed in the same outer packaging (ship unit). The transportation classifications of the individual components appear in Section 14 of the attached SDSs.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current

regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	32-4327-6	Version Number:	2.00
Issue Date:	01/10/2021	Supersedes Date:	25/10/2016

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Panel Bonding Adhesive Part B PN 08115, 38315, 58115

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Structural Panel Bonding Adhesive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS:	3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone:	03-7884 2888
E Mail:	3mmyehsr@mmm.com
Website:	www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Germ Cell Mutagenicity: Category 2.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark | Health Hazard | Environment |

Pictograms



Hazard Statements:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

General:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention:

P273	Avoid release to the environment.
P280E	Wear protective gloves.
P281	Use personal protective equipment as required.

Response:

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
4,4'-isopropylidenediphenol-epichlorohydrin polymer	25068-38-6	50 - 60
Oxide Glass Chemicals	65997-17-3	10 - 30
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	14228-73-0	7 - 13
Fused Silica	60676-86-0	7 - 13
Acrylate Polymer	Trade Secret	1 - 11
Silica	7631-86-9	1 - 5

3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	0.5 - 1.5
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	0.5 - 1.5
Carbon Black	1333-86-4	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent

material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon Black	1333-86-4	Malaysia OELs	TWA(8 hours):3.5 mg/m3	
CAS NO SEQ117921	60676-86-0	ACGIH	TWA(inhalable particulates):10 mg/m3	
CAS NO SEQ117922	60676-86-0	ACGIH	TWA(respirable particles):3 mg/m3	
DUST, INERT OR NUISANCE	60676-86-0	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m3;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m3	
Fused Silica	60676-86-0	Malaysia OELs	TWA(respirable fraction)(8 hours):0.1 mg/m3	
CERAMIC FIBERS	65997-17-3	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
GLASS FILAMENTS	65997-17-3	Malaysia OELs	TWA(inhalable fraction)(8 hours):5 mg/m3;TWA(as fiber)(8 hours):1 fibers/ml	
Oxide Glass Chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3	
SPECIAL PURPOSE GLASS FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcin.
CAS NO SEQ117921	7631-86-9	ACGIH	TWA(inhalable particulates):10 mg/m3	

CAS NO SEQ117922	7631-86-9	ACGIH	TWA(respirable particles):3 mg/m3	
DUST, INERT OR NUISANCE	7631-86-9	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m3;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	Black
Odor	Acrylic
Odor threshold	No Data Available

pH	<i>No Data Available</i>
Melting point/Freezing point	<i>No Data Available</i>
Boiling point/Initial boiling point/Boiling range	$\geq 35\text{ }^{\circ}\text{C}$
Flash Point	$\geq 104.4\text{ }^{\circ}\text{C}$ [Test Method: Closed Cup]
Evaporation rate	≤ 1 Units not avail. or not appl. [Ref Std: BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	$\leq 186,158.4\text{ Pa}$
Vapor Density and/or Relative Vapor Density	<i>No Data Available</i>
Density	1 kg/l
Density	0.96 g/ml
Relative Density	0.96 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity/Kinematic Viscosity	100,000 mPa-s - 225,000 mPa-s [Test Method: Brookfield]
Volatile Organic Compounds	15 g/l [Test Method: calculated SCAQMD rule 443.1]
Volatile Organic Compounds	1.6 % weight [Test Method: calculated per CARB title 2]
Percent volatile	1.6 % weight
VOC Less H₂O & Exempt Solvents	15 g/l [Test Method: calculated SCAQMD rule 443.1]
Molecular weight	<i>No Data Available</i>

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Amines

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

Aldehydes

Not Specified

Carbon monoxide

Not Specified

Carbon dioxide

Not Specified

Hydrogen Chloride

Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Rat	LD50 > 1,600 mg/kg

4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Oxide Glass Chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide Glass Chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Fused Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	Ingestion	Rat	LD50 1,000 mg/kg
Fused Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fused Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Acrylate Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
3-(Trimethoxysilyl)propyl Glycidyl Ether	Dermal	Rabbit	LD50 4,000 mg/kg
3-(Trimethoxysilyl)propyl Glycidyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Rat	LD50 7,010 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Mild irritant
Oxide Glass Chemicals	Professional judgement	No significant irritation
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	In vitro data	Irritant
Fused Silica	Rabbit	No significant irritation
Acrylate Polymer	Professional judgement	Minimal irritation
Silica	Rabbit	No significant irritation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Rabbit	Mild irritant
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Moderate irritant
Oxide Glass Chemicals	Professional judgement	No significant irritation
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	In vitro data	No significant irritation
Fused Silica	Rabbit	No significant irritation
Acrylate Polymer	Professional judgement	Mild irritant

Silica	Rabbit	No significant irritation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Sensitization:
Skin Sensitization

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human and animal	Sensitizing
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	similar compounds	Sensitizing
Fused Silica	Human and animal	Not classified
Silica	Human and animal	Not classified
3-(Trimethoxysilyl)propyl Glycidyl Ether	Guinea pig	Not classified
Dimethyl Siloxane, Reaction Product With Silica	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In vivo	Not mutagenic
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Oxide Glass Chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	In Vitro	Mutagenic; structurally related to germ cell mutagens
Fused Silica	In Vitro	Not mutagenic
Silica	In Vitro	Not mutagenic
3-(Trimethoxysilyl)propyl Glycidyl Ether	In vivo	Not mutagenic
3-(Trimethoxysilyl)propyl Glycidyl Ether	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product With Silica	In Vitro	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Oxide Glass Chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Fused Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

3-(Trimethoxysilyl)propyl Glycidyl Ether	Dermal	Mouse	Not carcinogenic
Dimethyl Siloxane, Reaction Product With Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Fused Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fused Silica	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fused Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
1,4-BIS[(2,3-EPOXYPROPOXY)MET HYL]CYCLOHEXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,4'-isopropylidenediphenol-	Dermal	liver	Not classified	Rat	NOAEL 1,000	2 years

epichlorohydrin polymer					mg/kg/day	
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Oxide Glass Chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Fused Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
3-(Trimethoxysilyl)propyl Glycidyl Ether	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Dimethyl Siloxane, Reaction Product With Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
4,4'-isopropylidene diphenol-	25068-38-6	Activated sludge	Estimated	3 hours	IC50	>100 mg/l

epichlorohydrin polymer						
4,4'-isopropylidene diphenol-epichlorohydrin polymer	25068-38-6	Green Algae	Estimated	72 hours	EC50	>11 mg/l
4,4'-isopropylidene diphenol-epichlorohydrin polymer	25068-38-6	Rainbow Trout	Estimated	96 hours	LC50	2 mg/l
4,4'-isopropylidene diphenol-epichlorohydrin polymer	25068-38-6	Water flea	Estimated	48 hours	EC50	1.8 mg/l
4,4'-isopropylidene diphenol-epichlorohydrin polymer	25068-38-6	Green Algae	Estimated	72 hours	NOEC	4.2 mg/l
4,4'-isopropylidene diphenol-epichlorohydrin polymer	25068-38-6	Water flea	Estimated	21 days	NOEC	0.3 mg/l
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
1,4-BIS[(2,3-EPOXYPROPOXY)METHYLCYCLOHEXANE	14228-73-0	Bacteria	Estimated	18 hours	EC50	10,264 mg/l
1,4-BIS[(2,3-EPOXYPROPOXY)METHYLCYCLOHEXANE	14228-73-0		Experimental	72 hours	EC50	38 mg/l
1,4-BIS[(2,3-EPOXYPROPOXY)METHYLCYCLOHEXANE	14228-73-0	Water flea	Experimental	48 hours	EC50	71 mg/l
1,4-BIS[(2,3-EPOXYPROPOXY)METHYLCYCLOHEXANE	14228-73-0		Experimental	72 hours	EC10	18 mg/l

Fused Silica	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Acrylate Polymer	Trade Secret		Data not available or insufficient for classification			N/A
Silica	7631-86-9		Data not available or insufficient for classification			N/A
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Bacteria	Experimental	5 hours	EC10	1,520 mg/l
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Crustacea other	Experimental	48 hours	LC50	324 mg/l
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Green algae	Experimental	96 hours	EC50	350 mg/l
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Green Algae	Experimental	96 hours	NOEC	130 mg/l
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Water flea	Experimental	21 days	NOEC	>=100 mg/l
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7		Data not available or insufficient for classification			N/A
Carbon Black	1333-86-4	Activated sludge	Experimental	3 hours	EC50	>=100 mg/l
Carbon Black	1333-86-4		Data not available or insufficient for classification			N/A

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
4,4'-isopropylidene diphenol-epichlorohydrin polymer	25068-38-6	Estimated Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	Non-standard method
4,4'-isopropylidene	25068-38-6	Estimated Biodegradation	28 days	Biological Oxygen	5 %BOD/COD	OECD 301F - Manometric Respiro

diphenol-epichlorohydrin polymer				Demand		
Oxide Glass Chemicals	65997-17-3	Data not availbl-insufficient			N/A	
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	14228-73-0	Experimental Biodegradation	28 days	Carbon dioxide evolution	1.3 %CO2 evolution/THC O2 evolution	OECD 301B - Mod. Sturm or CO2
Fused Silica	60676-86-0	Data not availbl-insufficient			N/A	
Acrylate Polymer	Trade Secret	Data not availbl-insufficient			N/A	
Silica	7631-86-9	Data not availbl-insufficient			N/A	
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life	6.5 hours (t 1/2)	Non-standard method
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 % weight	Non-standard method
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	Data not availbl-insufficient			N/A	
Carbon Black	1333-86-4	Data not availbl-insufficient			N/A	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
4,4'-isopropylidene diphenol-epichlorohydrin polymer	25068-38-6	Estimated Bioconcentration		Log of Octanol/H2O part. coeff	3.242	Non-standard method
Oxide Glass Chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	14228-73-0	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.05	Non-standard method
Fused Silica	60676-86-0	Data not	N/A	N/A	N/A	N/A

		available or insufficient for classification				
Acrylate Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3-(Trimethoxysilyl)propyl Glycidyl Ether	2530-83-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon Black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

Air Transport (IATA)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	09-3599-9	Version Number:	4.00
Issue Date:	14/04/2024	Supersedes Date:	26/02/2019

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 38515, 58115

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Use with Part B, MSDS 32-4327-6

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 1.
Serious Eye Damage/Irritation: Category 1.
Skin Sensitizer: Category 1.
Reproductive Toxicity: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 2.
Acute Aquatic Toxicity: Category 1.
Chronic Aquatic Toxicity: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard | Environment |

Pictograms



Hazard Statements:

H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H371	May cause damage to organs: .
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements

General:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Prevention:

P201	Obtain special instructions before use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.
P280D	Wear protective gloves, protective clothing, and eye/face protection.
P281	Use personal protective equipment as required.

Response:

P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

All or part of the classification is based on toxicity test data., May cause chemical gastrointestinal burns., May cause drowsiness or dizziness., Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Polymeric Diamide	68911-25-1	30 - 60
Butadiene Acrylonitrile Copolymer	68683-29-4	10 - 30
Fused Silica	60676-86-0	10 - 30
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	< 10
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	90-72-2	5 - 10
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	1 - 5
Amine Epoxy Curing Agent	288-32-4	1 - 5
Nitric acid, ammonium calcium salt	15245-12-2	1 - 5
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	0.1 - 1.5
N-Aminoethylpiperazine	140-31-8	0.1 - 1
Toluene	108-88-3	< 0.5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO₂ (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50	SKIN

			ppm)	
DUST, INERT OR NUISANCE	60676-86-0	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m ³ ;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m ³	
Fused Silica	60676-86-0	Malaysia OELs	TWA(respirable fraction)(8 hours):0.1 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
----------------	--------

Specific Physical Form:	Viscous liquid
Color	Tan
Odor	Slight Amine
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	≥ 110 °C
Flash Point	110 °C [<i>Test Method</i> :Closed Cup]
Evaporation rate	≤ 1 [<i>Ref Std</i> :BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	$\leq 26,664.4$ Pa [<i>@ 20 °C</i>]
Vapor Density and/or Relative Vapor Density	<i>No Data Available</i>
Density	1.2 g/ml
Density	1.2 kg/l
Relative Density	1.2 [<i>Ref Std</i> :WATER=1]
Water solubility	<i>No Data Available</i>
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity/Kinematic Viscosity	100,000 mPa-s - 225,000 mPa-s [<i>Test Method</i> :Brookfield]
Volatile Organic Compounds	4 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0.4 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	0.4 % weight
VOC Less H₂O & Exempt Solvents	4 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Molecular weight	<i>No Data Available</i>

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalized weakness.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Polymeric Diamide	Dermal	Rat	LD50 > 2,000 mg/kg
Polymeric Diamide	Ingestion	Rat	LD50 > 2,000 mg/kg
Fused Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Fused Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Fused Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Butadiene Acrylonitrile Copolymer	Dermal	Rabbit	LD50 > 3,000 mg/kg
Butadiene Acrylonitrile Copolymer	Ingestion	Rat	LD50 > 15,300 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	Rat	LD50 1,280 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	Rat	LD50 1,000 mg/kg
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Dermal	Rabbit	LD50 2,525 mg/kg
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Rat	LD50 2,850 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Amine Epoxy Curing Agent	Ingestion	Rat	LD50 970 mg/kg
Amine Epoxy Curing Agent	Dermal	similar compounds	LD50 400 mg/kg
Nitric acid, ammonium calcium salt	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, ammonium calcium salt	Dermal	similar compounds	LD50 > 2,000 mg/kg
Bis[(Dimethylamino)Methyl]Phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
N-Aminoethylpiperazine	Dermal	Rabbit	LD50 865 mg/kg
N-Aminoethylpiperazine	Ingestion	Rat	LD50 1,470 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Corrosive
Polymeric Diamide	Rat	Irritant
Fused Silica	Rabbit	No significant irritation
Butadiene Acrylonitrile Copolymer	Rabbit	Irritant
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Rabbit	Corrosive
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Amine Epoxy Curing Agent	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	similar compounds	No significant irritation
Bis[(Dimethylamino)Methyl]Phenol	similar compounds	Corrosive
N-Aminoethylpiperazine	Rabbit	Corrosive
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	similar health hazards	Corrosive
Polymeric Diamide	In vitro data	Severe irritant
Fused Silica	Rabbit	No significant irritation
Butadiene Acrylonitrile Copolymer	Rabbit	Mild irritant
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Rabbit	Corrosive
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Amine Epoxy Curing Agent	Rabbit	Corrosive
Nitric acid, ammonium calcium salt	Rabbit	Corrosive
Bis[(Dimethylamino)Methyl]Phenol	similar compound	Corrosive
N-Aminoethylpiperazine	Rabbit	Corrosive
Toluene	Rabbit	Moderate irritant

Sensitization:
Skin Sensitization

Name	Species	Value
Overall product	Guinea pig	Sensitizing
Polymeric Diamide	Guinea pig	Sensitizing
Fused Silica	Human and animal	Not classified
Butadiene Acrylonitrile Copolymer	Guinea pig	Sensitizing
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Guinea pig	Not classified
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Professional judgement	Sensitizing
Dimethyl Siloxane, Reaction Product with Silica	Human and animal	Not classified
Nitric acid, ammonium calcium salt	Mouse	Not classified
N-Aminoethylpiperazine	Guinea pig	Sensitizing
Toluene	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Polymeric Diamide	In Vitro	Not mutagenic
Fused Silica	In Vitro	Not mutagenic
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	In Vitro	Not mutagenic
Bis(3-Aminopropyl) Ether of Diethylene Glycol	In Vitro	Not mutagenic
Dimethyl Siloxane, Reaction Product with Silica	In Vitro	Not mutagenic
Amine Epoxy Curing Agent	In Vitro	Not mutagenic
Amine Epoxy Curing Agent	In vivo	Not mutagenic
Nitric acid, ammonium calcium salt	In Vitro	Not mutagenic

N-Aminoethylpiperazine	In vivo	Not mutagenic
N-Aminoethylpiperazine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Fused Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product with Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Polymeric Diamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Polymeric Diamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Polymeric Diamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Fused Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Fused Silica	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Fused Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	2 generation
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	Not classified for development	Rabbit	NOAEL 15 mg/kg/day	during gestation
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Amine Epoxy Curing Agent	Ingestion	Toxic to development	Rat	NOAEL 60 mg/kg/day	during organogenesis
N-Aminoethylpiperazine	Ingestion	Not classified for female reproduction	Rat	NOAEL 598 mg/kg/day	premating & during gestation
N-Aminoethylpiperazine	Ingestion	Not classified for male reproduction	Rat	NOAEL 409 mg/kg/day	32 days

N-Aminoethylpiperazine	Ingestion	Toxic to development	Rabbit	NOAEL 75 mg/kg/day	during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Polymeric Diamide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Polymeric Diamide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Butadiene Acrylonitrile Copolymer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Amine Epoxy Curing Agent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, ammonium calcium salt	Ingestion	methemoglobinemia	Causes damage to organs	similar compounds	NOAEL Not available	
N-Aminoethylpiperazine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Polymeric Diamide	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days

		bladder respiratory system vascular system				
Fused Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	skin	Not classified	Rat	NOAEL 25 mg/kg/day	4 weeks
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	4 weeks
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	heart endocrine system hematopoietic system liver muscles nervous system kidney and/or bladder respiratory system vascular system auditory system skin gastrointestinal tract bone, teeth, nails, and/or hair immune system eyes	Not classified	Rat	NOAEL 150 mg/kg/day	90 days
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
Dimethyl Siloxane, Reaction Product with Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Amine Epoxy Curing Agent	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
Amine Epoxy Curing Agent	Ingestion	heart liver blood nervous system eyes	Not classified	Rat	NOAEL 180 mg/kg/day	90 days
N-Aminoethylpiperazine	Dermal	skin	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
N-Aminoethylpiperazine	Dermal	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
N-Aminoethylpiperazine	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.2 mg/m3	13 weeks
N-Aminoethylpiperazine	Inhalation	hematopoietic system eyes kidney and/or bladder	Not classified	Rat	NOAEL 53.8 mg/m3	13 weeks
N-Aminoethylpiperazine	Ingestion	heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 598 mg/kg/day	28 days

Toluene	Inhalation	auditory system nervous system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Polymeric Diamide	68911-25-1	Fathead Minnow	Experimental	96 hours	LL50	2.16 mg/l
Polymeric Diamide	68911-25-1	Green algae	Experimental	72 hours	EL50	0.43 mg/l
Polymeric Diamide	68911-25-1	Water flea	Experimental	48 hours	EL50	0.57 mg/l
Polymeric Diamide	68911-25-1	Green algae	Experimental	72 hours	NOEL	0.28 mg/l
Polymeric Diamide	68911-25-1	Activated sludge	Experimental	3 hours	EC50	410.3 mg/l
Butadiene Acrylonitrile Copolymer	68683-29-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Fused Silica	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
Amine Epoxy Curing Agent	288-32-4	Green algae	Experimental	72 hours	ErC50	133 mg/l
Amine Epoxy Curing Agent	288-32-4	Water flea	Experimental	48 hours	EC50	341.5 mg/l
Amine Epoxy Curing Agent	288-32-4	Green algae	Experimental	72 hours	NOEC	25 mg/l
Amine Epoxy Curing Agent	288-32-4	Activated sludge	Experimental	30 minutes	EC50	>1,000 mg/l
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Nitric acid, ammonium calcium salt	15245-12-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Nitric acid, ammonium calcium salt	15245-12-2	Fathead Minnow	Estimated	32 days	NOEC	157 mg/l
Nitric acid, ammonium calcium	15245-12-2	Green algae	Experimental	72 hours	NOEC	100 mg/l

salt						
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	N/A	Data not available or insufficient for classification	N/A	N/A	NA
N-Aminoethylpiperazine	140-31-8	Bacteria	Experimental	17 hours	EC10	100 mg/l
N-Aminoethylpiperazine	140-31-8	Golden Orfe	Experimental	96 hours	LC50	368 mg/l
N-Aminoethylpiperazine	140-31-8	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
N-Aminoethylpiperazine	140-31-8	Water flea	Experimental	48 hours	EC50	58 mg/l
N-Aminoethylpiperazine	140-31-8	Green algae	Experimental	72 hours	NOEC	31 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Polymeric Diamide	68911-25-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	0 %BOD/ThOD	OECD 301F - Manometric Respiro
Butadiene Acrylonitrile Copolymer	68683-29-4	Data not available - insufficient	N/A	N/A	N/A	N/A
Fused Silica	60676-86-0	Data not available - insufficient	N/A	N/A	N/A	N/A
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Experimental Biodegradation	25 days	Carbon dioxide evolution	-8 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Experimental Biodegradation	28 days	Biological Oxygen Demand	4 %BOD/ThOD	OECD 301D - Closed Bottle Test
Amine Epoxy Curing Agent	288-32-4	Experimental Biodegradation	18 days	Dissolv. Organic Carbon Deplet	98 %removal of DOC	OECD 301A - DOC Die Away Test
Amine Epoxy Curing Agent	288-32-4	Experimental Aquatic Inherent Biodegrad.	8 days	Carbon dioxide evolution	83 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
Amine Epoxy	288-32-4	Experimental	19 days	Percent degraded	86 %removal of	OECD 303A - Simulated

Curing Agent		Biodegradation			DOC	Aerobic
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available - insufficient	N/A	N/A	N/A	N/A
Nitric acid, ammonium calcium salt	15245-12-2	Data not available - insufficient	N/A	N/A	N/A	N/A
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	Modeled Biodegradation	28 days	Biological Oxygen Demand	41 %CO ₂ evolution/THCO ₂ evolution	Catalogic™
N-Aminoethylpiperazine	140-31-8	Experimental Biodegradation	28 days	Biological Oxygen Demand	0 %BOD/ThOD	OECD 301C - MITI (I)
Toluene	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 %BOD/ThOD	APHA Std Meth Water/Wastewater
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Polymeric Diamide	68911-25-1	Modeled Bioconcentration		Bioaccumulation Factor	42	Catalogic™
Polymeric Diamide	68911-25-1	Modeled Bioconcentration		Log of Octanol/H ₂ O part. coeff	11.7	Episuite™
Butadiene Acrylonitrile Copolymer	68683-29-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fused Silica	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	-1.25	
Tris(2,4,6-Dimethylaminomethyl)Phenol	90-72-2	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	-0.66	830.7550 Part.Coeff Shake Flask
Amine Epoxy Curing Agent	288-32-4	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	-0.02	OECD 107 log Kow shake flask mtd
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Nitric acid, ammonium calcium salt	15245-12-2	Estimated Bioconcentration		Log of Octanol/H ₂ O part. coeff	-3.1	OECD 107 log Kow shake flask mtd
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	Modeled Bioconcentration		Log of Octanol/H ₂ O part. coeff	-2.34	ACD/Labs ChemSketch™
N-Aminoethylpiperazine	140-31-8	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	0.3	
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation Factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	2.73	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN3267

Proper Shipping Name:CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

Technical Name:(Bis(3-Aminopropyl) Ether of Diethylene Glycol; Bis[(Dimethylamino)Methyl]Phenol)

Hazard Class/Division:8

Subsidiary Risk:None assigned.

Packing Group:II

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN3267

Proper Shipping Name:CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

Technical Name:(Bis(3-Aminopropyl) Ether of Diethylene Glycol; Bis[(Dimethylamino)Methyl]Phenol)

Hazard Class/Division:8

Subsidiary Risk:None assigned.

Packing Group:II

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions

may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my