

Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 07-1596-1
 Version Number:
 4.00

 Issue Date:
 14/10/2022
 Supercedes Date:
 25/07/2019

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

Structural Sealing Tape #5230 #5231 #5232

Product Identification Numbers

I I oddet I delitilitedti	on i tallibers			
70-0711-0528-5	70-0711-0529-3	DT-2114-4784-2	DT-2114-4785-9	DT-2114-4876-6
DT-2114-4877-4	DT-2114-4941-8	DT-2114-4942-6	DT-2114-4981-4	DT-2114-5016-8
DT-2114-5036-6	DT-2114-5037-4	DT-2114-5038-2	DT-2114-5066-3	DT-2114-5067-1
DT-2114-5091-1	DT-2114-5092-9	DT-2114-5093-7	DT-2114-5094-5	DT-2114-5095-2
DT-2114-5145-5	DT-2114-5205-7	DT-2114-5208-1	DT-2114-5215-6	DT-2114-5285-9
DT-2114-5334-5	DT-5230-0015-6	DT-5231-0008-9	HB-0042-5662-2	HB-0043-3526-9
HB-0043-3528-5	JR-1505-6722-0	JR-1540-1460-9	JR-1540-2047-3	JR-1540-4109-9
JT-2800-1042-5	JT-2800-1661-2	JT-2800-1860-0	JT-2800-2037-4	JT-2800-2153-9
JT-2800-2218-0	JT-2800-2256-0	JT-2800-3348-4	JT-2800-3680-0	JT-2800-3696-6
JT-2800-4055-4	JT-2800-4056-2	JT-2800-4129-7	JT-2800-4370-7	JT-2800-4592-6
JT-2800-4597-5	JT-2800-4602-3	JT-2800-4603-1	JT-2800-4609-8	JT-2800-4613-0
JT-2800-4616-3	JT-2800-4793-0	JT-2800-5099-1	JT-2800-5123-9	RR-0009-3582-7
RR-0009-3583-5	RR-0009-4817-6	RR-0009-5004-0	RT-0009-5871-5	RT-0009-5872-3
RT-0009-5873-1	RT-0009-5877-2	RT-0009-5928-3	RT-0009-5939-0	RT-0009-5974-7
RT-0009-5975-4	RT-0009-5976-2	RT-0009-5977-0	RT-0009-6014-1	RT-0009-6015-8
RT-0009-6016-6	RT-0009-6602-3	RT-0009-8551-0		

1.2. Recommended use and restrictions on use

Recommended use

Sealing discontinuities for automotive in-line application.

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark | Environment |

Pictograms





Hazard Statements:

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P273 Avoid release to the environment.

P280E Wear protective gloves.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
4-4'-ISOPROPYLLIDENEDIPHENOL-	25068-38-6	30 - 60
EPICHOLOROHYDRIN POLYMER		
ACRYLIC COPOLYMER	Trade Secret	30 - 60
CALCIUM CARBONATE	471-34-1	5 - 10

SYNTHETIC POLYMER	Trade Secret	5 - 10
DICYANDIAMIDE	461-58-5	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
DUST, INERT OR NUISANCE	471-34-1	Malaysia OELs	TWA (proposed)(respirable	
			particles)(8 hours):3	
			mg/m3;TWA	
			(proposed)(Inhalable	
			particulate)(8 hours):10 mg/m3	
Limestone	471-34-1	Malaysia OELs	TWA (proposed)(8 hours):10	
			mg/m3	
Particles (insoluble or poorly	471-34-1	ACGIH	TWA(inhalable	
soluble) not otherwise specified,			particulates):10 mg/m3	
inhalable particles				
Particles (insoluble or poorly	471-34-1	ACGIH	TWA(respirable particles):3	
soluble) not otherwise specified,			mg/m3	
respirable particles				

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer's Recommended Guidelines

Malaysia OELs: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Information on basic physical and chemical properties				
Physical state	Solid			
Specific Physical Form:	Roll of Tape			
Color	Milky White			
Odor	Slight Acrylic			
Odor threshold	No Data Available			
pH	Not Applicable			
Melting point/Freezing point	No Data Available			
Boiling point/Initial boiling point/Boiling range	Not Applicable			
Flash Point	No flash point			
Evaporation rate	Not Applicable			
Flammability (solid, gas)	Not Classified			
Flammable Limits(LEL)	Not Applicable			
Flammable Limits(UEL) Not Applicable				
Vapor Pressure Not Applicable				
Vapor Density and/or Relative Vapor Density	Not Applicable			
Density 1.08 - 1.3 g/cm3				
Relative Density 1.08 - 1.3 [Ref Std:WATER=1]				
Water solubility Nil				
Solubility- non-water	No Data Available			
Partition coefficient: n-octanol/ water	No Data Available			
Autoignition temperature Not Applicable				
Decomposition temperature No Data Available				
iscosity/Kinematic Viscosity Not Applicable				
Volatile Organic Compounds Not Applicable				
Percent volatile <=2 %				
VOC Less H2O & Exempt Solvents Not Applicable				
Molecular weight	No Data Available			

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

Heat

10.5. Incompatible materials

Strong acids Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

Condition
Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Vapors released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

Structural Sealing Tape #5230 #5231 #5232

4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN	Dermal	Rat	LD50 > 1,600 mg/kg
POLYMER			
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN	Ingestion	Rat	LD50 > 1,000 mg/kg
POLYMER			
SYNTHETIC POLYMER	Dermal	Rabbit	LD50 > 7,940 mg/kg
CALCIUM CARBONATE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCIUM CARBONATE	Inhalation-	Rat	LC50 3 mg/l
	Dust/Mist		
	(4 hours)		
CALCIUM CARBONATE	Ingestion	Rat	LD50 6,450 mg/kg
SYNTHETIC POLYMER	Ingestion	Rat	LD50 > 10,000 mg/kg
DICYANDIAMIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
DICYANDIAMIDE	Ingestion	Rat	LD50 > 30,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN POLYMER	Rabbit	Mild irritant
CALCIUM CARBONATE	Rabbit	No significant irritation
DICYANDIAMIDE	Human	Minimal irritation
	and	
	animal	

Serious Eye Damage/Irritation

Name	Species	Value
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN POLYMER	Rabbit	Moderate irritant
CALCIUM CARBONATE	Rabbit	No significant irritation
DICYANDIAMIDE	Professio	Mild irritant
	nal	
	judgemen	
	t	

Sensitization:

Skin Sensitization

Name	Species	Value
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN POLYMER	Human	Sensitizing
	and	
	animal	
DICYANDIAMIDE	Guinea	Not classified
	pig	

Respiratory Sensitization

Name	Species	Value
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN POLYMER	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN POLYMER	In vivo	Not mutagenic
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN POLYMER	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
DICYANDIAMIDE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
4-4'-ISOPROPYLLIDENEDIPHENOL-EPICHOLOROHYDRIN	Dermal	Mouse	Some positive data exist, but the data are not
POLYMER			sufficient for classification

DICYANDIAMIDE	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
4-4'-ISOPROPYLLIDENEDIPHENOL- EPICHOLOROHYDRIN POLYMER	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4-4'-ISOPROPYLLIDENEDIPHENOL- EPICHOLOROHYDRIN POLYMER	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4-4'-ISOPROPYLLIDENEDIPHENOL- EPICHOLOROHYDRIN POLYMER	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4-4'-ISOPROPYLLIDENEDIPHENOL- EPICHOLOROHYDRIN POLYMER	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
CALCIUM CARBONATE	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
DICYANDIAMIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
DICYANDIAMIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
DICYANDIAMIDE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

specific ranger organ rowicity single exposure							
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure	
						Duration	
CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Rat	NOAEL	90 minutes	
					0.812 mg/l	ļ.	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4-4'- ISOPROPYLLIDENEDIP HENOL- EPICHOLOROHYDRIN POLYMER	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
4-4'- ISOPROPYLLIDENEDIP HENOL- EPICHOLOROHYDRIN POLYMER	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4-4'- ISOPROPYLLIDENEDIP HENOL- EPICHOLOROHYDRIN POLYMER	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
CALCIUM CARBONATE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
DICYANDIAMIDE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Туре	Exposure	Test Endpoint	
4-4'-	25068-38-6	Activated	Estimated	3 hours	IC50	>100 mg/l
ISOPROPYLL		sludge				
IDENEDIPHE						
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
4-4'-	25068-38-6	Green algae	Estimated	72 hours	EC50	>11 mg/l
ISOPROPYLL						
IDENEDIPHE						
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
4-4'-	25068-38-6	Rainbow Trout	Estimated	96 hours	LC50	2 mg/l
ISOPROPYLL						
IDENEDIPHE						
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
4-4'-	25068-38-6	Water flea	Estimated	48 hours	EC50	1.8 mg/l
ISOPROPYLL						
IDENEDIPHE						
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
4-4'-	25068-38-6	Green algae	Estimated	72 hours	NOEC	4.2 mg/l
ISOPROPYLL						
IDENEDIPHE						
NOL-						

EDIGITAL ADA	I	1	I	1	1	1
EPICHOLORO						
HYDRIN						
POLYMER						
4-4'-	25068-38-6	Water flea	Estimated	21 days	NOEC	0.3 mg/l
ISOPROPYLL						
IDENEDIPHE						
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
CALCIUM	471-34-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
CARBONATE	7/1-34-1	Green argae	Experimental	/2 Hours	LC30	2 100 mg/1
CALCIUM	471-34-1	Rainbow Trout	Evnorimental	96 hours	LC50	>100 mg/l
CARBONATE	4/1-34-1	Kambow Hout	Experimental	96 Hours	LC30	~ 100 mg/1
	471 24 1	W d	F ' / 1	40.1	IEC50	> 100 //
CALCIUM	471-34-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
CARBONATE						
CALCIUM	471-34-1	Green algae	Experimental	72 hours	EC10	100 mg/l
CARBONATE						
SYNTHETIC	Trade Secret	N/A	Data not	N/A	N/A	N/A
POLYMER			available or			
			insufficient for			
			classification			
DICYANDIA	461-58-5	Bluegill	Experimental	96 hours	LC50	>1,000 mg/l
MIDE			1			
DICYANDIA	461-58-5	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
MIDE	.01 00 0	oreen ungue	Z.ip erimenum	72 110 0115		1,000 mg/1
DICYANDIA	461-58-5	Water flea	Experimental	48 hours	EC50	3,177 mg/l
MIDE	1401 30 3	vv ater frea	Experimental	40 Hours	Leso	3,1 / / Hig/1
DICYANDIA	461-58-5	Green algae	Experimental	72 hours	NOEC	310 mg/l
MIDE	401-30-3	Green argae	Experimental	/2 Hours	NOLC	310 mg/1
	461 50 5	W-4 O	F	21 1	NOEC	25 /1
DICYANDIA	461-58-5	Water flea	Experimental	21 days	NOEC	25 mg/l
MIDE	144 50 5	ļ .			1.050	2.200 11 17
DICYANDIA	461-58-5	Redworm	Experimental	14 days	LC50	>3,200 mg/kg (Dry
MIDE						Weight)

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
4-4'-	25068-38-6	Estimated	28 days	Biological	5 %BOD/COD	OECD 301F -
ISOPROPYLL		Biodegradation		Oxygen		Manometric Respiro
IDENEDIPHE				Demand		
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
4-4'-	25068-38-6	Estimated		Hydrolytic	117 hours (t	
ISOPROPYLL		Hydrolysis		half-life	1/2)	
IDENEDIPHE						
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
CALCIUM	471-34-1	Data not	N/A	N/A	N/A	N/A
CARBONATE		availbl-				
		insufficient				

SYNTHETIC POLYMER	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
DICYANDIA MIDE	461-58-5	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	1	OECD 301E - Modif. OECD Screen
DICYANDIA MIDE	461-58-5	Experimental Aquatic Inherent Biodegrad.	14 days		0 %removal of DOC	OECD 302B Zahn- Wellens/EVPA
DICYANDIA MIDE	461-58-5	Experimental Biodegradation	61 days	Carbon dioxide evolution	1.1 %CO2 evolution/THC O2 evolution	OECD 309 Aero Sim Biod Water

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
4-4'-	25068-38-6	Estimated		Log of	3.242	
ISOPROPYLL		Bioconcentrati		Octanol/H2O		
IDENEDIPHE		on		part. coeff		
NOL-						
EPICHOLORO						
HYDRIN						
POLYMER						
CALCIUM	471-34-1	Data not	N/A	N/A	N/A	N/A
CARBONATE		available or				
		insufficient for				
		classification				
SYNTHETIC	Trade Secret	Data not	N/A	N/A	N/A	N/A
POLYMER		available or				
		insufficient for				
		classification				
DICYANDIA	461-58-5	Experimental	42 days	Bioaccumulatio	<=3.1	OECD305-
MIDE		BCF - Fish		n Factor		Bioconcentration
DICYANDIA	461-58-5	Experimental		Log of	-0.52	OECD 107 log Kow
MIDE		Bioconcentrati		Octanol/H2O		shke flsk mtd
		on		part. coeff		

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number: UN3077

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Technical Name: (Epoxy Resin) Hazard Class/Division: 9 Subsidiary Risk: None assigned.

Packing Group:III

Limited Quantity: None assigned. Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number: UN3077

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

Technical Name: (Epoxy Resin) Hazard Class/Division: 9 Subsidiary Risk: None assigned.

Packing Group:III

Limited Quantity: None assigned. **Marine Pollutant:** None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

Structural Sealing Tape #5230 #5231 #5232	
2M Molovsio SDSs are available at yaway 2M com my	
3M Malaysia SDSs are available at www.3M.com.my	

Page: 13 of 13