



## Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	08-6252-4	<b>Version Number:</b>	6.00
<b>Issue Date:</b>	29/12/2023	<b>Supersedes Date:</b>	20/12/2018

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810 Tan and Low Odor Acrylic Adhesive 810 Tan, Part A

#### Product Identification Numbers

62-3398-8530-3      62-3398-8730-9

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive

For Industrial or Professional use only

#### 1.3. Supplier's details

**ADDRESS:** 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301  
Petaling, Jaya, Selangor  
**Telephone:** 03-7884 2888  
**E Mail:** 3mmyehsr@mmm.com  
**Website:** www.3M.com.my

#### 1.4. Emergency telephone number

+60 03-7884 2888

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 2.

Chronic Aquatic Toxicity: Category 2.

#### 2.2. Label elements

##### Signal word

Danger

## Symbols

Corrosion | Exclamation mark | Health Hazard | Environment |

## Pictograms



## Hazard Statements:

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system   respiratory system.
H411	Toxic to aquatic life with long lasting effects.

## Precautionary statements

### Prevention:

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P273	Avoid release to the environment.
P280B	Wear protective gloves and eye/face protection.

### Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

### Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

## 2.3. Other hazards

None known

## SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Phenoxyethyl Methacrylate	10595-06-9	10 - 40
Hydroxypropyl Methacrylate	27813-02-1	10 - 30
2-Hydroxyethyl Methacrylate	868-77-9	10 - 30
Acrylate Oligomer	41637-38-1	5 - 20
Acrylonitrile-Butadiene Polymer	9010-81-5	5 - 20
Cumene Hydroperoxide	80-15-9	1 - 5
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	< 1
Cumene	98-82-8	< 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide

Carbon dioxide

Oxides of Nitrogen

Toxic Vapor, Gas, Particulate

#### Condition

During Combustion

During Combustion

During Combustion

During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Cumene	98-82-8	ACGIH	TWA:5 ppm	A3: Confirmed animal carcin.
Cumene	98-82-8	Malaysia OELs	TWA(8 hours):246 mg/m <sup>3</sup> (50 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid
<b>Specific Physical Form:</b>	Paste
<b>Color</b>	White
<b>Odor</b>	Low Odor
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>Not Applicable</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	$\geq 102.8$ °C
<b>Flash Point</b>	102.2 °C [ <i>Test Method: Closed Cup</i> ]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	$\leq 13.3$ Pa
<b>Vapor Density and/or Relative Vapor Density</b>	<i>Not Applicable</i>
<b>Density</b>	1.07 g/ml
<b>Relative Density</b>	1.07 [ <i>Ref Std: WATER=1</i> ]
<b>Water solubility</b>	Slight (less than 10%)
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity/Kinematic Viscosity</b>	20,000 mPa-s
<b>Volatile Organic Compounds</b>	<i>No Data Available</i>
<b>Percent volatile</b>	<i>No Data Available</i>
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	3.1 g/l [ <i>Details: when used as intended with Part B</i> ]
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	0.3 % [ <i>Details: when used as intended with Part B</i> ]
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	349 g/l [ <i>Test Method: tested per EPA method 24</i> ] [ <i>Details: as supplied</i> ]

Molecular weight

No Data Available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization may occur.

**10.4. Conditions to avoid**

Heat  
Sparks and/or flames  
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

**10.5. Incompatible materials**

Amines  
Reducing agents  
Reactive metals

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Prolonged or repeated exposure may cause target organ effects:

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Phenoxyethyl Methacrylate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Phenoxyethyl Methacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Acrylonitrile-Butadiene Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile-Butadiene Polymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Hydroxypropyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxypropyl Methacrylate	Ingestion	Rat	LD50 > 11,200 mg/kg
Acrylate Oligomer	Dermal	Rat	LD50 > 2,000 mg/kg
Acrylate Oligomer	Ingestion	Rat	LD50 > 2,000 mg/kg
Cumene Hydroperoxide	Dermal	Rat	LD50 500 mg/kg
Cumene Hydroperoxide	Inhalation-Vapor (4 hours)	Rat	LC50 1.4 mg/l
Cumene Hydroperoxide	Ingestion	Rat	LD50 382 mg/kg
Cumene	Dermal	Rabbit	LD50 > 3,160 mg/kg
Cumene	Inhalation-Vapor (4 hours)	Rat	LC50 39.4 mg/l
Cumene	Ingestion	Rat	LD50 1,400 mg/kg

2,2'-Methylenebis[6-tert-butyl-p-cresol]	Dermal	Rabbit	LD50 > 10,000 mg/kg
2,2'-Methylenebis[6-tert-butyl-p-cresol]	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Phenoxyethyl Methacrylate	similar compounds	Irritant
2-Hydroxyethyl Methacrylate	Rabbit	Minimal irritation
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Minimal irritation
Acrylate Oligomer	In vitro data	No significant irritation
Cumene Hydroperoxide	official classification	Corrosive
Cumene	Rabbit	Minimal irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Phenoxyethyl Methacrylate	similar compounds	Severe irritant
2-Hydroxyethyl Methacrylate	Rabbit	Moderate irritant
Acrylonitrile-Butadiene Polymer	Professional judgement	No significant irritation
Hydroxypropyl Methacrylate	Rabbit	Moderate irritant
Acrylate Oligomer	In vitro data	No significant irritation
Cumene Hydroperoxide	official classification	Corrosive
Cumene	Rabbit	Mild irritant

### Sensitization:

#### Skin Sensitization

Name	Species	Value
2-Hydroxyethyl Methacrylate	Human and animal	Sensitizing
Hydroxypropyl Methacrylate	Human and animal	Sensitizing
Acrylate Oligomer	Multiple animal species	Not classified
Cumene	Guinea pig	Not classified

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity



Name	Route	Value
Phenoxyethyl Methacrylate	In Vitro	Not mutagenic
2-Hydroxyethyl Methacrylate	In vivo	Not mutagenic
2-Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydroxypropyl Methacrylate	In vivo	Not mutagenic
Hydroxypropyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Acrylate Oligomer	In Vitro	Not mutagenic
Cumene Hydroperoxide	In vivo	Not mutagenic
Cumene Hydroperoxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cumene	In Vitro	Not mutagenic
Cumene	In vivo	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
Cumene	Inhalation	Multiple animal species	Carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-Hydroxyethyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Hydroxypropyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Hydroxypropyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxypropyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Acrylate Oligomer	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Acrylate Oligomer	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Acrylate Oligomer	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Cumene	Inhalation	Not classified for development	Rabbit	NOAEL 11.3 mg/l	during organogenesis
2,2'-Methylenebis[6-tert-butyl-p-cresol]	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	premating & during gestation
2,2'-Methylenebis[6-tert-butyl-p-cresol]	Ingestion	Toxic to male reproduction	Rat	NOAEL 12.5 mg/kg/day	50 days

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810 Tan and Low Odor Acrylic Adhesive 810 Tan, Part A**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydroxypropyl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Cumene Hydroperoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Cumene Hydroperoxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Cumene Hydroperoxide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Cumene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
Cumene	Inhalation	respiratory irritation	May cause respiratory irritation	Human	LOAEL 0.2 mg/l	occupational exposure
Cumene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydroxypropyl Methacrylate	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
Hydroxypropyl Methacrylate	Ingestion	hematopoietic system   heart   endocrine system   liver   immune system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Acrylate Oligomer	Ingestion	hematopoietic system   liver   immune system   kidney and/or bladder   endocrine system   eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Cumene Hydroperoxide	Inhalation	nervous system   respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	7 days
Cumene Hydroperoxide	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	90 days
Cumene	Inhalation	auditory system   endocrine system   hematopoietic system   liver   nervous system   eyes	Not classified	Rat	NOAEL 59 mg/l	13 weeks
Cumene	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4.9 mg/l	13 weeks
Cumene	Inhalation	respiratory system	Not classified	Rat	NOAEL 59 mg/l	13 weeks
Cumene	Ingestion	kidney and/or bladder   heart   endocrine system   hematopoietic system   liver   respiratory system	Not classified	Rat	NOAEL 769 mg/kg/day	6 months

**Aspiration Hazard**

Name	Value
Cumene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

#### Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

#### Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Phenoxyethyl Methacrylate	10595-06-9	Activated sludge	Analogous Compound	3 hours	EC50	177 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Golden Orfe	Analogous Compound	96 hours	LC50	10 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Green algae	Analogous Compound	96 hours	ErC50	4.4 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Water flea	Analogous Compound	48 hours	EC50	1.21 mg/l
Phenoxyethyl Methacrylate	10595-06-9	Green algae	Analogous Compound	96 hours	ErC10	0.74 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	Fathead Minnow	Experimental	96 hours	LC50	227 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
2-Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Hydroxypropyl Methacrylate	27813-02-1	Bacteria	Experimental	N/A	EC10	1,140 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Golden Orfe	Experimental	48 hours	EC50	493 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Green algae	Experimental	72 hours	ErC50	>97.2 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Water flea	Experimental	48 hours	EC50	>143 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Green algae	Experimental	72 hours	NOEC	97.2 mg/l
Hydroxypropyl Methacrylate	27813-02-1	Water flea	Experimental	21 days	NOEC	45.2 mg/l
Acrylate Oligomer	41637-38-1	Activated sludge	Analogous Compound	3 hours	EC50	>1,000 mg/l
Acrylate Oligomer	41637-38-1	Green algae	Analogous	72 hours	No tox obs at lmt	>100 mg/l

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810 Tan and Low Odor Acrylic Adhesive 810 Tan, Part A**

			Compound		of water sol	
Acrylate Oligomer	41637-38-1	Rainbow Trout	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
Acrylate Oligomer	41637-38-1	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Acrylonitrile-Butadiene Polymer	9010-81-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Cumene Hydroperoxide	80-15-9	Bacteria	Experimental	18 hours	EC10	0.103 mg/l
Cumene Hydroperoxide	80-15-9	Green algae	Experimental	72 hours	EC50	3.1 mg/l
Cumene Hydroperoxide	80-15-9	Rainbow Trout	Experimental	96 hours	LC50	3.9 mg/l
Cumene Hydroperoxide	80-15-9	Water flea	Experimental	48 hours	EC50	18.84 mg/l
Cumene Hydroperoxide	80-15-9	Green algae	Experimental	72 hours	NOEC	1 mg/l
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	Green algae	Endpoint not reached	72 hours	EC50	>100 mg/l
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	Water flea	Endpoint not reached	48 hours	EC50	>100 mg/l
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	Medaka	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	Green algae	Experimental	72 hours	NOEC	1.3 mg/l
Cumene	98-82-8	Activated sludge	Experimental	3 hours	EC10	>2,000 mg/l
Cumene	98-82-8	Green algae	Experimental	72 hours	EC50	2.6 mg/l
Cumene	98-82-8	Mysid Shrimp	Experimental	96 hours	EC50	1.2 mg/l
Cumene	98-82-8	Rainbow Trout	Experimental	96 hours	LC50	2.7 mg/l
Cumene	98-82-8	Water flea	Experimental	48 hours	EC50	2.14 mg/l
Cumene	98-82-8	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
Cumene	98-82-8	Water flea	Experimental	21 days	NOEC	0.35 mg/l

**12.2. Persistence and degradability**

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Phenoxyethyl Methacrylate	10595-06-9	Analogous Compound Biodegradation	28 days	Biological Oxygen Demand	22.3 %BOD/ThOD	OECD 301D - Closed Bottle Test
Phenoxyethyl Methacrylate	10595-06-9	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	1 years (t 1/2)	OECD 111 Hydrolysis func of pH
2-Hydroxyethyl Methacrylate	868-77-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	84 %BOD/COD	OECD 301D - Closed Bottle Test
2-Hydroxyethyl Methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
Hydroxypropyl Methacrylate	27813-02-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	81 %BOD/ThOD	OECD 301C - MITI (I)
Acrylate Oligomer	41637-38-1	Experimental Biodegradation	28 days	Biological Oxygen Demand	24 %BOD/ThOD	OECD 301D - Closed Bottle Test
Acrylonitrile-Butadiene Polymer	9010-81-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Cumene Hydroperoxide	80-15-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	0 %BOD/ThOD	OECD 301C - MITI (I)
2,2'-	119-47-1	Experimental	28 days	Biological Oxygen	0 %BOD/ThOD	OECD 301C - MITI (I)

Methylenebis[6-tert-butyl-p-cresol]		Biodegradation		Demand		
Cumene	98-82-8	Experimental Biodegradation	14 days	Biological Oxygen Demand	33 %BOD/ThOD	OECD 301C - MITI (I)
Cumene	98-82-8	Experimental Photolysis		Photolytic half-life (in air)	4.5 days (t 1/2)	

### 12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Phenoxyethyl Methacrylate	10595-06-9	Modeled Bioconcentration		Bioaccumulation Factor	5.8	Catalogic™
Phenoxyethyl Methacrylate	10595-06-9	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3.137	OECD 117 log Kow HPLC method
2-Hydroxyethyl Methacrylate	868-77-9	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.42	OECD 107 log Kow shke flask mtd
Hydroxypropyl Methacrylate	27813-02-1	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.97	EC A.8 Partition Coefficient
Acrylate Oligomer	41637-38-1	Modeled Bioconcentration		Bioaccumulation Factor	7	
Acrylate Oligomer	41637-38-1	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	≥4.66	OECD 117 log Kow HPLC method
Acrylonitrile-Butadiene Polymer	9010-81-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Cumene Hydroperoxide	80-15-9	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	1.82	
2,2'-Methylenebis[6-tert-butyl-p-cresol]	119-47-1	Experimental BCF - Fish	60 days	Bioaccumulation Factor	840	OECD305-Bioconcentration
Cumene	98-82-8	Modeled Bioconcentration		Bioaccumulation Factor	140	Catalogic™
Cumene	98-82-8	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	3.55	OECD 107 log Kow shke flask mtd

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

## SECTION 14: Transport Information

### Marine Transport (IMDG)

**UN Number:**None assigned.

**Proper Shipping Name:**None assigned.

**Technical Name:**None assigned.  
**Hazard Class/Division:**None assigned.  
**Subsidiary Risk:**None assigned.  
**Packing Group:**None assigned.  
**Limited Quantity:**None assigned.  
**Marine Pollutant:** None assigned.  
**Marine Pollutant Technical Name:** None assigned.  
**Other Dangerous Goods Descriptions:**  
Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

#### **Air Transport (IATA)**

**UN Number:**None assigned.  
**Proper Shipping Name:**None assigned.  
**Technical Name:**None assigned.  
**Hazard Class/Division:**None assigned.  
**Subsidiary Risk:**None assigned.  
**Packing Group:**None assigned.  
**Limited Quantity:**None assigned.  
**Marine Pollutant:** None assigned.  
**Marine Pollutant Technical Name:** None assigned.  
**Other Dangerous Goods Descriptions:**  
Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## **SECTION 16: Other information**

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume

tracking, and potential substance registration/notification.

**3M Malaysia SDSs are available at [www.3M.com.my](http://www.3M.com.my)**