



## Safety Data Sheet

Copyright,2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	37-5794-5	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	26/04/2023	<b>Supersedes Date:</b>	20/05/2018

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Screen Print UV Matte Clear 9800M

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Experimental use only

#### 1.3. Supplier's details

**ADDRESS:** 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301  
Petaling, Jaya, Selangor  
**Telephone:** 03-7884 2888  
**E Mail:** 3mmyehsr@mmm.com  
**Website:** www.3M.com.my

#### 1.4. Emergency telephone number

+60 03-7884 2888

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 2.

Chronic Aquatic Toxicity: Category 2.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |Health Hazard |Environment |

##### Pictograms

**Hazard Statements:**

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements****Prevention:**

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P273	Avoid release to the environment.
P280E	Wear protective gloves.
P281	Use personal protective equipment as required.

**Response:**

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

**Disposal:**

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

**2.3. Other hazards**

None known

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
POLYPROPYLENE	9003-07-0	15 - 30
Urethane Acrylate	Trade Secret	15 - 30
Hexanedioic acid, polymer with 2,2-dimethyl-1,3-propanediol, 2-hydroxyethyl 2-propenoate and 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane	70766-56-2	10 - 20
PHENOXY ETHYL ACRYLATE	48145-04-6	5 - 15
VINYLCAPROLACTAM	2235-00-9	5 - 10
1,6-hexanediol diacrylate	13048-33-4	1 - 5
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	7473-98-5	1 - 5
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	1 - 5

DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	1 - 5
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	28961-43-5	1 - 5
Acrylic Copolymer	Trade Secret	1 - 5
Oligo[2-Hydroxy-2-methyl-1-[4(1-methyl-vinyl)phenyl]propanone	Trade Secret	1 - 5
Silicone Defoamer	Trade Secret	0.5 - 1.5
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	52408-84-1	< 0.5
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	82919-37-7	< 0.5
Polyol Acrylate	Trade Secret	< 0.5

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide

#### Condition

During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid breathing of vapors created during cure cycle. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
VINYLCAPROLACTAM	2235-00-9	Manufacturer determined	TWA(8 hours):0.1 ppm(0.57 mg/m3)	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Color</b>	Colorless
<b>Odor</b>	Mild Acrylic, Sweet Acrylic
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>Not Applicable</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	>=149 °C
<b>Flash Point</b>	>=93.9 °C [ <i>Test Method:Pensky-Martens Closed Cup</i> ]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>No Data Available</i>
<b>Flammable Limits(UEL)</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density and/or Relative Vapor Density</b>	<i>No Data Available</i>
<b>Density</b>	1.02 g/ml
<b>Relative Density</b>	1.02 [ <i>Ref Std:WATER=1</i> ]
<b>Water solubility</b>	<i>No Data Available</i>
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>

Viscosity/Kinematic Viscosity	No Data Available
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	< 11 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

Light

Sparks and/or flames

### 10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

Reducing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.  
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

#### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

##### Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Dermal Effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
POLYPROPYLENE	Dermal		LD50 estimated to be > 5,000 mg/kg
POLYPROPYLENE	Ingestion	Mouse	LD50 > 8,000 mg/kg
PHENOXY ETHYL ACRYLATE	Dermal	Rat	LD50 > 2,000 mg/kg
PHENOXY ETHYL ACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
VINYLCAPROLACTAM	Dermal	Rabbit	LD50 1,700 mg/kg
VINYLCAPROLACTAM	Ingestion	Rat	LD50 1,049 mg/kg
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Ingestion	Rat	LD50 1,860 mg/kg
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Dermal	Rabbit	LD50 > 13,200 mg/kg
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg
1,6-hexanediol diacrylate	Dermal	Rabbit	LD50 3,636 mg/kg
1,6-hexanediol diacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Ingestion	Rat	LD50 3,125 mg/kg
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	Dermal	Rat	LD50 6,929 mg/kg
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	Ingestion	Rat	LD50 1,694 mg/kg
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Ingestion	Rat	LD50 3,125 mg/kg

.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Dermal	Rabbit	LD50 > 2,000 mg/kg
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
POLYPROPYLENE	Human and animal	No significant irritation
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
VINYLCAPROLACTAM	Rabbit	Minimal irritation
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Rabbit	Irritant
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Rabbit	Minimal irritation
1,6-hexanediol diacrylate	Rabbit	Irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Rabbit	Minimal irritation
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	Rabbit	No significant irritation
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Rabbit	Minimal irritation
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
POLYPROPYLENE	Professional judgement	No significant irritation
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
VINYLCAPROLACTAM	Rabbit	Severe irritant
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Rabbit	Severe irritant
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Rabbit	Severe irritant
1,6-hexanediol diacrylate	Rabbit	Moderate irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Rabbit	Mild irritant
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	Rabbit	Mild irritant
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Rabbit	Mild irritant
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Rabbit	Severe irritant

**Sensitization:****Skin Sensitization**

Name	Species	Value
POLYPROPYLENE	Human and animal	Not classified
PHENOXY ETHYL ACRYLATE	Guinea pig	Sensitizing
VINYLCAPROLACTAM	Mouse	Sensitizing
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Guinea pig	Sensitizing
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Guinea pig	Sensitizing
1,6-hexanediol diacrylate	Guinea pig	Sensitizing
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Guinea pig	Sensitizing
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Guinea pig	Sensitizing



.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Mouse	Sensitizing
---	-------	-------------

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
POLYPROPYLENE	In Vitro	Not mutagenic
VINYLCAPROLACTAM	In Vitro	Not mutagenic
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	In vivo	Not mutagenic
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,6-hexanediol diacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	In vivo	Not mutagenic
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	In Vitro	Some positive data exist, but the data are not sufficient for classification
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	In vivo	Not mutagenic
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
POLYPROPYLENE	Not Specified	Rat	Some positive data exist, but the data are not sufficient for classification
1,6-hexanediol diacrylate	Dermal	Mouse	Not carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
PHENOXY ETHYL ACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 800 mg/kg/day	43 days
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to development	Rat	NOAEL 300 mg/kg/day	premating into lactation
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
1,6-hexanediol diacrylate	Not Specified	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	premating into lactation
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Ingestion	Toxic to female reproduction	Rat	NOAEL 804 mg/kg/day	premating into lactation
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,493 mg/kg/day	29 days
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Ingestion	Not classified for development	Rat	NOAEL 209 mg/kg/day	premating into lactation
METHYL 1,2,2,6,6-PENTAMETHYL-4-	Ingestion	Toxic to female reproduction	Rat	NOAEL 804	premating

PIPERIDINYL SEBACATE				mg/kg/day	into lactation
----------------------	--	--	--	-----------	----------------

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
VINYLCAPROLACTAM	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
1,6-hexanediol diacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
VINYLCAPROLACTAM	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.001 mg/l	28 days
VINYLCAPROLACTAM	Inhalation	blood   liver   kidney and/or bladder   eyes	Not classified	Rat	NOAEL 0.18 mg/l	90 days
VINYLCAPROLACTAM	Ingestion	liver	Not classified	Rat	NOAEL 260 mg/kg/day	3 months
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Ingestion	endocrine system   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
1,6-hexanediol diacrylate	Dermal	skin	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 70 mg/kg/day	80 weeks
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Ingestion	gastrointestinal tract   liver   immune system   heart   endocrine system   hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Ingestion	eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	28 days
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	Ingestion	gastrointestinal tract   liver   immune system   heart   endocrine system   hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 1,493 mg/kg/day	29 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

#### Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

#### Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
POLYPROPYLENE	9003-07-0	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hexanedioic acid, polymer with 2,2-dimethyl-1,3-propanediol, 2-hydroxyethyl 2-propenoate and 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane	70766-56-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
PHENOXY ETHYL ACRYLATE	48145-04-6	Activated sludge	Experimental	3 hours	EC50	177 mg/l
PHENOXY ETHYL ACRYLATE	48145-04-6	Golden Orfe	Experimental	96 hours	LC50	10 mg/l
PHENOXY ETHYL ACRYLATE	48145-04-6	Green algae	Experimental	72 hours	EC50	4.4 mg/l
PHENOXY ETHYL ACRYLATE	48145-04-6	Water flea	Experimental	48 hours	EC50	1.21 mg/l
PHENOXY ETHYL ACRYLATE	48145-04-6	Green algae	Experimental	72 hours	EC10	0.71 mg/l
VINYLCAPROLACTAM	2235-00-9	Bacteria	Experimental	17 hours	EC50	622 mg/l
VINYLCAPROLACTAM	2235-00-9	Green algae	Experimental	72 hours	ErC50	>100 mg/l
VINYLCAPROLACTAM	2235-00-9	Water flea	Experimental	48 hours	EC50	>100 mg/l
VINYLCAPROLACTAM	2235-00-9	Zebra Fish	Experimental	96 hours	LC50	307 mg/l
VINYLCAPROLACTAM	2235-00-9	Green algae	Experimental	72 hours	NOEC	25 mg/l

**3M™ Screen Print UV Matte Clear 9800M**

1,6-hexanediol diacrylate	13048-33-4	Green algae	Experimental	72 hours	EC50	2.33 mg/l
1,6-hexanediol diacrylate	13048-33-4	Medaka	Experimental	96 hours	LC50	0.38 mg/l
1,6-hexanediol diacrylate	13048-33-4	Water flea	Experimental	48 hours	EC50	2.7 mg/l
1,6-hexanediol diacrylate	13048-33-4	Green algae	Experimental	72 hours	NOEC	0.9 mg/l
1,6-hexanediol diacrylate	13048-33-4	Medaka	Experimental	39 days	NOEC	0.072 mg/l
1,6-hexanediol diacrylate	13048-33-4	Water flea	Experimental	21 days	NOEC	0.14 mg/l
1,6-hexanediol diacrylate	13048-33-4	Activated sludge	Experimental	30 minutes	EC50	270 mg/l
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	7473-98-5	Activated sludge	Experimental	180 minutes	EC50	>1,000 mg/l
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	7473-98-5	Green algae	Experimental	72 hours	ErC50	1.95 mg/l
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	7473-98-5	Water flea	Experimental	48 hours	EC50	>119 mg/l
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	7473-98-5	Green algae	Experimental	72 hours	NOEC	0.194 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Green algae	Analogous Compound	72 hours	ErC50	1.68 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Water flea	Analogous Compound	24 hours	EC50	20 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Zebra Fish	Analogous Compound	96 hours	LC50	0.9 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Green algae	Analogous Compound	72 hours	ErC10	0.34 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Water flea	Analogous Compound	21 days	NOEC	1 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Activated sludge	Analogous Compound	3 hours	IC50	>=100 mg/l
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	Activated sludge	Experimental	3 hours	EC50	770 mg/l
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	Golden Orfe	Experimental	96 hours	LC50	10 mg/l
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	Green algae	Experimental	72 hours	EC50	3.2 mg/l
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	Water flea	Experimental	48 hours	EC50	10.56 mg/l

ETHER ACRYLATE						
TRIMETHYLOLP ROPANE ETHOXYLATE TRIACRYLATE	28961-43-5	Activated sludge	Experimental	3 hours	EC20	292 mg/l
TRIMETHYLOLP ROPANE ETHOXYLATE TRIACRYLATE	28961-43-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
.ALPHA.,.ALPHA. ,.ALPHA."-1,2,3- PROPANETRIYL TRIS[POLYPROP YLENE GLYCOL ACRYLATE]	52408-84-1	Activated sludge	Experimental	3 hours	EC20	507 mg/l
.ALPHA.,.ALPHA. ,.ALPHA."-1,2,3- PROPANETRIYL TRIS[POLYPROP YLENE GLYCOL ACRYLATE]	52408-84-1	Green algae	Experimental	72 hours	ErC50	12.2 mg/l
.ALPHA.,.ALPHA. ,.ALPHA."-1,2,3- PROPANETRIYL TRIS[POLYPROP YLENE GLYCOL ACRYLATE]	52408-84-1	Water flea	Experimental	48 hours	EC50	91.4 mg/l
.ALPHA.,.ALPHA. ,.ALPHA."-1,2,3- PROPANETRIYL TRIS[POLYPROP YLENE GLYCOL ACRYLATE]	52408-84-1	Zebra Fish	Experimental	96 hours	LC50	5.74 mg/l
.ALPHA.,.ALPHA. ,.ALPHA."-1,2,3- PROPANETRIYL TRIS[POLYPROP YLENE GLYCOL ACRYLATE]	52408-84-1	Green algae	Experimental	72 hours	NOEC	0.921 mg/l
METHYL 1,2,2,6,6- PENTAMETHYL- 4-PIPERIDINYL SEBACATE	82919-37-7	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
METHYL 1,2,2,6,6- PENTAMETHYL- 4-PIPERIDINYL SEBACATE	82919-37-7	Algae or other aquatic plants	Estimated	72 hours	EC50	1.68 mg/l
METHYL 1,2,2,6,6- PENTAMETHYL- 4-PIPERIDINYL SEBACATE	82919-37-7	Water flea	Estimated	24 hours	EC50	20 mg/l
METHYL 1,2,2,6,6- PENTAMETHYL- 4-PIPERIDINYL SEBACATE	82919-37-7	Zebra Fish	Estimated	96 hours	LC50	0.9 mg/l
METHYL 1,2,2,6,6- PENTAMETHYL- 4-PIPERIDINYL SEBACATE	82919-37-7	Water flea	Estimated	21 days	NOEC	1 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
POLYPROPYLENE	9003-07-0	Data not available - insufficient	N/A	N/A	N/A	N/A
Hexanedioic acid, polymer with 2,2-dimethyl-1,3-propanediol, 2-hydroxyethyl 2-propenoate and 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane	70766-56-2	Data not available - insufficient	N/A	N/A	N/A	N/A
PHENOXY ETHYL ACRYLATE	48145-04-6	Experimental Biodegradation	28 days	Biological Oxygen Demand	22.3 %BOD/ThOD	OECD 301D - Closed Bottle Test
PHENOXY ETHYL ACRYLATE	48145-04-6	Estimated Photolysis		Photolytic half-life (in air)	9.7 hours (t 1/2)	
VINYLCAPROLACTAM	2235-00-9	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	30-40 %removal of DOC	OECD 301A - DOC Die Away Test
VINYLCAPROLACTAM	2235-00-9	Experimental Biodegradation		Dissolv. Organic Carbon Deplet	98 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
VINYLCAPROLACTAM	2235-00-9	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
VINYLCAPROLACTAM	2235-00-9	Experimental Hydrolysis		Hydrolytic half-life acidic pH	6.5 hours (t 1/2)	OECD 111 Hydrolysis func of pH
1,6-hexanediol diacrylate	13048-33-4	Experimental Biodegradation	28 days	Carbon dioxide evolution	60-70 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
1,6-hexanediol diacrylate	13048-33-4	Estimated Photolysis		Photolytic half-life (in air)	1 days (t 1/2)	Episuite™
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	7473-98-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	90 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Modeled Biodegradation	28 days	Biological Oxygen Demand	27 %BOD/ThOD	Catalogic™
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Analogous Compound Hydrolysis		Hydrolytic half-life (pH 7)	68 days (t 1/2)	OECD 111 Hydrolysis func of pH
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	Experimental Biodegradation	28 days	Carbon dioxide evolution	98 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	28961-43-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	58-61 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
.ALPHA.,.ALPHA.,.ALPHA."-1,2,3-PROPANETRIYL TRIS[POLYPROPYLENE GLYCOL ACRYLATE]	52408-84-1	Experimental Biodegradation	28 days	Carbon dioxide evolution	72-85 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	82919-37-7	Estimated Biodegradation	28 days	Biological Oxygen Demand	51 %BOD/ThOD	

### 12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
POLYPROPYLENE	9003-07-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hexanedioic acid, polymer with 2,2-dimethyl-1,3-propanediol, 2-hydroxyethyl 2-propenoate and 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane	70766-56-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
PHENOXY ETHYL ACRYLATE	48145-04-6	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.58	
VINYLCAPROLACTAM	2235-00-9	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	1.2	similar to OECD 107
1,6-hexanediol diacrylate	13048-33-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.81	
2-HYDROXY-2-METHYL-1-PHENYL-1-PROPANONE	7473-98-5	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	1.62	OECD 107 log Kow shke flsk mtd
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Experimental BCF - Fish	56 days	Bioaccumulation Factor	<31.4	
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	41556-26-7	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.37	OECD 107 log Kow shke flsk mtd
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	1.105	
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	28961-43-5	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.89	OECD 107 log Kow shke flsk mtd
.ALPHA.,.ALPHA.,.ALPHA."-1,2,3-PROPANETRIYL TRIS[POLYPROPYLENE GLYCOL ACRYLATE]	52408-84-1	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.52	OECD 107 log Kow shke flsk mtd
METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL SEBACATE	82919-37-7	Estimated Bioconcentration		Bioaccumulation Factor	11	

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

## SECTION 14: Transport Information

### Marine Transport (IMDG)

**UN Number:**None assigned.

**Proper Shipping Name:**None assigned.

**Technical Name:**None assigned.

**Hazard Class/Division:**None assigned.

**Subsidiary Risk:**None assigned.

**Packing Group:**None assigned.

**Limited Quantity:**None assigned.

**Marine Pollutant:** None assigned.

**Marine Pollutant Technical Name:** None assigned.

**Other Dangerous Goods Descriptions:**

Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

### Air Transport (IATA)

**UN Number:**None assigned.

**Proper Shipping Name:**None assigned.

**Technical Name:**None assigned.

**Hazard Class/Division:**None assigned.

**Subsidiary Risk:**None assigned.

**Packing Group:**None assigned.

**Limited Quantity:**None assigned.

**Marine Pollutant:** None assigned.

**Marine Pollutant Technical Name:** None assigned.

**Other Dangerous Goods Descriptions:**

Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA.

## SECTION 16: Other information



DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

**3M Malaysia SDSs are available at [www.3M.com.my](http://www.3M.com.my)**