



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	39-3722-4	Version Number:	1.00
Issue Date:	07/06/2023	Supersedes Date:	Initial Issue

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Scratch Remover, 39044, 39044S, 39070

Product Identification Numbers

60-4550-5557-8 60-4550-6574-2

1.2. Recommended use and restrictions on use

Recommended use

Automotive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com

Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 3.

Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Flame |

Pictograms

**Hazard Statements:**

H226	Flammable liquid and vapor.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements**General:**

P102	Keep out of reach of children.
------	--------------------------------

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	---

Response:

P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.
-------------	---

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

Aspiration classification does not apply due to the viscosity of the product., Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70
Decamethylcyclopentasiloxane	541-02-6	< 10
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	< 7
Hydrotreated Light Petroleum Distillates	64742-47-8	< 6
Isopropyl Alcohol	67-63-0	< 6
Aluminum Oxide (non-fibrous)	1344-28-1	1 - 5
Dodecamethylcyclohexasiloxane	540-97-6	< 5
Kaolin, calcined	92704-41-1	1 - 5
Poly(Dimethylsiloxane)	63148-62-9	1 - 5
White Mineral Oil (Petroleum)	8042-47-5	0.5 - 1.5

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get

medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Hydrocarbons

Formaldehyde

Carbon monoxide

Carbon dioxide

Oxides of Nitrogen

Condition

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by

a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum Oxide (non-fibrous)	1344-28-1	Malaysia OELs	TWA (proposed)(8 hours):10 mg/m ³	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	1344-28-1	ACGIH	TWA(inhalable particulates):10 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	1344-28-1	ACGIH	TWA(respirable particles):3 mg/m ³	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m ³	A3: Confirmed animal carcin., SKIN
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
Isopropyl Alcohol	67-63-0	Malaysia OELs	TWA(8 hours):983 mg/m ³ (400 ppm)	
MINERAL OILS, HIGHLY-REFINED OILS	8042-47-5	ACGIH	TWA(inhalable fraction):5 mg/m ³	A4: Not class. as human carcin
OIL MIST, MINERAL	8042-47-5	Malaysia OELs	TWA(as mist)(8 hours):5 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Color	White
Odor	Slight Solvent
Odor threshold	No Data Available
pH	8
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	100 °C
Flash Point	43.9 - 45 °C [Test Method: Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	2,399.8 Pa [@ 20 °C]
Vapor Density and/or Relative Vapor Density	No Data Available
Density	1 - 1 kg/l
Relative Density	0.98 - 1 [Ref Std: WATER=1]
Water solubility	No Data Available
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	12,000 - 18,000 mPa-s [Test Method: Brookfield]
Volatile Organic Compounds	15.8 % weight [Test Method: calculated per CARB title 2]

Volatile Organic Compounds	164 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Percent volatile	81.7 % weight [<i>Test Method</i> :Estimated]
VOC Less H2O & Exempt Solvents	462 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

Heat

Light

10.5. Incompatible materials

Strong oxidizing agents

Strong acids

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Decamethylcyclopentasiloxane	Dermal	Rabbit	LD50 > 15,000 mg/kg
Decamethylcyclopentasiloxane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 8.7 mg/l
Decamethylcyclopentasiloxane	Ingestion	Rat	LD50 > 24,134 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Dermal	Rabbit	LD50 > 2,000 mg/kg
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2,000 mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 50,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Kaolin, calcined	Dermal	similar compounds	LD50 > 5,000 mg/kg
Kaolin, calcined	Ingestion	similar compounds	LD50 > 5,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Decamethylcyclopentasiloxane	Rabbit	No significant irritation
Isopropyl Alcohol	Multiple animal species	No significant irritation
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Professional judgement	Mild irritant
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Kaolin, calcined	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation

White Mineral Oil (Petroleum)	Rabbit	No significant irritation
-------------------------------	--------	---------------------------

Serious Eye Damage/Irritation

Name	Species	Value
Decamethylcyclpentasiloxane	Rabbit	No significant irritation
Isopropyl Alcohol	Rabbit	Severe irritant
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Professional judgement	Mild irritant
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Kaolin, calcined	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
White Mineral Oil (Petroleum)	Rabbit	Mild irritant

Sensitization:**Skin Sensitization**

Name	Species	Value
Decamethylcyclpentasiloxane	Mouse	Not classified
Isopropyl Alcohol	Guinea pig	Not classified
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Guinea pig	Not classified
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified
White Mineral Oil (Petroleum)	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Decamethylcyclpentasiloxane	In Vitro	Not mutagenic
Decamethylcyclpentasiloxane	In vivo	Not mutagenic
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	In Vitro	Not mutagenic
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Decamethylcyclpentasiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal	Not carcinogenic

		species	
--	--	---------	--

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Decamethylcyclpentasiloxane	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclpentasiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclpentasiloxane	Inhalation	Not classified for development	Rat	NOAEL 2.43 mg/l	2 generation
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
Dodecamethylcyclhexasiloxane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Dodecamethylcyclhexasiloxane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Dodecamethylcyclhexasiloxane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Notavailable	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Decamethylcyclopentasiloxane	Dermal	hematopoietic system eyes	Not classified	Rat	NOAEL 1,600 mg/kg/day	28 days
Decamethylcyclopentasiloxane	Inhalation	hematopoietic system respiratory system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 2.42 mg/l	2 years
Decamethylcyclopentasiloxane	Ingestion	liver immune system respiratory system heart hematopoietic system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
Dodecamethylcyclohexasiloxane	Ingestion	endocrine system liver respiratory system nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Aluminum Oxide (non-fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non-fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Kaolin, calcined	Inhalation	pneumoconiosis	Not classified	similar compounds	NOAEL not available	occupational exposure
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

Aspiration Hazard

Name	Value
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	Aspiration hazard
Hydrotreated Light Petroleum Distillates	Aspiration hazard
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Decamethylcyclotrisiloxane	541-02-6	Activated sludge	Experimental	3 hours	EC50	>2,000 mg/l
Decamethylcyclotrisiloxane	541-02-6	Green algae	Experimental	96 hours	ErC50	>100 mg/l
Decamethylcyclotrisiloxane	541-02-6	Rainbow Trout	Experimental	96 hours	LC50	>100 mg/l
Decamethylcyclotrisiloxane	541-02-6	Water flea	Experimental	48 hours	EC50	>100 mg/l
Decamethylcyclotrisiloxane	541-02-6	Green algae	Experimental	96 hours	NOEC	100 mg/l
Decamethylcyclotrisiloxane	541-02-6	Rainbow Trout	Experimental	90 days	NOEC	100 mg/l
Decamethylcyclotrisiloxane	541-02-6	Water flea	Experimental	21 days	NOEC	100 mg/l
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
Hydrotreated Light Petroleum Distillates	64742-47-8	Green algae	Estimated	72 hours	EC50	1 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Rainbow Trout	Estimated	96 hours	LL50	2 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Water flea	Estimated	48 hours	EL50	1.4 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Green algae	Estimated	72 hours	NOEL	1 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Water flea	Estimated	21 days	NOEL	0.48 mg/l
Isopropyl Alcohol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
Isopropyl Alcohol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	N/A	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l

Dodecamethylcycl ohexasiloxane	540-97-6	Activated sludge	Experimental	3 hours	EC50	>100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Green algae	Experimental	72 hours	EC50	>100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Fathead Minnow	Experimental	49 days	NOEC	100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Green algae	Experimental	72 hours	NOEC	100 mg/l
Dodecamethylcycl ohexasiloxane	540-97-6	Water flea	Experimental	21 days	NOEC	100 mg/l
Kaolin, calcined	92704-41-1	Bacteria	Estimated	16 hours	EC10	1,400 mg/l
Kaolin, calcined	92704-41-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Poly(Dimethylsilox ane)	63148-62-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Decamethylcyclope ntasiloxane	541-02-6	Experimental Biodegradation	28 days	Carbon dioxide evolution	0.14 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
Decamethylcyclope ntasiloxane	541-02-6	Experimental Photolysis		Photolytic half-life (in air)	20.4 days (t 1/2)	
Decamethylcyclope ntasiloxane	541-02-6	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	66 days (t 1/2)	
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Isopropyl Alcohol	67-63-0	Experimental Biodegradation	14 days	Biological Oxygen Demand	86 %BOD/ThOD	OECD 301C - MITI (I)
Aluminum Oxide (non-fibrous)	1344-28-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Dodecamethylcycl ohexasiloxane	540-97-6	Experimental Biodegradation	28 days	Carbon dioxide evolution	4.47 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
Kaolin, calcined	92704-41-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Poly(Dimethylsilox ane)	63148-62-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A
White Mineral Oil (Petroleum)	8042-47-5	Experimental Biodegradation	28 days	Carbon dioxide evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Decamethylcyclope	541-02-6	Experimental BCF	35 days	Bioaccumulation	7060	OECD305-Bioconcentration

ntasiloxane		- Fish		Factor		
Decamethylcyclotetrasiloxane	541-02-6	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	8.03	
DISTILLATES (PETROLEUM), ACID TREATED, LIGHT	64742-14-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Isopropyl Alcohol	67-63-0	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	0.05	
Aluminum Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dodecamethylcyclotetrasiloxane	540-97-6	Experimental BCF - Fish	49 days	Bioaccumulation Factor	1160	OECD305-Bioconcentration
Kaolin, calcined	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly(Dimethylsiloxane)	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
White Mineral Oil (Petroleum)	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN1866

Proper Shipping Name:RESIN SOLUTION

Technical Name:None assigned.

Hazard Class/Division:3

Subsidiary Risk:None assigned.

Packing Group:III

Limited Quantity:Yes

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN1866
Proper Shipping Name:RESIN SOLUTION
Technical Name:None assigned.
Hazard Class/Division:3
Subsidiary Risk:None assigned.
Packing Group:III
Limited Quantity:None assigned.
Marine Pollutant: None assigned.
Marine Pollutant Technical Name: None assigned.
Other Dangerous Goods Descriptions:
None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my