

Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	33-9002-8	Version Number:	2.00
Issue Date:	15/07/2021	Supercedes Date:	22/03/2019

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

Scotchgard[™] Stainless Steel Cleaner

Product Identification Numbers

70-0052-6225-1 70-0070-2960-9

1.2. Recommended use and restrictions on use

Recommended use

Consumer use, Cleans stainless steel surfaces.

For Consumer Use

1.3. Supplier's details

ADDRESS:3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, SelangorTelephone:03-7884 2888E Mail:3mmyehsr@mmm.comWebsite:www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Aerosol: Category 1. Gas Under Pressure: Liquefied gas. Specific Target Organ Toxicity (single exposure): Category 2.

2.2. Label elements Signal word Danger

Symbols Flame |Gas cylinder |Health Hazard |

Pictograms



Hazard Statements:	E transla Communitation and
H222	Extremely flammable aerosol.
H280	Contains gas under pressure; may explode if heated.
H371	May cause damage to organs: cardiovascular system.
Precautionary statements	
General:	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
Prevention:	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
Storage:	
P403	Store in a well-ventilated place.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.
Disposal:	
P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Aspiration classification does not apply as this product is sold in sealed, self-pressurized containers with nozzles designed to prevent formation of a stream during usage.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70
White Mineral Oil (Petroleum)	8042-47-5	10 - 30
ISOBUTANE	75-28-5	< 10
Sorbitan Oleate	1338-43-8	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Wash with soap and water. If you feel unwell, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>			
Carbon monoxide			
Carbon dioxide			

<u>Condition</u> During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe

dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ISOBUTANE	75-28-5	ACGIH	STEL:1000 ppm	
MINERAL OILS, HIGHLY-	8042-47-5	ACGIH	TWA(inhalable fraction):5	A4: Not class. as human
REFINED OILS			mg/m3	carcin
OIL MIST, MINERAL	8042-47-5	Malaysia OELs	TWA(as mist)(8 hours):5	
		-	mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Specific Physical Form:	Aerosol	
x v		
Color	White	
Odor	Citrus	
Odor threshold	No Data Available	
рН	9 - 11	
Melting point/Freezing point	No Data Available	
Boiling point/Initial boiling point/Boiling range	> 100 °C	
Flash Point	No flash point	
Evaporation rate	No Data Available	
Flammability (solid, gas)	Not Applicable	
Flammable Limits(LEL)	No Data Available	
Flammable Limits(UEL)	No Data Available	
Vapor Pressure	No Data Available	
Vapor Density and/or Relative Vapor Density	No Data Available	
Density	Approximately 0.95 g/ml	
Relative Density	0.92 - 0.98 [<i>Ref Std</i> :WATER=1]	
Water solubility	Complete	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Viscosity/Kinematic Viscosity	< 4,500 mPa-s [Details:For Liquid]	
Volatile Organic Compounds	7.8 %	
Percent volatile	75 - 80 %	
VOC Less H2O & Exempt Solvents	No Data Available	
Average particle size	No Data Available	
Bulk density	No Data Available	
Molecular weight	No Data Available	
Softening point	No Data Available	

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents Strong acids

10.6. Hazardous decomposition products Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Single exposure may cause target organ effects:

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
ISOBUTANE	Inhalation-	Rat	LC50 276,000 ppm
	Gas (4		

	hours)		
Sorbitan Oleate	Dermal		LD50 estimated to be > 5,000 mg/kg
Sorbitan Oleate	Ingestion	Rat	LD50 > 39,800 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
White Mineral Oil (Petroleum)	Rabbit	No significant irritation
ISOBUTANE	Professio	No significant irritation
	nal	
	judgemen	
	t	

Serious Eye Damage/Irritation

Name	Species	Value
White Mineral Oil (Petroleum)	Rabbit	Mild irritant
ISOBUTANE	Professio	No significant irritation
	nal	
	judgemen	
	t	

Sensitization:

Skin Sensitization

Name	Species	Value
White Mineral Oil (Petroleum)	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic
ISOBUTANE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple animal	Not carcinogenic
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ISOBUTANE	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
ISOBUTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
ISOBUTANE	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
White Mineral Oil	Ingestion	hematopoietic	Not classified	Rat	NOAEL	90 days
(Petroleum)	_	system			1,381	-
		-			mg/kg/day	
White Mineral Oil	Ingestion	liver immune	Not classified	Rat	NOAEL	90 days
(Petroleum)	-	system			1,336	-
					mg/kg/day	
ISOBUTANE	Inhalation	kidney and/or	Not classified	Rat	NOAEL	13 weeks
		bladder			4,500 ppm	

Aspiration Hazard

Name	Value
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Туре	Exposure	Test Endpoint	Test Result
White Mineral	8042-47-5	Water flea	Estimated	48 hours	EL50	>100 mg/l
Oil (Petroleum)						
White Mineral	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
Oil (Petroleum)		_	_			_
White Mineral	8042-47-5	Green algae	Estimated	72 hours	NOEL	100 mg/l
Oil (Petroleum)						

White Mineral	8042-47-5	Water flea	Estimated	21 days	NOEL	>100 mg/l
Oil (Petroleum)						
ISOBUTANE	75-28-5		Data not			N/A
			available or			
			insufficient for			
			classification			
Sorbitan Oleate	1338-43-8	Rainbow Trout	Experimental	96 hours	LC50	>100 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
White Mineral	8042-47-5	Experimental	28 days	Carbon dioxide	0 % weight	OECD 301B - Mod.
Oil (Petroleum)		Biodegradation		evolution		Sturm or CO2
ISOBUTANE	75-28-5	Experimental		Photolytic half-	13.4 days (t	Non-standard method
		Photolysis		life (in air)	1/2)	
Sorbitan Oleate	1338-43-8	Estimated	28 days	Biological	68 % weight	OECD 301B - Mod.
		Biodegradation		Oxygen		Sturm or CO2
				Demand		

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
White Mineral	8042-47-5	Data not	N/A	N/A	N/A	N/A
Oil (Petroleum)		available or				
		insufficient for				
		classification				
ISOBUTANE	75-28-5	Experimental		Log of	2.76	Non-standard method
		Bioconcentrati		Octanol/H2O		
		on		part. coeff		
Sorbitan Oleate	1338-43-8	Estimated		Bioaccumulatio	7.8	Est: Bioconcentration
		Bioconcentrati		n Factor		factor
		on				

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

The surfactant(s) contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN1950 Proper Shipping Name:AEROSOLS, FLAMMABLE Technical Name:None assigned. Hazard Class/Division:2.1 Subsidiary Risk:None assigned. Packing Group:None assigned. Limited Quantity:Yes Marine Pollutant: None assigned. Marine Pollutant Technical Name: None assigned. Other Dangerous Goods Descriptions: None assigned.

Air Transport (IATA)

UN Number:UN1950 Proper Shipping Name:AEROSOLS, FLAMMABLE Technical Name:None assigned. Hazard Class/Division:2.1 Subsidiary Risk:None assigned. Packing Group:None assigned. Limited Quantity:None assigned. Marine Pollutant: None assigned. Marine Pollutant Technical Name: None assigned. Other Dangerous Goods Descriptions: None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use

(except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my