



Safety Data Sheet

© 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 16-3472-4 **Version number:** 4.00
Issue Date: 02/05/2021 **Supersedes date:** 08/09/2019

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M Super 77 Multipurpose Adhesive

Product Identification Numbers

62-4977-4930-9

1.2. Recommended use and restrictions on use

Recommended use

Adhesive aerosol., General Purpose Aerosol adhesive

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Flammable Aerosol: Category 1	2.1.2A Flammable Aerosol
Serious Eye Damage/Irritation: Category 2	6.4A Irritating to the eye
Skin Corrosion/Irritation: Category 3	6.3B Irritating to the skin
Reproductive Toxicity: Category 1B	6.8A Known/presumed human reproductive/developmental toxicant
Specific Target Organ Toxicity (single exposure):	6.9A Toxic to human target organs/systems

Category 1	
Specific Target Organ Toxicity (repeated exposure): Category 1	6.9A Toxic to human target organs/systems
Specific Target Organ Toxicity (single exposure): Category 3	6.9B Narcotic effects
Acute Aquatic Toxicity: Category 2	9.1D Aquatic toxicity (acute)

2.2. Label elements

SIGNAL WORD

DANGER!

Symbols:

Flame | Exclamation mark | Health Hazard |

Pictograms



HAZARD STATEMENTS:

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.
- H229 Pressurized container: may burst if heated.

- H319 Causes serious eye irritation.
- H316 Causes mild skin irritation.
- H360 May damage fertility or the unborn child.
- H336 May cause drowsiness or dizziness.

- H370 Causes damage to organs:
cardiovascular system |

- H372 Causes damage to organs through prolonged or repeated exposure:
nervous system |

- H401 Toxic to aquatic life.

PRECAUTIONARY STATEMENTS

Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251A Pressurized container: Do not pierce or burn, even after use.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280E Wear protective gloves.
- P270 Do not eat, drink or smoke when using this product.
- P264B Wash exposed skin thoroughly after handling.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical advice/attention.
 P332 + P313 If skin irritation occurs: Get medical advice/attention.
 P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P321 Specific treatment (see Notes to Physician on this label).

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50oC.
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

3M Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. Aspiration classification does not apply as this product is sold in sealed, self-pressurized containers with nozzles designed to prevent formation of a stream during usage. May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Acetone	67-64-1	20 - 30
Non-volatile components	Trade Secret	10 - 30
Propane	74-98-6	15 - 25
2-Methylpentane	107-83-5	5 - 20
Cyclohexane	110-82-7	5 - 15
Terpane Polymer	31393-98-3	1 - 10
Ethanol	64-17-5	< 4
Hexane	110-54-3	< 3
Pentane	109-66-0	< 2
Limestone	1317-65-3	< 1.5
Toluene	108-88-3	< 1
Methylene Chloride	75-09-2	< 0.01

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

5.4. Hazchem code: 2YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
2-Methylpentane	107-83-5	ACGIH	TWA:500 ppm;STEL:1000 ppm	
Hexane (isomers other than n-hexane)	107-83-5	New Zealand WES	TWA(8 hours): 1760 mg/m3 (500 ppm); STEL(15 minutes): 3500 mg/m3 (1000 ppm)	
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcinogen, Ototoxicant
Toluene	108-88-3	New Zealand WES	TWA(8 hours): 188 mg/m3 (50 ppm)	Skin
Pentane	109-66-0	ACGIH	TWA:1000 ppm	
Pentane	109-66-0	New Zealand WES	TWA(8 hours): 1770 mg/m3 (600 ppm); STEL(15 minutes): 2120 mg/m3 (750 ppm)	
Hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous absorption
Hexane	110-54-3	New Zealand WES	TWA(8 hours): 72 mg/m3 (20 ppm)	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	New Zealand WES	TWA(8 hours):350 mg/m3(100 ppm);STEL(15 minutes):1050 mg/m3(300 ppm)	
Limestone	1317-65-3	New Zealand WES	TWA(8 hours):10 ppm	
Ethanol	64-17-5	ACGIH	STEL:1000 ppm	A3: Confirmed animal carcinogen.
Ethanol	64-17-5	New Zealand WES	TWA(8 hours):1880 mg/m3(1000 ppm)	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcinogen

Acetone	67-64-1	New Zealand WES	TWA(8 hours):1185 mg/m ³ (500 ppm);STEL(15 minutes):2375 mg/m ³ (1000 ppm)	
Propane	74-98-6	ACGIH	Limit value not established:	asphyxiant
Propane	74-98-6	New Zealand WES	Limit value not established:	Explosion hazard - asphyxiant
Methylene Chloride	75-09-2	ACGIH	TWA:50 ppm	A3: Confirmed animal carcinogen.
Methylene Chloride	75-09-2	New Zealand WES	TWA(8 hours): 174 mg/m ³ (50 ppm)	Class-subclass 6.7, carc HCB

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator.

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid, aerosol
Specific Physical Form:	Aerosol
Colour	Colourless
Odour	Sweet Odour, Fruity Odour
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>Not applicable.</i>
Flash point	-41.1 °C [<i>Test Method: Tagliabue closed cup</i>]
Evaporation rate	1.9 [<i>Ref Std: ETHER=1</i>]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	[<i>Details: Compressed gas</i>] <i>Not applicable.</i>
Vapor Density and/or Relative Vapor Density	2.97 [<i>Ref Std: AIR=1</i>]
Density	0.726 g/ml
Relative density	0.726 [<i>Ref Std: WATER=1</i>]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>Not applicable.</i>
Viscosity/Kinematic Viscosity	<i>Not applicable.</i>
Volatile organic compounds (VOC)	
Percent volatile	
VOC less H ₂ O & exempt solvents	≤51 % [<i>Test Method: calculated per CARB title 2</i>]
Solids content	≥22.4 %

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:

Peripheral neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

This product contains ethanol. Alcoholic beverages and ethanol in alcoholic beverages have been classified by the International Agency for Research on Cancer as carcinogenic to humans. There are also data associating human consumption of alcoholic beverages with developmental toxicity and liver toxicity. Exposure to ethanol during the foreseeable use of this product is not expected to cause cancer, developmental toxicity, or liver toxicity.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
2-Methylpentane	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Methylpentane	Inhalation-Vapor		LC50 estimated to be > 50 mg/l
2-Methylpentane	Ingestion		LD50 estimated to be > 5,000 mg/kg
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg
Cyclohexane	Inhalation-Vapor (4 hours)	Rat	LC50 > 32.9 mg/l
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Non-volatile components	Dermal		LD50 estimated to be > 5,000 mg/kg
Non-volatile components	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Terpane Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Terpane Polymer	Ingestion	Rat	LD50 > 34,000 mg/kg
Ethanol	Dermal	Rabbit	LD50 > 15,800 mg/kg
Ethanol	Inhalation-Vapor (4 hours)	Rat	LC50 124.7 mg/l
Ethanol	Ingestion	Rat	LD50 17,800 mg/kg
Pentane	Dermal	Rabbit	LD50 3,000 mg/kg
Pentane	Inhalation-Vapor (4 hours)	Rat	LC50 > 18 mg/l
Pentane	Ingestion	Rat	LD50 > 2,000 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

3M Super 77 Multipurpose Adhesive

Methylene Chloride	Dermal	Rat	LD50 > 2,000 mg/kg
Methylene Chloride	Inhalation-Vapor (4 hours)	Rat	LC50 63.7 mg/l
Methylene Chloride	Ingestion	Rat	LD50 1,410 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Propane	Rabbit	Minimal irritation
Acetone	Mouse	Minimal irritation
2-Methylpentane	Professional judgement	Mild irritant
Cyclohexane	Rabbit	Mild irritant
Non-volatile components	Professional judgement	Minimal irritation
Ethanol	Rabbit	No significant irritation
Pentane	Rabbit	Minimal irritation
Hexane	Human and animal	Mild irritant
Limestone	Rabbit	No significant irritation
Toluene	Rabbit	Irritant
Methylene Chloride	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Propane	Rabbit	Mild irritant
Acetone	Rabbit	Severe irritant
2-Methylpentane	Professional judgement	Moderate irritant
Cyclohexane	Rabbit	Mild irritant
Ethanol	Rabbit	Severe irritant
Pentane	Rabbit	Mild irritant
Hexane	Rabbit	Mild irritant
Limestone	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant
Methylene Chloride	Rabbit	Severe irritant

Sensitisation:**Skin Sensitisation**

Name	Species	Value
Ethanol	Human	Not classified
Pentane	Guinea pig	Not classified
Hexane	Human	Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Propane	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not sufficient for classification
Ethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Ethanol	In vivo	Some positive data exist, but the data are not sufficient for classification
Pentane	In vivo	Not mutagenic
Pentane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Methylene Chloride	In vivo	Not mutagenic
Methylene Chloride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Acetone	Not specified.	Multiple animal species	Not carcinogenic
Ethanol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Methylene Chloride	Inhalation	Multiple animal species	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Ethanol	Inhalation	Not classified for development	Rat	NOAEL 38 mg/l	during gestation
Ethanol	Ingestion	Not classified for development	Rat	NOAEL	prematuring &

3M Super 77 Multipurpose Adhesive

				5,200 mg/kg/day	during gestation
Pentane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
Pentane	Inhalation	Not classified for development	Rat	NOAEL 30 mg/l	during organogenesis
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Methylene Chloride	Inhalation	Not classified for female reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for male reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for development	Multiple animal species	NOAEL 4.3 mg/l	during gestation

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
2-Methylpentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Methylpentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-Methylpentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	

3M Super 77 Multipurpose Adhesive

2-Methylpentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Ethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	LOAEL 9.4 mg/l	not available
Ethanol	Inhalation	central nervous system depression	Not classified	Human and animal	NOAEL not available	
Ethanol	Ingestion	central nervous system depression	Not classified	Multiple animal species	NOAEL not available	
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg	
Pentane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
Pentane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
Pentane	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL Not available	not available
Pentane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	not available
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Methylene Chloride	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours
Methylene Chloride	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Methylene Chloride	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methylene Chloride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
2-Methylpentane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 5.3 mg/l	14 weeks
2-Methylpentane	Ingestion	peripheral nervous system	Not classified	Rat	NOAEL Not available	8 weeks
2-Methylpentane	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,000 mg/kg	28 days
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Ethanol	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 124 mg/l	365 days
Ethanol	Inhalation	hematopoietic system immune system	Not classified	Rat	NOAEL 25 mg/l	14 days
Ethanol	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 8,000 mg/kg/day	4 months
Ethanol	Ingestion	kidney and/or bladder	Not classified	Dog	NOAEL 3,000 mg/kg/day	7 days
Pentane	Inhalation	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Pentane	Inhalation	heart skin endocrine system gastrointestinal tract	Not classified	Rat	NOAEL 20 mg/l	13 weeks

3M Super 77 Multipurpose Adhesive

		bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system				
Pentane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days
Hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
Hexane	Inhalation	auditory system immune system eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart skin endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system hematopoietic system liver immune system kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500	13 weeks

3M Super 77 Multipurpose Adhesive

					mg/kg/day	
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Methylene Chloride	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 6.95 mg/l	2 years
Methylene Chloride	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.17 mg/l	2 years
Methylene Chloride	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 35 mg/l	8 weeks
Methylene Chloride	Inhalation	heart	Not classified	Human	NOAEL Not available	
Methylene Chloride	Inhalation	immune system	Not classified	Rat	NOAEL 18 mg/l	28 days
Methylene Chloride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,200 mg/kg/day	3 months
Methylene Chloride	Ingestion	blood	Not classified	Rat	NOAEL 249 mg/kg/day	2 years
Methylene Chloride	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,469 mg/kg/day	3 months
Methylene Chloride	Ingestion	eyes	Not classified	Rat	NOAEL 249 mg/kg/day	104 weeks

Aspiration Hazard

Name	Value
2-Methylpentane	Aspiration hazard
Cyclohexane	Aspiration hazard
Pentane	Aspiration hazard
Hexane	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Ecotoxic to the aquatic environment.

Acute Aquatic Toxicity: Category 2 (HSNO 9.1D Aquatic toxicity)

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Acetone	67-64-1	Algae other	Experimental	96 hours	EC50	11,493 mg/l
Acetone	67-64-1	Crustacea other	Experimental	24 hours	LC50	2,100 mg/l

3M Super 77 Multipurpose Adhesive

Acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
Acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
Acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
Acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
Non-volatile components	Trade Secret		Data not available or insufficient for classification			N/A
Propane	74-98-6		Data not available or insufficient for classification			N/A
2-Methylpentane	107-83-5		Data not available or insufficient for classification			N/A
Cyclohexane	110-82-7	Bacteria	Experimental	24 hours	IC50	97 mg/l
Cyclohexane	110-82-7	Fathead minnow	Experimental	96 hours	LC50	4.53 mg/l
Cyclohexane	110-82-7	Water flea	Experimental	48 hours	EC50	0.9 mg/l
Terpane Polymer	31393-98-3	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
Terpane Polymer	31393-98-3	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Terpane Polymer	31393-98-3	Water flea	Endpoint not reached	21 days	EL10	>100 mg/l
Ethanol	64-17-5	Fathead minnow	Experimental	96 hours	LC50	14,200 mg/l
Ethanol	64-17-5	Fish other	Experimental	96 hours	LC50	11,000 mg/l
Ethanol	64-17-5	Green algae	Experimental	72 hours	EC50	275 mg/l
Ethanol	64-17-5	Water flea	Experimental	48 hours	LC50	5,012 mg/l
Ethanol	64-17-5	Green algae	Experimental	72 hours	ErC10	11.5 mg/l
Ethanol	64-17-5	Water flea	Experimental	10 days	NOEC	9.6 mg/l
Hexane	110-54-3	Fathead minnow	Experimental	96 hours	LC50	2.5 mg/l
Hexane	110-54-3	Water flea	Experimental	48 hours	LC50	3.9 mg/l
Pentane	109-66-0	Green Algae	Experimental	72 hours	EC50	10.7 mg/l
Pentane	109-66-0	Rainbow trout	Experimental	96 hours	LC50	4.26 mg/l
Pentane	109-66-0	Water flea	Experimental	48 hours	EC50	2.7 mg/l
Pentane	109-66-0	Green Algae	Experimental	72 hours	NOEC	2.04 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
Toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
Toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l

3M Super 77 Multipurpose Adhesive

Toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
Toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
Toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
Toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
Toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)
Methylene Chloride	75-09-2	Fathead minnow	Experimental	96 hours	LC50	193 mg/l
Methylene Chloride	75-09-2	Green Algae	Experimental	72 hours	EC50	242 mg/l
Methylene Chloride	75-09-2	Water flea	Experimental	48 hours	LC50	27 mg/l
Methylene Chloride	75-09-2	Fathead minnow	Experimental	28 days	NOEC	83 mg/l
Methylene Chloride	75-09-2	Green Algae	Experimental	72 hours	EC10	115 mg/l
Methylene Chloride	75-09-2	Activated sludge	Experimental	40 minutes	EC50	2,590 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 % BOD/ThBOD	OECD 301D - Closed bottle test
Non-volatile components	Trade Secret	Data not available - insufficient			N/A	
Propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	Non-standard method
2-Methylpentane	107-83-5	Data not available - insufficient			N/A	
Cyclohexane	110-82-7	Experimental Photolysis		Photolytic half-life (in air)	4.14 days (t 1/2)	Non-standard method
Cyclohexane	110-82-7	Experimental Biodegradation	28 days	BOD	77 % BOD/ThBOD	OECD 301F - Manometric respirometry
Terpane Polymer	31393-98-3	Experimental Biodegradation	28 days	BOD	4 % BOD/ThBOD	OECD 301D - Closed bottle test
Ethanol	64-17-5	Experimental Biodegradation	14 days	BOD	89 % BOD/ThBOD	OECD 301C - MITI test (I)
Hexane	110-54-3	Experimental Photolysis		Photolytic half-life (in air)	5.4 days (t 1/2)	Non-standard method
Hexane	110-54-3	Experimental Bioconcentration	28 days	BOD	100 % weight	OECD 301C - MITI test (I)
Pentane	109-66-0	Experimental Photolysis		Photolytic half-life (in air)	8.07 days (t 1/2)	Non-standard method
Pentane	109-66-0	Experimental Biodegradation	28 days	BOD	87 % BOD/ThBOD	OECD 301F - Manometric

						respirometry
Limestone	1317-65-3	Data not available - insufficient			N/A	
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater
Methylene Chloride	75-09-2	Experimental Photolysis		Photolytic half-life (in air)	226 days (t 1/2)	
Methylene Chloride	75-09-2	Experimental Biodegradation	28 days	BOD	68 % BOD/ThBOD	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	
Acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	
Non-volatile components	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	Non-standard method
2-Methylpentane	107-83-5	Estimated Bioconcentration		Bioaccumulation factor	150	Estimated: Bioconcentration factor
Cyclohexane	110-82-7	Experimental BCF-Carp	56 days	Bioaccumulation factor	129	OECD 305E - Bioaccumulation flow-through fish test
Terpane Polymer	31393-98-3	Experimental Bioconcentration		Log Kow	7.41	Non-standard method
Ethanol	64-17-5	Experimental Bioconcentration		Log Kow	-0.35	Non-standard method
Hexane	110-54-3	Estimated Bioconcentration		Bioaccumulation factor	50	Estimated: Bioconcentration factor
Pentane	109-66-0	Estimated Bioconcentration		Bioaccumulation factor	26	Estimated: Bioconcentration factor
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation factor	90	
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	

		on				
Methylene Chloride	75-09-2	Experimental BCF-Carp	42 days	Bioaccumulation factor	≤40	OECD305-Bioconcentration
Methylene Chloride	75-09-2	Experimental Bioconcentration		Log Kow	1.25	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. Facility must be capable of handling aerosol cans.

Disposal of the aerosol dispenser (that may or may not contain any residual substance), may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: UN1950

Proper Shipping Name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Special Instructions: Limited quantity may apply

Hazchem Code: 2YE

IERG: 49

International Air Transport Association (IATA) - Air Transport

UN No.: UN1950

Proper Shipping Name: AEROSOLS, FLAMMABLE

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: UN1950

Proper Shipping Name: AEROSOLS

Class/Division: 2.1

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

HSNO Approval number HSR002515

3M Super 77 Multipurpose Adhesive

Group standard name Aerosols (Flammable) Group Standard 2017
HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	3,000 L (aggregate water capacity)
Hazardous atmosphere zone	3,000 L (aggregate water capacity)
Fire extinguishers	One required for 3,000 L (aggregate water capacity)
Emergency response plan	3,000 L (aggregate water capacity)
Secondary containment	Not required
Tracking	Not required
Warning signage	3,000 L (aggregate water capacity)

SECTION 16: Other information

Revision information:

Complete document review.

Document group:	16-3472-4	Version number:	4.00
Issue Date:	02/05/2021	Supersedes date:	08/09/2019

Key to abbreviations and acronyms

GHS means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>