



Safety Data Sheet

© 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	19-9940-8	Version number:	3.00
Issue Date:	13/06/2023	Supersedes date:	03/09/2019

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Adhesion Promoter 111

Product Identification Numbers

70-0064-0398-7

1.2. Recommended use and restrictions on use

Recommended use

Adhesion Promoter., Industrial use.

For Industrial or Professional use only

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquids: Category 2

Eye irritation: Category 2

Specific target organ toxicity – single exposure: Category 3 narcotic effects

2.2. Label elements

SIGNAL WORD

Danger

Symbols:

Flame | Exclamation mark |

Pictograms**HAZARD STATEMENTS:**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS**Prevention**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.

Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P337 + P313	IF eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Disposal

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Isopropyl Alcohol	67-63-0	98 - 100
Metal Alkoxide	Trade Secret	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: 2YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcinogen
Isopropyl Alcohol	67-63-0	New Zealand WES	TWA(8 hours):983 mg/m3(400 ppm);STEL(15 minutes):1230 mg/m3(500 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines
 New Zealand WES : New Zealand Workplace Exposure Standards.
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 ppm: parts per million
 mg/m³: milligrams per cubic metre
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
 Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber.

Fluoroelastomer

Nitrile rubber.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Colourless
Odour	Mild Odour
Odour threshold	<i>No data available.</i>
pH	8
Melting point/Freezing point	<i>Not applicable.</i>

Boiling point/Initial boiling point/Boiling range	82.4 °C
Flash point	11 °C [<i>Test Method</i> :Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	2 % volume
Flammable Limits(UEL)	12.7 % volume
Vapour pressure	4,399.6 Pa [<i>@ 20 °C</i>]
Vapor Density and/or Relative Vapor Density	2.1
Density	0.789 g/ml
Relative density	0.789 [<i>Ref Std</i> :WATER=1]
Water solubility	Complete
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	425 °C
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	780 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Percent volatile	99 % weight [<i>Test Method</i> :Estimated]
VOC less H₂O & exempt solvents	780 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Molecular weight	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Metal Alkoxide	Dermal	Professional judgement	LD50 not available
Metal Alkoxide	Ingestion	Rat	LD50 7,500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Isopropyl Alcohol	Multiple animal species	No significant irritation
Metal Alkoxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
------	---------	-------

Isopropyl Alcohol	Rabbit	Severe irritant
Metal Alkoxide	Rabbit	Severe irritant

Sensitisation:**Skin Sensitisation**

Name	Species	Value
Isopropyl Alcohol	Guinea pig	Not classified
Metal Alkoxide	Mouse	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
Metal Alkoxide	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Metal Alkoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	
Metal Alkoxide	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL not	

			data are not sufficient for classification	health hazards	available	
Metal Alkoxide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compounds	NOAEL not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Isopropyl Alcohol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
Isopropyl Alcohol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Isopropyl Alcohol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
Isopropyl Alcohol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
Metal Alkoxide	Trade Secret	Green algae	Experimental	72 hours	EC50	>960 mg/l
Metal Alkoxide	Trade Secret	Water flea	Experimental	48 hours	EC50	700 mg/l
Metal Alkoxide	Trade Secret	Green algae	Experimental	72 hours	NOEC	237 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isopropyl	67-63-0	Experimental	14 days	BOD	86 %BOD/ThO	OECD 301C - MITI

Alcohol		Biodegradation			D	test (I)
Metal Alkoxide	Trade Secret	Experimental Hydrolysis		Hydrolytic half-life	<3 minutes (t 1/2)	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Isopropyl Alcohol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	
Metal Alkoxide	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: UN1219

Proper Shipping Name: ISOPROPANOL

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: Limited quantity may apply

Hazchem Code: 2YE

IERG: 16

International Air Transport Association (IATA) - Air Transport

UN No.: UN1219

Proper Shipping Name: ISOPROPANOL

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

International Maritime Dangerous Goods Code (IMDG) - Marine Transport**UN No.:** UN1219**Proper Shipping Name:** ISOPROPANOL**Class/Division:** 3**Sub Risk:** Not applicable.**Packing Group:** II**Marine Pollutant:** Not applicable.**Special Instructions:** Limited quantity may apply**SECTION 15: Regulatory information**

HSNO Approval number HSR002662
 Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2020
 HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	100 L (closed containers greater than 5 L) 250 L (closed containers up to and including 5 L) 50 L (open containers)
Hazardous atmosphere zone	100 L (closed containers) 25 L (decanting) 5 L (open occasionally) 1 L (open containers in continuous use)
Fire extinguishers	Two required for 250 L
Emergency response plan	100 L (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L (for all other substances)
Secondary containment	100 L (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L (for all other substances)
Tracking	Not required
Warning signage	100 L (for Hazardous to the aquatic environment Category 1 substances); or 250 L (for all other substances)

SECTION 16: Other information**Revision information:**

Complete document review.

Document group:	19-9940-8	Version number:	3.00
Issue Date:	13/06/2023	Supersedes date:	03/09/2019

Key to abbreviations and acronyms**GHS** refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or

application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>