



## Safety Data Sheet

© 2019, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 19-0314-5 **Version number:** 3.00  
**Issue Date:** 23/01/2019 **Supersedes date:** 20/06/2013

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

##### Product Identification Numbers

YP-2060-0001-7	YP-2060-0002-5	YP-2060-0003-3	YP-2060-0004-1	YP-2060-0006-6
YP-2060-0008-2	YP-2060-0009-0	YP-2060-0013-2	YP-2060-0014-0	YP-2060-0015-7
YP-2060-0016-5	YP-2060-0017-3	YP-2060-0019-9	YP-2060-0021-5	YP-2060-0022-3
YP-2060-0026-4	YP-2060-0027-2	YP-2060-0028-0	YP-2060-0029-8	YP-2060-0030-6
YP-2060-0032-2	YP-2060-0034-8	YP-2060-0035-5	YP-2060-0040-5	

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Immobilization of upper and lower extremities

For Professional use only

#### 1.3. Supplier's details

**Address:** 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland  
**Telephone:** (09) 477 4040  
**E Mail:** innovation@nz.mmm.com  
**Website:** 3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

### SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

GHS	HSNO
Acute Toxicity (oral): Category 5	6.1E Acute toxicity (oral)
Skin Corrosion/Irritation: Category 3	6.3B Irritating to the skin
Respiratory Sensitiser: Category 1	6.5A Respiratory sensitiser
Skin Sensitiser: Category 1	6.5B Skin sensitiser
Specific Target Organ Toxicity (repeated exposure): Category 1	6.9A Toxic to human target organs/systems

**2.2. Label elements**

**SIGNAL WORD**

DANGER!

**Symbols:**

Health Hazard |

**Pictograms**



**HAZARD STATEMENTS:**

- H303 May be harmful if swallowed.
- H316 Causes mild skin irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
  
- H372 Causes damage to organs through prolonged or repeated exposure: respiratory system |

**PRECAUTIONARY STATEMENTS**

**General:**

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.

**Prevention:**

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P284A In case of inadequate ventilation wear respiratory protection.
- P280E Wear protective gloves.
- P270 Do not eat, drink or smoke when using this product.
- P264B Wash exposed skin thoroughly after handling.
- P272A Contaminated work clothing must not be allowed out of the workplace.

**Response:**

- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
  
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P332 + P313 If skin irritation occurs: Get medical advice/attention.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.
- P321 Specific treatment (see Notes to Physician on this label).

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

P312 Call a POISON CENTRE or doctor/physician if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.

### Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

## SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Glass Yarn	65997-17-3	40 - 70
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	15 - 40
4,4'-methylenediphenyl diisocyanate	26447-40-5	1 - 10
Calcium Metasilicate	13983-17-0	1 - 5

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide.

#### Condition

During combustion.

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

Carbon dioxide.  
Hydrogen cyanide.  
Oxides of nitrogen.

During combustion.  
During combustion.  
During combustion.

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

5.4. Hazchem code: Not applicable.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed. Store away from strong bases. Store away from oxidising agents. Store away from amines.

### 7.3. Certified handler

Not required

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Free isocyanates	26447-40-5	New Zealand WES	TWA(as NCO)(8 hours):0.02 mg/m <sup>3</sup> ;STEL(as NCO)(15 minutes):0.07 mg/m <sup>3</sup>	Capable of csng resp/skin sens
Glass filaments	65997-17-3	New Zealand	TWA(as inhalable dust)(8	

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

WES hours):5 mg/m<sup>3</sup>;TWA(as respirable dust)(8 hours):1 f/mL;TWA(Respirable fibers)(8 hours):1 f/mL

ACGIH : American Conference of Governmental Industrial Hygienists  
AIHA : American Industrial Hygiene Association  
CMRG : Chemical Manufacturer's Recommended Guidelines  
New Zealand WES : New Zealand Workplace Exposure Standards.  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
ppm: parts per million  
mg/m<sup>3</sup>: milligrams per cubic metre  
CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Eye protection not required.

##### Skin/hand protection

Gloves providing sufficient protection must be worn while applying the casting tape. E.g. nitrile gloves with a minimum thickness of 0.127 mm (5 mil, 0.005 inch) have proven to provide effective protection. The cast surface should be free of monomer and polymer isocyanate within 30 minutes when proper wetting techniques are used.

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

##### Respiratory protection

Results from air sampling during simulated product application show that vapours of methylenediphenyl-diisocyanate as used in the product are not detectable during use in Health Care facility cast rooms. Detection limits were extremely low and far below international safety recommendations for working with isocyanates. Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. People with bronchial problems or with isocyanate sensitivity may still respond to low isocyanate concentrations. In general it is recommended to use synthetic casting material in rooms with normal general/dilution ventilation.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid.
<b>Specific Physical Form:</b>	Roll of Tape. (Fiberglass knitted tape impregnated with moisture curable polyurethane prepolymer resin)
<b>Appearance/Odour</b>	Slight odour; colour is dependent on colourant used
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>No data available.</i>
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	<i>No data available.</i>
<b>Flash point</b>	No flash point

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

Evaporation rate	Negligible
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour density	<i>No data available.</i>
Density	1.1 g/ml
Relative density	1.1 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity	35,000 - 65,000 mPa-s [@ 23 °C ]
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	Negligible
VOC less H2O & exempt solvents	<i>No data available.</i>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Sparks and/or flames.

### 10.5 Incompatible materials

Strong bases.

Amines.

Alcohols.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to Section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

**Skin contact**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

**Additional information:**

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates. Results from air sampling for simulated dry and wet product application show that vapours of methylenediphenyl-diisocyanate as used in the product are not detectable during use. Detection limits were extremely low and far below international safety recommendations for working with isocyanates. People with bronchial problems or with isocyanate sensitivity may still respond to low isocyanate concentrations.

Direct contact with the cast surface without the use of gloves should be avoided until curing has completed. The cast surface should be free of monomer and polymer isocyanate within 30 minutes when proper wetting techniques are used.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

<b>Name</b>	<b>Route</b>	<b>Species</b>	<b>Value</b>
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Glass Yarn	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass arm	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	Dermal		LD50 estimated to be > 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Calcium Metasilicate	Dermal		LD50 estimated to be > 5,000 mg/kg
Calcium Metasilicate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Glass Yarn	Professional judgement	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Glass Yarn	Professional judgement	No significant irritation
4,4'-methylenediphenyl diisocyanate	official classification	Severe irritant

**Skin Sensitisation**

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	official classification	Sensitising

**Respiratory Sensitisation**

Name	Species	Value
4,4'-methylenediphenyl diisocyanate	Human	Sensitising

**Germ Cell Mutagenicity**

Name	Route	Value
Glass Yarn	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Calcium Metasilicate	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Glass Yarn	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis



**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)****Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Glass Yarn	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Calcium Metasilicate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Calcium Metasilicate	Inhalation	pulmonary fibrosis	Not classified	Human and animal	NOAEL Not available	

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Glass Yarn	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Glass Yarn	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Glass Yarn	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Glass Yarn	65997-17-3	Green algae	Experimental	72 hours	NOEC	≥1,000 mg/l
4,4'-Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	Water flea	Estimated	24 hours	EC50	>100 mg/l
4,4'-Methylenediph	9048-57-1	Zebra Fish	Estimated	24 hours	LC50	>100 mg/l

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

enyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)						
4,4'-methylenediph enyl diisocyanate	26447-40-5	Water flea	Estimated		EC50	>100 mg/l
Calcium Metasilicate	13983-17-0		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass Yarn	65997-17-3	Data not availbl-insufficient			N/A	
4,4'-Methylenediph enyl diisocyanate, oligomeric reaction products with a-hydro-w-hydroxypoly(oxy-1,2-ethanediyl)	9048-57-1	Data not availbl-insufficient			N/A	
4,4'-methylenediph enyl diisocyanate	26447-40-5	Estimated Hydrolysis		Hydrolytic half-life	<2 hours (t 1/2)	Other methods
4,4'-methylenediph enyl diisocyanate	26447-40-5	Estimated Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)
Calcium Metasilicate	13983-17-0	Data not availbl-insufficient			N/A	

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Glass Yarn	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
4,4'-	9048-57-1	Data not	N/A	N/A	N/A	N/A

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

Methylenediphenyl diisocyanate, oligomeric reaction products with a-hydroxy-poly(oxy-1,2-ethanediyl)		available or insufficient for classification				
4,4'-methylenediphenyl diisocyanate	26447-40-5	Estimated BCF-Carp	28 days	Bioaccumulation factor	200	Other methods
Calcium Metasilicate	13983-17-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

During cleanup or disposal of open, uncured product, gloves providing sufficient protection must be worn. E.g. nitrile gloves with a minimum thickness of 0.127 mm (5 mil, 0.005 inch) have proven to provide effective protection. Additionally the following skin protection may be needed: laboratory coat or long-sleeve protective gauntlets. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

**SECTION 14: Transport Information****New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport**

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable.

IERG: Not applicable.

## 3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)

### International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

### International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

## SECTION 15: Regulatory information

HSNO Approval number	HSR002552
Group standard name	Cosmetic Products Group Standard 2017
HSNO Hazard classification	Refer to Section 2: Hazard identification

### NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

### Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	10,000 L or 10,000 kg (for 6.7B, 6.9A, 8.2C, 8.3A, 9.1D substance)
Secondary containment	10,000 L or 10,000 kg (for 6.7B, 6.9A, 8.2C, 8.3A, 9.1D substance)
Tracking	Not required
Warning signage	Not required

## SECTION 16: Other information

### Revision information:

Complete document review.

<b>Document group:</b>	19-0314-5	<b>Version number:</b>	3.00
<b>Issue Date:</b>	23/01/2019	<b>Supersedes date:</b>	20/06/2013

### Key to abbreviations and acronyms

**GHS** means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013

**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use

**3M™ Scotchcast™ Plus Enhancing Performance Casting Tape (Standard Colors)**

and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>**