



Safety Data Sheet

© 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 25-4665-3 **Version number:** 3.00
Issue Date: 28/09/2020 **Supersedes date:** 18/01/2017

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Red Cream Hardener PN 05830

Product Identification Numbers

60-9800-2275-4

1.2. Recommended use and restrictions on use

Recommended use

Automotive. Catalyst for automotive body filler

For Industrial or Professional use only

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Organic Peroxide: Type E	5.2E Organic peroxide: Type E
Acute Toxicity (dermal): Category 5	6.1E Acute toxicity (skin)
Serious Eye Damage/Irritation: Category 2	6.4A Irritating to the eye
Skin Sensitiser: Category 1	6.5B Skin sensitiser

Acute Aquatic Toxicity: Category 1	9.1A Aquatic toxicity (acute)
Chronic Aquatic Toxicity: Category 1	9.1A Aquatic toxicity (chronic)

2.2. Label elements

SIGNAL WORD

WARNING!

Symbols:

Flame | Exclamation mark | Environment |

Pictograms



HAZARD STATEMENTS:

H242	Heating may cause a fire.
H313	May be harmful in contact with skin.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H410	Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P210A	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240B	Ground and bond container and receiving equipment.
P235	Keep cool.
P234A	Keep only in original packaging.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280A	Wear eye/face protection.
P280B	Wear protective gloves and eye/face protection.
P280E	Wear protective gloves.
P273	Avoid release to the environment.
P264B	Wash exposed skin thoroughly after handling.
P272A	Contaminated work clothing must not be allowed out of the workplace.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P321	Specific treatment (see Notes to Physician on this label).
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P370 + P378I	In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

Storage:

P410	Protect from sunlight.
------	------------------------

3M™ Red Cream Hardener PN 05830

P403 Store in a well-ventilated place.
P411 Store at temperatures not exceeding 5C/40F.
P420A Store separately.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Dibenzoyl peroxide	94-36-0	30 - 60
Benzoic Acid, C9-11-Branched Alkyl Esters	131298-44-7	10 - 30
Water	7732-18-5	10 - 30
Zinc Stearate	557-05-1	3 - 7
Calcium Sulfate	7778-18-9	1 - 5
Iron oxide (FE2O3)	1309-37-1	1 - 5
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Part of the oxygen for combustion is supplied by the peroxide itself.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: 1W

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Eliminate all ignition sources if safe to do so. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Avoid breathing of dust created by cutting, sanding, grinding or machining. Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store at temperatures not exceeding 32C. Keep cool. Keep only in original container. Store away from other materials. Keep/store away from clothing and other combustible materials.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Iron oxide (FE2O3)	1309-37-1	ACGIH	TWA(respirable fraction):5 mg/m3	A4: Not class. as human carcinogen

Iron oxide (FE2O3)	1309-37-1	New Zealand WES	TWA(as Fe, dust and fume)(8 hours):5 mg/m3	
Stearates	557-05-1	ACGIH	TWA(respirable fraction):3 mg/m3;TWA(inhalable fraction):10 mg/m3	A4: Not class. as human carcinogin
Stearates	557-05-1	New Zealand WES	TWA(8 hours):10 mg/m3	
Calcium Sulfate	7778-18-9	ACGIH	TWA(inhalable fraction):10 mg/m3	
Calcium Sulfate	7778-18-9	New Zealand WES	TWA(8 hours):10 mg/m3	
Dibenzoyl peroxide	94-36-0	ACGIH	TWA:5 mg/m3	A4: Not class. as human carcinogin
Dibenzoyl peroxide	94-36-0	New Zealand WES	TWA(8 hours):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilation adequate to maintain dust concentration below minimum explosive concentrations. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

Wear respiratory protection if ventilation is inadequate to prevent overexposure. An exposure assessment may be needed to

decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid.
Specific Physical Form:	Viscous.
Colour	Red
Odour	Slight Ester
Odour threshold	<i>No data available.</i>
pH	<i>No data available.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	111 °C [<i>Test Method:Estimated</i>]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Organic Peroxide: Type E.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapour pressure	<i>Not applicable.</i>
Vapor Density and/or Relative Vapor Density	<i>Not applicable.</i>
Density	1.2 g/cm ³
Relative density	1.2 [<i>@ 25 °C</i>] [<i>Ref Std: WATER=1</i>]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	0 g/l [<i>Test Method:calculated SCAQMD rule 443.1</i>]
Volatile organic compounds (VOC)	0 % weight [<i>Test Method:calculated per CARB title 2</i>]
Percent volatile	20 % weight [<i>Details: Water is the volatile component</i>]
VOC less H ₂ O & exempt solvents	0 g/l [<i>Test Method:calculated SCAQMD rule 443.1</i>]

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable. Stable unless exposed to heat, flames and drying conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Accelerators

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	Not specified.
Carbon dioxide.	Not specified.
Toxic vapour, gas, particulate.	Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

May be harmful in contact with skin.

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

3M™ Red Cream Hardener PN 05830

Dibenzoyl peroxide	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Dibenzoyl peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 24.3 mg/l
Dibenzoyl peroxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Dermal	Rabbit	LD50 > 2,000 mg/kg
Benzoic Acid, C9-11-Branched Alkyl Esters	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Benzoic Acid, C9-11-Branched Alkyl Esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Zinc Stearate	Dermal	Rabbit	LD50 > 2,000 mg/kg
Zinc Stearate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Zinc Stearate	Ingestion	Rat	LD50 > 5,000 mg/kg
Calcium Sulfate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Dermal	Rabbit	LD50 > 16,960 mg/kg
Calcium Sulfate	Ingestion	Rat	LD50 > 5,000 mg/kg
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5 mg/l
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	LD50 4,240 mg/kg
Iron oxide (FE2O3)	Dermal	Not available	LD50 3,100 mg/kg
Iron oxide (FE2O3)	Ingestion	Not available	LD50 3,700 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Dibenzoyl peroxide	Rabbit	Minimal irritation
Zinc Stearate	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	Minimal irritation
Iron oxide (FE2O3)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Dibenzoyl peroxide	Rabbit	Severe irritant
Zinc Stearate	Rabbit	No significant irritation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Rabbit	No significant irritation
Iron oxide (FE2O3)	Rabbit	No significant irritation

Sensitisation:**Skin Sensitisation**

Name	Species	Value
Dibenzoyl peroxide	Guinea pig	Sensitising
Iron oxide (FE2O3)	Human	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

3M™ Red Cream Hardener PN 05830

Dibenzoyl peroxide	In Vitro	Not mutagenic
Dibenzoyl peroxide	In vivo	Not mutagenic
Iron oxide (FE2O3)	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Dibenzoyl peroxide	Ingestion	Multiple animal species	Not carcinogenic
Dibenzoyl peroxide	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	Rat	Not carcinogenic
Iron oxide (FE2O3)	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Dibenzoyl peroxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Dibenzoyl peroxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	pre mating & during gestation
Dibenzoyl peroxide	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	pre mating & during gestation
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 1 mg/l	2 weeks

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	nervous system	Not classified	Rat	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	endocrine system hematopoietic system liver nervous system	Not classified	Rat	NOAEL 1 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.005 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.001 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Inhalation	heart	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 145 mg/kg/day	90 days
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 500 mg/kg/day	2 years

3M™ Red Cream Hardener PN 05830

Oxirane, Polymer with Methyloxirane, Monobutyl Ether	Ingestion	heart endocrine system respiratory system	Not classified	Rat	NOAEL 3,770 mg/kg/day	90 days
Iron oxide (FE2O3)	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Ecotoxic to the aquatic environment.**

Acute Aquatic Toxicity: Category 1 (HSNO 9.1A Aquatic toxicity)

Chronic Aquatic Toxicity: Category 1 (HSNO 9.1A Aquatic toxicity)

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Dibenzoyl peroxide	94-36-0	Green Algae	Experimental	72 hours	EC50	0.071 mg/l
Dibenzoyl peroxide	94-36-0	Rainbow trout	Experimental	96 hours	LC50	0.06 mg/l
Dibenzoyl peroxide	94-36-0	Water flea	Experimental	48 hours	EC50	0.11 mg/l
Dibenzoyl peroxide	94-36-0	Green Algae	Experimental	72 hours	NOEC	0.02 mg/l
Dibenzoyl peroxide	94-36-0	Water flea	Experimental	21 hours	Effect Concentration 10%	0.001 mg/l
Benzoic Acid, C9-11- Branched Alkyl Esters	131298-44-7		Data not available or insufficient for classification			
Zinc Stearate	557-05-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Zinc Stearate	557-05-1	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Calcium Sulfate	7778-18-9	Algae or other aquatic plants	Experimental	96 hours	EC50	3,200 mg/l
Calcium Sulfate	7778-18-9	Bluegill	Experimental	96 hours	LC50	>2,980 mg/l
Calcium Sulfate	7778-18-9	Water flea	Experimental	48 hours	LC50	>1,970 mg/l
Calcium Sulfate	7778-18-9	Water flea	Estimated	21 days	NOEC	1,270 mg/l
Iron oxide	1309-37-1	Golden Orfe	Experimental	48 hours	LC50	>1,000 mg/l

3M™ Red Cream Hardener PN 05830

(FE2O3)						
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Inland Silverside	Analogous Compound	96 hours	LC50	650 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoyl peroxide	94-36-0	Experimental Hydrolysis		Hydrolytic half-life	<24 hours (t _{1/2})	Other methods
Dibenzoyl peroxide	94-36-0	Experimental Biodegradation	28 days	BOD	71 % weight	OECD 301D - Closed bottle test
Benzoic Acid, C9-11- Branched Alkyl Esters	131298-44-7	Data not availbl- insufficient			N/A	
Zinc Stearate	557-05-1	Experimental Biodegradation	28 days	BOD	14.6 % BOD/ThBOD	OECD 301D - Closed bottle test
Calcium Sulfate	7778-18-9	Data not availbl- insufficient			N/A	
Iron oxide (FE2O3)	1309-37-1	Data not availbl- insufficient			N/A	
Oxirane, Polymer with Methyloxirane, Monobutyl Ether	9038-95-3	Data not availbl- insufficient			N/A	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoyl peroxide	94-36-0	Experimental Bioconcentration		Log Kow	3.2	Other methods
Benzoic Acid, C9-11- Branched Alkyl Esters	131298-44-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Zinc Stearate	557-05-1	Experimental Bioconcentration		Log Kow	4.64	OECD 117 log Kow HPLC method
Calcium Sulfate	7778-18-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Iron oxide (FE2O3)	1309-37-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxirane, Polymer with	9038-95-3	Data not available or	N/A	N/A	N/A	N/A

3M™ Red Cream Hardener PN 05830

Methyloxirane, Monobutyl Ether		insufficient for classification				
--------------------------------------	--	------------------------------------	--	--	--	--

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities. This product has been classified on the basis that it is stable as sold. Material may become unstable if allowed to dry out. Classify appropriately before disposal.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information**New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport**

UN No.: UN3108

Proper Shipping Name: ORGANIC PEROXIDE TYPE E, SOLID , (Dibenzoyl Peroxide (As a Paste), <= 52%)

Class/Division: 5.2

Sub Risk: Not applicable.

Packing Group: Not applicable.

Special Instructions: Limited quantity may apply

Hazchem Code: 1W

IERG: 32

International Air Transport Association (IATA) - Air Transport

UN No.: UN3108

Proper Shipping Name: ORGANIC PEROXIDE TYPE E, SOLID , (Dibenzoyl Peroxide (As a Paste), <= 52%)

Class/Division: 5.2

Sub Risk: Not applicable.

Packing Group: Not applicable.

Special Instructions: FORBIDDEN BY THIS MODE OF TRANSPORT, 3M DIVISION POLICY

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: UN3108

Proper Shipping Name: ORGANIC PEROXIDE TYPE E, SOLID , (Dibenzoyl Peroxide (As a Paste), <= 52%)

Class/Division: 5.2

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

HSNO Approval number HSR002629
Group standard name Organic Peroxides Group Standard 2017
HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	25 kg
Hazardous atmosphere zone	Not required
Fire extinguishers	One required for 50 L or 50 kg
Emergency response plan	100 L or 100 kg
Secondary containment	100 L or 100 kg
Tracking	Not required
Warning signage	10 L or 10 kg

SECTION 16: Other information**Revision information:**

Complete document review.

Document group:	25-4665-3	Version number:	3.00
Issue Date:	28/09/2020	Supersedes date:	18/01/2017

Key to abbreviations and acronyms

GHS means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>