

Safety Data Sheet

© 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-1016-6	Version number:	3.00
Issue Date:	10/09/2023	Supersedes date:	28/09/2020

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

IDENTIFICATION:

1.1. Product identifier

3M[™] Semi-Rigid Plastic Repair PN 34240

Product Identification Numbers 60-4550-5240-1

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

28-7005-3, 28-7003-8

One or more components of this KIT is classified as a hazardous substance in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

TRANSPORT INFORMATION

NOT HAZARDOUS FOR TRANSPORT

Revision information:

Complete document review.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz



Safety Data Sheet

© 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-7003-8	Version number:	3.00
Issue Date:	10/09/2023	Supersedes date:	28/09/2020

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M[™] Semi-Rigid Plasic Repair PN 34240 (Part A)

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin irritation: Category 2 Eye irritation: Category 2 Respiratory sensitisation: Category 1 Skin sensitisation: Category 1 Carcinogenicity: Category 2 Specific target organ toxicity – repeated exposure: Category 1 Specific target organ toxicity – single exposure: Category 3 respiratory tract irritation

2.2. Label elements SIGNAL WORD

Danger

Symbols:

Exclamation mark |Health Hazard |

Pictograms



HAZARD STATEMENTS:	
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure: respiratory system.

PRECAUTIONARY STATEMENTS

Prevention	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280F	Wear respiratory protection.
P284	Wear respiratory protection.
Response	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	IF eye irritation persists: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Storage	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
Disposal	
P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Castor Oil, Polymer With 1,1'-Methylenebis[4-Isocyanatobenzene]	68424-09-9	30 - 60
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	30 - 60
4,4'-Methylenediphenyl diisocyanate, oligomers	25686-28-6	10 - 30
Oxirane, Methyl-, Polymer With Oxirane, Ether With 1,2,3-Propanetriol	59675-67-1	1 - 5
(3:1), Polymer With 1,1'-Methylenebis[4-Isocyantobenzene]		
Carbon black	1333-86-4	0.1 - 1
Chromium Compound 1	71701-12-7	0.01 - 0.3
Chromium Compound 2	74421-71-9	0.01 - 0.1
Chromium Compound 3	71839-90-2	0.01 - 0.1
Chromium	7440-47-3	< 0.02

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide. <u>Condition</u> During combustion.

Carbon dioxide.	During combustion.
Hydrogen cyanide.	During combustion.
Oxides of nitrogen.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

for the component.				
Ingredient	CAS Nbr	Agency	Limit type	Additional comments
P,P'-Methylenebis(phenyl	101-68-8	ACGIH	TWA:0.005 ppm	
isocyanate)				
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	New Zealand WES	TWA(inhalable fraction and vapor)(8 hours):0.02	Dermal sensitiser, Respiratory sensitiser
			mg/m3;STEL(inhalable fraction and vapor)(15	1 5
Carbon black	1333-86-4	ACGIH	minutes):0.07 mg/m3 TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcinogen.
Carbon black	1333-86-4	New Zealand WES	TWA(8 hours): 3 mg/m3	Suspected human carcinogen.
Free isocyanates	25686-28-6	New Zealand WES	TWA(as NCO,Inhalable fraction and vapor)(8 hours):0.02 mg/m3;TWA(as NCO)(8 hours):0.02 mg/m3;STEL(as NCO,Inhalable fraction and vapor)(15 minutes):0.07 mg/m3;STEL(as NCO)(15 minutes):0.07 mg/m3	Capable of csng resp/skin sens, Dermal sensitiser, Respiratory sensitiser
Free isocyanates	68424-09-9	New Zealand WES	TWA(as NCO,Inhalable fraction and vapor)(8 hours):0.02 mg/m3;TWA(as NCO)(8 hours):0.02 mg/m3;STEL(as NCO,Inhalable fraction and vapor)(15 minutes):0.07 mg/m3;STEL(as NCO)(15 minutes):0.07 mg/m3	Capable of csng resp/skin sens, Dermal sensitiser, Respiratory sensitiser
Chromium (III) oxide	71701-12-7	ACGIH	TWA(as Cr(III), inhalable fraction):0.003 mg/m3;TWA(as Cr):0.5 mg/m3	A4: Not class. as human carcinogin
Chromium (III) oxide	71701-12-7	New Zealand WES	TWA(as Cr)(8 hours):0.5 mg/m3	
Chromium (III) oxide	71839-90-2		TWA(as Cr(III), inhalable fraction):0.003 mg/m3;TWA(as Cr):0.5 mg/m3	A4: Not class. as human carcinogin
Chromium (III) oxide	71839-90-2	New Zealand WES	TWA(as Cr)(8 hours):0.5 mg/m3	
Chromium	7440-47-3	ACGIH	TWA(as Cr(0), inhalable fraction):0.5 mg/m3	
Chromium	7440-47-3	New Zealand WES	TWA(8 hours): 0.5 mg/m3	Respiratory sensitiser
Chromium (III) oxide	74421-71-9	ACGIH	TWA(as Cr(III), inhalable fraction):0.003 mg/m3;TWA(as Cr):0.5 mg/m3	A4: Not class. as human carcinogin
Chromium (III) oxide		New Zealand WES	TWA(as Cr)(8 hours):0.5 mg/m3	
ACGIH : American Conference of Gov		Hygienists		

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

 $New\ Zealand\ WES: New\ Zealand\ Workplace\ Exposure\ Standards.$

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit ppm: parts per million mg/m³: milligrams per cubic metre CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect vented goggles.

Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous.
Colour	Black
Odour	Low Odour, Odourless
Odour threshold	No data available.

рН	Not applicable.		
Melting point/Freezing point	No data available.		
Boiling point/Initial boiling point/Boiling range	>=204.4 °C		
Flash point	>=143.3 °C [<i>Test Method</i> :Tagliabue closed cup]		
Evaporation rate	<=1 [<i>Details</i> :Gels with exposure to humidity.]		
Flammability (solid, gas)	Not applicable.		
Flammable Limits(LEL)	Not applicable.		
Flammable Limits(UEL)	Not applicable.		
Vapour pressure	<=0 Pa [@ 20 °C]		
Vapor Density and/or Relative Vapor Density	>=1 [<i>Ref Std</i> :AIR=1]		
Density	1 - 1.2 g/ml		
Relative density	1 - 1.2 [<i>Ref Std</i> :WATER=1]		
Water solubility	Negligible		
Solubility- non-water	No data available.		
Partition coefficient: n-octanol/water	No data available.		
Autoignition temperature	Not applicable.		
Decomposition temperature	No data available.		
Viscosity/Kinematic Viscosity	No data available.		
Volatile organic compounds (VOC)	0 g/l [Test Method:calculated SCAQMD rule 443.1]		
Volatile organic compounds (VOC)	0 % weight [<i>Test Method</i> :calculated per CARB title 2]		
Percent volatile	0 % weight		
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]		

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid None known.

10.5 Incompatible materials Water Strong acids. Strong bases.

10.6 Hazardous decomposition products <u>Substance</u>

None known.

Condition

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be

present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Prolonged or repeated exposure by inhalation may cause:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
P,P'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomers	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation-	Rat	LC50 0.368 mg/l
	Dust/Mist		
	(4 hours)		
4,4'-Methylenediphenyl diisocyanate, oligomers	Ingestion	Rat	LD50 31,600 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	official classificat ion	Irritant
4,4'-Methylenediphenyl diisocyanate, oligomers	official classificat ion	Irritant
Carbon black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	official classificat	Severe irritant
	ion	
4,4'-Methylenediphenyl diisocyanate, oligomers	official	Severe irritant
	classificat	
	ion	
Carbon black	Rabbit	No significant irritation

Sensitisation:

Skin Sensitisation

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	official classificat ion	Sensitising
4,4'-Methylenediphenyl diisocyanate, oligomers	official classificat ion	Sensitising

Respiratory Sensitisation

Name		Value
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitising
4,4'-Methylenediphenyl diisocyanate, oligomers	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Methylenediphenyl diisocyanate, oligomers	In Vitro	Some positive data exist, but the data are not sufficient for classification
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic

3M [™] Semi-Rigid Plasic	Repair PN 34240 (Part A)	
-----------------------------------	--------------------------	--

Carbon black	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	respiratory irritation	May cause respiratory irritation	official classifica tion	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
4,4'-Methylenediphenyl diisocyanate, oligomers	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Castor Oil,	68424-09-9	N/A	Data not	N/A	N/A	NA
Polymer With			available or			
1,1'-			insufficient for			
Methylenebis[4			classification			
-						
Isocyanatobenz						

ene]						
P,P'-	101-68-8	Activated	Analogous	3 hours	EC50	>100 mg/l
Methylenebis(p		sludge	Compound	5 110015	LC30	> 100 mg/1
henyl		siddge	Compound			
isocyanate)						
P,P'-	101-68-8	Green algae	Analogous	72 hours	EC50	> 1 (40 m = /1
		Green algae		72 nours	EC30	>1,640 mg/l
Methylenebis(p			Compound			
henyl						
isocyanate)						
P,P'-	101-68-8	Water flea	Analogous	24 hours	EC50	>1,000 mg/l
Methylenebis(p			Compound			
henyl						
isocyanate)						
P,P'-	101-68-8	Zebra Fish	Analogous	96 hours	LC50	>1,000 mg/l
Methylenebis(p			Compound			
henyl			1			
isocyanate)						
P,P'-	101-68-8	Green algae	Analogous	72 hours	NOEC	1,640 mg/l
Methylenebis(p		Green uigue	Compound	/2 110015	INOLU	1,010 mg/1
henyl			Compound			
isocyanate)						
P,P'-	101-68-8	Weter Clea	A	21 1	NOEC	10
		Water flea	Analogous	21 days	NOEC	10 mg/l
Methylenebis(p			Compound			
henyl						
isocyanate)						
4,4'-	25686-28-6	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
Methylenediph						
enyl						
diisocyanate,						
oligomers						
4,4'-	25686-28-6	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
Methylenediph						_
enyl						
diisocyanate,						
oligomers						
4,4'-	25686-28-6	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
Methylenediph	25000 20 0		Estimated	<i>y</i> 0 nours	LCSU	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
enyl						
diisocyanate,						
oligomers						
	25696 29 6		Estimated	72 h a	NOEI	1 (40 m ~/l
4,4'-	25686-28-6	Green algae	Estimated	72 hours	NOEL	1,640 mg/l
Methylenediph						
enyl						
diisocyanate,						
oligomers						
4,4'-	25686-28-6	Water flea	Estimated	21 days	NOEC	10 mg/l
Methylenediph						
enyl						
diisocyanate,						
oligomers						
Oxirane,	59675-67-1	N/A	Data not	N/A	N/A	N/A
Methyl-,			available or			
Polymer With			insufficient for			
Oxirane, Ether			classification			
With 1,2,3-						
., 1011 1,2,2	1	1	I	1	<u> </u>	1

Propanetriol (3:1), Polymer With 1,1'- Methylenebis[4 - Isocyantobenze ne]						
Carbon black	1333-86-4	Activated sludge	Experimental	3 hours	EC50	>=100 mg/l
Carbon black	1333-86-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Chromium Compound 1	71701-12-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Chromium Compound 2	74421-71-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Chromium Compound 3	71839-90-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Chromium	7440-47-3	N/A	Data not available or insufficient for classification	N/A	N/A	n/a

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Castor Oil, Polymer With 1,1'- Methylenebis[4 - Isocyanatobenz ene]		Data not availbl- insufficient	N/A	N/A	N/A	N/A
P,P'- Methylenebis(p henyl isocyanate)	101-68-8	Data not availbl- insufficient	N/A	N/A	N/A	N/A
4,4'- Methylenediph enyl diisocyanate, oligomers	25686-28-6	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Oxirane, Methyl-, Polymer With Oxirane, Ether With 1,2,3- Propanetriol	59675-67-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A

(3:1), Polymer With 1,1'- Methylenebis[4 - Isocyantobenze ne]							
Carbon black	1333-86-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A	
Chromium Compound 1	71701-12-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A	
Chromium Compound 2	74421-71-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A	
Chromium Compound 3	71839-90-2	Data not availbl- insufficient	N/A	N/A	N/A	N/A	
Chromium	7440-47-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Castor Oil, Polymer With 1,1'- Methylenebis[4 - Isocyanatobenz ene]		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
P,P'- Methylenebis(p henyl isocyanate)	101-68-8	Analogous Compound BCF - Fish	28 days	Bioaccumulatio n factor	200	OECD305- Bioconcentration
4,4'- Methylenediph enyl diisocyanate, oligomers	25686-28-6	Estimated BCF - Fish	28 days	Bioaccumulatio n factor	200	OECD305- Bioconcentration
Oxirane, Methyl-, Polymer With Oxirane, Ether With 1,2,3- Propanetriol (3:1), Polymer With 1,1'- Methylenebis[4 - Isocyantobenze ne]		Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or	N/A	N/A	N/A	N/A

		insufficient for classification				
Chromium Compound 1	71701-12-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chromium Compound 2	74421-71-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chromium Compound 3	71839-90-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Chromium	7440-47-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable. IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport UN No.: Not applicable.

Proper Shipping Name: Not applicable.Class/Division: Not applicable.Sub Risk: Not applicable.Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.
Proper Shipping Name: Not applicable.
Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval numberHSR002679Group standard nameSurface Coatings and Colourants (Carcinogenic) Group Standard 2020HSNO Hazard classificationRefer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for all other substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for all other substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

SECTION 16: Other information

Revision information:

Complete document review.

Document group:	28-7003-8	Version number:	3.00
Issue Date:	10/09/2023	Supersedes date:	28/09/2020

Key to abbreviations and acronyms

GHS refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017 **HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz



Safety Data Sheet

 \bigcirc 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-7005-3	Version number:	2.00
Issue Date:	28/09/2020	Supersedes date:	31/01/2017

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M[™] Semi-Rigid Plastic Repair PN 34240 - Part B

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Serious Eye Damage/Irritation: Category 2	6.4A Irritating to the eye
Skin Corrosion/Irritation: Category 2	6.3A Irritating to the skin
Skin Sensitiser: Category 1	6.5B Skin sensitiser

2.2. Label elements SIGNAL WORD WARNING!

Symbols: Exclamation mark |

Pictograms



HAZARD STATEMENTS:	
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

Prevention:	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280A	Wear eye/face protection.
P280E	Wear protective gloves.
P264B	Wash exposed skin thoroughly after handling.
P272A	Contaminated work clothing must not be allowed out of the workplace.
Response:	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P321	Specific treatment (see Notes to Physician on this label).
Disposal:	
P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Polyether Polyol	9082-00-2	40 - 70
Propoxylated trimethylolpropane	25723-16-4	10 - 30
Tetrakis(2-hydroxypropyl)ethylenediamine	102-60-3	10 - 30
M-xylene-alpha,alpha'-diamine	1477-55-0	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Oxides of nitrogen.	During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially

available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type			
M-xylene-alpha,alpha'-diamine	1477-55-0	ACGIH	CEIL:0.018 ppm			
			11			
M-xylene-alpha,alpha'-diamine	1477-55-0	New Zealand	CEIL: 0.1 mg/m3			
		WES	C			
ACGIH : American Conference of Governmental Industrial Hygienists						
AIHA : American Industrial Hygiene Association						
CMRG : Chemical Manufacturer's Recom	mended Guidelin	es				

Additional comments Danger of cutaneous absorption Skin

8.2. Exposure controls

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

mg/m³: milligrams per cubic metre

ppm: parts per million

CEIL: Ceiling

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

New Zealand WES : New Zealand Workplace Exposure Standards.

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl rubber. Neoprene.

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber Neoprene apron.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous.
Colour	Colourless
Odour	Slight Ammoniacal
Odour threshold	No data available.
рН	Not applicable.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	>=210 °C
Flash point	>=143.3 °C [<i>Test Method:</i> Tagliabue closed cup]
Evaporation rate	<=1 [<i>Ref Std</i> :WATER=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	Not applicable.
Vapor Density and/or Relative Vapor Density	>=1 [<i>Ref Std</i> :AIR=1]
Density	1 - 1.1 g/ml
Relative density	1 - 1.1 [<i>Ref Std</i> :WATER=1]
Water solubility	Negligible
Solubility- non-water	No data available.

Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	Not applicable.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	1,400 - 1,800 mPa-s
Volatile organic compounds (VOC)	0 g/l [Test Method:calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0 % weight [Test Method: calculated per CARB title 2]
Percent volatile	0.49 % weight
VOC less H2O & exempt solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1]

Nanoparticles

This material does not contain nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids. Strong oxidising agents.

10.6 Hazardous decomposition products

Substance None known. **Condition**

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Route	Species	Value
Dermal		No data available; calculated ATE >5,000 mg/kg
Ingestion		No data available; calculated ATE >5,000 mg/kg
Dermal	Rabbit	LD50 > 5,000 mg/kg
Ingestion	Rat	LD50 > 10,000 mg/kg
Dermal	Rat	LD50 > 2,000 mg/kg
Ingestion	Rat	LD50 > 2,500 mg/kg
Dermal	Rat	LD50 > 2,000 mg/kg
Ingestion	Rat	LD50 2,890 mg/kg
Dermal	Rabbit	LD50 > 2,000 mg/kg
Inhalation-	Rat	LC50 1.2 mg/l
Dust/Mist		
(4 hours)		
Ingestion	Rat	LD50 980 mg/kg
	Dermal Ingestion Dermal Ingestion Dermal Ingestion Dermal Inhalation- Dust/Mist (4 hours)	DermalIngestionDermalRabbitIngestionRatDermalRatIngestionRatDermalRatIngestionRatDermalRatIngestionRatDermalRabbitInhalation- Dust/Mist (4 hours)Rat

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Propoxylated trimethylolpropane	Rabbit	No significant irritation
Tetrakis(2-hydroxypropyl)ethylenediamine	Rabbit	No significant irritation
M-xylene-alpha,alpha'-diamine	Rat	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Propoxylated trimethylolpropane	Rabbit	Mild irritant
Tetrakis(2-hydroxypropyl)ethylenediamine	Rabbit	Severe irritant
M-xylene-alpha,alpha'-diamine	Rabbit	Corrosive

Sensitisation:

Skin Sensitisation

Name	Species	Value
Tetrakis(2-hydroxypropyl)ethylenediamine	Guinea	Not classified
	pig	
M-xylene-alpha,alpha'-diamine	Guinea	Sensitising
	pig	

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Tetrakis(2-hydroxypropyl)ethylenediamine	In Vitro	Not mutagenic
M-xylene-alpha,alpha'-diamine	In Vitro	Not mutagenic
M-xylene-alpha,alpha'-diamine	In vivo	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	30 days
Tetrakis(2-hydroxypropyl)ethylenediamine	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
M-xylene-alpha,alpha'-diamine	Ingestion	Not classified for female reproduction	Rat	NOAEL 450 mg/kg/day	1 generation
M-xylene-alpha,alpha'-diamine	Ingestion	Not classified for male reproduction	Rat	NOAEL 450 mg/kg	1 generation
M-xylene-alpha,alpha'-diamine	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	1 generation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tetrakis(2- hydroxypropyl)ethylenedia mine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Positive	
M-xylene-alpha,alpha'- diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not avaliable	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tetrakis(2- hydroxypropyl)ethylenedia mine	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 300 mg/kg/day	30 days
Tetrakis(2- hydroxypropyl)ethylenedia mine	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles eyes kidney and/or	Not classified	Rat	NOAEL 1,000 mg/kg/day	30 days

		bladder respiratory system vascular system				
M-xylene-alpha,alpha'- diamine	Ingestion	endocrine system blood bone marrow	Not classified	Rat	NOAEL 600 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Polyether Polyol	9082-00-2	Inland Silverside	Estimated	96 hours	LC50	650 mg/l
Propoxylated trimethylolprop ane	25723-16-4	Green algae	Experimental	72 hours	EC50	>100 mg/l
Propoxylated trimethylolprop ane	25723-16-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Propoxylated trimethylolprop ane	25723-16-4	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Propoxylated trimethylolprop ane	25723-16-4	Green algae	Experimental	72 hours	NOEC	100 mg/l
Propoxylated trimethylolprop ane	25723-16-4	Water flea	Experimental	21 days	NOEC	8.5 mg/l
Tetrakis(2- hydroxypropyl) ethylenediamin e	102-60-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Tetrakis(2- hydroxypropyl) ethylenediamin e	102-60-3	Water flea	Estimated	48 hours	EC50	>500 mg/l
Tetrakis(2- hydroxypropyl) ethylenediamin e	102-60-3	Fathead minnow	Experimental	96 hours	LC50	>1,000 mg/l
Tetrakis(2-	102-60-3	Green algae	Estimated	72 hours	Effect	16.1 mg/l

hydroxypropyl) ethylenediamin e					Concentration 10%	
M-xylene- alpha,alpha'- diamine	1477-55-0	Green Algae	Experimental	72 hours	EC50	28 mg/l
M-xylene- alpha,alpha'- diamine	1477-55-0	Ricefish	Experimental	96 hours	LC50	87.6 mg/l
M-xylene- alpha,alpha'- diamine	1477-55-0	Water flea	Experimental	48 hours	EC50	15.2 mg/l
M-xylene- alpha,alpha'- diamine	1477-55-0	Green Algae	Experimental	72 hours	NOEC	9.8 mg/l
M-xylene- alpha,alpha'- diamine	1477-55-0	Water flea	Experimental	21 days	NOEC	4.7 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Polyether	9082-00-2	Data not			N/A	
Polyol		availbl-				
-		insufficient				
Propoxylated	25723-16-4	Experimental	28 days	BOD	84 %	Other methods
trimethylolprop		Biodegradation			BOD/ThBOD	
ane						
Tetrakis(2-	102-60-3	Experimental	28 days	BOD	1 %	OECD 301C - MITI
hydroxypropyl)		Biodegradation			BOD/ThBOD	test (I)
ethylenediamin						
e						
M-xylene-	1477-55-0	Experimental	28 days	CO2 evolution	49 %CO2	OECD 301B - Modified
alpha,alpha'-		Biodegradation	-		evolution/THC	sturm or CO2
diamine		_			O2 evolution	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Polyether	9082-00-2	Data not	N/A	N/A	N/A	N/A
Polyol		available or				
		insufficient for				
		classification				
Propoxylated	25723-16-4	Experimental		Log Kow	1.8	Other methods
trimethylolprop		Bioconcentrati				
ane		on				
Tetrakis(2-	102-60-3	Experimental		Log Kow	0.27	Other methods
hydroxypropyl)		Bioconcentrati				
ethylenediamin		on				
e						
M-xylene-	1477-55-0	Experimental	42 days	Bioaccumulatio	<2.7	OECD 305E -
alpha,alpha'-		BCF-Carp		n factor		Bioaccumulation flow-
diamine		_				through fish test

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable. IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval numberHSR002670Group standard nameSurface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017HSNO Hazard classificationRefer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C substance);
	or 10,000 L or 10,000 kg (for a HSNO 6.6A, 6.8A, 6.9A, 8.3A, 9.1D
	substance)
Secondary containment	1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C substance);
	or 10,000 L or 10,000 kg (for a HSNO 6.6A, 6.8A, 6.9A, 8.3A, 9.1D
	substance)
Tracking	Not required
Warning signage	1,000 L or 1,000 kg (for a HSNO 8.3A, 9.1B or 9.1C substance); or 10,000 L
	or 10,000 kg (for a HSNO 6.1D or 9.1D substance)

SECTION 16: Other information

Revision information:

Complete document review.

Document group:	28-7005-3	Version number:	2.00
Issue Date:	28/09/2020	Supersedes date:	31/01/2017

Key to abbreviations and acronyms

GHS means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013 **HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz