



Safety Data Sheet

© 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 20-0585-8 **Version number:** 3.00
Issue Date: 09/06/2020 **Supersedes date:** 08/02/2016

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343E

Product Identification Numbers

70-2007-7077-7

1.2. Recommended use and restrictions on use

Recommended use

Skin protectant barrier film.

For Consumer or Professional use only

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Flammable Liquid: Category 2	3.1B Flammable Liquid
Aspiration Hazard: Category 1	6.1E Aspiration Hazard
Specific Target Organ Toxicity (single exposure): Category 3	6.9B Narcotic effects

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

Acute Aquatic Toxicity: Category 1	9.1A Aquatic toxicity (acute)
Chronic Aquatic Toxicity: Category 1	9.1A Aquatic toxicity (chronic)

2.2. Label elements

SIGNAL WORD

DANGER!

Symbols:

Flame | Exclamation mark | Health Hazard | Environment |

Pictograms



HAZARD STATEMENTS:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

- P210A Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240B Ground and bond container and receiving equipment.
- P242A Use non-sparking tools.
- P233 Keep container tightly closed.
- P243A Take action to prevent static discharges.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P280B Wear protective gloves and eye/face protection.
- P273 Avoid release to the environment.

Response:

- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P331 Do NOT induce vomiting.
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
- P370 + P378G In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.
- P303 + P361 + P353A IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Storage:

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

Disposal:

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Hexamethyldisiloxane	107-46-0	35 - 65
Isooctane	540-84-1	0 - 15
Acrylate Terpolymer	Trade Secret	1 - 8

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

No need for first aid is anticipated.

Eye contact

No need for first aid is anticipated.

If swallowed

Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: 1Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Do not get in eyes. Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Octane	540-84-1	ACGIH	TWA:300 ppm	
Octane	540-84-1	New Zealand WES	TWA(8 hours):1400 mg/m3(300 ppm);STEL(15 minutes):1750 mg/m3(375 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

CMRG : Chemical Manufacturer's Recommended Guidelines
New Zealand WES : New Zealand Workplace Exposure Standards.
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
ppm: parts per million
mg/m³: milligrams per cubic metre
CELL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Eye protection not required.

Skin/hand protection

No protective gloves required.

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Fluid on foam applicator or wipe.
Colour	Colourless
Odour	Odourless
Odour threshold	<i>No data available.</i>
pH	± 7 [<i>Details:</i> (For liquid portion)]
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	100 °C [<i>Test Method:</i> Tested per ASTM protocol] [<i>Details:</i> (For liquid portion)]
Flash point	-10 °C [<i>Test Method:</i> Closed Cup]
Evaporation rate	<=1 [<i>Test Method:</i> Tested per ASTM protocol] [<i>Ref Std:</i> ETHER=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	0.8 %
Flammable Limits(UEL)	14.1 %
Vapour pressure	<= 5,466.2 Pa

Vapour density	<i>Not applicable.</i>
Density	0.78 g/ml [<i>Details:</i> (For liquid portion)]
Relative density	0.78 [<i>Test Method:</i> Tested per ASTM protocol] [<i>Ref Std:</i> WATER=1]
Water solubility	<=0.1 % [<i>Test Method:</i> Tested per ASTM protocol]
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Autoignition temperature	351.7 °C
Decomposition temperature	<i>No data available.</i>
Viscosity	<i>Not applicable.</i>
Volatile organic compounds (VOC)	720 g/l [<i>Details:</i> (For liquid portion)]
Percent volatile	88 - 94 %
VOC less H2O & exempt solvents	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

and throat pain. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Chemical (aspiration) pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hexamethyldisiloxane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexamethyldisiloxane	Inhalation-Vapor (4 hours)	Rat	LC50 106 mg/l
Hexamethyldisiloxane	Ingestion	Rat	LD50 > 5,000 mg/kg
Isooctane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Isooctane	Inhalation-Vapor (4 hours)	Rat	LC50 > 33.5 mg/l
Isooctane	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	No significant irritation
Hexamethyldisiloxane	Rabbit	No significant irritation
Isooctane	Human and animal	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Hexamethyldisiloxane	Rabbit	Mild irritant
Isooctane	Rabbit	Mild irritant

Sensitisation:

Skin Sensitisation

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

Name	Species	Value
Hexamethyldisiloxane	Guinea pig	Not classified
Isooctane	Human	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hexamethyldisiloxane	In Vitro	Not mutagenic
Hexamethyldisiloxane	In vivo	Not mutagenic
Isooctane	In vivo	Not mutagenic
Isooctane	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hexamethyldisiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hexamethyldisiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 33 mg/l	13 weeks
Isooctane	Inhalation	Not classified for development	Rat	NOAEL 5.6 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hexamethyldisiloxane	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 33 mg/l	6 hours
Hexamethyldisiloxane	Ingestion	central nervous system depression	Not classified	Guinea pig	LOAEL 22,900 mg/kg	not applicable
Isooctane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
Isooctane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Isooctane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hexamethyldisiloxane	Dermal	liver kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Hexamethyldisiloxane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 33 mg/l	13 weeks

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

Hexamethyldisiloxane	Inhalation	liver	Not classified	Multiple animal species	NOAEL 29 mg/l	15 days
Hexamethyldisiloxane	Inhalation	heart endocrine system immune system nervous system respiratory system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Isooctane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Isooctane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 0.2 mg/l	1 years
Isooctane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL Not available	4 weeks
Isooctane	Ingestion	liver	Not classified	Rat	NOAEL 500 mg/kg/day	21 days

Aspiration Hazard

Name	Value
Isooctane	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Ecotoxic to the aquatic environment.

Acute Aquatic Toxicity: Category 1 (HSNO 9.1A Aquatic toxicity)

Chronic Aquatic Toxicity: Category 1 (HSNO 9.1A Aquatic toxicity)

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Hexamethyldisiloxane	107-46-0	Green Algae	Experimental	70 hours	EC50	>0.55 mg/l
Hexamethyldisiloxane	107-46-0	Rainbow trout	Experimental	96 hours	LC50	0.46 mg/l
Hexamethyldisiloxane	107-46-0	Green Algae	Experimental	70 hours	Effect Concentration 10%	0.09 mg/l
Hexamethyldisiloxane	107-46-0	Water flea	Experimental	21 days	NOEC	0.08 mg/l
Isooctane	540-84-1	Water flea	Estimated	48 hours	EC50	0.4 mg/l
Isooctane	540-84-1	Ricefish	Experimental	96 hours	LC50	0.561 mg/l
Acrylate Terpolymer	Trade Secret		Data not available or insufficient for classification			

12.2. Persistence and degradability

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hexamethyldisiloxane	107-46-0	Experimental Photolysis		Photolytic half-life (in air)	22.5 days (t _{1/2})	Other methods
Hexamethyldisiloxane	107-46-0	Experimental Hydrolysis		Hydrolytic half-life	120 hours (t _{1/2})	Other methods
Isooctane	540-84-1	Experimental Photolysis		Photolytic half-life (in air)	8.36 days (t _{1/2})	Other methods
Isooctane	540-84-1	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)
Acrylate Terpolymer	Trade Secret	Data not available - insufficient			N/A	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hexamethyldisiloxane	107-46-0	Experimental BCF-Carp	56 days	Bioaccumulation factor	2410	OECD 305C-Bioaccumulation degree fish
Isooctane	540-84-1	Experimental BCF-Carp	28 days	Bioaccumulation factor	540	OECD 305E - Bioaccumulation flow-through fish test
Acrylate Terpolymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: UN3175

Proper Shipping Name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , (Hexamethyldisiloxane and Isooctane)

Class/Division: 4.1

Sub Risk: Not applicable.

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

Packing Group: II

Special Instructions: Not restricted, as per Special Provision 216.

Hazchem Code: 1Z

IERG: 20

International Air Transport Association (IATA) - Air Transport

UN No.: UN3175

Proper Shipping Name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , (Hexamethyldisiloxane and Isooctane)

Class/Division: 4.1

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: IATA: Not subject to these regulations as per Special Provision A46

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: UN3175

Proper Shipping Name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. , (Hexamethyldisiloxane and Isooctane)

Class/Division: 4.1

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Hexamethyldisiloxane and Isooctane

Special Instructions: IMDG- Not subject to the provisions of this code as per Special Provision 216

SECTION 15: Regulatory information

HSNO Approval number HSR002552
Group standard name Cosmetic Products Group Standard 2017
HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	100 L (closed containers greater than 5 L) 250 L (closed containers up to and including 5 L) 50 L (open containers)
Hazardous atmosphere zone	100 L (closed containers) 25 L (decanting) 5 L (open occasionally) 1 L (open containers in continuous use)
Fire extinguishers	Two required for 250 L
Emergency response plan	100 L (for a HSNO 9.1A substance); or 1,000 L (for all other HSNO 3.1B substances)
Secondary containment	100 L (for a HSNO 9.1A substance); or 1,000 L (for all other HSNO 3.1B substances)
Tracking	Not required
Warning signage	100 L (for a HSNO 9.1A substance); or 250 L (for all other HSNO 3.1B substances)

SECTION 16: Other information

Revision information:

Complete document review.

Document group:	20-0585-8	Version number:	3.00
------------------------	-----------	------------------------	------

3M™ Cavilon™ No Sting Barrier Film with Foam Applicator (IO) 3343, 3344, 3345, 3343E, 3344E, 3345E, 3343P, 3345P, 3343K, 3344ENS

Issue Date:	09/06/2020	Supersedes date:	08/02/2016
--------------------	------------	-------------------------	------------

Key to abbreviations and acronyms

GHS means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>