

# Safety Data Sheet

 $\odot$  2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	34-6120-9	Version number:	2.00
Issue Date:	04/08/2020	Supersedes date:	17/05/2016

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>™</sup> Perfect-It<sup>™</sup> Gelcoat Light Cutting Polish + Wax 36109, 36110

 Product Identification
 Numbers

 60-4550-8607-8
 60-4550-8608-6

#### 1.2. Recommended use and restrictions on use

## Recommended use

Surface Refinishing Product, Marine

For Industrial or Professional use only

#### 1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

## **SECTION 2: Hazard identification**

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

## 2.1. Classification of the substance or mixture

GHS	HSNO		
Chronic Aquatic Toxicity: Category 3	9.1C Aquatic toxicity (chronic)		
Acute Aquatic Toxicity: Category 3	9.1D Aquatic toxicity (acute)		
No GHS Equivalent	9.4C Terrestrial invertebrate toxicity		

## **2.2. Label elements SIGNAL WORD** Not applicable.

#### **Symbols:** Not applicable.

HAZARD STATEMENTS:	
H412	Harmful to aquatic life with long lasting effects.
H443	Harmful to terrestrial invertebrates.

## PRECAUTIONARY STATEMENTS

# Prevention:

P273

Avoid release to the environment.

## **Disposal:**

P501

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

Repeated exposure may cause skin dryness or cracking.

# **SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	30 - 60
Aluminium oxide	1344-28-1	10 - 30
Polyethylene Glycol Sorbitan Monooleate	9005-65-6	3 - 7
Poly(Dimethylsiloxane)	63148-62-9	1 - 5
Amino Alkyl Polysiloxane	Trade Secret	1 - 5
Glycerin	56-81-5	0.5 - 1.5
Polyethylene-Polypropylene Glycol	9003-11-6	0.5 - 1.5

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## Inhalation

No need for first aid is anticipated.

## Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

## Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

## If swallowed

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

#### **4.3. Indication of any immediate medical attention and special treatment required** Not applicable

# **SECTION 5:** Fire-fighting measures

**5.1. Suitable extinguishing media** Material will not burn.

**5.2. Special hazards arising from the substance or mixture** None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide. Carbon dioxide. <u>Condition</u> During combustion. During combustion.

## 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

**5.4. Hazchem code:** Not applicable.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

Refer to Section 15 - Controls for more information

#### 7.1. Precautions for safe handling

Avoid eye contact. Keep out of reach of children. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

#### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## 7.3. Certified handler

Not required

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Aluminium oxide	1344-28-1	New Zealand	TWA(8 hours):10 mg/m3	
		WES		
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcinogin
Glycerin	56-81-5	New Zealand	TWA(as mist)(8 hours):10	
		WES	mg/m3	
ACGIH : American Conference of Governi	mental Industrial	Hygienists		
AIHA : American Industrial Hygiene Asso	ciation			

AIHA : American Industrial Hygiene Association CMRG : Chemical Manufacturer's Recommended Guidelines New Zealand WES : New Zealand Workplace Exposure Standards. TWA: Time-Weighted-Average STEL: Short Term Exposure Limit ppm: parts per million mg/m<sup>3</sup>; milligrams per cubic metre CEIL: Ceiling

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

No engineering controls required.

## 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used:Nitrile rubber.

## **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

Physical state	Liquid.	
Specific Physical Form:	Gel	
Colour	White	
Odour	Slight Solvent	
Odour threshold	No data available.	
рН	8 - 9.2	
Melting point/Freezing point	No data available.	
Boiling point/Initial boiling point/Boiling range	No data available.	
Flash point	No flash point	
Evaporation rate	No data available.	
Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapor Density and/or Relative Vapor Density	No data available.	
Density	1.1 - 1.1 kg/l	
Relative density	1.07 - 1.12 [ <i>Ref Std</i> :WATER=1]	
Water solubility	No data available.	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Viscosity/Kinematic Viscosity	20,000 - 75,000 mPa-s [Test Method:Brookfield]	
Volatile organic compounds (VOC)	14.5 % weight [ <i>Test Method</i> :calculated per CARB title 2]	
Percent volatile	71.2 % weight	
VOC less H2O & exempt solvents	417 g/l [Test Method:calculated SCAQMD rule 443.1]	

## 9.1. Information on basic physical and chemical properties

## Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

## **10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

## 10.2 Chemical stability

Stable.

## **10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

# **10.4 Conditions to avoid** None known.

**10.5 Incompatible materials** None known.

## 10.6 Hazardous decomposition products

Substance None known. **Condition** 

Refer to Section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects** 

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

No known health effects.

## Skin contact

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

### Eye contact

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Polyethylene Glycol Sorbitan Monooleate	Dermal	Not available	LD50 > 5,000 mg/kg
Polyethylene Glycol Sorbitan Monooleate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l
Polyethylene Glycol Sorbitan Monooleate	Ingestion	Rat	LD50 20,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Polyethylene-Polypropylene Glycol	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Polyethylene-Polypropylene Glycol	Ingestion	Rat	LD50 5,700 mg/kg
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

## **Skin Corrosion/Irritation**

Name	Species	Value

## **3MTM** Perfect-It<sup>TM</sup> Gelcoat Light Cutting Polish + Wax 36109, 36110, 36111

Aluminium oxide	Rabbit	No significant irritation
Polyethylene Glycol Sorbitan Monooleate	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation

## **Serious Eye Damage/Irritation**

Name	Species	Value
Aluminium oxide	Rabbit	No significant irritation
Polyethylene Glycol Sorbitan Monooleate	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Glycerin	Rabbit	No significant irritation

## Sensitisation:

## **Skin Sensitisation**

Name	Species	Value
Polyethylene Glycol Sorbitan Monooleate	Guinea pig	Not classified
Glycerin	Guinea pig	Not classified

## **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Germ Cell Mutagenicity

Name	Route	Value
Aluminium oxide	In Vitro	Not mutagenic
Polyethylene Glycol Sorbitan Monooleate	In Vitro	Not mutagenic

## Carcinogenicity

Name	Route	Species	Value
Aluminium oxide	Inhalation	Rat	Not carcinogenic
Polyethylene Glycol Sorbitan Monooleate	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification

## **Reproductive Toxicity**

## **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Polyethylene Glycol Sorbitan Monooleate	Ingestion	Not classified for female reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Polyethylene Glycol Sorbitan Monooleate	Ingestion	Not classified for male reproduction	Rat	NOAEL 6,666 mg/kg/day	3 generation
Polyethylene Glycol Sorbitan Monooleate	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesis
Glycerin	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation

## 3M<sup>TM</sup> Perfect-It<sup>TM</sup> Gelcoat Light Cutting Polish + Wax 36109, 36110, 36111

Glycerin	Ingestion	Not classified for development	Rat	NOAEL 2,000	2 generation
				mg/kg/day	

## Target Organ(s)

## Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Polyethylene Glycol Sorbitan Monooleate	Ingestion	heart   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 4,132 mg/kg/day	90 days
Glycerin	Inhalation	respiratory system   heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 years

#### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

#### 12.1. Toxicity

**Ecotoxic to the aquatic environment.** Acute Aquatic Toxicity: Category 3 (HSNO 9.1D Aquatic toxicity) Chronic Aquatic Toxicity: Category 3 (HSNO 9.1C Aquatic toxicity)

## Ecotoxic to terrestrial invertebrates

9.4C Terrestrial invertebrate toxicity

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Aluminium	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
oxide						
Aluminium	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
oxide		~				
Aluminium	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
oxide						
Aluminium	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l
oxide	0005 65 6	G 1		40.1		. 10.000 /1
Polyethylene	9005-65-6	Copepods	Estimated	48 hours	Lethal Level	>10,000 mg/l
Glycol Sorbitan Monooleate					50%	
Polyethylene	9005-65-6	Green Algae	Estimated	72 hours	Effect Level	58.84 mg/l
Glycol Sorbitan		Oleen Algae	Estimated	72 110015	50%	50.04 mg/1
Monooleate					5070	
Polyethylene	9005-65-6	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Glycol Sorbitan				50 110 410	2000	100
Monooleate						
Polyethylene	9005-65-6	Green Algae	Estimated	72 hours	Effect	19.05 mg/l
Glycol Sorbitan					Concentration	
Monooleate					10%	
Polyethylene	9005-65-6	Water flea	Estimated	21 days	No obs Effect	10 mg/l
Glycol Sorbitan					Level	
Monooleate						
Poly(Dimethyls	63148-62-9		Data not			
iloxane)			available or			
			insufficient for			
Classerin	56-81-5	Dainhan trant	classification	96 hours	LC50	54,000 m c/l
Glycerin		Rainbow trout Water flea	Experimental	48 hours	LC50 LC50	54,000 mg/l
Glycerin Polyethylene-	56-81-5 9003-11-6	water nea	Experimental Data not	48 nours		1,955 mg/l
Polypropylene	9003-11-0		available or			
Glycol			insufficient for			
Giycol			classification			
L	1	1	elussification	1	1	

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Aluminium	1344-28-1	Data not			N/A	
oxide		availbl-				
		insufficient				
Polyethylene	9005-65-6	Experimental	28 days	CO2 evolution	61 % weight	Other methods
Glycol Sorbitan		Biodegradation				
Monooleate						
Poly(Dimethyls	63148-62-9	Data not			N/A	
iloxane)		availbl-				
		insufficient				
Glycerin	56-81-5	Experimental	14 days	BOD	63 %	OECD 301C - MITI
		Biodegradation	-		BOD/ThBOD	test (I)
Polyethylene-	9003-11-6	Data not			N/A	
Polypropylene		availbl-				
Glycol		insufficient				

## **12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Aluminium	1344-28-1	Data not	N/A	N/A	N/A	N/A
oxide		available or				
		insufficient for				
		classification				
Polyethylene	9005-65-6	Data not	N/A	N/A	N/A	N/A
Glycol Sorbitan		available or				
Monooleate		insufficient for				
		classification				
Poly(Dimethyls	63148-62-9	Data not	N/A	N/A	N/A	N/A
iloxane)		available or				
		insufficient for				
		classification				
Glycerin	56-81-5	Experimental		Log Kow	-1.76	Other methods
		Bioconcentrati				
		on				
Polyethylene-	9003-11-6	Data not	N/A	N/A	N/A	N/A
Polypropylene		available or				
Glycol		insufficient for				
		classification				

### 12.4. Mobility in soil

Please contact manufacturer for more details

## 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## **13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

# **SECTION 14: Transport Information**

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable. IERG: Not applicable. International Air Transport Association (IATA) - Air Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable.

## **SECTION 15: Regulatory information**

HSNO Approval numberHSR002670Group standard nameSurface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017HSNO Hazard classificationRefer to Section 2: Hazard identification

## NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017						
Certified handler	Not required					
Location Compliance Certificate	Not required					
Hazardous atmosphere zone	Not required					
Fire extinguishers	Not required					
Emergency response plan	1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C					
	substance); or 10,000 L or 10,000 kg (for a HSNO 6.6A, 6.8A, 6.9A, 8.3A, 9.1D substance)					
Secondary containment	1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for a HSNO 6.6A, 6.8A, 6.9A,					
	8.3A, 9.1D substance)					
Tracking	Not required					
Warning signage	1,000 L or 1,000 kg (for a HSNO 8.3A, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for a HSNO 6.1D or 9.1D substance)					

# **SECTION 16: Other information**

## **Revision information:**

Complete document review.

Document group:	34-6120-9	Version number:	2.00
Issue Date:	04/08/2020	Supersedes date:	17/05/2016

#### Key to abbreviations and acronyms

**GHS** means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013 **HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED

TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz