

## **Safety Data Sheet**

 $\odot$  2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	34-6342-9	Version number:	2.00
Issue Date:	04/08/2020	Supersedes date:	17/05/2016

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

## **SECTION 1: Identification**

**1.1. Product identifier** 3M<sup>™</sup> Perfect-It<sup>™</sup> Boat Wax 36112 36113

 Product Identification
 Numbers

 60-4550-8610-2
 60-4550-8611-0

#### 1.2. Recommended use and restrictions on use

**Recommended use** Surface Refinishing Product. Marine

For Industrial or Professional use only

#### **1.3.** Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

## **SECTION 2: Hazard identification**

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

### 2.1. Classification of the substance or mixture

GHS	HSNO	
Carcinogenicity: Category 2	6.7B Suspected human carcinogen	
No GHS Equivalent	9.4B Terrestrial invertebrate toxicity	

## 2.2. Label elements

## SIGNAL WORD WARNING!

Symbols: Health Hazard | Environment |

Pictograms



HAZARD STATEMENTS:	
H351	Suspected of causing cancer.
H442	Toxic to terrestrial invertebrates

## PRECAUTIONARY STATEMENTS

<b>Prevention:</b> P201 P202 P280E P273	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Avoid release to the environment.
<b>Response:</b> P308 + P313 P391	IF exposed or concerned: Get medical advice/attention. Collect spillage.
Storage: P405	Store locked up.
<b>Disposal:</b> P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Other hazards

Repeated exposure may cause skin dryness or cracking.

# **SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	50 - 70
Kaolin, calcined	92704-41-1	3 - 7
Carnauba Wax	8015-86-9	1 - 5
Poly(Dimethylsiloxane)	63148-62-9	1 - 5
Synthetic Hydrocarbon Mixture	Trade Secret	0.5 - 1.5
White Mineral Oil (Petroleum)	8042-47-5	< 1

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you are concerned, get medical advice.

#### Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye contact

No need for first aid is anticipated.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

#### **4.3. Indication of any immediate medical attention and special treatment required** Not applicable

## **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Formaldehyde	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.
Irritant vapours or gases.	During combustion.

#### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**5.4. Hazchem code:** Not applicable.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2.** Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and

water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## **SECTION 7: Handling and storage**

Refer to Section 15 - Controls for more information

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents.

### 7.3. Certified handler

Not required

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b> Mineral oils, highly-refined oils	CAS Nbr 8042-47-5	8 .
Paraffin oil	8042-47-5	New Zealand WES

ACGIH : American Conference of Governmental Industrial Hygienists AIHA : American Industrial Hygiene Association CMRG : Chemical Manufacturer's Recommended Guidelines New Zealand WES : New Zealand Workplace Exposure Standards. TWA: Time-Weighted-Average STEL: Short Term Exposure Limit ppm: parts per million mg/m<sup>3</sup>: milligrams per cubic metre CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection None required.

#### **Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

Limit type TWA(inhalable fraction):5 mg/m3 TWA(as mist)(8 hours):5 mg/m3;STEL(as mist)(15 minutes):10 mg/m3

Additional comments A4: Not class. as human carcinogin

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used:Nitrile rubber.

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

. Information on basic physical and chemical properties		
Physical state	Liquid.	
Colour	Light Yellow	
Odour	Banana	
Odour threshold	No data available.	
рН	7.5 - 8.5	
Melting point/Freezing point	Not applicable.	
Boiling point/Initial boiling point/Boiling range	198.9 °C	
Flash point	Flash point > 93 °C (200 °F)	
Evaporation rate	No data available.	
Flammability (solid, gas)	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapour pressure	No data available.	
Vapor Density and/or Relative Vapor Density	No data available.	
Density	950 - 986 g/l	
Relative density	0.95 - 0.986 [ <i>Ref Std</i> :WATER=1]	
Water solubility	Moderate	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Viscosity/Kinematic Viscosity	17,000 - 30,000 mPa-s [@ 25 °C ]	
Volatile organic compounds (VOC)	14.8 % weight [ <i>Test Method</i> :calculated per CARB title 2]	
Percent volatile	85.6 % weight [Test Method:Estimated]	
VOC less H2O & exempt solvents	503 g/l [Test Method:calculated SCAQMD rule 443.1]	

#### Nanoparticles

This material does not contain nanoparticles.

# **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

## 10.2 Chemical stability

Stable.

#### **10.3 Possibility of hazardous reactions** Hazardous polymerisation will not occur.

### **10.4 Conditions to avoid**

Temperatures above the boiling point.

### **10.5 Incompatible materials**

Strong acids. Strong bases. Strong oxidising agents.

### 10.6 Hazardous decomposition products

<u>Substance</u>

None known.

### **Condition**

Refer to Section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects** 

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

May cause additional health effects (see below).

## Skin contact

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

## Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### **Additional Health Effects:**

### **Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
Carnauba Wax	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Carnauba Wax	Ingestion	Rat	LD50 > 8,800 mg/kg
White Mineral Oil (Petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
White Mineral Oil (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
ATE - a suta taminita antimata			

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name	Species	Value
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Carnauba Wax	Professio	No significant irritation
	nal	
	judgemen	
	t	
White Mineral Oil (Petroleum)	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Carnauba Wax	Professio	No significant irritation
	nal	
	judgemen	
	t	
White Mineral Oil (Petroleum)	Rabbit	Mild irritant

### Sensitisation:

#### **Skin Sensitisation**

Name	Species	Value
White Mineral Oil (Petroleum)	Guinea	Not classified
	pig	

### **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
White Mineral Oil (Petroleum)	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
White Mineral Oil (Petroleum)	Dermal	Mouse	Not carcinogenic
White Mineral Oil (Petroleum)	Inhalation	Multiple	Not carcinogenic
		animal	
		species	

#### **Reproductive Toxicity**

### **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
White Mineral Oil (Petroleum)	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
White Mineral Oil (Petroleum)	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation

#### Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
White Mineral Oil (Petroleum)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
White Mineral Oil (Petroleum)	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days

#### **Aspiration Hazard**

Name	Value
White Mineral Oil (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

## 12.1. Toxicity

### Ecotoxic to terrestrial invertebrates

9.4B Terrestrial invertebrate toxicity

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	EC50	2,500 mg/l
Kaolin, calcined	92704-41-1	Water flea	Estimated	48 hours	EC50	>100 mg/l
Kaolin, calcined	92704-41-1	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Kaolin, calcined	92704-41-1	Green algae	Estimated	72 hours	Effect Concentration 10%	41 mg/l
Kaolin, calcined	92704-41-1	Rainbow trout	Estimated	30 days	NOEC	>100 mg/l
Carnauba Wax	8015-86-9		Data not available or insufficient for classification			
Poly(Dimethyls iloxane)	63148-62-9		Data not available or insufficient for classification			
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Bluegill	Experimental	96 hours	Lethal Level 50%	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
White Mineral Oil (Petroleum)	8042-47-5	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l

# 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Kaolin,	92704-41-1	Data not			N/A	
calcined		availbl-				
		insufficient				
Carnauba Wax	8015-86-9	Estimated	28 days	CO2 evolution	96 % weight	OECD 301B - Modified
		Biodegradation				sturm or CO2
Poly(Dimethyls	63148-62-9	Data not			N/A	
iloxane)		availbl-				
		insufficient				
White Mineral	8042-47-5	Experimental	28 days	CO2 evolution	0 % weight	OECD 301B - Modified
Oil (Petroleum)		Biodegradation				sturm or CO2

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Kaolin,	92704-41-1	Data not	N/A	N/A	N/A	N/A
calcined		available or				
		insufficient for				
		classification				
Carnauba Wax	8015-86-9	Estimated		Bioaccumulatio	7.4	Estimated:
		Bioconcentrati		n factor		Bioconcentration factor
		on				
Poly(Dimethyls	63148-62-9	Data not	N/A	N/A	N/A	N/A

iloxane)	available or insufficient for classification				
White Mineral Oil (Petroleum)	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

### 12.4. Mobility in soil

Please contact manufacturer for more details

## 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

# **SECTION 14: Transport Information**

## New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable. IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport UN No.: Not applicable. Proper Shipping Name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

## International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.
Proper Shipping Name: Not applicable.
Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.
Marine Pollutant: Not applicable.

# **SECTION 15: Regulatory information**

HSNO Approval numberHSR002679Group standard nameSurface Coatings and Colourants (Toxic [6.7]) Group Standard 2017HSNO Hazard classificationRefer to Section 2: Hazard identification

## NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

#### Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	10,000 L or 10,000 kg (for all other substances)
Secondary containment	10,000 L or 10,000 kg (for all other substances)
Tracking	Not required
Warning signage	Not required

# **SECTION 16: Other information**

### **Revision information:**

Complete document review.

Document group:	34-6342-9	Version number:	2.00
Issue Date:	04/08/2020	Supersedes date:	17/05/2016

### Key to abbreviations and acronyms

**GHS** means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013 **HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

### 3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz