

Safety Data Sheet

© 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 34-6746-1
 Version number:
 3.00

 Issue Date:
 21/03/2024
 Supersedes date:
 13/07/2022

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3MTM CavilonTM Advanced Skin Protectant 5050, 5050G, 5050G4P, 5051, 5051G, 5051C, 5051GP, 5051G4P

Product Identification Numbers

70-2007-8927-2 70-2011-8944-9

1.2. Recommended use and restrictions on use

Recommended use

Skin Protectant

For Professional use only

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland

Telephone: (09) 477 4040

E Mail: innovation@nz.mmm.com

Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquids: Category 2 Eye irritation: Category 2

Hazardous to the aquatic environment acute: Category 1 Hazardous to the aquatic environment chronic: Category 1

2.2. Label elements SIGNAL WORD

Danger

Symbols:

Flame |Exclamation mark |

Pictograms





HAZARD STATEMENTS:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337 + P313 IF eye irritation persists: Get medical advice/attention.

P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry

chemical or carbon dioxide to extinguish.

P391 Collect spillage.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

This material has been tested for eye damage/irritation and the test results are reflected in the assigned classification.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
1151 041011	01101101	70 kg 11 cagaze

Hexamethyldisiloxane	107-46-0	80 - 90
Acrylic Polymer	Trade Secret	5 - 10
2-Octyl Cyanoacrylate	133978-15-1	5 - 10

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eve contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxide.During combustion.Carbon dioxide.During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: -3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Avoid eye contact. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended:

Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

information on basic physical and chemical propertie	23
Physical state	Liquid.
Colour	Colourless
Odour	Slight Odour
Odour threshold	Not applicable.
pH	Not applicable.
Melting point/Freezing point	-59 ℃
Boiling point/Initial boiling point/Boiling range	101 °C
Flash point	-8.3 °C [Test Method:Closed Cup]
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	0.5 %
Flammable Limits(UEL)	21.8 %
Vapour pressure	Not applicable.
Vapor Density and/or Relative Vapor Density	5.61 [<i>Ref Std</i> :AIR=1]
Density	0.77 g/ml
Relative density	0.77
Water solubility	Not applicable.
Solubility- non-water	Not applicable.
Partition coefficient: n-octanol/water	Not applicable.
Autoignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity/Kinematic Viscosity	Not applicable.
Volatile organic compounds (VOC)	No data available.
Percent volatile	No data available.
VOC less H2O & exempt solvents	No data available.
Molecular weight	Not applicable.
	L

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eve contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hexamethyldisiloxane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexamethyldisiloxane	Inhalation-	Rat	LC50 106 mg/l
	Vapor (4		
	hours)		
Hexamethyldisiloxane	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
------	---------	-------

Overall product	Rabbit	No significant irritation
Hexamethyldisiloxane	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	In vitro data	Severe irritant
Hexamethyldisiloxane	Rabbit	Mild irritant

Sensitisation:

Skin Sensitisation

Name	Species	Value
Overall product	Human	Not classified
Hexamethyldisiloxane	Guinea	Not classified
	pig	

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Germ Cen Mungementy		
Name	Route	Value
77 4 17 7	T 77'4	N
Hexamethyldisiloxane	In Vitro	Not mutagenic
Hexamethyldisiloxane	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hexamethyldisiloxane	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

reproductive und, or Developmenta	Liletts				
Name	Route	Value	Species	Test result	Exposure Duration
Hexamethyldisiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 33 mg/l	13 weeks

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hexamethyldisiloxane	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 33 mg/l	6 hours
Hexamethyldisiloxane	Ingestion	central nervous system depression	Not classified	Guinea pig	LOAEL 22,900 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Specific Target Organ Toxicity - repeated exposure							
Name	Route	Target Organ(s)	Value	Species	Test result	Exposure	
						Duration	
Overall product	Dermal	heart skin endocrine system bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 63 mg/cm2/day	90 days	

Dagg. 7 of 11

		hematopoietic system liver immune system muscles nervous system kidney and/or bladder respiratory system vascular system				
Hexamethyldisiloxane	Dermal	liver kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Hexamethyldisiloxane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	liver	Not classified	Multiple animal species	NOAEL 29 mg/l	15 days
Hexamethyldisiloxane	Inhalation	heart endocrine system immune system nervous system respiratory system	Not classified	Rat	NOAEL 33 mg/l	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Ecotoxic to the aquatic environment.

Acute Aquatic Toxicity: Category 1 Chronic Aquatic Toxicity: Category 1

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Hexamethyldisi loxane	107-46-0	Green algae	Experimental	70 hours	ErC50	>0.55 mg/l
Hexamethyldisi loxane	107-46-0	Rainbow trout	Experimental	96 hours	LC50	0.46 mg/l
Hexamethyldisi loxane	107-46-0	Green algae	Experimental	70 hours	ErC10	0.09 mg/l
Hexamethyldisi loxane	107-46-0	Water flea	Experimental	21 days	NOEC	0.08 mg/l
2-Octyl Cyanoacrylate	133978-15-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hexamethyldisi	107-46-0	Experimental		Photolytic half-	22.5 days (t	
loxane		Photolysis		life (in air)	1/2)	
Hexamethyldisi	107-46-0	Experimental		Hydrolytic	120 hours (t	
loxane		Hydrolysis		half-life (pH 7)	1/2)	
2-Octyl	133978-15-1	Data not	N/A	N/A	N/A	N/A
Cyanoacrylate		availbl-				
		insufficient				

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hexamethyldisi	107-46-0	Experimental	56 days	Bioaccumulatio	2410	OECD305-
loxane		BCF - Fish		n factor		Bioconcentration
Hexamethyldisi loxane	107-46-0	Experimental Bioconcentrati on		Log Kow	4.2	
2-Octyl Cyanoacrylate	133978-15-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: UN1866

Proper Shipping Name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable. Packing Group: II

Special Instructions: Limited quantity may apply

Hazchem Code: -3YE

IERG: 14

International Air Transport Association (IATA) - Air Transport

UN No.: UN1866

Proper Shipping Name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable. Packing Group: II

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: UN1866

Proper Shipping Name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable. **Packing Group:** II

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

HSNO Approval number HSR002552

Group standard name Cosmetic Products Group Standard 2020 HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler Not required

Location Compliance Certificate 100 L (closed containers greater than 5 L) 250 L (closed containers up to and

including 5 L) 50 L (open containers)

Hazardous atmosphere zone 100 L (closed containers) 25 L (decanting) 5 L (open occasionally) 1 L

(open containers in continuous use)

Fire extinguishers Two required for 250 L

Emergency response plan 100 L (for Hazardous to the aquatic environment Category 1 substances); or 1

000 L (for all other Flammable liquid Category 2 substances)

Secondary containment 100 L (for Hazardous to the aquatic environment Category 1 substances); or 1

000 L (for all other Flammable liquid Category 2 substances)

Tracking Not required

Warning signage 100 L (for Hazardous to the aquatic environment Category 1 substances); or

250 L (for all other Flammable liquid Category 2 substances)

SECTION 16: Other information

Revision information:

Complete document review.

Document group:	34-6746-1	Version number:	3.00
Issue Date:	21/03/2024	Supersedes date:	13/07/2022

Key to abbreviations and acronyms

GHS refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017 HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: http://solutions.3mnz.co.nz