



## Safety Data Sheet

© 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	34-3734-0	<b>Version number:</b>	3.00
<b>Issue Date:</b>	19/11/2023	<b>Supersedes date:</b>	02/05/2021

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

### IDENTIFICATION:

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Low Odour Acrylic Adhesive DP8810NS Green

#### Product Identification Numbers

62-2854-1446-2

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive

#### 1.3. Supplier's details

**Address:** 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland  
**Telephone:** (09) 477 4040  
**E Mail:** innovation@nz.mmm.com  
**Website:** 3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:**

34-3730-8, 34-3732-4

One or more components of this KIT is classified as a hazardous substance in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

### TRANSPORT INFORMATION

NOT HAZARDOUS FOR TRANSPORT

#### Revision information:

Complete document review.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>**



## Safety Data Sheet

© 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	34-3730-8	<b>Version number:</b>	2.00
<b>Issue Date:</b>	19/11/2023	<b>Supersedes date:</b>	01/09/2020

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green and Low Odor Acrylic Adhesive 8810NS Green, Part B

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive, Activator for 2-part acrylic adhesive

For Industrial or Professional use only

#### 1.3. Supplier's details

**Address:** 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland

**Telephone:** (09) 477 4040

**E Mail:** innovation@nz.mmm.com

**Website:** 3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

### SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Eye irritation: Category 2

Skin sensitisation: Category 1

Reproductive Toxicity: Category 1

Hazardous to the aquatic environment chronic: Category 3

#### 2.2. Label elements

##### SIGNAL WORD

Danger

**Symbols:**

Exclamation mark |Health Hazard |

**Pictograms**



**HAZARD STATEMENTS:**

H319 Causes serious eye irritation.  
 H317 May cause an allergic skin reaction.  
 H360 May damage fertility or the unborn child.  
 H412 Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS**

**Prevention**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P264 Wash thoroughly after handling.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280K Wear protective gloves and respiratory protection.

**Response**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P337 + P313 IF eye irritation persists: Get medical advice/attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage**

P405 Store locked up.

**Disposal**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	% by Weight
Tetrahydrofurfuryl Methacrylate	2455-24-5	25 - 45
Kaolin	1332-58-7	1 - 20
Butadiene-Acrylonitrile Polymer	9003-18-3	1 - 20
Hydroxyethyl Methacrylate	868-77-9	1 - 20
Isobornyl Methacrylate	7534-94-3	5 - 15
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	0.1 - 10
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	95175-93-2	< 3

Tetrahydrofurfuryl alcohol	97-99-4	< 0.3
Copper Naphthenates	1338-02-9	< 0.1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide.

Carbon dioxide.

Oxides of nitrogen.

#### Condition

During combustion.

During combustion.

During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

Refer to Section 15 - Controls for more information

**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

**7.3. Certified handler**

Not required

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Kaolin	1332-58-7	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcinogen
Kaolin	1332-58-7	New Zealand WES	TWA(as respirable dust)(8 hours):2 mg/m3;TWA(8 hours):10 mg/m3	
Copper compounds	1338-02-9	ACGIH	TWA(as Cu, fume):0.2 mg/m3;TWA(as Cu dust or mist):1 mg/m3	
Tetrahydrofurfuryl alcohol	97-99-4	AIHA	TWA:2 mg/m3(0.5 ppm)	Skin

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 New Zealand WES : New Zealand Workplace Exposure Standards.  
 TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit  
 ppm: parts per million  
 mg/m<sup>3</sup>: milligrams per cubic metre  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety glasses with side shields.
- Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

- Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	White
<b>Odour</b>	Acrylate
<b>Odour threshold</b>	No data available.

pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	$\geq 37.8$ °C
Flash point	$> 93.3$ °C [Test Method: Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	1.13 g/ml
Relative density	1.13 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	100,000 - 125,000 mPa-s
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>
VOC less H <sub>2</sub> O & exempt solvents	4.8 g/l [Details: when used as intended with Part A]
VOC less H <sub>2</sub> O & exempt solvents	612 g/l [Details: as supplied]
VOC less H <sub>2</sub> O & exempt solvents	0.5 % [Details: when used as intended with Part A]
Molecular weight	<i>Not applicable.</i>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

### 10.6 Hazardous decomposition products

#### Substance

None known.

#### Condition

Refer to Section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information



The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

##### Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

##### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

##### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### Additional Health Effects:

##### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Tetrahydrofurfuryl Methacrylate	Ingestion	Rat	LD50 4,000 mg/kg
Tetrahydrofurfuryl Methacrylate	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Butadiene-Acrylonitrile Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Butadiene-Acrylonitrile Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Isobornyl Methacrylate	Dermal	Rabbit	LD50 > 3,000 mg/kg
Isobornyl Methacrylate	Ingestion	Rat	LD50 3,100 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	Dermal	Rat	LD50 > 2,000 mg/kg

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green and Low Odor Acrylic Adhesive 8810NS Green, Part B**

Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	Ingestion	Rat	LD50 > 35,000 mg/kg
Poly[oxy(methyl-1,2-ethanediy)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly[oxy(methyl-1,2-ethanediy)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Tetrahydrofurfuryl alcohol	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Tetrahydrofurfuryl alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 > 3.1 mg/l
Tetrahydrofurfuryl alcohol	Ingestion	Rat	LD50 > 2,000 mg/kg
Copper Naphthenates	Dermal	similar compounds	LD50 > 2,000 mg/kg
Copper Naphthenates	Ingestion	similar compounds	LD50 >300, < 2,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Tetrahydrofurfuryl Methacrylate	Rabbit	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Minimal irritation
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation
Isobornyl Methacrylate	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	Rabbit	Minimal irritation
Poly[oxy(methyl-1,2-ethanediy)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Not available	Irritant
Tetrahydrofurfuryl alcohol	Rabbit	No significant irritation
Copper Naphthenates	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Tetrahydrofurfuryl Methacrylate	Rabbit	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Moderate irritant
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation
Isobornyl Methacrylate	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	Rabbit	No significant irritation
Poly[oxy(methyl-1,2-ethanediy)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Not available	Corrosive
Tetrahydrofurfuryl alcohol	Rabbit	Severe irritant
Copper Naphthenates	In vitro data	No significant irritation

**Sensitisation:**

**Skin Sensitisation**

Name	Species	Value
Tetrahydrofurfuryl Methacrylate	In vitro data	Sensitising
Hydroxyethyl Methacrylate	Human and animal	Sensitising
Isobornyl Methacrylate	Guinea pig	Not classified
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	Guinea pig	Not classified
Tetrahydrofurfuryl alcohol	Mouse	Not classified
Copper Naphthenates	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Tetrahydrofurfuryl Methacrylate	In Vitro	Not mutagenic
Hydroxyethyl Methacrylate	In vivo	Not mutagenic
Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Isobornyl Methacrylate	In Vitro	Not mutagenic
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	In Vitro	Not mutagenic
Tetrahydrofurfuryl alcohol	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Kaolin	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Tetrahydrofurfuryl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	29 days
Tetrahydrofurfuryl Methacrylate	Ingestion	Toxic to female reproduction	Rat	NOAEL 120 mg/kg/day	premating into lactation
Tetrahydrofurfuryl Methacrylate	Ingestion	Toxic to development	Rat	NOAEL 120 mg/kg/day	premating into lactation
Hydroxyethyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Hydroxyethyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxyethyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Isobornyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
Isobornyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	4 weeks
Isobornyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	premating into lactation

Tetrahydrofurfuryl alcohol	Ingestion	Toxic to female reproduction	Rat	NOAEL 50 mg/kg/day	prematuring into lactation
Tetrahydrofurfuryl alcohol	Dermal	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	13 weeks
Tetrahydrofurfuryl alcohol	Ingestion	Toxic to male reproduction	Rat	NOAEL 150 mg/kg/day	47 days
Tetrahydrofurfuryl alcohol	Inhalation	Toxic to male reproduction	Rat	NOAEL 0.6 mg/l	90 days
Tetrahydrofurfuryl alcohol	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	prematuring into lactation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Isobornyl Methacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Tetrahydrofurfuryl alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tetrahydrofurfuryl Methacrylate	Ingestion	hematopoietic system   nervous system	Not classified	Rat	NOAEL 300 mg/kg/day	29 days
Isobornyl Methacrylate	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	90 days
Isobornyl Methacrylate	Ingestion	endocrine system   hematopoietic system   kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Tetrahydrofurfuryl alcohol	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	90 days
Tetrahydrofurfuryl alcohol	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.6 mg/l	90 days
Tetrahydrofurfuryl alcohol	Inhalation	eyes	Not classified	Rat	NOAEL 2.1 mg/l	90 days
Tetrahydrofurfuryl alcohol	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 69 mg/kg/day	91 days
Tetrahydrofurfuryl alcohol	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	28 days
Tetrahydrofurfuryl alcohol	Ingestion	endocrine system   kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	28 days
Tetrahydrofurfuryl alcohol	Ingestion	liver   eyes	Not classified	Rat	NOAEL 781 mg/kg/day	91 days
Tetrahydrofurfuryl alcohol	Ingestion	heart   nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

#### Ecotoxic to the aquatic environment.

Acute Aquatic Toxicity: Category 3

Chronic Aquatic Toxicity: Category 3

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Tetrahydrofurfuryl Methacrylate	2455-24-5	Fathead minnow	Experimental	96 hours	LC50	34.7 mg/l
Tetrahydrofurfuryl Methacrylate	2455-24-5	Green algae	Experimental	72 hours	ErC50	>100 mg/l
Tetrahydrofurfuryl Methacrylate	2455-24-5	Green algae	Experimental	72 hours	ErC10	100 mg/l
Tetrahydrofurfuryl Methacrylate	2455-24-5	Water flea	Experimental	21 days	NOEC	37.2 mg/l
Butadiene-Acrylonitrile Polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
Hydroxyethyl Methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green and Low Odor Acrylic Adhesive 8810NS Green, Part B**

Isobornyl Methacrylate	7534-94-3	Green algae	Experimental	72 hours	EC50	2.3 mg/l
Isobornyl Methacrylate	7534-94-3	Water flea	Experimental	48 hours	EC50	1.1 mg/l
Isobornyl Methacrylate	7534-94-3	Zebra Fish	Experimental	96 hours	LC50	1.8 mg/l
Isobornyl Methacrylate	7534-94-3	Green algae	Experimental	72 hours	EC10	0.751 mg/l
Isobornyl Methacrylate	7534-94-3	Water flea	Experimental	21 days	NOEC	0.233 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Green algae	Estimated	72 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Water flea	Estimated	48 hours	EL50	>100 mg/l
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Zebra Fish	Estimated	96 hours	LL50	>100 mg/l
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	95175-93-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Tetrahydrofurfuryl alcohol	97-99-4	Green algae	Experimental	72 hours	EC50	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Medaka	Experimental	96 hours	LC50	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Water flea	Experimental	21 days	NOEC	>100 mg/l
Copper Naphthenates	1338-02-9	Green algae	Estimated	72 hours	ErC50	0.629 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
Copper Naphthenates	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.07 mg/l
Copper	1338-02-9	Fathead	Estimated	32 days	EC10	0.0354 mg/l

Naphthenates		minnow				
Copper Naphthenates	1338-02-9	Green algae	Estimated	N/A	NOEC	0.132 mg/l
Copper Naphthenates	1338-02-9	Sediment Worm	Estimated	28 days	NOEC	110 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Water flea	Estimated	7 days	NOEC	0.02 mg/l
Copper Naphthenates	1338-02-9	Activated sludge	Estimated	N/A	EC50	42 mg/l
Copper Naphthenates	1338-02-9	Barley	Estimated	4 days	NOEC	96 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Redworm	Estimated	56 days	NOEC	60 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Soil microbes	Estimated	4 days	NOEC	72 mg/kg (Dry Weight)
Copper Naphthenates	1338-02-9	Springtail	Estimated	28 days	NOEC	167 mg/kg (Dry Weight)

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurfuryl Methacrylate	2455-24-5	Experimental Biodegradation	28 days	BOD	75 %BOD/ThOD (< 10 day window)	OECD 301F - Manometric respirometry
Butadiene-Acrylonitrile Polymer	9003-18-3	Data not available-insufficient	N/A	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/CO <sub>2</sub>	OECD 301D - Closed bottle test
Hydroxyethyl Methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t <sub>1/2</sub> )	OECD 111 Hydrolysis func of pH
Kaolin	1332-58-7	Data not available-insufficient	N/A	N/A	N/A	N/A
Isobornyl Methacrylate	7534-94-3	Experimental Biodegradation	28 days	CO <sub>2</sub> evolution	70 %CO <sub>2</sub> evolution/THCO <sub>2</sub> evolution	OECD 310 CO <sub>2</sub> Headspace
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Experimental Biodegradation	28 days	Percent degraded	24 % degraded	
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	95175-93-2	Data not available-insufficient	N/A	N/A	N/A	N/A
Tetrahydrofurfuryl alcohol	97-99-4	Experimental Biodegradation	28 days	BOD	92 %BOD/ThOD	OECD 301C - MITI test (I)
Tetrahydrofurfuryl alcohol	97-99-4	Experimental		Hydrolytic	>1 years (t <sub>1/2</sub> )	OECD 111 Hydrolysis

uryl alcohol		Hydrolysis		half-life (pH 7)		func of pH
Copper Naphthenates	1338-02-9	Data not availbl- insufficient	N/A	N/A	N/A	N/A

### 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurfuryl Methacrylate	2455-24-5	Experimental Bioconcentration		Log Kow	1.76	OECD 117 log Kow HPLC method
Butadiene-Acrylonitrile Polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flsk mtd
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Isobornyl Methacrylate	7534-94-3	Modeled Bioconcentration		Bioaccumulation factor	39	Catalogic™
Isobornyl Methacrylate	7534-94-3	Experimental Bioconcentration		Log Kow	5.09	OECD 117 log Kow HPLC method
Bisphenol A Polyethylene Glycol Diether Dimethacrylate (polymer)	41637-38-1	Estimated Bioconcentration		Bioaccumulation factor	6.6	
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	95175-93-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tetrahydrofurfuryl alcohol	97-99-4	Experimental Bioconcentration		Log Kow	-0.11	OECD 107 log Kow shke flsk mtd
Copper Naphthenates	1338-02-9	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	≤27	OECD305-Bioconcentration

### 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.



## SECTION 13: Disposal considerations

### 13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

## SECTION 14: Transport Information

### New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

**UN No.:** Not applicable.

**Proper Shipping Name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Hazchem Code:** Not applicable.

**IERG:** Not applicable.

### International Air Transport Association (IATA) - Air Transport

**UN No.:** Not applicable.

**Proper Shipping Name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

### International Maritime Dangerous Goods Code (IMDG) - Marine Transport

**UN No.:** Not applicable.

**Proper Shipping Name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Marine Pollutant:** Not applicable.

## SECTION 15: Regulatory information

HSNO Approval number HSR002670

Group standard name Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020

HSNO Hazard classification Refer to Section 2: Hazard identification

### NZ Inventory of Chemicals (NZIoC) Status

All ingredients are listed on the New Zealand Inventory of Chemicals.

**Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous**

**Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017**

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

**SECTION 16: Other information**

**Revision information:**

Complete document review.

<b>Document group:</b>	34-3730-8	<b>Version number:</b>	2.00
<b>Issue Date:</b>	19/11/2023	<b>Supersedes date:</b>	01/09/2020

**Key to abbreviations and acronyms**

**GHS** refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017

**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>**



## Safety Data Sheet

© 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	34-3732-4	<b>Version number:</b>	4.00
<b>Issue Date:</b>	19/11/2023	<b>Supersedes date:</b>	18/04/2021

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green, Part A

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesive

For Industrial or Professional use only

#### 1.3. Supplier's details

**Address:** 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland  
**Telephone:** (09) 477 4040  
**E Mail:** innovation@nz.mmm.com  
**Website:** 3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

### SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin sensitisation: Category 1

Hazardous to the aquatic environment chronic: Category 3

#### 2.2. Label elements

##### SIGNAL WORD

Warning

##### Symbols:

Exclamation mark |

**Pictograms****HAZARD STATEMENTS:**

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**PRECAUTIONARY STATEMENTS****Prevention**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P273 Avoid release to the environment.  
 P280E Wear protective gloves.

**Response**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.

**Disposal**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	% by Weight
Dibenzoate Propanol	27138-31-4	45 - 80
Acrylate Polymer	25101-28-4	5 - 30
Catalyst.	Trade Secret	1 - 20
Organic Peroxide	13122-18-4	1 - 10

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Hydrocarbons.	During combustion.
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

#### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

#### 5.4. Hazchem code: Not applicable.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

### SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

#### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

### 7.3. Certified handler

Not required

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of nitrile rubber are recommended. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

##### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Blue
Odour	Hydrocarbon
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	> 93.3 °C
Flash point	> 93.3 °C [Test Method: Closed Cup]
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	1.08 g/ml
Relative density	1.08 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	20,000 mPa-s
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>
VOC less H2O & exempt solvents	4.8 g/l [Details: when used as intended with Part B]
VOC less H2O & exempt solvents	0.5 % [Details: when used as intended with Part B]
VOC less H2O & exempt solvents	59.4 g/l [Details: as supplied]
Molecular weight	<i>Not applicable.</i>

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.4 Conditions to avoid**

Heat.

Sparks and/or flames.

**10.5 Incompatible materials**

Amines.

Strong acids.

Strong bases.



Strong oxidising agents.

**10.6 Hazardous decomposition products**

**Substance**

**Condition**

None known.

Refer to Section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects**

**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

This product may have a characteristic odour; however, no adverse health effects are anticipated.

**Skin contact**

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion**

May be harmful if swallowed.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Dibenzoate Propanol	Dermal	Rat	LD50 > 2,000 mg/kg
Dibenzoate Propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Dibenzoate Propanol	Ingestion	Rat	LD50 3,295 mg/kg
Acrylate Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Catalyst.	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Catalyst.	Ingestion	Rat	LD50 > 2,000 mg/kg

**3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green, Part A**

Organic Peroxide	Dermal	Rat	LD50 > 2,000 mg/kg
Organic Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.8 mg/l
Organic Peroxide	Ingestion	Rat	LD50 12,905 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Dibenzoate Propanol	Rabbit	No significant irritation
Organic Peroxide	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Dibenzoate Propanol	Rabbit	No significant irritation
Organic Peroxide	Rabbit	No significant irritation

**Sensitisation:****Skin Sensitisation**

Name	Species	Value
Dibenzoate Propanol	Guinea pig	Not classified
Catalyst.	Mouse	Not classified
Organic Peroxide	Guinea pig	Sensitising

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Dibenzoate Propanol	In Vitro	Not mutagenic
Catalyst.	In Vitro	Not mutagenic

**Carcinogenicity**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Dibenzoate Propanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
------	-------	-----------------	-------	---------	-------------	----------

						Duration
Catalyst.	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dibenzoate Propanol	Ingestion	hematopoietic system   liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Ecotoxic to the aquatic environment.**

Acute Aquatic Toxicity: Category 2

Chronic Aquatic Toxicity: Category 3

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Dibenzoate Propanol	27138-31-4	Fathead minnow	Experimental	96 hours	LC50	3.7 mg/l
Dibenzoate Propanol	27138-31-4	Green algae	Experimental	72 hours	EL50	4.9 mg/l
Dibenzoate Propanol	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Dibenzoate Propanol	27138-31-4	Green algae	Experimental	72 hours	EC10	0.89 mg/l
Acrylate Polymer	25101-28-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Catalyst.	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Organic Peroxide	13122-18-4	Activated sludge	Experimental	3 hours	NOEC	26.3 mg/l
Organic Peroxide	13122-18-4	Green algae	Experimental	N/A	EC50	0.51 mg/l
Organic Peroxide	13122-18-4	Rainbow trout	Experimental	N/A	LC50	7 mg/l
Organic	13122-18-4	Water flea	Experimental	N/A	EC50	>100 mg/l

Peroxide						
Organic Peroxide	13122-18-4	Green algae	Experimental	N/A	NOEC	0.125 mg/l

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoate Propanol	27138-31-4	Experimental Biodegradation	28 days	CO2 evolution	85 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Acrylate Polymer	25101-28-4	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Catalyst.	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	29.1 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Catalyst.	Trade Secret	Estimated Photolysis		Photolytic half-life (in air)	1.48 days (t 1/2)	
Organic Peroxide	13122-18-4	Estimated Biodegradation	28	BOD	14 %BOD/Tho D	OECD 301C - MITI test (I)

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Dibenzoate Propanol	27138-31-4	Modeled Bioconcentration		Bioaccumulation factor	8	Catalogic™
Acrylate Polymer	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Catalyst.	Trade Secret	Experimental Bioconcentration		Log Kow	2.57	
Organic Peroxide	13122-18-4	Estimated Bioconcentration		Bioaccumulation factor	363	

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5 Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the

respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

## SECTION 14: Transport Information

### New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

**UN No.:** Not applicable.

**Proper Shipping Name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Hazchem Code:** Not applicable.

**IERG:** Not applicable.

### International Air Transport Association (IATA) - Air Transport

**UN No.:** Not applicable.

**Proper Shipping Name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

### International Maritime Dangerous Goods Code (IMDG) - Marine Transport

**UN No.:** Not applicable.

**Proper Shipping Name:** Not applicable.

**Class/Division:** Not applicable.

**Sub Risk:** Not applicable.

**Packing Group:** Not applicable.

**Marine Pollutant:** Not applicable.

## SECTION 15: Regulatory information

HSNO Approval number HSR002670

Group standard name Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020

HSNO Hazard classification Refer to Section 2: Hazard identification

### NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

### Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic

Secondary containment	environment Category 4 substances) 100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Germ cell mutagenicity Category 1, Reproductive toxicity Category 1, Specific target organ toxicity Category 1, Serious eye damage Category 1, Hazardous to the aquatic environment Category 4 substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

**SECTION 16: Other information**

**Revision information:**  
Complete document review.

<b>Document group:</b>	34-3732-4	<b>Version number:</b>	4.00
<b>Issue Date:</b>	19/11/2023	<b>Supersedes date:</b>	18/04/2021

**Key to abbreviations and acronyms**

**GHS** refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017  
**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>