



Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	16-0852-0	Version number:	10.01
Revision date:	11/10/2023	Supersedes date:	15/05/2023
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M(TM) Scotch-Weld(TM) Low Odor Acrylic Adhesive DP810NS Tan

Product Identification Numbers

62-2799-1435-2 62-2799-1436-0 62-2799-3530-8

7100082551 7100069366 7100148748

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000

E Mail: tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

16-0795-1, 16-0802-5

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Carcinogenicity, Category 1B - Carc. 1B; H350

Reproductive Toxicity, Category 1B - Repr. 1B; H360F

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Contains:

6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol; mequinol; HYDROXYPROPYL METHACRYLATE; 2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate; α , α -dimethylbenzyl hydroperoxide; 2-hydroxyethyl methacrylate; Phenothiazine; cumene

HAZARD STATEMENTS:

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H350	May cause cancer.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system respiratory system
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201 Obtain special instructions before use.

P260A Do not breathe vapours.
P273 Avoid release to the environment.
P280B Wear protective gloves and eye/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H350 May cause cancer.
H360F May damage fertility.

<=125 ml Precautionary statements

Prevention:

P201 Obtain special instructions before use.
P280B Wear protective gloves and eye/face protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

GB Label: CLP Ingredients - kit components information was modified.
Section 2: <125ml Precautionary - Prevention information was modified.
Label: CLP Precautionary - Prevention information was modified.



Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	16-0795-1	Version number:	8.00
Revision date:	19/08/2022	Supersedes date:	30/09/2009

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
2-hydroxyethyl methacrylate	868-77-9	212-782-2	10 - 30
HYDROXYPROPYL METHACRYLATE	27813-02-1	248-666-3	10 - 30
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2	258-053-2	< 4
mequinol	150-76-5	205-769-8	< 1
Phenothiazine	92-84-2	202-196-5	< 1

HAZARD STATEMENTS:

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P273	Avoid release to the environment.
P280B	Wear protective gloves and eye/face protection.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.

<=125 ml Precautionary statements

Prevention:

P280B

Wear protective gloves and eye/face protection.

Response:

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a POISON CENTRE or doctor/physician.

P333 + P313

If skin irritation or rash occurs: Get medical advice/attention.

Contains 25% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Phenoxyethyl methacrylate	(CAS-No.) 10595-06-9 (EC-No.) 234-201-1	10 - 40	Aquatic Chronic 2, H411 Skin Irrit. 2, H315 Eye Irrit. 2, H319
HYDROXYPROPYL METHACRYLATE	(CAS-No.) 27813-02-1 (EC-No.) 248-666-3	10 - 30	Eye Irrit. 2, H319 Skin Sens. 1, H317
2-hydroxyethyl methacrylate	(CAS-No.) 868-77-9 (EC-No.) 212-782-2	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Nota D
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	(CAS-No.) 9010-81-5	5 - 20	Substance not classified as hazardous
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	(CAS-No.) 25101-28-4	5 - 20	Substance not classified as hazardous
Bisphenol A polyethylene glycol diether dimethacrylate	(CAS-No.) 41637-38-1 (EC-No.) 609-946-4	5 - 20	Aquatic Chronic 4, H413
Silane, dichlorodimethyl-, reaction products with silica	(CAS-No.) 68611-44-9 (EC-No.) 271-893-4	1 - 10	Substance with a national occupational exposure limit
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	(CAS-No.) 52628-03-2 (EC-No.) 258-053-2	< 4	Skin Corr. 1C, H314 Skin Sens. 1B, H317
Phenothiazine	(CAS-No.) 92-84-2 (EC-No.) 202-196-5	< 1	Acute Tox. 4, H302 Skin Sens. 1B, H317 STOT RE 2, H373 Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1

mequinol	(CAS-No.) 150-76-5 (EC-No.) 205-769-8	< 1	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
----------	--	-----	---

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.
Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide.
Hydrogen Chloride
Oxides of nitrogen.
Toxic vapour, gas, particulate.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus,

bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Keep away from reactive metals (eg. Aluminium, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Silicon dioxide	68611-44-9	UK HSC	TWA(as respirable dust):2.4 mg/m ³ ;TWA(as inhalable dust):6 mg/m ³	

UK HSC : UK Health and Safety Commission
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid.

Specific Physical Form:

Paste

Colour	Green
Odor	Methacrylate
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	87 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	> 93.3 °C [Test Method:Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-polar/aprotic</i>
Kinematic Viscosity	84,112 mm ² /sec
Water solubility	Slight (less than 10%)
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<=13.3 Pa
Density	1.07 g/ml
Relative density	1.07 [Ref Std: WATER=1]
Relative Vapor Density	<i>No data available.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Molecular weight	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Amines.

Reducing agents.

Reactive metals

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.
Photosensitisation: Signs/symptoms may include a sunburn-like reaction such as blistering, redness, swelling, and itching from minor exposure to sunlight.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-Phenoxyethyl methacrylate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
2-Phenoxyethyl methacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Dermal		LD50 estimated to be > 5,000 mg/kg
HYDROXYPROPYL METHACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROXYPROPYL METHACRYLATE	Ingestion	Rat	LD50 > 11,200 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Silane, dichlorodimethyl-, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part B

Silane, dichlorodimethyl-, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Ingestion	Rat	LD50 > 2,000 mg/kg
mequinol	Dermal	Rat	LD50 > 2,000 mg/kg
mequinol	Ingestion	Rat	LD50 1,630 mg/kg
Phenothiazine	Dermal	Rat	LD50 > 2,000 mg/kg
Phenothiazine	Ingestion	Rat	LD50 1,370 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
2-Phenoxyethyl methacrylate	similar compounds	Irritant
HYDROXYPROPYL METHACRYLATE	Rabbit	Minimal irritation
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Professional judgement	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate	In vitro data	No significant irritation
Silane, dichlorodimethyl-, reaction products with silica	Rabbit	No significant irritation
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Rabbit	Corrosive
mequinol	Rabbit	Mild irritant
Phenothiazine	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
2-Phenoxyethyl methacrylate	similar compounds	Severe irritant
HYDROXYPROPYL METHACRYLATE	Rabbit	Moderate irritant
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Professional judgement	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate	In vitro data	No significant irritation
Silane, dichlorodimethyl-, reaction products with silica	Rabbit	No significant irritation
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	similar health hazards	Corrosive
mequinol	Rabbit	Severe irritant
Phenothiazine	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
2-hydroxyethyl methacrylate	Human and animal	Sensitising
HYDROXYPROPYL METHACRYLATE	Human and animal	Sensitising
Bisphenol A polyethylene glycol diether dimethacrylate	Multiple animal species	Not classified
Silane, dichlorodimethyl-, reaction products with silica	Human	Not classified

	and animal	
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Mouse	Sensitising
mequinol	Guinea pig	Sensitising
Phenothiazine	Guinea pig	Sensitising

Photosensitisation

Name	Species	Value
Phenothiazine	Human	Sensitising

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Phenoxyethyl methacrylate	In Vitro	Not mutagenic
HYDROXYPROPYL METHACRYLATE	In vivo	Not mutagenic
HYDROXYPROPYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A polyethylene glycol diether dimethacrylate	In Vitro	Not mutagenic
Silane, dichlorodimethyl-, reaction products with silica	In Vitro	Not mutagenic
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	In Vitro	Not mutagenic
mequinol	In vivo	Not mutagenic
mequinol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Phenothiazine	In Vitro	Not mutagenic
Phenothiazine	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silane, dichlorodimethyl-, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
mequinol	Dermal	Multiple animal species	Not carcinogenic
mequinol	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part B

HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Bisphenol A polyethylene glycol diether dimethacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Bisphenol A polyethylene glycol diether dimethacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Bisphenol A polyethylene glycol diether dimethacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
mequinol	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
mequinol	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	Not classified for development	Rat	NOAEL 200 mg/kg/day	during gestation
Phenothiazine	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
HYDROXYPROPYL METHACRYLATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
mequinol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
HYDROXYPROPYL METHACRYLATE	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
HYDROXYPROPYL METHACRYLATE	Ingestion	hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Bisphenol A polyethylene glycol diether dimethacrylate	Ingestion	hematopoietic system liver immune system kidney and/or bladder endocrine	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks

		system eyes				
Silane, dichlorodimethyl-, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	Ingestion	hematopoietic system kidney and/or bladder heart liver immune system eyes	Not classified	Rat	NOAEL 300 mg/kg/day	90 days
mequinol	Ingestion	gastrointestinal tract	Not classified	Rat	LOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	liver immune system	Not classified	Rat	NOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 300 mg/kg/day	28 days
mequinol	Ingestion	heart endocrine system hematopoietic system nervous system respiratory system	Not classified	Rat	NOAEL 300 mg/kg/day	28 days
Phenothiazine	Ingestion	hematopoietic system	May cause damage to organs though prolonged or repeated exposure	Dog	NOAEL 18 mg/kg/day	13 weeks
Phenothiazine	Ingestion	heart endocrine system liver kidney and/or bladder respiratory system	Not classified	Dog	NOAEL 67 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
2-Phenoxyethyl methacrylate	10595-06-9	Activated sludge	Experimental	3 hours	EC50	177 mg/l
2-Phenoxyethyl methacrylate	10595-06-9	Golden Orfe	Experimental	96 hours	LC50	10 mg/l
2-Phenoxyethyl methacrylate	10595-06-9	Green algae	Experimental	96 hours	EC50	4.1 mg/l
2-Phenoxyethyl methacrylate	10595-06-9	Water flea	Experimental	48 hours	EC50	1.21 mg/l

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part B

2-Phenoxyethyl methacrylate	10595-06-9	Green algae	Experimental	96 hours	EC10	0.42 mg/l
2-hydroxyethyl methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-hydroxyethyl methacrylate	868-77-9		Experimental	16 hours	EC0	>3,000 mg/l
2-hydroxyethyl methacrylate	868-77-9		Experimental	18 hours	LD50	<98 mg per kg of bodyweight
HYDROXYPROPYL METHACRYLATE	27813-02-1	Bacteria	Experimental		EC10	1,140 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Golden Orfe	Experimental	48 hours	EC50	493 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Green algae	Experimental	72 hours	EC50	>97.2 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Water flea	Experimental	48 hours	EC50	>143 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Green algae	Experimental	72 hours	NOEC	97.2 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Water flea	Experimental	21 days	NOEC	45.2 mg/l
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	9010-81-5		Data not available or insufficient for classification			N/A
Bisphenol A polyethylene glycol diether dimethacrylate	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate	41637-38-1	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate	41637-38-1	Rainbow trout	Estimated	96 hours	No tox obs at lmt of water sol	>100 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate	41637-38-1	Green algae	Estimated	72 hours	No tox obs at lmt of water sol	>100 mg/l
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4		Data not available or insufficient for classification			N/A
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9		Data not available or insufficient for classification			N/A
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2	Green algae	Experimental	72 hours	EC50	>120 mg/l
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2	Rainbow trout	Experimental	96 hours	LC50	>112 mg/l
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2	Water flea	Experimental	48 hours	EC50	68 mg/l
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester,	52628-03-2	Green algae	Experimental	72 hours	NOEC	30 mg/l

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part B

phosphate						
mequinol	150-76-5	Ciliated protozoa	Experimental	40 hours	IC50	171.4 mg/l
mequinol	150-76-5	Green algae	Experimental	72 hours	EC50	54.7 mg/l
mequinol	150-76-5	Rainbow trout	Experimental	96 hours	LC50	28.5 mg/l
mequinol	150-76-5	Water flea	Experimental	48 hours	EC50	2.2 mg/l
mequinol	150-76-5	Green algae	Experimental	72 hours	NOEC	2.96 mg/l
mequinol	150-76-5	Water flea	Experimental	21 days	NOEC	0.68 mg/l
Phenothiazine	92-84-2	Activated sludge	Experimental	3 hours	IC50	>100 mg/l
Phenothiazine	92-84-2	Ciliated protozoa	Experimental	48 hours	IC50	8 mg/l
Phenothiazine	92-84-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
Phenothiazine	92-84-2	Rainbow trout	Experimental	96 hours	LC50	0.597 mg/l
Phenothiazine	92-84-2	Water flea	Experimental	48 hours	EC50	0.154 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-Phenoxyethyl methacrylate	10595-06-9	Experimental Biodegradation	28 days	BOD	22.3 %BOD/ThOD	OECD 301D - Closed bottle test
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/CO _D	OECD 301D - Closed bottle test
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t _{1/2})	OECD 111 Hydrolysis func of pH
HYDROXYPROPYL METHACRYLATE	27813-02-1	Experimental Biodegradation	28 days	BOD	81 %BOD/ThO _D	OECD 301C - MITI test (I)
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	9010-81-5	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Bisphenol A polyethylene glycol diether dimethacrylate	41637-38-1	Experimental Biodegradation	28 days	BOD	24 %BOD/ThO _D	OECD 301D - Closed bottle test
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2	Experimental Biodegradation	28 days	BOD	93.1 %BOD/ThOD	OECD 301F - Manometric respirometry
mequinol	150-76-5	Experimental Biodegradation	28 days	BOD	86 %BOD/ThO _D	OECD 301C - MITI test (I)
Phenothiazine	92-84-2	Experimental Biodegradation	28 days	BOD	0 %BOD/ThO _D	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2-Phenoxyethyl methacrylate	10595-06-9	Estimated Bioconcentration		Bioaccumulation factor	5.8	
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flsk mtd
HYDROXYPROPYL METHACRYLATE	27813-02-1	Experimental Bioconcentration		Log Kow	0.97	
Acrylonitrile - 1,3-	9010-81-5	Data not available	N/A	N/A	N/A	N/A

butadiene - methacrylic acid copolymer		or insufficient for classification				
Bisphenol A polyethylene glycol diether dimethacrylate	41637-38-1	Estimated Bioconcentration		Bioaccumulation factor	6.6	
Bisphenol A polyethylene glycol diether dimethacrylate	41637-38-1	Experimental Bioconcentration		Log Kow	≥4.66	OECD 117 log Kow HPLC method
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2	Experimental Bioconcentration		Log Kow	1 - 2.72	OECD 117 log Kow HPLC method
mequinol	150-76-5	Experimental Bioconcentration		Log Kow	1.58	
Phenothiazine	92-84-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	660	

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-Phenoxyethyl methacrylate	10595-06-9	Estimated Mobility in Soil	Koc	380 l/kg	Episuite™
2-hydroxyethyl methacrylate	868-77-9	Experimental Mobility in Soil	Koc	42.7 l/kg	
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	52628-03-2	Modeled Mobility in Soil	Koc	10 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are

complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ACRYLATE MONOMER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ACRYLATE MONOMER)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ACRYLATE MONOMER)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information**List of relevant H statements**

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use

(except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	16-0802-5	Version number:	10.00
Revision date:	11/10/2023	Supersedes date:	26/06/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Carcinogenicity, Category 1B - Carc. 1B; H350
Reproductive Toxicity, Category 1B - Repr. 1B; H360F
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
2-hydroxyethyl methacrylate	868-77-9	212-782-2	10 - 40
HYDROXYPROPYL METHACRYLATE	27813-02-1	248-666-3	7 - 30
α, α-dimethylbenzyl hydroperoxide	80-15-9	201-254-7	< 5
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	204-327-1	< 1
cumene	98-82-8	202-704-5	< 1

HAZARD STATEMENTS:

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H350	May cause cancer.
H360F	May damage fertility.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system respiratory system.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P260A	Do not breathe vapours.
P273	Avoid release to the environment.
P280I	Wear protective gloves, eye/face protection, and respiratory protection.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318 Causes serious eye damage.
 H317 May cause an allergic skin reaction.
 H350 May cause cancer.
 H360F May damage fertility.

<=125 ml Precautionary statements

Prevention:

P201 Obtain special instructions before use.
 P280I Wear protective gloves, eye/face protection, and respiratory protection.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTRE or doctor/physician.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

Contains 25% of components with unknown hazards to the aquatic environment.

H242 not required because material does not meet classification requirements based on available oxygen percentage from organic peroxides and hydrogen peroxide concentration.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
2-Phenoxyethyl methacrylate	(CAS-No.) 10595-06-9 (EC-No.) 234-201-1	10 - 40	Aquatic Chronic 2, H411 Skin Irrit. 2, H315 Eye Irrit. 2, H319
2-hydroxyethyl methacrylate	(CAS-No.) 868-77-9 (EC-No.) 212-782-2	10 - 40	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Nota D
HYDROXYPROPYL METHACRYLATE	(CAS-No.) 27813-02-1 (EC-No.) 248-666-3	7 - 30	Eye Irrit. 2, H319 Skin Sens. 1, H317
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	(CAS-No.) 9010-81-5	5 - 20	Substance not classified as hazardous

Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	(CAS-No.) 25101-28-4	5 - 20	Substance not classified as hazardous
Reaction product of ethoxylated 4,4'-isopropylidenediphenol and methacrylic acid	(EC-No.) 935-411-2	5 - 20	Substance not classified as hazardous
Silane, dichlorodimethyl-, reaction products with silica	(CAS-No.) 68611-44-9 (EC-No.) 271-893-4	1 - 10	Substance with a national occupational exposure limit
α , α -dimethylbenzyl hydroperoxide	(CAS-No.) 80-15-9 (EC-No.) 201-254-7	< 5	Org. Perox. EF, H242 Acute Tox. 2, H330 Acute Tox. 3, H311 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 1, H372 Aquatic Chronic 2, H411
cumene	(CAS-No.) 98-82-8 (EC-No.) 202-704-5	< 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Aquatic Chronic 2, H411
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	(CAS-No.) 119-47-1 (EC-No.) 204-327-1	< 1	Substance not classified as hazardous

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
α , α -dimethylbenzyl hydroperoxide	(CAS-No.) 80-15-9 (EC-No.) 201-254-7	(C \geq 10%) Skin Corr. 1B, H314 (3% \leq C < 10%) Skin Irrit. 2, H315 (C \geq 3%) Eye Dam. 1, H318 (1% \leq C < 3%) Eye Irrit. 2, H319 (C \geq 10%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide.
Hydrogen Chloride
Oxides of nitrogen.
Toxic vapour, gas, particulate.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Keep away from reactive metals (eg. Aluminium, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Silicon dioxide	68611-44-9	UK HSC	TWA(as respirable dust):2.4 mg/m ³ ;TWA(as inhalable dust):6 mg/m ³	
cumene	98-82-8	UK HSC	TWA:125 mg/m ³ (25 ppm);STEL:250 mg/m ³ (50 ppm)	SKIN

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Low Odor
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	87 °C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	102.2 °C [Test Method:Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	84,112 mm ² /sec
Water solubility	Slight (less than 10%)
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	<=13.3 Pa
Density	1.07 g/ml
Relative density	1.07 [Ref Std: WATER=1]

Relative Vapour Density

No data available.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

No data available.

Evaporation rate

No data available.

Molecular weight

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5 Incompatible materials

Amines.

Reducing agents.

Reactive metals

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.
 Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.
 May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >20 - =50 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
2-Phenoxyethyl methacrylate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
2-Phenoxyethyl methacrylate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Dermal		LD50 estimated to be > 5,000 mg/kg
HYDROXYPROPYL METHACRYLATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
HYDROXYPROPYL METHACRYLATE	Ingestion	Rat	LD50 > 11,200 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Silane, dichlorodimethyl-, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silane, dichlorodimethyl-, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
α, α-dimethylbenzyl hydroperoxide	Dermal	Rat	LD50 500 mg/kg
α, α-dimethylbenzyl hydroperoxide	Inhalation-	Rat	LC50 1.4 mg/l

	Vapour (4 hours)		
α , α -dimethylbenzyl hydroperoxide	Ingestion	Rat	LD50 382 mg/kg
cumene	Dermal	Rabbit	LD50 > 3,160 mg/kg
cumene	Inhalation-Vapour (4 hours)	Rat	LC50 39.4 mg/l
cumene	Ingestion	Rat	LD50 1,400 mg/kg
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	Dermal	Rabbit	LD50 > 10,000 mg/kg
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
2-Phenoxyethyl methacrylate	similar compounds	Irritant
HYDROXYPROPYL METHACRYLATE	Rabbit	Minimal irritation
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Professional judgement	No significant irritation
Silane, dichlorodimethyl-, reaction products with silica	Rabbit	No significant irritation
α , α -dimethylbenzyl hydroperoxide	official classification	Corrosive
cumene	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
2-Phenoxyethyl methacrylate	similar compounds	Severe irritant
HYDROXYPROPYL METHACRYLATE	Rabbit	Moderate irritant
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	Professional judgement	No significant irritation
Silane, dichlorodimethyl-, reaction products with silica	Rabbit	No significant irritation
α , α -dimethylbenzyl hydroperoxide	official classification	Corrosive
cumene	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
2-hydroxyethyl methacrylate	Human and animal	Sensitising
HYDROXYPROPYL METHACRYLATE	Human and animal	Sensitising
Silane, dichlorodimethyl-, reaction products with silica	Human and animal	Not classified
cumene	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-Phenoxyethyl methacrylate	In Vitro	Not mutagenic
HYDROXYPROPYL METHACRYLATE	In vivo	Not mutagenic
HYDROXYPROPYL METHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silane, dichlorodimethyl-, reaction products with silica	In Vitro	Not mutagenic
α , α -dimethylbenzyl hydroperoxide	In vivo	Not mutagenic
α , α -dimethylbenzyl hydroperoxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
cumene	In Vitro	Not mutagenic
cumene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silane, dichlorodimethyl-, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
cumene	Inhalation	Multiple animal species	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
HYDROXYPROPYL METHACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silane, dichlorodimethyl-, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
cumene	Inhalation	Not classified for development	Rabbit	NOAEL 11.3 mg/l	during organogenesis
6,6'-Di-tert-butyl-2,2'-methylene-di-p-cresol	Ingestion	Not classified for female reproduction	Rat	NOAEL 50 mg/kg/day	prematuring & during gestation
6,6'-Di-tert-butyl-2,2'-methylene-di-p-cresol	Ingestion	Toxic to male reproduction	Rat	NOAEL 12.5	50 days

				mg/kg/day	
--	--	--	--	-----------	--

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
HYDROXYPROPYL METHACRYLATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
α , α -dimethylbenzyl hydroperoxide	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
α , α -dimethylbenzyl hydroperoxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
α , α -dimethylbenzyl hydroperoxide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
cumene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available
cumene	Inhalation	respiratory irritation	May cause respiratory irritation	Human	LOAEL 0.2 mg/l	occupational exposure
cumene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
HYDROXYPROPYL METHACRYLATE	Inhalation	blood	Not classified	Rat	NOAEL 0.5 mg/l	21 days
HYDROXYPROPYL METHACRYLATE	Ingestion	hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	41 days
Silane, dichlorodimethyl-, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
α , α -dimethylbenzyl hydroperoxide	Inhalation	nervous system respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	7 days
α , α -dimethylbenzyl hydroperoxide	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 0.03 mg/l	90 days
cumene	Inhalation	auditory system endocrine system hematopoietic system liver nervous system eyes	Not classified	Rat	NOAEL 59 mg/l	13 weeks
cumene	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4.9 mg/l	13 weeks
cumene	Inhalation	respiratory system	Not classified	Rat	NOAEL 59 mg/l	13 weeks
cumene	Ingestion	kidney and/or bladder heart endocrine system hematopoietic system liver respiratory system	Not classified	Rat	NOAEL 769 mg/kg/day	6 months

Aspiration Hazard

Name	Value
cumene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
2-hydroxyethyl methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
2-Phenoxyethyl methacrylate	10595-06-9	Activated sludge	Analogous Compound	3 hours	EC50	177 mg/l
2-Phenoxyethyl methacrylate	10595-06-9	Golden Orfe	Analogous Compound	96 hours	LC50	10 mg/l
2-Phenoxyethyl methacrylate	10595-06-9	Green algae	Analogous Compound	96 hours	ErC50	4.4 mg/l
2-Phenoxyethyl methacrylate	10595-06-9	Water flea	Analogous Compound	48 hours	EC50	1.21 mg/l
2-Phenoxyethyl methacrylate	10595-06-9	Green algae	Analogous Compound	96 hours	ErC10	0.74 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Bacteria	Experimental	N/A	EC10	1,140 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Golden Orfe	Experimental	48 hours	EC50	493 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Green algae	Experimental	72 hours	ErC50	>97.2 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Water flea	Experimental	48 hours	EC50	>143 mg/l
HYDROXYPROPYL METHACRYLATE	27813-02-1	Green algae	Experimental	72 hours	NOEC	97.2 mg/l

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part A

METHACRYLATE						
HYDROXYPROPYL METHACRYLATE	27813-02-1	Water flea	Experimental	21 days	NOEC	45.2 mg/l
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	9010-81-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
α , α -dimethylbenzyl hydroperoxide	80-15-9	Bacteria	Experimental	18 hours	EC10	0.103 mg/l
α , α -dimethylbenzyl hydroperoxide	80-15-9	Green algae	Experimental	72 hours	EC50	3.1 mg/l
α , α -dimethylbenzyl hydroperoxide	80-15-9	Rainbow trout	Experimental	96 hours	LC50	3.9 mg/l
α , α -dimethylbenzyl hydroperoxide	80-15-9	Water flea	Experimental	48 hours	EC50	18.84 mg/l
α , α -dimethylbenzyl hydroperoxide	80-15-9	Green algae	Experimental	72 hours	NOEC	1 mg/l
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	Green algae	Endpoint not reached	72 hours	EC50	>100 mg/l
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	Water flea	Endpoint not reached	48 hours	EC50	>100 mg/l
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	Medaka	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
6,6'-Di-tert-butyl-2,2'-methylenedi-p-cresol	119-47-1	Green algae	Experimental	72 hours	NOEC	1.3 mg/l
cumene	98-82-8	Activated sludge	Experimental	3 hours	EC10	>2,000 mg/l
cumene	98-82-8	Green algae	Experimental	72 hours	EC50	2.6 mg/l
cumene	98-82-8	Mysid Shrimp	Experimental	96 hours	EC50	1.2 mg/l
cumene	98-82-8	Rainbow trout	Experimental	96 hours	LC50	2.7 mg/l
cumene	98-82-8	Water flea	Experimental	48 hours	EC50	2.14 mg/l
cumene	98-82-8	Green algae	Experimental	72 hours	NOEC	0.22 mg/l
cumene	98-82-8	Water flea	Experimental	21 days	NOEC	0.35 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
----------	---------	-----------	----------	------------	-------------	----------

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP810NS Tan and Low Odor Acrylic Adhesive 810NS Tan, Part A

2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/COD	OECD 301D - Closed bottle test
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
2-Phenoxyethyl methacrylate	10595-06-9	Analogous Compound Biodegradation	28 days	BOD	22.3 %BOD/ThOD	OECD 301D - Closed bottle test
2-Phenoxyethyl methacrylate	10595-06-9	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	1 years (t 1/2)	OECD 111 Hydrolysis func of pH
HYDROXYPROPYL METHACRYLATE	27813-02-1	Experimental Biodegradation	28 days	BOD	81 %BOD/ThOD	OECD 301C - MITI test (I)
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	9010-81-5	Data not available - insufficient	N/A	N/A	N/A	N/A
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not available - insufficient	N/A	N/A	N/A	N/A
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	Data not available - insufficient	N/A	N/A	N/A	N/A
α , α -dimethylbenzyl hydroperoxide	80-15-9	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
6,6'-Di-tert-butyl-2,2'-methylene-dip-cresol	119-47-1	Experimental Biodegradation	28 days	BOD	0 %BOD/ThOD	OECD 301C - MITI test (I)
cumene	98-82-8	Experimental Biodegradation	14 days	BOD	33 %BOD/ThOD	OECD 301C - MITI test (I)
cumene	98-82-8	Experimental Photolysis		Photolytic half-life (in air)	4.5 days (t 1/2)	

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flask mtd
2-Phenoxyethyl methacrylate	10595-06-9	Modeled Bioconcentration		Bioaccumulation factor	5.8	Catalogic™
2-Phenoxyethyl methacrylate	10595-06-9	Experimental Bioconcentration		Log Kow	3.137	OECD 117 log Kow HPLC method
HYDROXYPROPYL METHACRYLATE	27813-02-1	Experimental Bioconcentration		Log Kow	0.97	EC A.8 Partition Coefficient
Acrylonitrile - 1,3-butadiene - methacrylic acid copolymer	9010-81-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
α , α -dimethylbenzyl hydroperoxide	80-15-9	Experimental Bioconcentration		Log Kow	1.82	
6,6'-Di-tert-butyl-	119-47-1	Experimental BCF	60 days	Bioaccumulation	840	OECD305-Bioconcentration

2,2'-methylene-di-p-cresol		- Fish		factor		
cumene	98-82-8	Modeled Bioconcentration		Bioaccumulation factor	140	Catalogic™
cumene	98-82-8	Experimental Bioconcentration		Log Kow	3.55	OECD 107 log Kow shke flask mtd

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-hydroxyethyl methacrylate	868-77-9	Experimental Mobility in Soil	Koc	42.7 l/kg	
2-Phenoxyethyl methacrylate	10595-06-9	Modeled Mobility in Soil	Koc	380 l/kg	Episuite™
HYDROXYPROP YL METHACRYLATE	27813-02-1	Experimental Mobility in Soil	Koc	10 l/kg	Episuite™
cumene	98-82-8	Modeled Mobility in Soil	Koc	700	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper	ENVIRONMENTALLY	ENVIRONMENTALLY	ENVIRONMENTALLY

shipping name	HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ACRYLATE MONOMER; CUMENE HYDROPEROXIDE)	HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ACRYLATE MONOMER; CUMENE HYDROPEROXIDE)	HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(ACRYLATE MONOMER; CUMENE HYDROPEROXIDE)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	Not applicable.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
cumene	98-82-8	Carc. 1B	Annex VI-18th ATP according to the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain
cumene	98-82-8	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
cumene	98-82-8	10	50
α , α -dimethylbenzyl hydroperoxide	80-15-9	50	200

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

- H226 Flammable liquid and vapour.
- H242 Heating may cause a fire.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation.
- H350 May cause cancer.
- H360F May damage fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure: nervous system | respiratory

H411 system.
Toxic to aquatic life with long lasting effects.

Revision information:

GB Section 02: CLP Ingredient table information was modified.
GB Section 15: Carcinogenicity information information was modified.
Section 3: Composition/ Information of ingredients table information was modified.
Section 8: glove data value information was deleted.
Section 8: glove data value information was modified.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Carcinogenicity Table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Mobility in soil information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Bioaccumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.