



Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	18-0079-6	Version number:	12.00
Revision date:	26/06/2023	Supersedes date:	25/02/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Structural Adhesive Primer EW-5000

Product Identification Numbers

62-3963-6545-4

7100004022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Corrosion Inhibiting Primer

1.3. Details of the supplier of the safety data sheet

Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	tox.uk@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Skin Sensitization, Category 1 - Skin Sens. 1; H317
 Carcinogenicity, Category 1B - Carc. 1B; H350i
 Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
 Hazardous to the Aquatic Environment (Acute), Category 1 - Aquatic Acute 1; H400
 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS07 (Exclamation mark) | GHS08 (Health Hazard) | GHS09 (Environment) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3		10 - 20
Phenol-formaldehyde polymer, glycidyl ether	28064-14-4		1 - 7
Barium Chromate	10294-40-3	233-660-5	1 - 5
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9		< 3
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	271-846-8	< 1
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	220-780-8	0.1 - 0.5

HAZARD STATEMENTS:

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H350i	May cause cancer by inhalation.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P260E	Do not breathe vapour or spray.
P273	Avoid release to the environment.
P280K	Wear protective gloves and respiratory protection.

Response:

P308 + P313
P333 + P313

IF exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

Contains 3% of components with unknown hazards to the aquatic environment.

H226 not applied based on test data.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Water	(CAS-No.) 7732-18-5 (EC-No.) 231-791-2	50 - 65	Substance not classified as hazardous
Bisphenol A diglycidyl ether - bisphenol A copolymer	(CAS-No.) 25036-25-3	10 - 20	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Phenol-formaldehyde polymer, glycidyl ether	(CAS-No.) 28064-14-4	1 - 7	Skin Sens. 1, H317 Aquatic Chronic 2, H411
2-(propyloxy)ethanol	(CAS-No.) 2807-30-9 (EC-No.) 220-548-6	1 - 5	Acute Tox. 4, H312 Eye Irrit. 2, H319 Flam. Liq. 3, H226
Barium Chromate	(CAS-No.) 10294-40-3 (EC-No.) 233-660-5	1 - 5	Nota A Carc. 1B, H350i STOT RE 1, H372 Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=1
propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7	1 - 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Bisphenol A - epichlorhydrin - formaldehyde copolymer	(CAS-No.) 28906-96-9	< 3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	(CAS-No.) 17526-94-2 (EC-No.) 241-523-6	1 - 3	Substance not classified as hazardous
acetone	(CAS-No.) 67-64-1	< 2	Flam. Liq. 2, H225

	(EC-No.) 200-662-2		Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(CAS-No.) 68609-97-2 (EC-No.) 271-846-8	< 1	Skin Irrit. 2, H315 Skin Sens. 1A, H317
trizinc bis(orthophosphate)	(CAS-No.) 7779-90-0 (EC-No.) 231-944-3	0.1 - 1	Aquatic Acute 1, H400,M=10 Aquatic Chronic 1, H410,M=10
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	(CAS-No.) 2897-60-1 (EC-No.) 220-780-8	0.1 - 0.5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
zinc oxide	(CAS-No.) 1314-13-2 (EC-No.) 215-222-5	< 0.1	Aquatic Acute 1, H400,M=1 Aquatic Chronic 1, H410,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Aldehydes.
Carbon monoxide
Carbon dioxide.

Condition

During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Chromium (hexavalent compounds)	10294-40-3	UK HSC	3M™ Scotch-Weld™ Structural Adhesive Primer EW-5000	Respiratory Sensitizer
DUST, INERT OR NUISANCE	1314-13-2	UK HSC	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	
propan-2-ol	67-63-0	UK HSC	TWA:999 mg/m ³ (400 ppm);STEL:1250 mg/m ³ (500 ppm)	
acetone	67-64-1	UK HSC	TWA:1210 mg/m ³ (500 ppm);STEL:3620 mg/m ³ (1500 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Ingredient	CAS Nbr	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
Chromium (hexavalent compounds)	10294-40-3	UK EH40 BMGVs	Chromium	Creatinine in urine	EOS	10 umol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)

EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Yellow
Odor	Slight Solvent
Odour threshold	No data available.
Melting point/freezing point	0 °C
Boiling point/boiling range	100 °C [@ 101,325 Pa]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	1.5 %
Flammable Limits(UEL)	12.7 %
Flash point	42.5 °C [Test Method: Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	6 - 8
Kinematic Viscosity	No data available.
Water solubility	Appreciable
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	1,999.8 Pa [@ 20 °C]
Density	1.04 - 1.09 g/ml
Relative density	1.09 [Ref Std: WATER=1]
Relative Vapour Density	1 [Ref Std: AIR=1]

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	96 - 101 g/l
Evaporation rate	No data available.
Percent volatile	69 % weight [<i>Test Method:</i> Tested per ASTM protocol]
Sustained Combustibility	Does not sustain combustion [<i>Test Method:</i> ASTM D4206]

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong acids.
Strong bases.
Strong oxidising agents.
Amines.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction

(non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Bisphenol A diglycidyl ether - bisphenol A copolymer	Dermal	Rat	LD50 > 1,600 mg/kg
Bisphenol A diglycidyl ether - bisphenol A copolymer	Ingestion	Rat	LD50 > 1,000 mg/kg
Phenol-formaldehyde polymer, glycidyl ether	Dermal	Rabbit	LD50 > 6,000 mg/kg
Phenol-formaldehyde polymer, glycidyl ether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.7 mg/l
Phenol-formaldehyde polymer, glycidyl ether	Ingestion	Rat	LD50 > 4,000 mg/kg
propan-2-ol	Dermal	Rabbit	LD50 12,870 mg/kg
propan-2-ol	Inhalation-Vapour (4 hours)	Rat	LC50 72.6 mg/l
propan-2-ol	Ingestion	Rat	LD50 4,710 mg/kg
2-(propyloxy)ethanol	Dermal	Rabbit	LD50 1,337 mg/kg
2-(propyloxy)ethanol	Inhalation-Vapour (4 hours)	Rat	LC50 > 11.1 mg/l
2-(propyloxy)ethanol	Ingestion	Rat	LD50 3,089 mg/kg
Barium Chromate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Barium Chromate	Ingestion	Rat	LD50 3,000 mg/kg
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Ingestion	Rat	LD50 > 2,000 mg/kg
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Dermal	Rat	LD50 > 2,000 mg/kg
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Ingestion	Rat	LD50 > 2,000 mg/kg
acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
acetone	Inhalation-Vapour (4 hours)	Rat	LC50 76 mg/l
acetone	Ingestion	Rat	LD50 5,800 mg/kg

trizinc bis(orthophosphate)	Dermal		LD50 estimated to be > 5,000 mg/kg
trizinc bis(orthophosphate)	Ingestion	Rat	LD50 > 5,000 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Dermal	Rabbit	LD50 > 4,000 mg/kg
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Ingestion	Rat	LD50 17,100 mg/kg
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	Dermal	Rabbit	LD50 > 2,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	Ingestion	Rat	LD50 > 2,000 mg/kg
zinc oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
zinc oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
zinc oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Bisphenol A diglycidyl ether - bisphenol A copolymer	Rabbit	Mild irritant
Phenol-formaldehyde polymer, glycidyl ether	Rabbit	Minimal irritation
propan-2-ol	Multiple animal species	No significant irritation
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Professional judgement	Irritant
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Rabbit	No significant irritation
acetone	Mouse	Minimal irritation
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Rabbit	Mild irritant
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	Rabbit	Minimal irritation
zinc oxide	Human and animal	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Bisphenol A diglycidyl ether - bisphenol A copolymer	Rabbit	Moderate irritant
Phenol-formaldehyde polymer, glycidyl ether	Rabbit	Mild irritant
propan-2-ol	Rabbit	Severe irritant
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Professional judgement	Severe irritant
N,N''-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	Rabbit	No significant irritation
acetone	Rabbit	Severe irritant
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Rabbit	Mild irritant
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	Rabbit	Mild irritant
zinc oxide	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Bisphenol A diglycidyl ether - bisphenol A copolymer	Human and animal	Sensitising
Phenol-formaldehyde polymer, glycidyl ether	Human and animal	Sensitising
propan-2-ol	Guinea pig	Not classified
Barium Chromate	similar compound	Not classified

	ds	
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Professional judgement	Sensitising
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Guinea pig	Sensitising
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	Guinea pig	Sensitising
zinc oxide	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
Bisphenol A diglycidyl ether - bisphenol A copolymer	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Bisphenol A diglycidyl ether - bisphenol A copolymer	In vivo	Not mutagenic
Bisphenol A diglycidyl ether - bisphenol A copolymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Phenol-formaldehyde polymer, glycidyl ether	In Vitro	Some positive data exist, but the data are not sufficient for classification
propan-2-ol	In Vitro	Not mutagenic
propan-2-ol	In vivo	Not mutagenic
acetone	In vivo	Not mutagenic
acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	In vivo	Not mutagenic
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	In Vitro	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In Vitro	Some positive data exist, but the data are not sufficient for classification
zinc oxide	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Bisphenol A diglycidyl ether - bisphenol A copolymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
propan-2-ol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Barium Chromate	Not specified.	similar compounds	Carcinogenic.
acetone	Not specified.	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Bisphenol A diglycidyl ether - bisphenol A copolymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A diglycidyl ether - bisphenol A copolymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation

Bisphenol A diglycidyl ether - bisphenol A copolymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Bisphenol A diglycidyl ether - bisphenol A copolymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
propan-2-ol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
propan-2-ol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
propan-2-ol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
propan-2-ol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
Barium Chromate	Not specified.	Not classified for reproduction and/or development	similar compounds	NOAEL Not available	premating & during gestation
acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Dermal	Not classified for development	Rat	NOAEL 200 mg/kg/day	during organogenesis
zinc oxide	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
propan-2-ol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propan-2-ol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
propan-2-ol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
propan-2-ol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Bisphenol A - epichlorhydrin - formaldehyde copolymer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL not available	
acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Dermal	heart blood liver nervous system kidney and/or bladder	Not classified	Rabbit	NOAEL 4,000 mg/kg	24 hours

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Bisphenol A diglycidyl ether - bisphenol A	Dermal	liver	Not classified	Rat	NOAEL 1,000	2 years

copolymer					mg/kg/day	
Bisphenol A diglycidyl ether - bisphenol A copolymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Bisphenol A diglycidyl ether - bisphenol A copolymer	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
propan-2-ol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
propan-2-ol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
propan-2-ol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
Barium Chromate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	similar compounds	NOAEL Not available	occupational exposure
acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Dermal	nervous system respiratory system	Not classified	Rat	NOAEL 100 mg/kg/day	14 weeks
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	Dermal	blood liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 100 mg/kg/day	13 weeks
zinc oxide	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
zinc oxide	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Green algae	Estimated	72 hours	EC50	>11 mg/l
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Green algae	Estimated	72 hours	NOEC	4.2 mg/l
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Water flea	Estimated	21 days	NOEC	0.3 mg/l
Phenol-formaldehyde polymer, glycidyl ether	28064-14-4	Golden Orfe	Experimental	96 hours	LC50	5.7 mg/l
Phenol-formaldehyde polymer, glycidyl ether	28064-14-4	Water flea	Experimental	48 hours	EC50	3.5 mg/l
Barium Chromate	10294-40-3	Water flea	Estimated	48 hours	EC50	0.04 mg/l
2-(propyloxy)ethanol	2807-30-9	Eastern oyster	Estimated	96 hours	LC50	89.4 mg/l
2-(propyloxy)ethanol	2807-30-9	Activated sludge	Experimental	16 hours	IC50	>1,000 mg/l
2-(propyloxy)ethanol	2807-30-9	Fathead minnow	Experimental	96 hours	LC50	>5,000 mg/l
2-(propyloxy)ethanol	2807-30-9	Green algae	Experimental	72 hours	EC50	>100 mg/l
2-(propyloxy)ethanol	2807-30-9	Water flea	Experimental	48 hours	EC50	>5,000 mg/l
2-(propyloxy)ethanol	2807-30-9	Green algae	Experimental	72 hours	NOEC	100 mg/l
propan-2-ol	67-63-0	Bacteria	Experimental	16 hours	LOEC	1,050 mg/l
propan-2-ol	67-63-0	Green algae	Experimental	72 hours	EC50	>1,000 mg/l

propan-2-ol	67-63-0	Invertebrate	Experimental	24 hours	LC50	>10,000 mg/l
propan-2-ol	67-63-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
propan-2-ol	67-63-0	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
propan-2-ol	67-63-0	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
propan-2-ol	67-63-0	Water flea	Experimental	21 days	NOEC	100 mg/l
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Green algae	Experimental	72 hours	ErC50	>100 mg/l
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
acetone	67-64-1	Algae or other aquatic plants	Experimental	96 hours	EC50	11,493 mg/l
acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l
acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	Green algae	Experimental	72 hours	IC50	843.75 mg/l
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	Rainbow trout	Experimental	96 hours	LC50	>5,000 mg/l
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	Water flea	Experimental	48 hours	EC50	7.2 mg/l
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	Green algae	Experimental	72 hours	NOEC	500 mg/l
trizinc bis(orthophosphate)	7779-90-0	Activated sludge	Estimated	3 hours	EC50	10 mg/l
trizinc bis(orthophosphate)	7779-90-0	Green algae	Estimated	72 hours	EC50	0.083 mg/l
trizinc bis(orthophosphate)	7779-90-0	Invertebrate	Estimated	48 hours	EC50	0.08 mg/l
trizinc bis(orthophosphate)	7779-90-0	Rainbow trout	Estimated	96 hours	LC50	0.33 mg/l

)						
trizinc bis(orthophosphate)	7779-90-0	Water flea	Estimated	48 hours	EC50	0.12 mg/l
trizinc bis(orthophosphate)	7779-90-0	Diatom	Estimated	72 hours	EC50	0.04 mg/l
trizinc bis(orthophosphate)	7779-90-0	Green algae	Estimated	72 hours	NOEC	0.01 mg/l
trizinc bis(orthophosphate)	7779-90-0	Water flea	Estimated	7 days	NOEC	0.026 mg/l
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Green algae	Experimental	72 hours	EC50	17 mg/l
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Rainbow trout	Experimental	96 hours	LC50	37.4 mg/l
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Water flea	Experimental	48 hours	EC50	3.1 mg/l
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Green algae	Experimental	72 hours	NOEC	1.8 mg/l
zinc oxide	1314-13-2	Activated sludge	Estimated	3 hours	EC50	6.5 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	EC50	0.052 mg/l
zinc oxide	1314-13-2	Rainbow trout	Estimated	96 hours	LC50	0.21 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	48 hours	EC50	0.07 mg/l
zinc oxide	1314-13-2	Green algae	Estimated	72 hours	NOEC	0.006 mg/l
zinc oxide	1314-13-2	Water flea	Estimated	7 days	NOEC	0.02 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Estimated Biodegradation	28 days	BOD	5 %BOD/ThOD	OECD 301F - Manometric respirometry
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Estimated Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
Phenol-formaldehyde polymer, glycidyl ether	28064-14-4	Laboratory Biodegradation	28 days	CO2 evolution	10-16 %CO2 evolution/THCO2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2
Barium Chromate	10294-40-3	Data not available - insufficient	N/A	N/A	N/A	N/A
2-(propyloxy)ethanol	2807-30-9	Experimental Biodegradation	20 days	BOD	100 %BOD/ThOD	

propan-2-ol	67-63-0	Experimental Biodegradation	14 days	BOD	86 %BOD/ThOD	OECD 301C - MITI test (I)
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Experimental Aquatic Inherent Biodegrad.	28 days	Dissolv. Organic Carbon Deplet	10 %removal of DOC (does not pass 10-day window)	similar to OECD 302B
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	33 days (t 1/2)	OECD 111 Hydrolysis func of pH
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 %BOD/ThOD	OECD 301D - Closed bottle test
acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	Experimental Biodegradation	28 days	BOD	34.7 % weight	OECD 301D - Closed bottle test
trizinc bis(orthophosphate)	7779-90-0	Data not availbl-insufficient	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Experimental Biodegradation	28 days	BOD	53 %BOD/ThOD	OECD 301F - Manometric respirometry
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Estimated Hydrolysis		Hydrolytic half-life	11.7 hours (t 1/2)	
zinc oxide	1314-13-2	Data not availbl-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Bisphenol A diglycidyl ether - bisphenol A copolymer	25036-25-3	Estimated Bioconcentration		Log Kow	3.242	
Phenol-formaldehyde polymer, glycidyl ether	28064-14-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Barium Chromate	10294-40-3	Estimated BCF - Other	40 days	Bioaccumulation factor	2650	
2-(propyloxy)ethanol	2807-30-9	Experimental Bioconcentration		Log Kow	0.673	
propan-2-ol	67-63-0	Experimental Bioconcentration		Log Kow	0.05	
N,N"-(4-Methyl-m-phenylene)bis[N',N'-dimethylurea]	17526-94-2	Modeled Bioconcentration		Log Kow	0.77	Episuite™
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	Modeled Bioconcentration		Bioaccumulation factor	5.7	Catalogic™
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	Modeled Bioconcentration		Log Kow	≥5.7	Episuite™
acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	
acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	Experimental Bioconcentration		Log Kow	3.77	
[3-(2,3-epoxypropoxy)propyl]diethoxymethylsilane	2897-60-1	Estimated Bioconcentration		Log Kow	1.3	
zinc oxide	1314-13-2	Experimental BCF - Fish	56 days	Bioaccumulation factor	≤217	OECD305-Bioconcentration

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Bisphenol A - epichlorhydrin - formaldehyde copolymer	28906-96-9	Modeled Mobility in Soil	Koc	≥3.5E+07 l/kg	Episuite™
acetone	67-64-1	Modeled Mobility in Soil	Koc	9.7 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(BISPHENOL A

	N.O.S.(BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER)	N.O.S.(BISPHENOL A DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER)	DIGLYCIDYL ETHER-BISPHENOL A COPOLYMER)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements

E1 Hazardous to the Aquatic environment	100	200
---	-----	-----

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
acetone	67-64-1	10	50
propan-2-ol	67-63-0	10	50
zinc oxide	1314-13-2	100	200
trizinc bis(orthophosphate)	7779-90-0	100	200

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H350i	May cause cancer by inhalation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

Formulation: Section 16: Annex information was deleted.
 GB Section 02: CLP Ingredient table information was added.
 GB Section 02: Other hazards phrase information was added.
 GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was added.
 GB Section 04: Information on toxicological effects information was added.
 GB Section 12: Classification Warning information was added.
 GB Section 15: Chemical Safety Assessment information was added.
 GB Section 15: Label remarks and EU Detergent information was added.
 GBSDS Section 14 Transport in bulk - Main Heading information was added.
 GBSDS Section 14 UN Number information was added.
 Industrial Use of Adhesives and Sealants: Section 16: Annex information was deleted.
 Industrial Use of Coatings: Section 16: Annex information was deleted.
 CLP: Ingredient table information was deleted.
 Label: CLP Classification information was modified.

Label: CLP Percent Unknown information was deleted.

Section 02: Label Elements: GB Percent Unknown information was added.

Section 2: Other hazards phrase information was deleted.

Section 3: Composition/ Information of ingredients table information was added.

Section 3: Composition/ Information of ingredients table information was deleted.

Section 04: First Aid - Symptoms and Effects (CLP) information was deleted.

Section 04: Information on toxicological effects information was deleted.

Section 5: Hazardous combustion products table information was modified.

Section 8: 8.2. Exposure controls information information was deleted.

Section 8: 8.2.3. Environmental exposure controls information information was deleted.

Section 8: DNEL table row information was deleted.

Section 8: Occupational exposure limit table information was modified.

Section 8: PNEC table row information was deleted.

Section 9: Vapour density value information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Classification disclaimer information was deleted.

Section 11: GB Classification disclaimer information was added.

Section 11: GB No endocrine disruptor information available warning information was added.

Section 11: No endocrine disruptor information available warning information was deleted.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Target Organs - Repeated Table information was added.

Section 11: Target Organs - Repeated Table information was deleted.

Section 12: 12.6. Endocrine Disrupting Properties information was deleted.

Section 12: 12.6. Other adverse effects information was added.

Section 12: 12.7. Other adverse effects information was deleted.

Section 12: Classification Warning information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was added.

Section 12: No Data text for mobility in soil information was deleted.

Section 12: No endocrine disruptor information available warning information was added.

Section 12: No endocrine disruptor information available warning information was deleted.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 13: Standard Phrase Category Waste GHS information was modified.

Section 14 Classification Code – Regulation Data information was modified.

Section 14 Control Temperature – Regulation Data information was modified.

Section 14 Emergency Temperature – Regulation Data information was modified.

Section 14 Multiplier – Main Heading information was deleted.

Section 14 Multiplier – Regulation Data information was deleted.

Section 14 Other Dangerous Goods – Regulation Data information was modified.

Section 14 Segregation – Regulation Data information was modified.

Section 14 Transport Category – Main Heading information was deleted.

Section 14 Transport Category – Regulation Data information was deleted.

Section 14 Transport in bulk – Regulation Data information was modified.

Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was deleted.

Section 14 Transport Not Permitted – Main Heading information was deleted.

Section 14 Transport Not Permitted – Regulation Data information was deleted.

Section 14 Tunnel Code – Main Heading information was deleted.

Section 14 Tunnel Code – Regulation Data information was deleted.

Section 14 UN Number information was deleted.

Section 15: Chemical Safety Assessment information was deleted.

Section 15: Label remarks and EU Detergent information was deleted.

Section 15: Regulations - Inventories information was added.

Section 15: Seveso Hazard Category Text information was added.

Section 15: Seveso Substance Text information was added.

Annex: Prediction of exposure statement information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was deleted.

Section 16: Web address information was added.

Section 16: Web address information was deleted.

Section 2: No PBT/vPvB information available warning information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.