



Safety Data Sheet

Copyright, 2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	27-5100-6	Version number:	5.00
Revision date:	16/08/2024	Supersedes date:	16/11/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Body Gard, Black - 08158 (PL9417)

Product Identification Numbers

UU-0083-6205-3 YP-2080-6031-6

7000116710 7100138681

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Aerosol, Category 1 - Aerosol 1; H222, H229
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD

DANGER.

Symbols

GHS02 (Flame) | GHS07 (Exclamation mark) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
n-butyl acetate	123-86-4	204-658-1	20 - 50

HAZARD STATEMENTS:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H336	May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261E	Avoid breathing vapour or spray.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	--

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

3% of the mixture consists of components of unknown acute oral toxicity.

Contains 3% of components with unknown hazards to the aquatic environment.

EU VOC Directive (2004/42/EC) labelling: 2004/42/EC IIB(e)(840)
634g/l

2.3. Other hazards

May displace oxygen and cause rapid suffocation.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1	20 - 50	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
Non-Volatile Components	Trade Secret	< 15	Substance not classified as hazardous
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9	< 12	Flam. Gas 1A, H220 Liquified gas, H280 Nota U
butane	(CAS-No.) 106-97-8 (EC-No.) 203-448-7	< 10	Flam. Gas 1A, H220 Liquified gas, H280 Nota C,U
Triiron tetraoxide	(CAS-No.) 1317-61-9 (EC-No.) 215-277-5	< 5	Substance not classified as hazardous
Poly[oxy(methyl-1,2-ethanediyl)]alpha-butyl-omega-hydroxy	(CAS-No.) 9003-13-8 (EC-No.) 500-003-1	< 5	Substance not classified as hazardous
isobutane	(CAS-No.) 75-28-5 (EC-No.) 200-857-2	< 5	Flam. Gas 1A, H220 Liquified gas, H280 Nota C,U
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	< 5	Substance with a national occupational exposure limit
Dolomite	(CAS-No.) 16389-88-1 (EC-No.) 240-440-2	< 3	Substance with a national occupational exposure limit
Magnesium carbonate	(CAS-No.) 546-93-0 (EC-No.) 208-915-9	< 3	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Dermal defatting (localized redness, itching, drying and cracking of skin). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion.

During combustion.

During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a

physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Vapours may travel long distances along the ground or floor to an ignition source and flash back. For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
butane	106-97-8	UK HSC	TWA:1450 mg/m ³ (600 ppm);STEL:1810 mg/m ³ (750 ppm)	
n-butyl acetate	123-86-4	UK HSC	TWA:724 mg/m ³ (150 ppm);STEL:966 mg/m ³ (200 ppm)	
Talc	14807-96-6	UK HSC	TWA(as respirable dust):1 mg/m ³	
DUST, INERT OR NUISANCE	16389-88-1	UK HSC	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	
Magnesium carbonate	546-93-0	UK HSC	TWA(as respirable dust):4 mg/m ³ ;TWA(as inhalable dust):10 mg/m ³	
propane	74-98-6	UK HSC	Limit value not established:	asphyxiant

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.
Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>0.3	=>8 hours
Polyvinyl alcohol (PVA).	>0.3	4-8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Colour	Black
Odor	Spicy, Sweet Odour
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	<i>No data available.</i>
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	-45 °C [<i>Test Method:Closed Cup</i>]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	<i>No data available.</i>
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	1.066 g/ml
Relative density	1.066 [<i>Ref Std:WATER=1</i>]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Percent volatile	72.06 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Harmful if inhaled. Simple asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg

Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >1 - =5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
n-butyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
n-butyl acetate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.4 mg/l
n-butyl acetate	Inhalation-Vapour (4 hours)	Rat	LC50 > 20 mg/l
n-butyl acetate	Ingestion	Rat	LD50 > 8,800 mg/kg
propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Non-Volatile Components	Dermal		LD50 estimated to be > 5,000 mg/kg
Non-Volatile Components	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
butane	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Triiron tetraoxide	Dermal	Not available	LD50 3,100 mg/kg
Triiron tetraoxide	Ingestion	Not available	LD50 3,700 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Magnesium carbonate	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Magnesium carbonate	Ingestion	Rat	LD50 > 2,000 mg/kg
Dolomite	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Dolomite	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
n-butyl acetate	Rabbit	Minimal irritation
propane	Rabbit	Minimal irritation
butane	Professional judgement	No significant irritation
isobutane	Professional judgement	No significant irritation
Triiron tetraoxide	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Magnesium carbonate	In vitro data	No significant irritation
Dolomite	Professional judgement	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
------	---------	-------

n-butyl acetate	Rabbit	Moderate irritant
propane	Rabbit	Mild irritant
butane	Rabbit	No significant irritation
isobutane	Professional judgement	No significant irritation
Triiron tetraoxide	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Magnesium carbonate	Rabbit	Mild irritant
Dolomite	Professional judgement	No significant irritation

Skin Sensitisation

Name	Species	Value
n-butyl acetate	Multiple animal species	Not classified
Triiron tetraoxide	Human	Not classified

Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
n-butyl acetate	In Vitro	Not mutagenic
propane	In Vitro	Not mutagenic
butane	In Vitro	Not mutagenic
isobutane	In Vitro	Not mutagenic
Triiron tetraoxide	In Vitro	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Triiron tetraoxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
n-butyl acetate	Inhalation	Not classified for female reproduction	Rat	NOAEL 7.1 mg/l	prematuring & during gestation
n-butyl acetate	Inhalation	Not classified for development	Rat	NOAEL 7.1 mg/l	prematuring & during gestation
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
n-butyl acetate	Inhalation	respiratory system	May cause damage to organs	Rat	LOAEL 2.6 mg/l	4 hours
n-butyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
n-butyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	not available
n-butyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
propane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
butane	Inhalation	cardiac sensitisation	Causes damage to organs	Human	NOAEL Not available	
butane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
butane	Inhalation	heart	Not classified	Dog	NOAEL 5,000 ppm	25 minutes
butane	Inhalation	respiratory irritation	Not classified	Rabbit	NOAEL Not available	
isobutane	Inhalation	cardiac sensitisation	Causes damage to organs	Multiple animal species	NOAEL Not available	
isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
n-butyl acetate	Inhalation	olfactory system	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
n-butyl acetate	Inhalation	liver kidney and/or bladder	Not classified	Rabbit	NOAEL 7.26 mg/l	13 days
butane	Inhalation	kidney and/or bladder blood	Not classified	Rat	NOAEL 4,489 ppm	90 days
isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
Triiron tetraoxide	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
n-butyl acetate	123-86-4	Green algae	Analogous Compound	72 hours	ErC50	397 mg/l
n-butyl acetate	123-86-4	Fathead minnow	Experimental	96 hours	LC50	18 mg/l
n-butyl acetate	123-86-4	Water flea	Experimental	48 hours	EC50	44 mg/l
n-butyl acetate	123-86-4	Green algae	Analogous Compound	72 hours	NOEC	196 mg/l
n-butyl acetate	123-86-4	Water flea	Analogous Compound	21 days	NOEC	23.2 mg/l
n-butyl acetate	123-86-4	Ciliated protozoa	Experimental	40 hours	IC50	356 mg/l
n-butyl acetate	123-86-4	Lettuce	Experimental	14 days	EC50	>1,000 mg/kg (Dry Weight)
Non-Volatile Components	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
propane	74-98-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
butane	106-97-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Triiron tetraoxide	1317-61-9	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Water flea	Analogous Compound	48 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Zebra Fish	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Water flea	Analogous Compound	21 days	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Activated sludge	Analogous Compound	3 hours	EC50	>=10,000 mg/l
isobutane	75-28-5	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Poly[oxy(methyl-1,2-ethanediyl)]alpha-butyl-omega-hydroxy	9003-13-8	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Dolomite	16389-88-1	Water flea	Estimated	48 hours	EC50	190 mg/l

3M Body Gard, Black - 08158 (PL9417)

Dolomite	16389-88-1	Western Mosquitofish	Estimated	96 hours	LC50	>100 mg/l
Dolomite	16389-88-1	Rainbow trout	Estimated	21 days	NOEC	>100 mg/l
Magnesium carbonate	546-93-0	Activated sludge	Estimated	3 hours	EC50	>900 mg/l
Magnesium carbonate	546-93-0	Fathead minnow	Estimated	96 hours	LC50	1,880 mg/l
Magnesium carbonate	546-93-0	Green algae	Estimated	72 hours	EC50	>100 mg/l
Magnesium carbonate	546-93-0	Water flea	Estimated	48 hours	LC50	486 mg/l
Magnesium carbonate	546-93-0	Green algae	Estimated	72 hours	NOEC	100 mg/l
Magnesium carbonate	546-93-0	Water flea	Estimated	21 days	EC10	284 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
n-butyl acetate	123-86-4	Experimental Biodegradation	28 days	BOD	83 %BOD/ThOD	OECD 301D - Closed bottle test
n-butyl acetate	123-86-4	Experimental Photolysis		Photolytic half-life (in air)	6.3 days (t 1/2)	
n-butyl acetate	123-86-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	3.1 years (t 1/2)	
Non-Volatile Components	Trade Secret	Data not available or insufficient	N/A	N/A	N/A	N/A
propane	74-98-6	Experimental Photolysis		Photolytic half-life (in air)	27.5 days (t 1/2)	
butane	106-97-8	Experimental Photolysis		Photolytic half-life (in air)	12.3 days (t 1/2)	
Triiron tetraoxide	1317-61-9	Data not available or insufficient	N/A	N/A	N/A	N/A
isobutane	75-28-5	Experimental Photolysis		Photolytic half-life (in air)	13.4 days (t 1/2)	
Poly[oxy(methyl-1,2-ethanediyl)]alpha-butyl-omega-hydroxy	9003-13-8	Modeled Biodegradation	28 days	BOD	79 %BOD/ThOD	Catalogic™
Talc	14807-96-6	Data not available or insufficient	N/A	N/A	N/A	N/A
Dolomite	16389-88-1	Data not available or insufficient	N/A	N/A	N/A	N/A
Magnesium carbonate	546-93-0	Data not available or insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
n-butyl acetate	123-86-4	Experimental Bioconcentration		Log Kow	2.3	OECD 117 log Kow HPLC method
Non-Volatile Components	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
propane	74-98-6	Experimental Bioconcentration		Log Kow	2.36	
butane	106-97-8	Experimental Bioconcentration		Log Kow	2.89	
Triiron tetraoxide	1317-61-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
isobutane	75-28-5	Experimental Bioconcentration		Log Kow	2.76	

3M Body Gard, Black - 08158 (PL9417)

Poly[oxy(methyl-1,2-ethanediyl)]alpha-butyl-omega-hydroxy	9003-13-8	Modeled Bioconcentration		Bioaccumulation factor	3	Catalogic™
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dolomite	16389-88-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Magnesium carbonate	546-93-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
n-butyl acetate	123-86-4	Modeled Mobility in Soil	Koc	135 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

EU waste code (product container after use)

15 01 04 Metallic packaging

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN1950	UN1950	UN1950

14.2 UN proper shipping name	AEROSOLS	AEROSOLS, FLAMMABLE	AEROSOLS
14.3 Transport hazard class(es)	2.1	2.1	2.1
14.4 Packing group	Not applicable.	Not applicable.	Not applicable.
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	5F	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P3a FLAMMABLE AEROSOLS	150 (net)	500 (net)

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
butane	106-97-8	10	50

isobutane	75-28-5	10	50
n-butyl acetate	123-86-4	10	50
propane	74-98-6	10	50

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information**List of relevant H statements**

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H336	May cause drowsiness or dizziness.

Revision information:

GB Section 02: CLP Ingredient table information was added.
GB Section 02: Other hazards phrase information was added.
GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was added.
GB Section 04: Information on toxicological effects information was added.
GB Section 12: Classification Warning information was added.
GB Section 15: Chemical Safety Assessment information was added.
GBSDS Section 14 Transport in bulk - Main Heading information was added.
GBSDS Section 14 UN Number information was added.
CLP: Ingredient table information was deleted.
Label: CLP Percent Unknown information was deleted.
Section 02: Label Elements: GB Percent Unknown information was added.
Section 2: Other hazards phrase information was deleted.
Section 3: Composition/ Information of ingredients table information was added.
Section 3: Composition/ Information of ingredients table information was deleted.
Section 04: First Aid - Symptoms and Effects (CLP) information was deleted.
Section 04: Information on toxicological effects information was deleted.
Section 6: Accidental release clean-up information information was modified.
Section 8: Eye/face protection information information was modified.
Section 8: glove data value information was added.
Section 8: glove data value information was modified.
Section 9: Flammability (solid, gas) information information was deleted.
Section 09: Flammability information information was added.
Section 09: Odor information was modified.
Section 09: Particle Characteristics N/A information was added.
Section 11: Classification disclaimer information was deleted.
Section 11: GB Classification disclaimer information was added.
Section 11: GB No endocrine disruptor information available warning information was added.
Section 11: No endocrine disruptor information available warning information was deleted.
Section 11: Prolonged or repeated exposure may cause standard phrases information was added.
Section 12: 12.6. Endocrine Disrupting Properties information was deleted.
Section 12: 12.6. Other adverse effects information was added.

Section 12: 12.7. Other adverse effects information was deleted.

Section 12: Classification Warning information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Prints No Data if Adverse effects information is not present information was deleted.

Section 12: No endocrine disruptor information available warning information was added.

Section 12: No endocrine disruptor information available warning information was deleted.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was deleted.

Section 14 UN Number information was deleted.

Section 15: Chemical Safety Assessment information was deleted.

Section 15: Seveso Hazard Category Text information was added.

Section 15: Seveso Substance Text information was added.

Section 15: Seveso Substance Text information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was deleted.

Section 16: Web address information was added.

Section 16: Web address information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.