



Safety Data Sheet

Copyright,2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 28-8088-8 **Version number:** 13.02
Revision date: 15/10/2020 **Supersedes date:** 15/10/2020
Transportation version number: 1.00 (16/06/2011)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 Kit

Product Identification Numbers

FS-9100-2896-8	FS-9100-4049-2	UU-0111-3394-7	UU-0111-3804-5
7000079932	7000080089	7100240965	7100241346

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

28-8077-1, 28-8085-4

TRANSPORTATION INFORMATION

FS-9100-2896-8, FS-9100-4049-2

Not hazardous for transportation

UU-0111-3394-7

UU-0111-3804-5

KIT LABEL

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H302
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Reproductive Toxicity, Category 1B - Repr. 1B; H360
Germ Cell Mutagenicity, Category 2 - Muta. 2; H341
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols:

GHS05 (Corrosion) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

Pictograms



Contains:

Boron, hexaethyl[μ -(1,6-hexanediamine-kN1:kN6)]di-; Tetrahydrofurfuryl methacrylate; 2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate); [2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate; 2-Ethylhexyl methacrylate; succinic anhydride; 2-hydroxyethyl methacrylate

HAZARD STATEMENTS:

H302	Harmful if swallowed.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H360D	May damage the unborn child.
H341	Suspected of causing genetic defects.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

P280B Wear protective gloves and eye/face protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318 Causes serious eye damage.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H360D May damage the unborn child.
H341 Suspected of causing genetic defects.

H412 Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P261A Avoid breathing vapours.
P280B Wear protective gloves and eye/face protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Label: CLP Ingredients - kit components information was modified.
Section 1: Product identification numbers information was modified.
Section 01: SAP Material Numbers information was modified.



Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-8085-4	Version number:	10.01
Revision date:	09/06/2022	Supersedes date:	07/06/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part A)

Product Identification Numbers

FS-9100-3812-4

7000080039

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318
Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Germ Cell Mutagenicity, Category 2 - Muta. 2; H341
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS05 (Corrosion) |GHS08 (Health Hazard) |GHS09 (Environment) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	64265-57-2	264-763-3	20 - 40
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	223674-50-8	426-100-8	5 - 20

HAZARD STATEMENTS:

H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A	Avoid breathing vapours.
P280B	Wear protective gloves and eye/face protection.

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.

<=125 ml Precautionary statements

Prevention:

P261A	Avoid breathing vapours.
P280B	Wear protective gloves and eye/face protection.

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

44% of the mixture consists of components of unknown acute oral toxicity.

Contains 100% of components with unknown hazards to the aquatic environment.

Notes on labelling

Polyfunctional aziridine is classified as Acute Tox. 2 (H330) based on dust/mist (aerosol) data.

When incorporated into this product, this substance cannot become aerosolized.

Based on available toxicology data and this substance's very low vapour pressure, the saturated vapour of polyfunctional aziridine is not expected to be acutely toxic. Therefore, the classification is not applicable for this material when used as intended.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polyester plasticizer	Trade Secret	40 - 60	Substance not classified as hazardous
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	(CAS-No.) 64265-57-2 (EC-No.) 264-763-3	20 - 40	Acute Tox. 2, H330 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	(CAS-No.) 223674-50-8 (EC-No.) ELINCS 426-100-8	5 - 20	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Sens. 1, H317

Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	0.5 - 1.5	Substance with a national occupational exposure limit
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	0.1 - 0.5	Carc. 2, H351 (inhalation)

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes.
Carbon monoxide
Carbon dioxide.
Irritant vapours or gases.
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
------------	---------	--------	------------	---------------------

Titanium dioxide	13463-67-7	UK HSC	TWA(respirable):4 mg/m ³ ;TWA(Inhalable):10 mg/m ³
Silicon dioxide	67762-90-7	UK HSC	TWA(as respirable dust):2.4 mg/m ³ ;TWA(as inhalable dust):6 mg/m ³

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Mild Odor
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>No data available.</i>
Boiling point/boiling range	≥ 181 °C [Details:758 mmHg]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Flash point	≥ 93.3 °C [Test Method:Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	33,333 mm ² /sec
Water solubility	Slight (less than 10%)
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	1.05 - 1.09 g/ml
Relative density	1.05 - 1.09 [Ref Std:WATER=1]
Relative Vapor Density	<i>No data available.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>Not applicable.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

10.5 Incompatible materials

Strong acids.
Strong bases.
Strong oxidising agents.
Amines.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision. Vapours released during curing may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or

the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >300 - =2,000 mg/kg
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Dermal	Rabbit	LD50 > 3,000 mg/kg
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.252 mg/l
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Ingestion	Rat	LD50 3,038 mg/kg
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	Ingestion	Rat	LD50 693 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Rabbit	Mild irritant
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	Rabbit	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Rabbit	Corrosive
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	Professional judgement	Severe irritant
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Human and animal	Sensitising
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	Guinea pig	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Titanium dioxide	Human and animal	Not classified

Respiratory Sensitisation

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part A)

Name	Species	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	In vivo	Mutagenic
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	64265-57-2	Algae or other aquatic plants	Unknown	72 hours	EC50	3.8 mg/l
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	64265-57-2	Fish	Unknown	96 hours	LC50	2.35 mg/l
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl]methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	64265-57-2	Invertebrate	Unknown	48 hours	EC50	6.96 mg/l
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	223674-50-8		Data not available or insufficient for classification			N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		Data not available or insufficient for classification			N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
2-ethyl-2-[[3-(2-methylaziridin-1-	64265-57-2	Experimental Biodegradation	28 days	CO2 evolution	<60 %CO2 evolution/THC	OECD 301B - Modified sturm or CO2

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part A)

yl)propionyl)methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)					O2 evolution	
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	223674-50-8	Experimental Biodegradation	28 days	CO2 evolution	44 %CO2 evolution/THC O2 evolution	EC C.4.C. CO2 Evolution Test
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available/insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not available/insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl)methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	64265-57-2	Modeled Bioconcentration		Log Kow	0.5	ACD/Labs ChemSketch™
Boron, hexaethyl[μ-(1,6-hexanediamine-kN1:kN6)]di-	223674-50-8	Experimental Bioconcentration		Log Kow	>5.99	EC A.8 Partition Coefficient
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Carp	42 days	Bioaccumulation factor	9.6	Non-standard method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-ethyl-2-[[3-(2-methylaziridin-1-yl)propionyl)methyl]propane-1,3-diyl bis(2-methylaziridine-1-propionate)	64265-57-2	Modeled Mobility in Soil	Koc	19,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or

polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.

IMDG Segregation Code	No data available.	No data available.	No data available.
------------------------------	--------------------	--------------------	--------------------

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

Titanium dioxide

CAS Nbr

13463-67-7

Classification

Grp. 2B: Possible human
carc.

Regulation

International Agency
for Research on Cancer

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

None

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H351i	Suspected of causing cancer by inhalation.
H411	Toxic to aquatic life with long lasting effects.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk



Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-8077-1	Version number:	11.00
Revision date:	07/06/2022	Supersedes date:	17/02/2020

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part B)

Product Identification Numbers

FS-9100-3811-6

7000080038

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317
 Reproductive Toxicity, Category 1B - Repr. 1B; H360D
 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Tetrahydrofurfuryl methacrylate	2455-24-5	219-529-5	40 - 50
2-Ethylhexyl methacrylate	688-84-6	211-708-6	10 - 20
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	244-096-4	3 - 7
succinic anhydride	108-30-5	203-570-0	< 1
2-hydroxyethyl methacrylate	868-77-9	212-782-2	< 0.2
methyl methacrylate	80-62-6	201-297-1	< 0.2

HAZARD STATEMENTS:

H317	May cause an allergic skin reaction.
H360D	May damage the unborn child.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P280E	Wear protective gloves.

Response:

P308 + P313	IF exposed or concerned: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317	May cause an allergic skin reaction.
H360D	May damage the unborn child.

H412 Harmful to aquatic life with long lasting effects.

<=125 ml Precautionary statements

Prevention:

P201 Obtain special instructions before use.
 P280E Wear protective gloves.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Restricted to professional users.

32% of the mixture consists of components of unknown acute oral toxicity.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Tetrahydrofurfuryl methacrylate	(CAS-No.) 2455-24-5 (EC-No.) 219-529-5	40 - 50	Skin Sens. 1, H317 Repr. 1B, H360D Aquatic Chronic 3, H412
Acrylate polymer	Trade Secret	20 - 30	Substance not classified as hazardous
2-Ethylhexyl methacrylate	(CAS-No.) 688-84-6 (EC-No.) 211-708-6 (REACH-No.) 01-2119490166-35	10 - 20	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	(CAS-No.) 21282-97-3 (EC-No.) 244-311-1	3 - 7	Substance not classified as hazardous
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	(CAS-No.) 20882-04-6 (EC-No.) 244-096-4	3 - 7	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Ashes (residues), cenospheres	(CAS-No.) 93924-19-7 (EC-No.) 300-212-6 (REACH-No.) 01-2119563688-21	1 - 5	Substance not classified as hazardous
succinic anhydride	(CAS-No.) 108-30-5 (EC-No.) 203-570-0 (REACH-No.) 01-	< 1	EUH071 Acute Tox. 4, H302 Skin Corr. 1, H314

	2119485841-30		Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1, H317
methyl methacrylate	(CAS-No.) 80-62-6 (EC-No.) 201-297-1	< 0.2	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Nota D
styrene	(CAS-No.) 100-42-5 (EC-No.) 202-851-5	< 0.2	Flam. Liq. 3, H226 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Repr. 2, H361d STOT RE 1, H372 Nota D Aquatic Chronic 3, H412 Asp. Tox. 1, H304 STOT SE 3, H335
2-hydroxyethyl methacrylate	(CAS-No.) 868-77-9 (EC-No.) 212-782-2	< 0.2	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Nota D

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:
Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons.
Carbon monoxide
Carbon dioxide.
Hydrogen cyanide.
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and

personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
styrene	100-42-5	UK HSC	TWA:430 mg/m ³ (100 ppm);STEL:1080 mg/m ³ (250 ppm)	
methyl methacrylate	80-62-6	UK HSC	TWA:208 mg/m ³ (50 ppm);STEL:416 mg/m ³ (100 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Off-White
Odor	Acrylic
Odour threshold	<i>No data available.</i>
Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	>=110 °C [<i>Details: CAS #688-84-6</i>]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	>=94 °C [<i>Details: CAS #688-84-6</i>]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	17,708 mm ² /sec
Water solubility	<i>Not applicable.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	0.96 - 1 g/ml
Relative density	0.96 - 1 [<i>Ref Std: WATER=1</i>]
Relative Vapor Density	<i>No data available.</i>

9.2. Other information**9.2.2 Other safety characteristics**

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>Not applicable.</i>
Percent volatile	1 %

SECTION 10: Stability and reactivity**10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.
Light.

10.5 Incompatible materials

Strong acids.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

May be harmful in contact with skin. Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Tetrahydrofurfuryl methacrylate	Ingestion	Rat	LD50 4,000 mg/kg
Tetrahydrofurfuryl methacrylate	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
2-Ethylhexyl methacrylate	Dermal		LD50 estimated to be > 5,000 mg/kg
2-Ethylhexyl methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Dermal	Rat	LD50 > 2,000 mg/kg
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Rat	LD50 > 5,000 mg/kg
succinic anhydride	Dermal	Rat	LD50 > 2,000 mg/kg
succinic anhydride	Ingestion	Rat	LD50 1,510 mg/kg
methyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
methyl methacrylate	Inhalation-Vapour (4 hours)	Rat	LC50 29 mg/l
methyl methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
styrene	Dermal	Rat	LD50 > 2,000 mg/kg
styrene	Inhalation-Vapour (4 hours)	Rat	LC50 11.8 mg/l
styrene	Ingestion	Rat	LD50 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Tetrahydrofurfuryl methacrylate	Rabbit	No significant irritation
2-Ethylhexyl methacrylate	Rabbit	Minimal irritation
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Not applicable	Irritant
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Rabbit	No significant irritation
succinic anhydride	In vitro data	Corrosive
methyl methacrylate	Human and animal	Mild irritant
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
styrene	Professional judgement	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part B)

Tetrahydrofurfuryl methacrylate	Rabbit	No significant irritation
2-Ethylhexyl methacrylate	Rabbit	No significant irritation
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Not available	Severe irritant
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Rabbit	No significant irritation
succinic anhydride	similar health hazards	Corrosive
methyl methacrylate	Rabbit	Moderate irritant
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
styrene	Professional judgement	Moderate irritant

Skin Sensitisation

Name	Species	Value
Tetrahydrofurfuryl methacrylate	In vitro data	Sensitising
2-Ethylhexyl methacrylate	Guinea pig	Sensitising
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	similar compounds	Sensitising
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Mouse	Not classified
succinic anhydride	Mouse	Sensitising
methyl methacrylate	Human and animal	Sensitising
2-hydroxyethyl methacrylate	Human and animal	Sensitising
styrene	Guinea pig	Not classified

Respiratory Sensitisation

Name	Species	Value
succinic anhydride	similar compounds	Sensitising
methyl methacrylate	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Tetrahydrofurfuryl methacrylate	In Vitro	Not mutagenic
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	In Vitro	Not mutagenic
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	In vivo	Not mutagenic
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	In Vitro	Some positive data exist, but the data are not sufficient for classification
succinic anhydride	In Vitro	Not mutagenic
methyl methacrylate	In vivo	Not mutagenic
methyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
styrene	In Vitro	Some positive data exist, but the data are not sufficient for classification
styrene	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
succinic anhydride	Ingestion	Multiple animal species	Not carcinogenic
methyl methacrylate	Ingestion	Rat	Not carcinogenic
methyl methacrylate	Inhalation	Human and animal	Not carcinogenic
styrene	Ingestion	Mouse	Carcinogenic.
styrene	Inhalation	Human and animal	Carcinogenic.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Tetrahydrofurfuryl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	29 days
Tetrahydrofurfuryl methacrylate	Ingestion	Toxic to female reproduction	Rat	NOAEL 120 mg/kg/day	premating into lactation
Tetrahydrofurfuryl methacrylate	Ingestion	Toxic to development	Rat	NOAEL 120 mg/kg/day	premating into lactation
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	premating into lactation
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	56 days
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
methyl methacrylate	Inhalation	Not classified for male reproduction	Mouse	NOAEL 36.9 mg/l	
methyl methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
styrene	Ingestion	Not classified for female reproduction	Rat	NOAEL 21 mg/kg/day	3 generation
styrene	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.1 mg/l	2 generation
styrene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.1 mg/l	2 generation
styrene	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	60 days
styrene	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during gestation
styrene	Inhalation	Not classified for development	Multiple animal species	NOAEL 2.1 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part B)

[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
succinic anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
methyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
styrene	Inhalation	auditory system	Causes damage to organs	Multiple animal species	LOAEL 4.3 mg/l	not available
styrene	Inhalation	liver	Causes damage to organs	Mouse	LOAEL 2.1 mg/l	not available
styrene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
styrene	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
styrene	Inhalation	endocrine system	Not classified	Rat	NOAEL Not available	not available
styrene	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2.1 mg/l	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Tetrahydrofurfuryl methacrylate	Ingestion	hematopoietic system nervous system	Not classified	Rat	NOAEL 300 mg/kg/day	29 days
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	Ingestion	hematopoietic system nervous system eyes	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
succinic anhydride	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Mouse	NOAEL 300 mg/kg/day	13 weeks
methyl methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
methyl methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
methyl methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
styrene	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
styrene	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
styrene	Inhalation	liver	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 0.85 mg/l	13 weeks
styrene	Inhalation	nervous system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 1.1 mg/l	not available
styrene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 0.85 mg/l	7 days

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part B)

styrene	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.6 mg/l	10 days
styrene	Inhalation	respiratory system	Not classified	Multiple animal species	LOAEL 0.09 mg/l	not available
styrene	Inhalation	heart gastrointestinal tract bone, teeth, nails, and/or hair muscles kidney and/or bladder	Not classified	Multiple animal species	NOAEL 4.3 mg/l	2 years
styrene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 500 mg/kg/day	8 weeks
styrene	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL Not available	not available
styrene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 677 mg/kg/day	6 months
styrene	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 600 mg/kg/day	470 days
styrene	Ingestion	heart respiratory system	Not classified	Rat	NOAEL 35 mg/kg/day	105 weeks

Aspiration Hazard

Name	Value
styrene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Tetrahydrofurfuryl methacrylate	2455-24-5	Fathead minnow	Experimental	96 hours	LC50	34.7 mg/l
Tetrahydrofurfuryl methacrylate	2455-24-5	Green algae	Experimental	72 hours	EC50	>100 mg/l
Tetrahydrofurfuryl methacrylate	2455-24-5	Green algae	Experimental	72 hours	EC10	100 mg/l
Tetrahydrofurfuryl methacrylate	2455-24-5	Water flea	Experimental	21 days	NOEC	37.2 mg/l
Acrylate polymer	Trade Secret		Data not available or insufficient for classification			N/A
2-Ethylhexyl methacrylate	688-84-6	Green algae	Experimental	72 hours	EC50	5.3 mg/l
2-Ethylhexyl methacrylate	688-84-6	Medaka	Experimental	96 hours	LC50	2.8 mg/l

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part B)

2-Ethylhexyl methacrylate	688-84-6	Water flea	Experimental	48 hours	EC50	4.6 mg/l
2-Ethylhexyl methacrylate	688-84-6	Green algae	Experimental	72 hours	NOEC	0.81 mg/l
2-Ethylhexyl methacrylate	688-84-6	Water flea	Experimental	21 days	NOEC	0.105 mg/l
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Green algae	Estimated	72 hours	EC50	710 mg/l
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Medaka	Estimated	96 hours	LC50	227 mg/l
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Water flea	Estimated	48 hours	EC50	380 mg/l
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Green algae	Estimated	72 hours	NOEC	160 mg/l
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Water flea	Estimated	21 days	NOEC	24.1 mg/l
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Activated sludge	Experimental	3 hours	NOEC	320 mg/l
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Green algae	Experimental	72 hours	EC50	>100 mg/l
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Water flea	Experimental	48 hours	EL50	>100 mg/l
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Green algae	Experimental	72 hours	NOEC	11.1 mg/l
Ashes (residues), cenospheres	93924-19-7	Activated sludge	Experimental	3 hours	NOEC	1,000 mg/l
Ashes (residues), cenospheres	93924-19-7	Green algae	Experimental	72 hours	EL50	>100 mg/l
Ashes (residues), cenospheres	93924-19-7	Guppy	Experimental	96 hours	LL50	>100 mg/l
Ashes (residues), cenospheres	93924-19-7	Water flea	Experimental	48 hours	EL50	>100 mg/l
Ashes (residues), cenospheres	93924-19-7	Green algae	Experimental	72 hours	NOEL	100 mg/l
Ashes (residues), cenospheres	93924-19-7	Water flea	Experimental	21 days	NOEL	100 mg/l
succinic anhydride	108-30-5	Green algae	Estimated	72 hours	EC50	>100 mg/l
succinic anhydride	108-30-5	Water flea	Estimated	48 hours	EC50	>100 mg/l
succinic anhydride	108-30-5	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
succinic anhydride	108-30-5	Green algae	Estimated	72 hours	NOEC	100 mg/l
2-hydroxyethyl methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part B)

2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-hydroxyethyl methacrylate	868-77-9		Experimental	16 hours	EC0	>3,000 mg/l
2-hydroxyethyl methacrylate	868-77-9		Experimental	18 hours	LD50	<98 mg per kg of bodyweight
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	EC50	>110 mg/l
methyl methacrylate	80-62-6	Rainbow trout	Experimental	96 hours	LC50	>79 mg/l
methyl methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l
methyl methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
methyl methacrylate	80-62-6	Activated sludge	Experimental	30 minutes	EC20	150 mg/l
methyl methacrylate	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry Weight)
styrene	100-42-5	Activated sludge	Experimental	30 minutes	EC50	500 mg/l
styrene	100-42-5	Fathead minnow	Experimental	96 hours	LC50	4.02 mg/l
styrene	100-42-5	Green algae	Experimental	72 hours	EC50	4.9 mg/l
styrene	100-42-5	Water flea	Experimental	48 hours	EC50	4.7 mg/l
styrene	100-42-5	Green algae	Experimental	96 hours	EC10	0.28 mg/l
styrene	100-42-5	Water flea	Experimental	21 days	NOEC	1.01 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurfuryl methacrylate	2455-24-5	Experimental Biodegradation	28 days	BOD	75 %BOD/ThB OD	OECD 301F - Manometric respirometry
Acrylate polymer	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
2-Ethylhexyl methacrylate	688-84-6	Experimental Biodegradation	28 days	BOD	88 %BOD/ThB OD	OECD 301C - MITI test (I)
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Estimated Biodegradation	14 days	BOD	95 % weight	OECD 301C - MITI test (I)
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Experimental Hydrolysis		Hydrolytic half-life	6.5 days (t 1/2)	Non-standard method
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Experimental Biodegradation	28 days	BOD	64 %BOD/ThB OD	OECD 301C - MITI test (I)
Ashes (residues), cenospheres	93924-19-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
succinic anhydride	108-30-5	Experimental Hydrolysis		Hydrolytic half-life	4.3 minutes (t 1/2)	Non-standard method
succinic anhydride	108-30-5	Estimated Biodegradation	28 days	Dissolv. Organic Carbon Deplet	96.55 % weight	OECD 301E - Modif. OECD Screen
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/CO D	OECD 301D - Closed bottle test
methyl methacrylate	80-62-6	Experimental	14 days	BOD	94 %BOD/ThB	OECD 301C - MITI test (I)

3M™ Scotch-Weld™ Acrylic Structural Adhesive DP-8005 (Part B)

		Biodegradation			OD	
styrene	100-42-5	Experimental Photolysis		Photolytic half-life (in air)	6.64 hours (t _{1/2})	Non-standard method
styrene	100-42-5	Experimental Biodegradation	28 days	BOD	70.9 %BOD/Th BOD	Non-standard method

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Tetrahydrofurfuryl methacrylate	2455-24-5	Estimated Bioconcentration		Bioaccumulation factor	3.42	Estimated: Bioconcentration factor
Acrylate polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-Ethylhexyl methacrylate	688-84-6	Experimental Bioconcentration	96 hours	Bioaccumulation factor	37	OECD 305C-Bioaccum degree fish
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Estimated Bioconcentration		Bioaccumulation factor	3.0	Estimated: Bioconcentration factor
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Experimental Bioconcentration		Log Kow	0.9	Non-standard method
Ashes (residues), cenospheres	93924-19-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
succinic anhydride	108-30-5	Experimental Bioconcentration		Log Kow	2.44	Non-standard method
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flask mtd
methyl methacrylate	80-62-6	Experimental Bioconcentration		Log Kow	1.38	OECD 107 log Kow shke flask mtd
styrene	100-42-5	Experimental Bioconcentration		Log Kow	2.96	Non-standard method

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
2-Ethylhexyl methacrylate	688-84-6	Estimated Mobility in Soil	Koc	2,348 l/kg	Episuite™
[2-[(2-Methyl-1-oxoallyl)oxy]ethyl] hydrogen succinate	20882-04-6	Estimated Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™
Butanoic acid, 3-oxo-, 2-[(2-methyl-1-oxo-2-propenyl)oxy]ethyl ester	21282-97-3	Experimental Mobility in Soil	Koc	51-129 l/kg	OECD 106 Adsp-Desb Batch Equil
2-hydroxyethyl methacrylate	868-77-9	Experimental Mobility in Soil	Koc	42.7 l/kg	
methyl methacrylate	80-62-6	Experimental Mobility in Soil	Koc	8.7-72 l/kg	

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

- 08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances
- 20 01 27* Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

ADR/IMDG/IATA: Not restricted for transport.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.

Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
methyl methacrylate	80-62-6	Gr. 3: Not classifiable	International Agency for Research on Cancer
styrene	100-42-5	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
succinic anhydride	108-30-5	Gr. 3: Not classifiable	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
methyl methacrylate	80-62-6	50	200
styrene	100-42-5	10	50

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH071	Corrosive to the respiratory tract.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

EU Section 09: pH information information was added.
Section 1: Product identification numbers information was added.
Section 01: SAP Material Numbers information was added.
Section 2: <125ml Precautionary - Response information was modified.
CLP: Ingredient table information was modified.
Label: CLP Classification information was modified.
Label: CLP Percent Unknown information was deleted.
Label: CLP Percent Unknown information was modified.
Label: CLP Precautionary - Disposal information was deleted.
Label: CLP Precautionary - Response information was modified.
Label: CLP Supplemental Precautionary Statements information was deleted.
Section 02: SDS Elements: CLP Supplemental Precautionary Statements information was added.
Section 03: Composition table % Column heading information was added.
Section 3: Composition/ Information of ingredients table information was modified.
Section 03: Substance not applicable information was added.
Section 04: First Aid - Symptoms and Effects (CLP) information was added.
Section 4: First aid for eye contact information information was modified.
Section 04: Information on toxicological effects information was modified.
Section 7: Precautions safe handling information information was modified.
Section 8: Appropriate Engineering controls information information was modified.
Section 8: Eye protection information information was added.
Section 8: Eye/face protection information information was deleted.
Section 8: Occupational exposure limit table information was added.
Section 8: Occupational exposure limit table information was modified.
OEL Reg Agency Desc information was added.
Section 8: Personal Protection - Eye information information was deleted.
Section 8: STEL key information was added.
Section 8: TWA key information was added.
Section 9: Evaporation Rate information information was deleted.
Section 9: Explosive properties information information was deleted.
Section 09: Kinematic Viscosity information information was added.
Section 9: Melting point information information was modified.
Section 9: Oxidising properties information information was deleted.
Section 9: pH information information was deleted.
Section 9: Property description for optional properties information was modified.
Section 9: Vapour density value information was added.

Section 9: Vapour density value information was deleted.
Section 9: Viscosity information information was deleted.
Section 11: Acute Toxicity table information was modified.
Section 11: Aspiration Hazard Table information was added.
Section 11: Aspiration Hazard text information was deleted.
Section 11: Cancer Hazards information information was added.
Section 11: Carcinogenicity Table information was modified.
Section 11: Classification disclaimer information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Health Effects - Eye information information was modified.
Section 11: Health Effects - Ingestion information information was modified.
Section 11: Health Effects - Skin information information was modified.
Section 11: No endocrine disruptor information available warning information was added.
Section 11: Reproductive Hazards information information was deleted.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Reproductive/developmental effects information information was added.
Section 11: Respiratory Sensitization Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Skin Sensitization Table information was modified.
Section 11: Target Organs - Repeated Table information was added.
Section 11: Target Organs - Repeated Table information was deleted.
Section 11: Target Organs - Single Table information was modified.
Section 12: 12.6. Endocrine Disrupting Properties information was added.
Section 12: 12.7. Other adverse effects information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Contact manufacturer for more detail. information was deleted.
Section 12: Mobility in soil information information was added.
Section 12: No endocrine disruptor information available warning information was added.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 14 Classification Code – Main Heading information was added.
Section 14 Classification Code – Regulation Data information was added.
Section 14 Control Temperature – Main Heading information was added.
Section 14 Control Temperature – Regulation Data information was added.
Section 14 Disclaimer Information information was added.
Section 14 Emergency Temperature – Main Heading information was added.
Section 14 Emergency Temperature – Regulation Data information was added.
Section 14 Hazard Class + Sub Risk – Main Heading information was added.
Section 14 Hazard Class + Sub Risk – Regulation Data information was added.
Section 14 Hazardous/Not Hazardous for Transportation information was added.
Section 14 Other Dangerous Goods – Main Heading information was added.
Section 14 Other Dangerous Goods – Regulation Data information was added.
Section 14 Packing Group – Main Heading information was added.
Section 14 Packing Group – Regulation Data information was added.
Section 14 Proper Shipping Name information was added.
Section 14 Regulations – Main Headings information was added.
Section 14 Segregation – Regulation Data information was added.
Section 14 Segregation Code – Main Heading information was added.
Section 14 Special Precautions – Main Heading information was added.
Section 14 Special Precautions – Regulation Data information was added.
Section 14 Transport in bulk – Regulation Data information was added.
Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was added.
Section 14 UN Number Column data information was added.
Section 14 UN Number information was added.

Section 15: Carcinogenicity information information was modified.

Section 15: Regulations - Inventories information was added.

Section 15: Seveso Substance Text information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Section 2: No PBT/vPvB information available warning information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk