

# Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 06-4616-6
 Version number:
 26.01

 Revision date:
 12/04/2022
 Supersedes date:
 17/04/2020

**Transportation version number:** 

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

# IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

3M<sup>™</sup> SCOTCH-WELD<sup>™</sup> Epoxy Adhesive DP-460 Off-White

### **Product Identification Numbers**

FS-9100-2203-7 UU-0101-3329-4 UU-0101-3331-0

7000079883 7100200496 7100200498

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Identified uses

Structural adhesive.

## 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000 tox.uk@mmm.com

Website: www.3M.com/uk

### 1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

06-4611-7, 06-4614-1

# TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

# KIT LABEL

# 2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

### **CLASSIFICATION:**

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314 Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318 Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

# 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

### SIGNAL WORD

DANGER.

## **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |





# Contains:

bis-[4-(2,3-epoxipropoxi)phenyl]propane; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); 2-Propenenitrile, polymer with 1,3-butadiene, carboxy-terminated, polymers with bisphenol A and epichlorhydrin; 2,4,6-tris(dimethylaminomethyl)phenol

## HAZARD STATEMENTS:

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

# PRECAUTIONARY STATEMENTS

**Prevention:** 

P260A Do not breathe vapours.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

# 3M™ SCOTCH-WELD™ Epoxy Adhesive DP-460 Off-White

### <=125 ml Hazard statements

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

## <=125 ml Precautionary statements

**Prevention:** 

P260A Do not breathe vapours.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

### **Revision information:**

Section 2: <125ml Precautionary - Response information was modified.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Response information was modified.



# Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 06-4611-7
 Version number:
 24.00

 Revision date:
 16/03/2023
 Supersedes date:
 23/06/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### 1.1. Product identifier

3M™ SCOTCH-WELD™ DP-460 Off-White Epoxy Structural Adhesive (Part B)

### **Product Identification Numbers**

UU-0116-0155-4

7100270164

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### **Identified uses**

Structural adhesive.

# 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

# 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

## **CLASSIFICATION:**

# 3M<sup>TM</sup> SCOTCH-WELD<sup>TM</sup> DP-460 Off-White Epoxy Structural Adhesive (Part B)

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

### SIGNAL WORD

WARNING.

### **Symbols**

GHS07 (Exclamation mark) |GHS09 (Environment) |

# **Pictograms**





Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	80 - 90
Acrylic copolymer	Trade Secret		7 - 13

# **HAZARD STATEMENTS:**

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

# PRECAUTIONARY STATEMENTS

**Prevention:** 

P280E Wear protective gloves.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

<=125 ml Hazard statements

H317 May cause an allergic skin reaction.

<=125 ml Precautionary statements

**Prevention:** 

P280E Wear protective gloves.

11% of the mixture consists of components of unknown acute oral toxicity.

Contains 11% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation
			(EC) No. 1272/2008 [CLP], as
			amended for GB
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3	80 - 90	Skin Irrit. 2, H315
	(EC-No.) 216-823-5		Eye Irrit. 2, H319
			Skin Sens. 1, H317
			Aquatic Chronic 2, H411
Acrylic copolymer	Trade Secret	7 - 13	Substance not classified as hazardous

Please see section 16 for the full text of any H statements referred to in this section

# **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
	· /	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

# Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

# Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

## 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

# 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

# **Hazardous Decomposition or By-Products**

Substance	Condition
Aldehydes.	During combustion.
Hydrocarbons.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Ketones.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

# 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

# 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

# 7.2. Conditions for safe storage including any incompatibilities

# 3M<sup>TM</sup> SCOTCH-WELD<sup>TM</sup> DP-460 Off-White Epoxy Structural Adhesive (Part B)

Store away from strong bases. Store away from amines.

# 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

# **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

# 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Curing enclosures must be exhausted to outdoors or to a suitable emission control device.

# 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

# Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>0.30	=>8 hours
		and the second s

Polyvinyl alcohol (PVA). >0.30 4-8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

\_\_\_\_\_

# Respiratory protection

None required.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical stateLiquid.Specific Physical Form:PasteColourOff-WhiteOdorEpoxy

Odour thresholdNo data available.Melting point/freezing pointNo data available.Boiling point/boiling rangeNo data available.Flammability (solid, gas)Not applicable.Flammable Limits(LEL)Not applicable.Flammable Limits(UEL)Not applicable.

Flash point >=101 °C [Test Method:Closed Cup]

Autoignition temperatureNo data available.Decomposition temperatureNo data available.

pH substance/mixture is non-soluble (in water)

Kinematic Viscosity13,158 mm²/secWater solubilityNo data available.Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Density1.12 - 1.17 g/ml

**Relative density** 1.12 - 1.17 [*Ref Std*:WATER=1]

Relative Vapour Density

Not applicable.

## 9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds

Evaporation rate

Molecular weight

Percent volatile

0.1 % weight

No data available.

No data available.

<=1 % weight

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

# 10.2 Chemical stability

Stable.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

## 10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

# 10.5 Incompatible materials

Amines.

# 3MTM SCOTCH-WELDTM DP-460 Off-White Epoxy Structural Adhesive (Part B)

Strong bases.

# 10.6 Hazardous decomposition products

Substance
None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

No health effects are expected.

### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

# Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

## **Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg

ATE = acute toxicity estimate

## Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant

# Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant

# 3MTM SCOTCH-WELDTM DP-460 Off-White Epoxy Structural Adhesive (Part B)

# **Skin Sensitisation**

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	

**Respiratory Sensitisation** 

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

# Target Organ(s)

# **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

# **Aspiration Hazard**

# 3M™ SCOTCH-WELD™ DP-460 Off-White Epoxy Structural Adhesive (Part B)

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

# 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen	1675-54-3	Experimental Biodegradation	28 days	BOD		OECD 301F - Manometric respirometry
yl]propane						
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH

# 12.3: Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-	1675-54-3	Experimental		Log Kow	3.242	OECD 117 log Kow HPLC
epoxipropoxi)phen		Bioconcentration				method
yl]propane						

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	<b>Test result</b>	Protocol
bis-[4-(2,3-	1675-54-3	Modeled Mobility	Koc	450 l/kg	Episuite <sup>TM</sup>

# 3M™ SCOTCH-WELD™ DP-460 Off-White Epoxy Structural Adhesive (Part B)

epoxipropoxi)pheny	in Soil		
l]propane			

## 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. If no other disposal options are available, waste product—that has been completely cured or polymerised may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

# EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3082	UN3082	UN3082
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(LIQUID EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(LIQUID EPOXY RESIN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(LIQUID EPOXY RESIN)
14.3 Transport hazard class(es)	9	9	9
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant

14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	M6	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Carcinogenicity

Ingredient	CAS Nbr	<u>Classification</u>	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

# Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3

# Global inventory status

Contact 3M for more information.

# COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

### Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

# **SECTION 16: Other information**

# List of relevant H statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

### **Revision information:**

GB Section 02: CLP Ingredient table information was added.

GB Section 02: Other hazards phrase information was added.

GB Section 04: Information on toxicological effects information was added.

GB Section 12: Classification Warning information was added.

GB Section 15: Carcinogenicity information information was added.

GB Section 15: Chemical Safety Assessment information was added.

GBSDS Section 14 Transport in bulk - Main Heading information was added.

GBSDS Section 14 UN Number information was added.

CLP: Ingredient table information was deleted.

Label: CLP Percent Unknown information was deleted.

Section 02: Label Elements: GB Percent Unknown information was added.

Section 2: Other hazards phrase information was deleted.

Section 3: Composition/Information of ingredients table information was added.

Section 3: Composition/Information of ingredients table information was deleted.

Section 03: SCL table information was added.

Section 03: SCL table information was deleted.

Section 04: Information on toxicological effects information was deleted.

Section 9: Vapour density text information was modified.

Section 11: Classification disclaimer information was deleted.

Section 11: GB Classification disclaimer information was added.

Section 11: GB No endocrine disruptor information available warning information was added.

Section 11: No endocrine disruptor information available warning information was deleted.

Section 12: 12.6. Endocrine Disrupting Properties information was deleted.

Section 12: 12.6. Other adverse effects information was added.

Section 12: 12.7. Other adverse effects information was deleted.

Section 12: Classification Warning information was deleted.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was added.

Prints No Data if Adverse effects information is not present information was deleted.

Section 12: No Data text for mobility in soil information was deleted.

Section 12: No endocrine disruptor information available warning information was added.

Section 12: No endocrine disruptor information available warning information was deleted.

Section 12: Persistence and Degradability information information was modified.

Section 12:Bioccumulative potential information information was modified.

Section 14 Marine transport in bulk according to IMO instruments – Main Heading information was deleted.

Section 14 UN Number information was deleted.

Section 14: Transportation classification information was deleted.

# 3M™ SCOTCH-WELD™ DP-460 Off-White Epoxy Structural Adhesive (Part B)

Section 15: Carcinogenicity information information was deleted.

Section 15: Chemical Safety Assessment information was deleted.

Section 15: Restrictions on manufacture ingredients information information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was deleted.

Section 16: Web address information was added.

Section 16: Web address information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

## 3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.



# Safety Data Sheet

Copyright, 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 06-4614-1
 Version number:
 25.01

 Revision date:
 20/06/2023
 Supersedes date:
 17/03/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### 1.1. Product identifier

3M Scotch-Weld DP-460 Epoxy Adhesive (Part A)

### **Product Identification Numbers**

UU-0116-0156-2

7100269980

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### **Identified uses**

Structural adhesive.

# 1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

**Telephone:** +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

# 1.4. Emergency telephone number

+44 (0)1344 858 000

# **SECTION 2: Hazard identification**

### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

# **CLASSIFICATION:**

# 3M Scotch-Weld DP-460 Epoxy Adhesive (Part A)

Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314

Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

### SIGNAL WORD

DANGER.

### **Symbols**

GHS05 (Corrosion) |GHS07 (Exclamation mark) |GHS09 (Environment) |

# **Pictograms**







Ingredient	CAS Nbr	EC No.	% by Wt
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	40 - 70
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	10 - 30
2-Propenenitrile, polymer with 1,3-butadiene, carboxy-terminated, polymers with bisphenol A and epichlorhydrin	68610-41-3		7 - 13
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		3 - 7
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	202-013-9	1 - 5

## **HAZARD STATEMENTS:**

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

## PRECAUTIONARY STATEMENTS

**Prevention:** 

P260A Do not breathe vapours.

P273 Avoid release to the environment.

P280D Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

# <=125 ml Hazard statements

# 3M Scotch-Weld DP-460 Epoxy Adhesive (Part A)

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

# <=125 ml Precautionary statements

**Prevention:** 

P260A Do not breathe vapours.

P280D Wear protective gloves, protective clothing, and eye/face protection.

**Response:** 

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTRE or doctor/physician.

Contains 17% of components with unknown hazards to the aquatic environment.

### 2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. This material does not contain any substances that are assessed to be a PBT or vPvB

# **SECTION 3: Composition/information on ingredients**

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	(CAS-No.) 4246-51-9 (EC-No.) 224-207-2	40 - 70	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
2-Propenenitrile, polymer with 1,3- butadiene, carboxy-terminated, polymers with bisphenol A and epichlorhydrin	(CAS-No.) 68610-41-3	7 - 13	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	3 - 7	Substance with a national occupational exposure limit
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9	1 - 5	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

Please see section 16 for the full text of any H statements referred to in this section

# **Specific Concentration Limits**

Ingredient	Identifier(s)	Specific Concentration Limits
	· /	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

# Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

# 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

# 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

# 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

# **Hazardous Decomposition or By-Products**

Substance	<b>Condition</b>
Aldehydes.	During combustion.
Amine compounds.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Irritant vapours or gases.	During combustion.
Oxides of nitrogen.	During combustion.
Toxic vapour, gas, particulate.	During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

# 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

## 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

# 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed.

# 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

# Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Silicon dioxide 67762-90-7 UK HSC TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable

dust):6 mg/m3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

# 8.2. Exposure controls

# 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

## 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 166

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimePolymer laminateNo data availableNo data available

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

## Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical stateLiquid.Specific Physical Form:Viscous liquidColourAmberOdorAmine

## 3M Scotch-Weld DP-460 Epoxy Adhesive (Part A)

Odour threshold Melting point/freezing point Boiling point/boiling range Flammability (solid, gas) Flammable Limits(LEL) Flammable Limits(UEL)

Flash point

**Autoignition temperature Decomposition temperature** 

рH

Kinematic Viscosity Water solubility Solubility- non-water

Partition coefficient: n-octanol/water

Vapour pressure

**Density** 

Relative density Relative Vapour Density No data available.
No data available.
Not applicable.
Not applicable.
No data available.

>=121 °C [Test Method:Closed Cup]

No data available. No data available.

No data available.

substance/mixture is non-soluble (in water)

11,111 - 23,148 mm²/sec Slight (less than 10%) No data available. No data available. Not applicable. 1.08 g/ml

1.06 - 1.1 [Ref Std:WATER=1] [Ref Std:AIR=1]Not applicable.

### 9.2. Other information

### 9.2.2 Other safety characteristics

EU Volatile Organic Compounds0.1 % weightEvaporation rateNot applicable.Molecular weightNo data available.Percent volatile<=1 % weight</th>

# **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

## 10.2 Chemical stability

Stable.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

# 10.5 Incompatible materials

None known.

# 10.6 Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications

in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

# Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### Skin contact

May be harmful in contact with skin. Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### Eve contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

## Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

### **Additional information:**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000
			mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000
			mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,525 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 2,850 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
2-Propenenitrile, polymer with 1,3-butadiene, carboxy-	Dermal	Not	LD50 3,000 mg/kg
terminated, polymers with bisphenol A and epichlorhydrin		available	
2-Propenenitrile, polymer with 1,3-butadiene, carboxy-	Ingestion	Not	LD50 > 34,000 mg/kg
terminated, polymers with bisphenol A and epichlorhydrin		available	
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-tris(dimethylaminomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

# 3M Scotch-Weld DP-460 Epoxy Adhesive (Part A)

Name S		Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
2-Propenenitrile, polymer with 1,3-butadiene, carboxy-terminated, polymers with	similar	Irritant
bisphenol A and epichlorhydrin	compoun	
	ds	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name		Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
2-Propenenitrile, polymer with 1,3-butadiene, carboxy-terminated, polymers with	similar	Severe irritant
bisphenol A and epichlorhydrin	compoun	
	ds	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
2,4,6-tris(dimethylaminomethyl)phenol	Rabbit	Corrosive

# **Skin Sensitisation**

Name	Species	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Professio nal judgemen t	Sensitising
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human and animal	Sensitising
2-Propenenitrile, polymer with 1,3-butadiene, carboxy-terminated, polymers with bisphenol A and epichlorhydrin	similar compoun ds	Sensitising
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
2,4,6-tris(dimethylaminomethyl)phenol	Guinea pig	Not classified

**Respiratory Sensitisation** 

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

**Germ Cell Mutagenicity** 

Name	Route	Value
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
2,4,6-tris(dimethylaminomethyl)phenol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

\_\_\_\_\_

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	premating into lactation
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	premating into lactation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	Duration
2,4,6- tris(dimethylaminomethyl) phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
3,3'- Oxybis(ethyleneoxy)bis(pr opylamine)	Ingestion	gastrointestinal tract   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system   heart   endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

D 10 C 14

		hematopoietic system   liver   eyes   kidney and/or bladder				
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2,4,6- tris(dimethylaminomethyl) phenol	Dermal	skin   liver   nervous system   auditory system   hematopoietic system   eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days

# **Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

# 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
3,3'-	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
3,3'-	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)						
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)			<u> </u>			
3,3'-	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)	1016.51.0			72.1	Total a	
3,3'-	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Oxybis(ethyleneox						
y)bis(propylamine)	1675 54 2	A (' ( 1 1 1 1	  A 1	2.1	1050	> 100 //
bis-[4-(2,3-	1675-54-3	Activated sludge	Analogous	3 hours	IC50	>100 mg/l
epoxipropoxi)phen			Compound			
yl]propane bis-[4-(2,3-	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
epoxipropoxi)phen	10/3-34-3	Kambow trout	Estimated	96 Hours	LC30	2 mg/1
yl]propane						
bis-[4-(2,3-	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
epoxipropoxi)phen	1073 313	Water freu	Estimated	10 Hours	Leso	1.0 mg/1
yl]propane						
bis-[4-(2,3-	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
epoxipropoxi)phen		3	F			
yl]propane						
bis-[4-(2,3-	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
epoxipropoxi)phen		_				

\_\_\_\_\_

yl]propane						
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
2-Propenenitrile, polymer with 1,3- butadiene, carboxy- terminated, polymers with bisphenol A and epichlorhydrin	68610-41-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	N/A	Experimental	96 hours	LC50	718 mg/l
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
3,3'- Oxybis(ethyleneox y)bis(propylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	, ,	OECD 111 Hydrolysis func of pH
2-Propenenitrile, polymer with 1,3- butadiene, carboxy- terminated, polymers with bisphenol A and epichlorhydrin	68610-41-3	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl- insufficient	N/A	N/A	N/A	N/A
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 %BOD/ThOD	OECD 301D - Closed bottle test

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
3,3'-	4246-51-9	Experimental		Log Kow	-1.25	

Oxybis(ethyleneox y)bis(propylamine)		Bioconcentration				
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow		OECD 117 log Kow HPLC method
2-Propenenitrile, polymer with 1,3- butadiene, carboxy- terminated, polymers with bisphenol A and epichlorhydrin	68610-41-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6- tris(dimethylamino methyl)phenol	90-72-2	Experimental Bioconcentration		Log Kow		830.7550 Part.Coef Shake Flask

# 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
3,3'- Oxybis(ethyleneoxy )bis(propylamine)	4246-51-9	Modeled Mobility in Soil	Koc	1 l/kg	ACD/Labs ChemSketch™
bis-[4-(2,3- epoxipropoxi)pheny l]propane	1675-54-3	Modeled Mobility in Soil	Koc	450 l/kg	Episuite <sup>TM</sup>

### 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

## EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

# **SECTION 14: Transportation information**

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN2735	UN2735	UN2735
14.2 UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))	AMINES, LIQUID, CORROSIVE, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY) BIS(PROPYLAMINE))	AMINES, LIQUID, CORROSIVE, N.O.S.(3,3'- OXYBIS(ETHYLENEOXY)BIS(PRO PYLAMINE); EPOXY RESIN)
14.3 Transport hazard class(es)	8	8	8
14.4 Packing group	II	II	II
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	C7	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	18 - ALKALIS

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# Carcinogenicity

Ingredient	CAS Nbr	<u>Classification</u>	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

# Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous

# 3M Scotch-Weld DP-460 Epoxy Adhesive (Part A)

conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

Ingredient **CAS Nbr** 

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of

Restriction

# Global inventory status

Contact 3M for more information.

# COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

### Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

# 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

# **SECTION 16: Other information**

## List of relevant H statements

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

### **Revision information:**

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Scotch-Weld DP-460 Epoxy Adnesive (Part A)	
3M SDSs for Great Britain are available at www.3M.com/uk	
For Northern Ireland documents, please contact your 3M representative to obtain a copy.	

Page: 16 of 16