

Safety Data Sheet

Copyright, 2022, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 06-2189-6
 Version number:
 22.00

 Revision date:
 07/12/2022
 Supersedes date:
 25/01/2021

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3MTM DynamarTM Polymer Processing Additive FX 5920A

Product Identification Numbers

ZF-0002-1277-7

7000042486

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Polymer processing additive.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

Telephone: +44 (0)1344 858 000 **E Mail:** tox.uk@mmm.com **Website:** www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

This material is not classified as hazardous according to Regulation (EC) No. 1272/2008, as amended, on classification, labelling, and packaging of substances and mixtures.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

Not applicable

SUPPLEMENTAL INFORMATION:

Supplemental Precautionary Statements:

Firefighting instructions: Does not burn without external flame. Wear self-contained breathing apparatus and protection from acidic hydrogen fluoride. Vapours liberated during processing may be hazardous if inhaled. Eye, nose, throat and lung irritation can occur from such vapours. Avoid contamination of tobacco with polymer resin. Before using, read the most current Safety Data Sheet.

2.3. Other hazards

May cause thermal burns. Vapours liberated during processing may be hazardous if inhaled. Eye, nose, throat and lung irritation can occur from such vapours.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polyethylene Glycol	(CAS-No.) 25322-68-3	60 - 70	Substance not classified as hazardous
Vinylidene fluoride-hexafluoropropylene polymer	(CAS-No.) 9011-17-0	20 - 40	Substance not classified as hazardous
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	< 5	Substance with a national occupational exposure limit
Calcium carbonate	(CAS-No.) 471-34-1 (EC-No.) 207-439-9	< 5	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE

MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye contact

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Eliminate all ignition sources if safe to do so. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Use wet sweeping compound or water to avoid dusting. Sweep up. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid inhalation of thermal decomposition products. Avoid skin contact with hot material. For industrial/occupational use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Talc	14807-96-6	UK HSC	TWA(as respirable dust):1 mg/m³	
DUST, INERT OR NUISANCE	471-34-1	UK HSC	TWA(as respirable dust):4 mg/m3;TWA(as inhalable dust):10 mg/m3	
Limestone	471-34-1	UK HSC	TWA(respirable):4 mg/m3;TWA(as respirable dust):4 mg/m3;TWA(Inhalable):10 mg/m3;TWA(as inhalable dust):10 mg/m3	

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Local exhaust required above 400 C.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimeNeoprene.No data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Neoprene apron.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type P

Thermal hazards

Wear heat insulating gloves Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

Applicable Norms/Standards Use gloves tested to EN 407

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateSolid.Specific Physical Form:Granules.ColourWhiteOdorOdourless

Odour thresholdNo data available.Melting point/freezing pointNot applicable.Boiling point/boiling rangeNot applicable.Flammability (solid, gas)Not classifiedFlammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.

Flash point 229 °C [Test Method: Pensky-Martens Closed Cup]

3MTM DynamarTM Polymer Processing Additive FX 5920A

Autoignition temperature 341 °C [Details: ASTM D-1929]

Decomposition temperatureNo data available.

pН

Kinematic Viscosity

Water solubility

Not applicable.

Moderate

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Vapour pressureNot applicable.Density1.15 g/cm3

Relative density 1.15 [Ref Std:WATER=1]

Relative Vapour Density *Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

Bulk density 0.7 g/cm³

EU Volatile Organic CompoundsNo data available.Evaporation rateNot applicable.Molecular weightNo data available.Percent volatileNot applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

Aluminium or magnesium powder and high/shear temperature conditions.

10.6 Hazardous decomposition products

SubstanceConditionCarbonyl fluoride.At elevated temperatures. ->300°CformaldehydeAt elevated temperatures. ->300°CCarbon monoxideAt elevated temperatures. ->300°CCarbon dioxide.At elevated temperatures. ->300°CHydrogen FluorideAt elevated temperatures. ->300°CToxic vapour, gas, particulate.At elevated temperatures. ->300°C

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient

classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

During heating:

Polymer fume fever: Sign/symptoms may include chest pain or tightness, shortness of breath, cough, malaise, muscle aches, increased heart rate, fever, chills, sweats, nausea and headache.

May cause additional health effects (see below).

Skin contact

Thermal burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction. Mechanical skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eve contact

Thermal burns; Signs/symptoms may include severe pain, redness and swelling, and tissue destruction. Mechanical eve irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyethylene Glycol	Dermal	Rabbit	LD50 > 20,000 mg/kg
Polyethylene Glycol	Ingestion	Rat	LD50 32,770 mg/kg
Vinylidene fluoride-hexafluoropropylene polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Vinylidene fluoride-hexafluoropropylene polymer	Ingestion	Rat	LD50 6,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Calcium carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium carbonate	Inhalation-	Rat	LC50 3 mg/l
	Dust/Mist		
	(4 hours)		
Calcium carbonate	Ingestion	Rat	LD50 6,450 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value

3MTM DynamarTM Polymer Processing Additive FX 5920A

Polyethylene Glycol	Rabbit	Minimal irritation
Vinylidene fluoride-hexafluoropropylene polymer	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Calcium carbonate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Polyethylene Glycol	Rabbit	Mild irritant
Vinylidene fluoride-hexafluoropropylene polymer	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Calcium carbonate	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Polyethylene Glycol	Guinea	Not classified
	pig	

Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Polyethylene Glycol	In Vitro	Not mutagenic
Polyethylene Glycol	In vivo	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Polyethylene Glycol	Ingestion	Rat	Not carcinogenic
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Polyethylene Glycol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not classified for male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
Polyethylene Glycol	Not specified.	Not classified for reproduction and/or development		NOEL N/A	
Polyethylene Glycol	Ingestion	Not classified for development	Mouse	NOAEL 562 mg/animal/da y	during gestation
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Calcium carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure
						Duration
Polyethylene Glycol	Inhalation	respiratory irritation	Not classified	Rat	NOAEL	2 weeks
					1.008 mg/l	
Calcium carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL	90 minutes
					0.812 mg/l	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polyethylene Glycol	Inhalation	respiratory system	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks
Polyethylene Glycol	Ingestion	kidney and/or bladder heart endocrine system hematopoietic system liver nervous system	Not classified	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Vinylidene fluoride- hexafluoropropylene polymer	Ingestion	liver	Not classified	Rat	NOAEL 10,000 mg/kg/day	2 weeks
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m³	113 weeks
Calcium carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Polyethylene Glycol	25322-68-3	Activated sludge	Experimental	N/A	EC50	>1,000 mg/l
Polyethylene Glycol	25322-68-3	Atlantic Salmon	Experimental	96 hours	LC50	>1,000 mg/l
Vinylidene fluoride- hexafluoropropylene polymer	9011-17-0	N/A	Data not available or insufficient for classification	N/A	N/A	n/a

Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Calcium carbonate	471-34-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Calcium carbonate	471-34-1	Green algae	Experimental	72 hours	EC10	100 mg/l
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polyethylene Glycol	25322-68-3	Experimental Biodegradation	28 days	BOD	53 %BOD/ThO D	OECD 301C - MITI test (I)
Vinylidene fluoride- hexafluoropropylene polymer	9011-17-0	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Calcium carbonate	471-34-1	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not availbl- insufficient	N/A	N/A	N/A	N/A

12.3: Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Polyethylene Glycol	25322-68-3	Estimated Bioconcentration		Bioaccumulation factor	2.3	
Vinylidene fluoride- hexafluoropropylene polymer	9011-17-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcium carbonate	471-34-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

No test data available.

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste

incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

070215 Wastes from additives other than those mentioned in 07 02 14

SECTION 14: Transportation information

Not hazardous for transportation.

Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
No data available.	No data available.	No data available.
No data available.	No data available.	No data available.
No data available.	No data available.	No data available.
No data available.	No data available.	No data available.
No data available.	No data available.	No data available.
Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
No data available.	No data available.	No data available.
No data available.	No data available.	No data available.
No data available.	No data available.	No data available.
No data available.	No data available.	No data available.
	No data available. Please refer to the other sections of the SDS for further information. No data available. No data available. No data available.	No data available. Please refer to the other sections of the SDS for further information. No data available. Please refer to the other sections of the SDS for further information. No data available. No data available. No data available. No data available. No data available.

3M TM Dynamar TM Polymer Processing Additive FX 5920A	ļ	3MTM D	vnamar TM	Polymer	Processing	Additive	FX	5920	A
---	---	--------	----------------------	----------------	-------------------	----------	----	------	---

IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1 None

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

Revision information:

- Section 3: Composition/Information of ingredients table information was modified.
- Section 5: Fire Advice for fire fighters information information was modified.
- Section 8: Appropriate Engineering controls information information was modified.
- Section 8: Eye/face protection information information was modified.
- Section 8: glove data value information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 8: Personal Protection Respiratory Information information was modified.
- Section 8: Personal Protection Skin/body information information was added.
- Section 8: Personal Protection Thermal hazards information information was modified.

3MTM DynamarTM Polymer Processing Additive FX 5920A

- Section 8: Skin protection protective clothing information information was added.
- Section 9: Vapour density value information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Health Effects Eye information information was modified.
- Section 11: Health Effects Inhalation information information was modified.
- Section 11: Health Effects Skin information information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.
- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Target Organs Repeated Table information was added.
- Section 11: Target Organs Repeated Table information was deleted.
- Section 11: Target Organs Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Section 13: Standard Phrase Category Waste GHS information was modified.
- Section 14 Classification Code Regulation Data information was modified.
- Section 14 Control Temperature Regulation Data information was modified.
- Section 14 Emergency Temperature Regulation Data information was modified.
- Section 14 Hazard Class + Sub Risk Regulation Data information was modified.
- Section 14 Multiplier Main Heading information was deleted.
- Section 14 Multiplier Regulation Data information was deleted.
- Section 14 Other Dangerous Goods Regulation Data information was modified.
- Section 14 Packing Group Regulation Data information was modified.
- Section 14 Proper Shipping Name information was modified.
- Section 14 Segregation Regulation Data information was modified.
- Section 14 Transport Category Main Heading information was deleted.
- Section 14 Transport Category Regulation Data information was deleted.
- Section 14 Transport in bulk Regulation Data information was modified.
- Section 14 Marine transport in bulk according to IMO instruments Main Heading information was modified.
- Section 14 Transport Not Permitted Main Heading information was deleted.
- Section 14 Transport Not Permitted Regulation Data information was deleted.
- Section 14 Tunnel Code Main Heading information was deleted.
- Section 14 Tunnel Code Regulation Data information was deleted.
- Section 14 UN Number Column data information was modified.
- Section 14 UN Number information was modified.
- Section 15: Regulations Inventories information was added.
- Section 2: No PBT/vPvB information available warning information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk