



## Safety Data Sheet

Copyright, 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	05-6840-2	<b>Version number:</b>	7.00
<b>Revision date:</b>	27/01/2020	<b>Supersedes date:</b>	11/10/2019
<b>Transportation version number:</b>	2.00 (16/07/2018)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent

#### Product Identification Numbers

62-3286-1436-7

7100148752

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Structural adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:**

05-6837-8, 05-6839-4

### TRANSPORTATION INFORMATION

62-3286-1436-7

**ADR/RID:** UN3082, NOT RESTRICTED AS PER SPECIAL PROVISION 375, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXEMPTION, (BISPHENOL A-EPICHLOROHYDRIN POLYMER), III, --.

**IMDG-CODE:** UN3082, NOT RESTRICTED AS PER IMDG CODE 2.10.2.7, MARINE POLLUTANT EXCEPTION, III,

## 3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent

IMDG-Code segregation code: NONE, EMS: --.

**ICAO/IATA:** UN3082, NOT RESTRICTED AS PER SPECIAL PROVISION A197, ENVIRONMENTALLY HAZARDOUS SUBSTANCE EXCEPTION, (BISPHENOL A-EPICHLOROHYDRIN POLYMER), III.

## KIT LABEL

### 2.1. Classification of the substance or mixture

**CLP REGULATION (EC) No 1272/2008**

#### CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Skin Sensitization, Category 1A - Skin Sens. 1A; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

### 2.2. Label elements

**CLP REGULATION (EC) No 1272/2008**

#### SIGNAL WORD

WARNING.

#### Symbols:

GHS07 (Exclamation mark) | GHS09 (Environment) |

#### Pictograms



Contains:

bis-[4-(2,3-epoxipropoxy)phenyl]propane; 4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane; 3,3'-Oxybis(ethyleneoxy)bis(propylamine); Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)

#### HAZARD STATEMENTS:

H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P261A Avoid breathing vapours.  
P280E Wear protective gloves.  
P273 Avoid release to the environment.

##### Response:

<b>3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent</b>
--

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

**Disposal:**

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

Refer to Safety Data Sheet for component % unknown values ([www.3M.com/msds](http://www.3M.com/msds)).

**Revision information:**

Kit: Component document group number(s) information was modified.

Label: CLP Ingredients - kit components information was modified.

Label: CLP Classification information was modified.

Label: CLP Precautionary - Prevention information was modified.



## Safety Data Sheet

Copyright,2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	05-6837-8	<b>Version number:</b>	6.00
<b>Revision date:</b>	29/01/2020	<b>Supersedes date:</b>	11/10/2019
<b>Transportation version number:</b>	1.00 (14/03/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Structural adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
Skin Sensitization, Category 1 - Skin Sens. 1; H317  
Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

##### SIGNAL WORD

WARNING.

## 3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B

### Symbols:

GHS07 (Exclamation mark) | GHS09 (Environment) |

### Pictograms



### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	216-823-5	60 - 70
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	500-070-7	30 - 40

### HAZARD STATEMENTS:

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS

#### Prevention:

P280E	Wear protective gloves.
P273	Avoid release to the environment.

#### Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.

#### Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

### 2.3. Other hazards

None known.

## SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	216-823-5	01-2119456619-26	60 - 70	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 2, H411
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-	30583-72-3	500-070-7		30 - 40	Skin Sens. 1, H317; Aquatic Chronic 3, H412

## 3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B

chloro-2,3-epoxypropane

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Toxic vapour, gas, particulate.	During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

## 3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from acids.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Dermal, Short-term exposure, Systemic effects	8.3 mg/kg bw/d
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Long-term exposure (8 hours),	12.3 mg/m <sup>3</sup>

**3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B**

ane			Systemic effects	
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Worker	Inhalation, Short-term exposure, Systemic effects	12.3 mg/m <sup>3</sup>

**Predicted no effect concentrations (PNEC)**

Ingredient	Degradation Product	Compartment	PNEC
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater	0.003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Freshwater sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Intermittent releases to water	0.013 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water	0.0003 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Marine water sediments	0.5 mg/kg d.w.
bis-[4-(2,3-epoxipropoxy)phenyl]propane		Sewage Treatment Plant	10 mg/l

**Recommended monitoring procedures:** Information on recommended monitoring procedures can be obtained from UK HSC

**8.2. Exposure controls**

In addition, refer to the annex for more information.

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

*Applicable Norms/Standards*

Use eye protection conforming to EN 166

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.



## 3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

### Applicable Norms/Standards

Use gloves tested to EN 374

### Respiratory protection

None required.

### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid.

Colour

Colourless

Specific Physical Form:

Viscous Liquid

Odor

Slight Epoxy

Odour threshold

No data available.

pH

Not applicable.

Boiling point/boiling range

>=98.9 °C

Melting point

Not applicable.

Flammability (solid, gas)

Not applicable.

Explosive properties

Not classified

Oxidising properties

Not classified

Flash point

>=93.3 °C [Test Method:Pensky-Martens Closed Cup]

Autoignition temperature

No data available.

Flammable Limits(LEL)

No data available.

Flammable Limits(UEL)

No data available.

Relative density

1.17 [Ref Std:WATER=1]

Water solubility

Nil

Solubility- non-water

No data available.

Partition coefficient: n-octanol/water

No data available.

Evaporation rate

Negligible

Vapour density

No data available.

Decomposition temperature

No data available.

Viscosity

2,000 - 8,000 mPa-s [@ 20 °C] [Test Method:Brookfield]

Density

1.17 g/ml [@ 20 °C]

### 9.2. Other information

EU Volatile Organic Compounds

No data available.

Molecular weight

No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5 Incompatible materials

Strong acids.

### 10.6 Hazardous decomposition products

**Substance**

**Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

No health effects are expected.

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg

ATE = acute toxicity estimate

**3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B****Skin Corrosion/Irritation**

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Rabbit	Moderate irritant

**Skin Sensitisation**

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human and animal	Sensitising

**Respiratory Sensitisation**

Name	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Human	Not classified

**Germ Cell Mutagenicity**

Name	Route	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxy)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years

**3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B**

bis-[4-(2,3-epoxipropoxy)phenyl]propane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3-epoxipropoxy)phenyl]propane	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

**Aspiration Hazard**

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Rainbow trout	Estimated	96 hours	LC50	2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green Algae	Experimental	72 hours	EC50	>11 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Green Algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Green algae	Experimental	72 hours	EC50	>100 mg/l
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Rainbow trout	Experimental	96 hours	LC50	11.5 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	Other methods

**3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B**

bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Experimental Biodegradation	28 days	BOD	0.1 % BOD/ThBOD	OECD 301D - Closed bottle test

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	Other methods
4,4'-Isopropylidenedicyclohexanol, oligomeric reaction products with 1-chloro-2,3-epoxypropane	30583-72-3	Experimental Bioconcentration		Log Kow	3.84	Other methods

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances  
20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

**SECTION 14: Transportation information**

Exemption: For vessels containing a net quantity of 5 l or a net mass of 5 kg or less per single or inner packaging, special provision 375 (ADR), exemption per 2.10.2.7 (IMDG) or special provision A197 (IATA) may be applied, if applicable

IATA: UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (BISPHENOL A-EPICHLOROHYDRIN POLYMER); 9; III.

IMDG: UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (BISPHENOL A-EPICHLOROHYDRIN POLYMER); 9; III; FA, SF.

ADR: UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (BISPHENOL A-EPICHLOROHYDRIN POLYMER); 9; III; (-); M6.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **Carcinogenicity**

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
bis-[4-(2,3-epoxipropoxy)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

### **15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## **SECTION 16: Other information**

### **List of relevant H statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Revision information:**

Formulation: Section 16: Annex information was modified.

Industrial Use of Adhesives: Section 16: Annex information was modified.

CLP: Ingredient table information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 5: Hazardous combustion products table information was modified.

Section 8: DNEL table row information was modified.

Section 8: PNEC table row information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Respiratory Sensitization Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Bioaccumulative potential information information was modified.

Section 14: Transportation classification information was modified.

**3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B**

Section 15: Carcinogenicity information information was modified.

Sectio 16: UK disclaimer information was deleted.

**Annex**

<b>1. Title</b>	
<b>Substance identification</b>	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
<b>Exposure Scenario Name</b>	Formulation
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
<b>Processes, tasks and activities covered</b>	Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: <= 225 days per year;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	Do not apply industrial sludge to natural soils; Prevent leaks and prevent soil / water pollution caused by leaks; Sludge should be incinerated, contained or reclaimed;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	bis-[4-(2,3-epoxipropoxi)phenyl]propane; EC No. 216-823-5; CAS Nbr 1675-54-3;
<b>Exposure Scenario Name</b>	Industrial Use of Adhesives
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article
<b>Processes, tasks and activities covered</b>	Application of product with applicator gun. Transfers without dedicated controls, including loading, filling, dumping, bagging.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Emission days per year: 220 days/year;

**3M™ Scotch-Weld™ Epoxy Adhesive DP190 Translucent, Part B**

<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Wear chemically resistant gloves (tested to EN374) in combination with ‘basic’ employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	Do not apply industrial sludge to natural soils; Prevent discharge of undissolved substance to or recover from wastewater; Prevent leaks and prevent soil / water pollution caused by leaks; Sludge should be incinerated, contained or reclaimed;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)**





## Safety Data Sheet

Copyright,2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 05-6839-4 **Version number:** 7.00  
**Revision date:** 03/01/2020 **Supersedes date:** 16/07/2018  
**Transportation version number:** 1.00 (03/03/2011)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Structural adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Skin Sensitization, Category 1A - Skin Sens. 1A; H317  
Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

##### SIGNAL WORD

WARNING.

**Symbols:**

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

GHS07 (Exclamation mark) |

**Pictograms****Ingredients:**

Ingredient	CAS Nbr	EC No.	% by Wt
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	68911-25-1		70 - 90
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	10 - 30

**HAZARD STATEMENTS:**

H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.

**PRECAUTIONARY STATEMENTS****Prevention:**

P261A	Avoid breathing vapours.
P280E	Wear protective gloves.

**Response:**

P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
-------------	--

Contains 85% of components with unknown hazards to the aquatic environment.

**Notes on labelling**

Testing indicates this material is a dermal sensitizer, not irritating to skin and not irritating to the eyes.

**2.3. Other hazards**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	68911-25-1			70 - 90	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1A, H317; STOT SE 3, H336
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	224-207-2	01-2119963377-26	10 - 30	Skin Sens. 1, H317 Skin Corr. 1B, H314
Calcium trifluoromethanesulphonate	55120-75-7	ELINCS 415-540-6	01-0000016247-70	1 - 5	Skin Irrit. 2, H315; Eye Dam. 1, H318
toluene	108-88-3	203-625-9		< 0.8	Flam. Liq. 2, H225; Asp.

## 3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A

					Tox. 1, H304; Skin Irrit. 2, H315; Repr. 2, H361d; STOT SE 3, H336; STOT RE 2, H373 Aquatic Chronic 3, H412 Eye Irrit. 2, H319
--	--	--	--	--	--

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide.  
Oxides of nitrogen.  
Oxides of sulphur.  
Toxic vapour, gas, particulate.

#### Condition

During combustion.  
During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
toluene	108-88-3	UK HSC	TWA: 191 mg/m <sup>3</sup> (50 ppm); STEL: 384 mg/m <sup>3</sup> (100 ppm)	SKIN

UK HSC : UK Health and Safety Commission  
TWA: Time-Weighted-Average  
STEL: Short Term Exposure Limit  
CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**Derived no effect level (DNEL)**

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	8.3 mg/kg bw/d
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Local effects	1 mg/m <sup>3</sup>
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	59 mg/m <sup>3</sup>
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Local effects	13 mg/m <sup>3</sup>
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Worker	Inhalation, Short-term exposure, Systemic effects	176 mg/m <sup>3</sup>

**Predicted no effect concentrations (PNEC)**

Ingredient	Degradation Product	Compartment	PNEC
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater	0.22 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Freshwater sediments	0.809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Intermittent releases to water	2.2 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water	0.022 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Marine water sediments	0.0809 mg/kg d.w.
3,3'-Oxybis(ethyleneoxy)bis(propylamine)		Sewage Treatment Plant	125 mg/l

**Recommended monitoring procedures:** Information on recommended monitoring procedures can be obtained from UK HSC

**8.2. Exposure controls**

In addition, refer to the annex for more information.

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

## 3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A

None required.

### Skin/hand protection

No protective gloves required. Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

### Applicable Norms/Standards

Use gloves tested to EN 374

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

### Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

### 8.2.3. Environmental exposure controls

Refer to Annex

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid.

Colour

Light Amber

Specific Physical Form:

Viscous Liquid

Odor

Slight Amine

Odour threshold

No data available.

pH

No data available.

Boiling point/boiling range

>=98.9 °C

Melting point

Not applicable.

Flammability (solid, gas)

Not applicable.

Explosive properties

Not classified

Oxidising properties

Not classified

Flash point

>=93.3 °C [Test Method:Closed Cup]

Autoignition temperature

No data available.

Flammable Limits(LEL)

No data available.

Flammable Limits(UEL)

No data available.

Vapour pressure

<=186,158.4 Pa [@ 55 °C ]

Relative density

1.03 [Ref Std:WATER=1]

Water solubility

Nil

## 3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A

<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Vapour density</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity</b>	7,000 - 15,000 mPa-s [ @ 20 °C ] [ <i>Test Method: Brookfield</i> ]
<b>Density</b>	1.03 g/ml [ @ 20 °C ]

### 9.2. Other information

<b>EU Volatile Organic Compounds</b>	<i>No data available.</i>
<b>Molecular weight</b>	<i>No data available.</i>

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

### 10.5 Incompatible materials

None known.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A****Skin contact**

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion**

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Additional information:**

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rat	LD50 > 2,000 mg/kg
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 > 2,000 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Dermal	Rabbit	LD50 2,500 mg/kg
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Ingestion	Rat	LD50 3,160 mg/kg
Calcium trifluoromethanesulphonate	Ingestion	Rat	LD50 > 2,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapour (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Overall product	In vitro data	No significant irritation
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Rat	Irritant
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Rabbit	Corrosive
Calcium trifluoromethanesulphonate	Rabbit	Irritant
toluene	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
------	---------	-------



**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

Overall product	In vitro data	No significant irritation
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	In vitro data	Severe irritant
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	similar health hazards	Corrosive
Calcium trifluoromethanesulphonate	Rabbit	Corrosive
toluene	Rabbit	Moderate irritant

**Skin Sensitisation**

Name	Species	Value
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Guinea pig	Sensitising
toluene	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	In Vitro	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**
**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(pro	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

pylamine)						
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
toluene	Inhalation	auditory system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

**Aspiration Hazard**

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(propylamine)	68911-25-1		Data not available or insufficient for classification			
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	Green algae	Experimental	72 hours	Effect Concentration 10%	5.4 mg/l
Calcium trifluoromethanesulphonate	55120-75-7	Green Algae	Estimated	72 hours	EC50	54 mg/l
Calcium trifluoromethanesulphonate	55120-75-7	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Calcium trifluoromethanesulphonate	55120-75-7	Water flea	Estimated	48 hours	EC50	>100 mg/l
Calcium trifluoromethanesulphonate	55120-75-7	Green Algae	Estimated	72 hours	NOEC	6.4 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Fish other	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho salmon	Experimental	40 days	NOEC	3.2 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(pro	68911-25-1	Data not availbl-insufficient			N/A	

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

pylamine)						
3,3'-Oxybis(ethyleneoxy)bis(pro pylamine)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t 1/2)	Other methods
3,3'-Oxybis(ethyleneoxy)bis(pro pylamine)	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Calcium trifluoromethanesulphonate	55120-75-7	Estimated Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301D - Closed bottle test
toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	Other methods
toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % weight	

**12.3 : Bioaccumulative potential**

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Fatty acids, C18-unsaturated, dimers, polymers with 3,3'-oxybis(ethyleneoxy)bis(pro pylamine)	68911-25-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
3,3'-Oxybis(ethyleneoxy)bis(pr opylamine)	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	Other methods
Calcium trifluoromethanesulphonate	55120-75-7	Estimated Bioconcentration	35 days	Bioaccumulation factor	0.03	OECD 305E - Bioaccumulation flow-through fish test
toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	Other methods

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

This material does not contain any substances that are assessed to be a PBT or vPvB

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

## 3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances  
20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

## SECTION 14: Transportation information

ADR/IMDG/IATA: Not restricted for transport.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
toluene	108-88-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>CAS Nbr</u>
toluene	108-88-3

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

### List of relevant H statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

#### Revision information:

Industrial Mixing and Application: Section 16: Annex information was modified.

Industrial Transfer: Section 16: Annex information was modified.

CLP Remark(phrase) information was deleted.

Label: CLP Classification information was modified.

Label: CLP Percent Unknown information was deleted.

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

Label: CLP Precautionary - Prevention information was modified.  
 Section 3: Composition/ Information of ingredients table information was modified.  
 Section 5: Hazardous combustion products table information was modified.  
 Section 7: Conditions safe storage information was modified.  
 Section 8: Occupational exposure limit table information was modified.  
 Section 8: Personal Protection - Skin/hand information information was modified.  
 Section 09: Color information was added.  
 Section 09: Odor information was added.  
 Sections 3 and 9: Odour, colour, grade information information was deleted.  
 Section 11: Acute Toxicity table information was modified.  
 Section 11: Aspiration Hazard Table information was modified.  
 Section 11: Carcinogenicity Table information was modified.  
 Section 11: Germ Cell Mutagenicity Table information was modified.  
 Section 11: Health Effects - Ingestion information information was modified.  
 Section 11: Health Effects - Skin information information was modified.  
 Section 11: Reproductive and/or Developmental Effects text information was deleted.  
 Section 11: Reproductive Toxicity Table information was modified.  
 Section 11: Serious Eye Damage/Irritation Table information was modified.  
 Section 11: Single exposure may cause standard phrases information was added.  
 Section 11: Skin Corrosion/Irritation Table information was modified.  
 Section 11: Skin Sensitization Table information was modified.  
 Section 11: Target Organs - Repeated Table information was modified.  
 Section 11: Target Organs - Single Table information was modified.  
 Section 12: Component ecotoxicity information information was modified.  
 Section 12: Persistence and Degradability information information was modified.  
 Section 12: Bioaccumulative potential information information was modified.  
 Section 13: 13.1. Waste disposal note information was modified.  
 Section 13: Standard Phrase Category Waste GHS information was modified.  
 Section 15: Carcinogenicity information information was modified.  
 Section 15: Regulations - Inventories information was deleted.  
 Section 15: Restrictions on manufacture ingredients information information was added.  
 Section 16: UK disclaimer information was deleted.

**Annex**

<b>1. Title</b>	
<b>Substance identification</b>	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
<b>Exposure Scenario Name</b>	Industrial Mixing and Application
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 04 -Chemical production where opportunity for exposure arises PROC 05 -Mixing or blending in batch processes PROC 13 -Treatment of articles by dipping and pouring ERC 06d -Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)
<b>Processes, tasks and activities covered</b>	Charging material in open systems where significant opportunity for exposure arises e.g. charging from open drum. Mixing or blending of solid or liquid materials.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Indoor use;

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	3,3'-Oxybis(ethyleneoxy)bis(propylamine); EC No. 224-207-2; CAS Nbr 4246-51-9;
<b>Exposure Scenario Name</b>	Industrial Transfer
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 09 -Transfer of substance or mixture into small containers (dedicated filling line, including weighing) ERC 02 -Formulation into mixture
<b>Processes, tasks and activities covered</b>	Transfers with dedicated controls, including loading, filling, dumping, bagging.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Duration of use: 8 hours/day; Frequency of exposure at workplace [for one worker]: 5 days/week; Indoor use; Outdoor use;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Face shield; Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Refer to Section 8 of the SDS for specific glove material.; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the

**3M(TM) Scotch-Weld(TM) Epoxy Adhesive DP190 Translucent, Part A**

product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)**