



Safety Data Sheet

Copyright,2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	35-8075-0	Version number:	5.00
Revision date:	14/07/2020	Supersedes date:	07/11/2018
Transportation version number:	1.00 (27/05/2016)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M™ Novec™ 73DE Engineered Fluid

Product Identification Numbers

98-0212-4901-0 98-0212-4902-8 98-0212-4903-6

7100095234 7100095233 7100095235

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

For Industrial Use Only. See Limitations on Use for supplemental information on intended applications including Medical Device applications.

Restrictions on Use

Novec™ Engineered Fluids are used in a wide variety of applications including but not limited to precision cleaning of medical devices and as lubricant deposition solvents for medical devices. When the product is used for applications where the finished device is implanted into the human body, no residual Novec™ solvent may remain on the parts. It is highly recommended that the supporting test results and protocol be cited during FDA registration. 3M Electronics Materials Solutions Division (EMSD) will not knowingly sample, support, or sell its products for incorporation in medical and pharmaceutical products and applications in which the 3M product will be temporarily or permanently implanted into humans or animals. The customer is responsible for evaluating and determining that a 3M EMSD product is suitable and appropriate for its particular use and intended application. The conditions of evaluation, selection, and use of a 3M product can vary widely and affect the use and intended application of a 3M product. Because many of these conditions are uniquely within the user's knowledge and control, it is essential that the user evaluate and determine whether the 3M product is suitable and appropriate for a particular use and intended application, and complies with all local applicable laws, regulations, standards, and guidance.

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

The acute inhalation toxicity classification is not applied based on test data.

CLASSIFICATION:

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
trans-dichloroethylene	156-60-5	205-860-2	60 - 90

HAZARD STATEMENTS:

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH018 In use, may form flammable/explosive vapour-air mixture.

Supplemental Precautionary Statements:

Provide ventilation adequate to maintain vapor concentration below lower explosive concentration.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
trans-dichloroethylene	156-60-5	205-860-2	01-2120093504-55	60 - 90	Flam. Liq. 2, H225; Acute Tox. 4, H332; Aquatic Chronic 3, H412 - Nota C Eye Irrit. 2, H319; STOT SE 3, H336
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	132182-92-4	ELINCS 459-520-5	01-0000019452-72	10 - 40	Substance with an occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If you feel unwell, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Exposure to extreme heat can give rise to thermal decomposition. No closed-cup flash point but flam/expl. vapor air mixture. Material displays no closed-cup flash point but may form flammable/explosive vapor air mixture.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.
Hydrogen Fluoride	During combustion.

5.3. Advice for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sparks/flames/extreme heat. Keep away from sparks, flames, and extreme heat. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Eliminate ignition sources when cleaning spill. Eliminate all potential ignition sources when cleaning up spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Contents may be under pressure, open carefully. Avoid inhalation of thermal decomposition products. Avoid skin contact with hot material. For industrial/occupational use only. Not for consumer sale or use. Store work clothes separately from other clothing, food and tobacco products. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to

3M™ Novec™ 73DE Engineered Fluid

the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products. Keep away from sparks/flames/extreme heat Keep away from sparks, flames, and extreme heat.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store at temperatures not exceeding 38C/100F Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-trans-dichloroethylene	132182-92-4	Manufacturer determined	TWA:100 ppm	
	156-60-5	UK HSC	TWA:806 mg/m ³ (200 ppm);STEL:1010 mg/m ³ (250 ppm)	

UK HSC : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
trans-dichloroethylene		Consumer	Inhalation, Long-term exposure (24 hours), Systemic effects	198 mg/m ³
trans-dichloroethylene		Consumer	Oral, Long-term exposure (24 hours), Systemic effects	57 mg/kg bw/d
trans-dichloroethylene		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	797 mg/m ³

Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
trans-dichloroethylene		Agricultural soil	0.0563 mg/kg d.w.
trans-dichloroethylene		Freshwater	0.0364 mg/l
trans-dichloroethylene		Freshwater sediments	0.5483 mg/kg d.w.
trans-dichloroethylene		Grassland average	0.0563 mg/kg d.w.
trans-dichloroethylene		Intermittent releases to water	0.3636 mg/l

3M™ Novec™ 73DE Engineered Fluid

trans-dichloroethylene		Marine water	0.0036 mg/l
trans-dichloroethylene		Marine water sediments	0.0548 mg/kg d.w.
trans-dichloroethylene		Sewage Treatment Plant	17 mg/l

Recommended monitoring procedures: Information on recommended monitoring procedures can be obtained from UK HSC

8.2. Exposure controls

In addition, refer to the annex for more information.

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide ventilation adequate to maintain vapor concentration below lower explosive concentration.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Chemical protective gloves not required under normal conditions. Chemical protective gloves are not required under normal use conditions. However, when the product is subjected to extreme heat, HF may be formed. For those cases, neoprene gloves and apron are recommended.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours
Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter type A

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

Applicable Norms/Standards

Use gloves tested to EN 407

8.2.3. Environmental exposure controls

Refer to Annex

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid.

Colour

Colourless

Specific Physical Form:

Liquid.

Odor

Slight Odor

Odour threshold

No data available.

pH

Not applicable.

Boiling point/boiling range

47.6 °C

Melting point

Not applicable.

Flammability (solid, gas)

Not applicable.

Explosive properties

Not classified

Oxidising properties

Not classified

Flash point

No flash point [*Details:*Tested according to ASTM Method D-3278-96 e-1 (additionally, not flammable below 250 C per KS M ISO 2592)]

Autoignition temperature

427 °C

Flammable Limits(LEL)

7.5 % volume [*Details:*Tested according to ASTM Method E681-15 (Per Annex A1, closed vessel test method for difficult-to-ignite materials)]

Flammable Limits(UEL)

15 % volume [*Details:*Tested according to ASTM Method E681-15 (Per Annex A1, closed vessel test method for difficult-to-ignite materials)]

Vapour pressure

35,063.7 Pa [@ 20 °C]

Relative density

1.2808 [*Ref Std:*WATER=1]

Water solubility

< 10 ppm

Solubility- non-water

No data available.

Partition coefficient: n-octanol/water

No data available.

Evaporation rate

No data available.

Vapour density

5.2

Decomposition temperature

No data available.

Viscosity

0.384 mPa-s [@ 25 °C]

Density

1.2808 g/ml

9.2. Other information

EU Volatile Organic Compounds

1,280.8 g/l

Molecular weight

Not applicable.

Percent volatile

100 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	At elevated temperatures. - extreme conditions of heat
Carbon dioxide.	At elevated temperatures. - extreme conditions of heat
Hydrogen Chloride	At elevated temperatures. - extreme conditions of heat
Hydrogen Fluoride	At elevated temperatures. - extreme conditions of heat
Perfluoroisobutylene (PFIB).	At elevated temperatures. - extreme conditions of heat
Toxic vapour, gas, particulate.	At elevated temperatures. - extreme conditions of heat

Refer to section 5.2 for hazardous decomposition products during combustion.

If the product is exposed to extreme conditions of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

3M™ Novec™ 73DE Engineered Fluid

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour (4 hours)	Rat	LC50 > 22.1 mg/l
trans-dichloroethylene	Dermal	Rabbit	LD50 > 5,000 mg/kg
trans-dichloroethylene	Inhalation-Vapour (4 hours)	Rat	LC50 95.6 mg/l
trans-dichloroethylene	Ingestion	Rat	LD50 7,902 mg/kg
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Dermal	Rat	LD50 > 2,000 mg/kg
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Inhalation-Vapour (4 hours)	Rat	LC50 > 430 mg/l
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
trans-dichloroethylene	Rabbit	Minimal irritation
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
trans-dichloroethylene	Rabbit	Moderate irritant
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Mouse	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
trans-dichloroethylene	In Vitro	Not mutagenic
trans-dichloroethylene	In vivo	Not mutagenic
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	In Vitro	Not mutagenic
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	In vivo	Not mutagenic

3M™ Novec™ 73DE Engineered Fluid

Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
trans-dichloroethylene	Inhalation	Not classified for development	Rat	NOAEL 24 mg/l	during organogenesis
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Inhalation	Not classified for female reproduction	Rat	NOAEL 281 mg/l	prematuring into lactation
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Inhalation	Not classified for male reproduction	Rat	NOAEL 281 mg/l	28 days
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Inhalation	Not classified for development	Rat	NOAEL 281 mg/l	prematuring into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
trans-dichloroethylene	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
trans-dichloroethylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
trans-dichloroethylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 4,500 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
trans-dichloroethylene	Inhalation	endocrine system liver kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 16 mg/l	90 days
trans-dichloroethylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
trans-dichloroethylene	Ingestion	blood liver	Not classified	Rat	NOAEL 125 mg/kg/day	14 weeks
trans-dichloroethylene	Ingestion	heart immune system respiratory system	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Inhalation	endocrine system liver heart hematopoietic system immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 281 mg/l	28 days
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Inhalation	respiratory system	Not classified	Rat	NOAEL 143 mg/l	5 days
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Ingestion	liver kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	28 days
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	Ingestion	endocrine system bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

3M™ Novec™ 73DE Engineered Fluid

(trifluoromethyl)-		hematopoietic system heart immune system nervous system				
--------------------	--	---	--	--	--	--

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
trans-dichloroethylene	156-60-5	Bluegill	Estimated	96 hours	LC50	140 mg/l
trans-dichloroethylene	156-60-5	Green Algae	Experimental	48 hours	EC50	36.36 mg/l
trans-dichloroethylene	156-60-5	Water flea	Experimental	48 hours	LC50	220 mg/l
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	132182-92-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	132182-92-4	Ricefish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	132182-92-4	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
trans-dichloroethylene	156-60-5	Experimental Photolysis		Photolytic half-life (in air)	13 days (t 1/2)	Other methods
trans-dichloroethylene	156-60-5	Experimental Biodegradation	28 days	BOD	8 % weight	OECD 301D - Closed bottle test
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	132182-92-4	Experimental Photolysis		Photolytic half-life (in air)	2.63 years (t 1/2)	Other methods
Pentane, 1,1,1,2,2,3,4,5,5,5-decafluoro-3-methoxy-4-(trifluoromethyl)-	132182-92-4	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301D - Closed bottle test

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
trans-dichloroethylene	156-60-5	Experimental Bioconcentration		Log Kow	2.09	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

070103*	Organic halogenated solvents, washing liquids and mother liquors
14 06 02*	Other halogenated solvents and solvent mixtures

SECTION 14: Transportation information

98-0212-4901-0, 98-0212-4902-8, 98-0212-4903-6

Not hazardous for transportation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

Industrial Laboratory Use: Section 16: Annex information was modified.
Industrial Use as a Solvent: Section 16: Annex information was modified.
Industrial Use in Vapour Degreasing Systems: Section 16: Annex information was modified.
Professional Laboratory Use: Section 16: Annex information was modified.
Professional Use as a Solvent: Section 16: Annex information was modified.
CLP: Ingredient table information was modified.
Label: CLP Supplemental Precautionary Statements information was added.
Section 3: Composition/ Information of ingredients table information was modified.
Section 5: Fire - Extinguishing media information information was modified.
Section 5: Fire - Special hazards information information was modified.
Section 5: Hazardous combustion products table information was added.
Section 6: Accidental release clean-up information information was modified.
Section 6: Accidental release personal information information was modified.
Section 7: Conditions safe storage information was modified.
Section 7: Precautions safe handling information information was modified.
Section 8: Appropriate Engineering controls information information was modified.
Section 8: DNEL table row information was modified.
Section 8: glove data value information was deleted.
Section 8: Personal Protection - Skin/body information information was deleted.
Section 8: Personal Protection - Skin/hand information information was modified.
Section 8: PNEC table row information was modified.
Section 8: Respiratory protection - recommended respirators information information was modified.
Section 8: Skin protection - protective clothing information information was deleted.
Section 8: Skin protection - recommended gloves text information was deleted.
Section 09: Color information was added.
Section 9: Flammable limits (LEL) information information was modified.
Section 9: Flammable limits (UEL) information information was modified.
Section 9: Flash point information information was modified.
Section 09: Odor information was added.
Sections 3 and 9: Odour, colour, grade information information was deleted.
Section 10: Conditions to avoid physical property information was modified.
Section 10: Hazardous decomposition or by-products table information was modified.
Section 10: Hazardous decomposition products during combustion text information was added.
Section 10: Hazardous Decomposition Products information information was modified.
Section 11: Acute Toxicity table information was modified.
Section 11: Germ Cell Mutagenicity Table information was modified.
Section 11: Reproductive and/or Developmental Effects text information was deleted.
Section 11: Reproductive Toxicity Table information was modified.
Section 11: Serious Eye Damage/Irritation Table information was modified.
Section 11: Skin Corrosion/Irritation Table information was modified.
Section 11: Target Organs - Repeated Table information was modified.
Section 11: Target Organs - Single Table information was modified.
Section 12: Component ecotoxicity information information was modified.
Prints No Data if Adverse effects information is not present information was added.
Section 12: Persistence and Degradability information information was modified.
Section 12: Biocumulative potential information information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 15: Label remarks and EU Detergent information was deleted.

Section 15: Regulations - Inventories information was deleted.

Section 16: UK disclaimer information was deleted.

Annex

1. Title	
Substance identification	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Industrial Laboratory Use
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 15 -Use a laboratory reagent ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
Processes, tasks and activities covered	Use as a laboratory reagent.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Duration of use; Indoors with LEV and good general ventilation;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Industrial Use as a Solvent
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 07 -Industrial spraying PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 10 -Roller application or brushing PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 07 -Use of functional fluid at industrial site
Processes, tasks and activities covered	Cleaning process equipment and parts. Cleaning surfaces by wiping, brushing. Spraying of substances/mixtures. Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes, bottles or small reservoirs.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid.

	<p>General operating conditions: Discharge volume of sewage treatment plant: 2,000,000 liters per day; Emission days per year: 365 days per year; Flow rate of receiving surface water: 18,000 cubic meters per day; Indoors with enhanced general ventilation; Indoors with good general ventilation; Large factory building (> 500 m³); Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;</p> <p>Task: Spraying; Duration of use: 4 hours/day;</p> <p>Task: Transferring Material; Duration of use: 4 hours/day;</p> <p>Task: Wiping Surfaces; Duration of use: 4 hours/day;</p>
Risk management measures	<p>Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;</p>
Waste management measures	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Industrial Use in Vapour Degreasing Systems
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 04 -Chemical production where opportunity for exposure arises PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article) ERC 07 -Use of functional fluid at industrial site
Processes, tasks and activities covered	Draining process equipment. Transfer of substance/mixture with dedicated engineering controls. Vapour Degreasing
2. Operational conditions and risk management measures	
Operating Conditions	<p>Physical state:Liquid. General operating conditions: Discharge volume of sewage treatment plant: 2,000,000 liters per day; Duration of use: 8 hours/day; Emission days per year: 300 days per year; Flow rate of receiving surface water: 18,000 cubic meters per day; Indoor use without Local Exhaust Ventilation; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ; Medium sized room or workshop (100 m³ - 500 m³); Partially open and partially closed process;</p>

Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Incinerate in a facility capable of handling halogenated waste;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Professional Laboratory Use
Lifecycle Stage	Use at industrial sites
Contributing activities	PROC 15 -Use a laboratory reagent ERC 04 -Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
Processes, tasks and activities covered	Use as a laboratory reagent.
2. Operational conditions and risk management measures	
Operating Conditions	Physical state: Liquid. General operating conditions: Discharge volume of sewage treatment plant: 2,000,000 liters per day; Duration of use: 8 hours/day; Flow rate of receiving surface water:: 18,000 cubic meters per day; Indoors with LEV and good general ventilation; Local freshwater dilution factor: 10 ; Local marine water dilution factor: 100 ;
Risk management measures	Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;
Waste management measures	Incinerate in a facility capable of handling halogenated waste;
3. Prediction of exposure	
Prediction of exposure	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

1. Title	
Substance identification	trans-dichloroethylene; EC No. 205-860-2; CAS Nbr 156-60-5;
Exposure Scenario Name	Professional Use as a Solvent
Lifecycle Stage	Widespread use by professional workers
Contributing activities	PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities

3M™ Novec™ 73DE Engineered Fluid

	<p>PROC 10 -Roller application or brushing PROC 11 -Non industrial spraying PROC 13 -Treatment of articles by dipping and pouring ERC 08a -Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 09a -Widespread use of functional fluid (indoor)</p>
Processes, tasks and activities covered	<p>Cleaning process equipment and parts. Cleaning surfaces by wiping, brushing. Spraying of substances/mixtures. Transfer of substance/mixture with dedicated engineering controls. Transfer of substances/mixtures into small containers e.g. tubes , bottles or small reservoirs.</p>
2. Operational conditions and risk management measures	
Operating Conditions	<p>Physical state:Liquid. General operating conditions: Indoors with good general ventilation; Medium sized room or workshop (100 m³ - 500 m³);</p> <p>Task: Pouring Material - Liquids; Duration of use: 15 min - 1 hour task;</p> <p>Task: Spraying; Duration of use: 15 min - 1 hour task;</p> <p>Task: Wiping Surfaces; Duration of use: 15 min - 1 hour task;</p>
Risk management measures	<p>Under the operational conditions described above the following risk management measures apply: General risk management measures: Human health: None needed; Environmental: None needed;</p>
Waste management measures	<p>No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:</p>
3. Prediction of exposure	
Prediction of exposure	<p>Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.</p>

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M United Kingdom MSDSs are available at www.3M.com/uk