

Safety Data Sheet

Copyright,2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-0372-0	Version number:	3.00
Revision date:	24/11/2023	Supersedes date:	15/03/2023

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Scotch-Weld Epoxy Adhesive EC-1469

Product Identification Numbers 87-2500-0453-5

7000058950

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Structural adhesive.

1.3. Details of the supplier of the safety data sheet

Address:3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.Telephone:+44 (0)1344 858 000E Mail:tox.uk@mmm.comWebsite:www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Self-Heating Substance or Mixture, Category 1 - Self-heat. 1; H251 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319 Skin Sensitization, Category 1 - Skin Sens. 1; H317 Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

2.2. Label elements The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD DANGER.

Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS09 (Environment) |

Pictograms



Ingredient	CAS Nbr	EC No.	% by Wt
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	216-823-5	70 - 90

HAZARD STATEMENTS:

H251	Self-heating; may catch fire.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention: P273 P280E	Avoid release to the environment. Wear protective gloves.
Response:	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
Storage:	
P407	Maintain air gap between stacks or pallets. Store bulk measure motor than $1 \log (2.2)$ the at terms patrons not encoding $5C/40E$
P413	Store bulk masses greater than 1 kg/2.2 lbs at temperatures not exceeding 5C/40F.

Product is classified H251 based on testing that followed ONU test method N4.

2.3. Other hazards

None known.

3M Scotch-Weld Epoxy Adhesive EC-1469

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)		Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
bis-[4-(2,3-epoxipropoxi)phenyl]propane	(CAS-No.) 1675-54-3 (EC-No.) 216-823-5	70 - 90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Hyrdrazide	Trade Secret	10 - 30	Substance not classified as hazardous
Synthetic amorphous silica, fumed, crystalline-free	(CAS-No.) 112945-52-5	1 - 5	Substance with a national occupational exposure limit

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
bis-[4-(2,3-epoxipropoxi)phenyl]propane		(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include: Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance	<u>Condition</u>
Aldehydes.	During combustion.
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.
Hydrogen Chloride	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient Silicon dioxide CAS Nbr Agency 112945-52-5 UK HSC Limit type TWA(as respirable dust):2.4 mg/m3;TWA(as inhalable dust):6 mg/m3 **Additional comments**

UK HSC : UK Health and Safety Commission TWA: Time-Weighted-Average STEL: Short Term Exposure Limit CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Safety glasses with side shields. Indirect vented goggles.

Applicable Norms/Standards Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material Polymer laminate Thickness (mm) No data available **Breakthrough Time** No data available

Applicable Norms/Standards Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White-Cream
Odor	Low Odor
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	>=260°C
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Flash point	>=104.4 °C [<i>Test Method</i> :Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
рН	substance/mixture is non-soluble (in water)
Kinematic Viscosity	50,000 mm ² /sec
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	Not applicable.
Density	1.2 g/ml
Relative density	1.2 [<i>Ref Std</i> :WATER=1]
Relative Vapour Density	Not applicable.

- 9.2. Other information
- 9.2.2 Other safety characteristics EU Volatile Organic Compounds Evaporation rate Molecular weight Percent volatile

No data available. Not applicable. No data available. Negligible

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Rat	LD50 > 1,600 mg/kg
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Rat	LD50 > 1,000 mg/kg
Hyrdrazide	Dermal		LD50 estimated to be > 5,000 mg/kg
Hyrdrazide	Ingestion	Rat	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic amorphous silica, fumed, crystalline-free	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Mild irritant
Hyrdrazide	Rabbit	No significant irritation
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Rabbit	Moderate irritant
Hyrdrazide	Rabbit	Mild irritant
Synthetic amorphous silica, fumed, crystalline-free	Rabbit	No significant irritation

Skin Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Sensitising
	and	
	animal	
Hyrdrazide	Mouse	Not classified
Synthetic amorphous silica, fumed, crystalline-free	Human	Not classified
	and	
	animal	

Respiratory Sensitisation

Name	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In vivo	Not mutagenic
bis-[4-(2,3-epoxipropoxi)phenyl]propane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hyrdrazide	In Vitro	Some positive data exist, but the data are not sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
bis-[4-(2,3-epoxipropoxi)phenyl]propane		Mouse	Some positive data exist, but the data are not
			sufficient for classification
Synthetic amorphous silica, fumed, crystalline-free	Not	Mouse	Some positive data exist, but the data are not
	specified.		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis

bis-[4-(2,3-epoxipropoxi)phenyl]propane	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic amorphous silica, fumed, crystalline-free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data is currently available or the data is not sufficient for classification.

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
bis-[4-(2,3- epoxipropoxi)phenyl]prop ane	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Synthetic amorphous silica, fumed, crystalline- free	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Specific Target Organ Toxicity - repeated exposure

Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Туре	Exposure	Test endpoint	Test result
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Activated sludge	Analogous Compound	3 hours	IC50	>100 mg/l
bis-[4-(2,3- epoxipropoxi)phen		Rainbow trout	Estimated	96 hours	LC50	2 mg/l

yl]propane						
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Estimated	48 hours	EC50	1.8 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	ErC50	>11 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Green algae	Experimental	72 hours	NOEC	4.2 mg/l
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Water flea	Experimental	21 days	NOEC	0.3 mg/l
Hyrdrazide	Trade Secret	Green algae	Experimental	72 hours	EC50	>84 mg/l
Hyrdrazide	Trade Secret	Water flea	Experimental	48 hours	EC50	>100 mg/l
Hyrdrazide	Trade Secret	Green algae	Experimental	72 hours	EC10	8.1 mg/l
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Green algae	Analogous Compound	72 hours	ErC50	>173.1 mg/l
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Sediment organism	Analogous Compound	96 hours	EC50	8,500 mg/kg (Dry Weight)
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Water flea	Analogous Compound	24 hours	EL50	>10,000 mg/l
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Zebra Fish	Analogous Compound	96 hours	LL50	>10,000 mg/l
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Green algae	Analogous Compound	72 hours	NOEC	173.1 mg/l
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Water flea	Analogous Compound	21 days	NOEC	68 mg/l
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Biodegradation	28 days	BOD	5 %BOD/COD	OECD 301F - Manometric respirometry
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	117 hours (t 1/2)	OECD 111 Hydrolysis func of pH
Hyrdrazide	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	5 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Data not availbl- insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)phen yl]propane	1675-54-3	Experimental Bioconcentration		Log Kow	3.242	OECD 117 log Kow HPLC method
Hyrdrazide	Trade Secret	Experimental Bioconcentration		Log Kow	-1.4	
Synthetic amorphous silica, fumed, crystalline- free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
bis-[4-(2,3- epoxipropoxi)pheny l]propane		Modeled Mobility in Soil	Кос	450 l/kg	Episuite™
Hyrdrazide	Trade Secret	Estimated Mobility in Soil	Кос	10 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09*Waste adhesives and sealants containing organic solvents or other dangerous substances20 01 27*Paint, inks, adhesives and resins containing dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN3531	UN3531	UN3531

14.2 UN proper shipping name	POLYMERIZING SUBSTANCE, SOLID, STABILIZED, N.O.S.(EPOXY RESIN)	POLYMERIZING SUBSTANCE, SOLID, STABILIZED, N.O.S.(EPOXY RESIN)	POLYMERIZING SUBSTANCE, SOLID, STABILIZED, N.O.S.(EPOXY RESIN)
14.3 Transport hazard class(es)	4.1	4.1	4.1
14.4 Packing group	III	III	III
14.5 Environmental hazards	Environmentally Hazardous	Not applicable	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	PM1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity <u>Ingredient</u>	<u>CAS Nbr</u>	Classification	Regulation
bis-[4-(2,3-epoxipropoxi)phenyl]propane	1675-54-3	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of		
	Lower-tier requirements	Upper-tier requirements	
E2 Hazardous to the Aquatic	200	500	
environment			

Seveso named dangerous substances, Annex 1, Part 2 None

Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

- H251 Self-heating; may catch fire.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

Revision information:

GB Section 04: First Aid - Symptoms and Effects (GB CLP) information was added. GB Section 04: Information on toxicological effects information was modified. Label: CLP Precautionary - Disposal information was deleted.

Label: CLP Precautionary - Storage information was modified.

Section 8: Eye/face protection information information was modified. Section 15: Seveso Hazard Category Text information was added.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.