



Safety Data Sheet

Copyright, 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	30-1105-3	Version number:	3.00
Revision date:	20/11/2018	Supersedes date:	15/06/2015
Transportation version number:	1.00 (07/05/2015)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M Power Tools with Air Tool Lubricant, Back-up Pads; Elite's

Product Identification Numbers

DC-2729-2700-5 DC-2729-2705-4

7000032231 7100010670

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Power Tools and Tool Lubricant for use with abrasives

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

35-2668-8

TRANSPORTATION INFORMATION

DC-2729-2700-5, DC-2729-2705-4

Not hazardous for transportation

KIT LABEL

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) |

Pictograms



Contains:

Distillates (petroleum), hydrotreated heavy paraffinic

HAZARD STATEMENTS:

H336 May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

No hazard statements are required for containers ≤ 125 mL.

No precautionary statements are required for containers ≤ 125 mL.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Revision information:

Label: CLP Percent Unknown - Kit information was added.

Kit: Component document group number(s) information was modified.

Label: CLP Ingredients - kit components information was added.

Section 1: Product identification numbers information was modified.

3M Power Tools with Air Tool Lubricant, Back-up Pads; Elite's

Section 01: SAP Material Numbers information was added.

CLP Remark(phrase) information was deleted.

Section 2: H phrase reference information was added.

Label: CLP <125ml Hazard - none information was added.

Label: CLP <125ml Precautionary - none information was added.

Label: CLP Classification information was added.

Label: CLP Precautionary - Prevention information was added.

Label: CLP Supplemental Hazard Statements information was modified.

Label: Graphic information was added.

Label: Signal Word information was added.

Section 15: Label remarks and EU Detergent information was deleted.



Safety Data Sheet

Copyright, 2018, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	35-2668-8	Version number:	3.02
Revision date:	08/03/2018	Supersedes date:	17/08/2017
Transportation version number:	3.00 (22/01/2018)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M Accessory Products, Air Tool Lubricant

Product Identification Numbers

60-4402-4214-1

7100054091

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Tool Lubricant

1.3. Details of the supplier of the safety data sheet

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone: +44 (0)1344 858 000
E Mail: tox.uk@mmm.com
Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

WARNING.

Symbols:

GHS07 (Exclamation mark) |

Pictograms



Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	50 - 65

HAZARD STATEMENTS:

H336 May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

Prevention:

P261A Avoid breathing vapours.

For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

No hazard statements are required for containers <=125 mL.

No precautionary statements are required for containers <=125 mL.

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

EUH066 Repeated exposure may cause skin dryness or cracking.

31% of the mixture consists of components of unknown acute oral toxicity.

Contains 14% of components with unknown hazards to the aquatic environment.

Notes on labelling

3M Accessory Products, Air Tool Lubricant

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1		50 - 65	Nota L STOT SE 3, H336; EUH066

3M Accessory Products, Air Tool Lubricant

Alkanes, C18-28, chloro	85535-86-0	287-478-6		10 - 20	Aquatic Chronic 4, H413
HYDROTREATED SPENT LUBE OIL (PETROLEUM)	64742-58-1	265-161-3		5 - 15	Substance not classified as hazardous
Polysulfides, di-tert-dodecyl	68425-15-0	270-335-7		1 - 10	Substance not classified as hazardous
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6		1 - 10	Nota L Acute Tox. 4, H332; Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7		< 1	Nota L

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide.	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus,

bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Mild petroleum odour, clear light amber liquid
Odour threshold	No data available.
pH	No data available.
Boiling point/boiling range	230 °C
Melting point	Not applicable.
Flammability (solid, gas)	Not applicable.
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	138 °C [Test Method:Pensky-Martens Closed Cup]
Autoignition temperature	No data available.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Vapour pressure	No data available.
Relative density	0.88 [@ 20 °C] [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.

Decomposition temperature

No data available.

Viscosity

6.1 - 35.4 mm²/sec [*@ 40 °C*] [*Test Method:* Tested per ASTM protocol] [*Details:* 10 wt. D-445]

Density

No data available.

9.2. Other information

EU Volatile Organic Compounds

No data available.

Percent volatile

2.2 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

Reducing agents.

Strong acids.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

3M Accessory Products, Air Tool Lubricant**Eye contact**

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic	Dermal	Rabbit	LD50 > 5,000 mg/kg
Distillates (petroleum), hydrotreated heavy paraffinic	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), hydrotreated light naphthenic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Distillates (petroleum), hydrotreated light naphthenic	Inhalation-Dust/Mist (4 hours)	Rat	LC50 2.2 mg/l
Distillates (petroleum), hydrotreated light naphthenic	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Dermal	Rabbit	LD50 > 5,000 mg/kg
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Distillates (petroleum), hydrotreated heavy paraffinic	Rabbit	Minimal irritation
Distillates (petroleum), hydrotreated light naphthenic	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Distillates (petroleum), hydrotreated heavy paraffinic	Rabbit	Mild irritant
Distillates (petroleum), hydrotreated light naphthenic	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
Distillates (petroleum), hydrotreated heavy paraffinic	Guinea pig	Not classified
Distillates (petroleum), hydrotreated light naphthenic	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
------	-------	-------

3M Accessory Products, Air Tool Lubricant

Distillates (petroleum), hydrotreated heavy paraffinic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light naphthenic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light naphthenic	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Distillates (petroleum), hydrotreated heavy paraffinic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light naphthenic	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated light naphthenic	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Distillates (petroleum), hydrotreated light naphthenic	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Distillates (petroleum), hydrotreated light naphthenic	Dermal	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	during gestation
Distillates (petroleum), hydrotreated light naphthenic	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Distillates (petroleum), hydrotreated light naphthenic	Dermal	Not classified for male reproduction	Rabbit	NOAEL 1,000 mg/kg/day	28 days

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated heavy paraffinic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated heavy paraffinic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated heavy paraffinic	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.21 mg/l	28 days

Aspiration Hazard

Name	Value
Distillates (petroleum), hydrotreated light naphthenic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Water flea	Estimated	48 hours	Effect Level 50%	>100 mg/l
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Fathead minnow	Experimental	96 hours	Lethal Level 50%	>100 mg/l
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Green algae	Estimated	72 hours	Effect Level 50%	>100 mg/l
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Green algae	Estimated	72 hours	No obs Effect Level	>100 mg/l
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Water flea	Estimated	21 days	No obs Effect Level	>100 mg/l
Alkanes, C18-28, chloro	85535-86-0	Water flea	Estimated	24 hours	EC50	102 mg/l
Alkanes, C18-28, chloro	85535-86-0	Rainbow trout	Estimated	96 hours	LC50	>300 mg/l
HYDROTREATED SPENT LUBE OIL (PETROLEUM)	64742-58-1		Data not available or insufficient for classification			
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	Water flea	Experimental	48 hours	EC50	>100 mg/l
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	Green algae	Estimated	96 hours	EC50	>100 mg/l
Polysulfides, di-tert-dodecyl	68425-15-0	Zebra Fish	Endpoint not reached	96 hours	Lethal Level 50%	>100 mg/l
Polysulfides, di-tert-dodecyl	68425-15-0	Green algae	Experimental	72 hours	EC50	>100 mg/l
Polysulfides, di-tert-dodecyl	68425-15-0	Water flea	Experimental	48 hours	EC50	>100 mg/l
Polysulfides, di-tert-dodecyl	68425-15-0	Green algae	Experimental	72 hours	NOEC	100 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Water flea	Estimated	48 hours	EC50	>100 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Green algae	Estimated	96 hours	EC50	>100 mg/l
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Water flea	Experimental	21 days	NOEC	100 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
----------	---------	-----------	----------	------------	-------------	----------

3M Accessory Products, Air Tool Lubricant

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Experimental Biodegradation	28 days	BOD	31 % weight	OECD 301F - Manometric respirometry
Alkanes, C18-28, chloro	85535-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREATED SPENT LUBE OIL (PETROLEUM)	64742-58-1	Experimental Biodegradation	28 days		9.1 % weight	Other methods
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	Experimental Biodegradation	28 days	BOD	42 % weight	OECD 301F - Manometric respirometry
Polysulfides, di-tert-dodecyl	68425-15-0	Experimental Bioconcentration		Log Kow	>6.2	Other methods
Polysulfides, di-tert-dodecyl	68425-15-0	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301F - Manometric respirometry
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Experimental Biodegradation	28 days	CO2 evolution	23 % weight	Other methods

12.3 : Bioaccumulative potential

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Estimated Bioconcentration		Bioaccumulation factor	7.5	Estimated: Bioconcentration factor
Alkanes, C18-28, chloro	85535-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
HYDROTREATED SPENT LUBE OIL (PETROLEUM)	64742-58-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	Estimated Bioconcentration		Log Kow	5.07	Other methods
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact manufacturer for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of

3M Accessory Products, Air Tool Lubricant

3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

130204* Mineral-based chlorinated engine, gear and lubricating oils

SECTION 14: Transportation information

60-4402-4214-1

Not hazardous for transportation

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA.

15.2. Chemical Safety Assessment

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H413	May cause long lasting harmful effects to aquatic life.

Revision information:

Section 2: <125ml Precautionary - Storage information was deleted.
Label: CLP Percent Unknown information was added.
Label: CLP Precautionary - Storage information was deleted.
Section 3: Composition/ Information of ingredients table information was modified.
Section 4: First aid for skin contact information information was modified.
Section 5: Fire - Advice for fire fighters information information was modified.
Section 6: Accidental release environmental information information was modified.
Section 7: Precautions safe handling information information was modified.
Section 8: Eye protection information information was added.
Section 8: Eye/face protection information information was deleted.
Section 8: Personal Protection - Eye information information was deleted.
Section 8: Personal Protection - Skin/body information information was deleted.
Section 8: Skin protection - protective clothing information information was deleted.
Section 9: Viscosity information information was modified.
Section 11: Health Effects - Skin information information was modified.
Section 12: Component ecotoxicity information information was modified.
Section 12: Persistence and Degradability information information was modified.
Section 12: Bioaccumulative potential information information was modified.
Section 13: Standard Phrase Category Waste GHS information was modified.
Section 15: Chemical Safety Assessment information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk